

OE-EC803A — Internet of Things

Semester VIII • 3L:0T:0P • 3 Credits

Module 6: Prototype to Reality: Business, Manufacturing & Ethics

CGEC | B.Tech ECE (2023–27) | Biraj Sarkar

Contents

1 IoT Business Models & Startups	2
1.1 A Short History of Business Models	2
1.2 Who is the Business Model For?	2
1.3 Business Model Canvas in IoT	2
1.4 Lean Startup Methodology	2
1.5 Funding Options	2
2 Moving to Manufacture	3
2.1 What are you Producing? & Designing Kits	3
2.2 Designing and Manufacturing PCBs	3
2.3 Mass-Producing Enclosures (Injection Molding)	4
2.4 Hardware Certification	4
2.5 Manufacturing Cost Concepts	4
2.6 Software Scaling and OTA Updates	4
3 Ethics, Security & Environmental Solutions	4
3.1 Characterizing the Internet of Things (Ethical Perspective)	5
3.2 Privacy and Control	5
3.3 Environmental Impact (E-Waste)	5

1. IoT Business Models & Startups

Transitioning an IoT prototype into a commercial product requires establishing sustainable business value.

1.1 A Short History of Business Models

Historically, business models revolved around the **transactional model** (Value-Transaction-Exchange), where companies designed, manufactured, and sold physical products as a one-time purchase. In the digital age, this evolved into the **subscription/service-based model** (e.g. SaaS). IoT merges these two histories: it combines the transactional sale of physical hardware with the ongoing subscription-based service model (Product-as-a-Service), creating a continuous customer relationship.

1.2 Who is the Business Model For?

An IoT business model serves three main target audiences:

- **Investors:** Demonstrates the viability, return on investment (ROI), scalability, and path to profitability (amortizing high upfront tooling and NRE costs).
- **Partners and Suppliers:** Clarifies roles in the value chain, such as PCB manufacturing houses, cloud providers, and distribution networks.
- **Internal Team:** Aligns the engineering, sales, and support departments on customer needs, product value propositions, and resource allocations.

1.3 Business Model Canvas in IoT

The **Business Model Canvas** defines the value chain across 9 building blocks. IoT products introduce distinct paradigms:

- **Value Proposition:** Selling continuous services instead of a single hardware purchase.
- **Revenue Streams (Product-as-a-Service):** Customers purchase the hardware at low cost and pay a monthly subscription fee for cloud features, database storage, and automated actions (e.g., smart home security monitoring).

1.4 Lean Startup Methodology

- **MVP (Minimum Viable Product):** Building a prototype containing only the core feature that solves the user's primary problem.
- **Feedback Loop:** The iterative **Build-Measure-Learn** loop helps refine the MVP based on real user feedback before funding expensive manufacturing tooling.

1.5 Funding Options

IoT startups fund early stages via:

- **Crowdfunding (Kickstarter):** Users pre-order the product, verifying market demand and funding initial production runs.
- **Venture Capital (VC) & Bootstrapping:** Institutional funding for scaling versus self-funding from revenues.


2. Moving to Manufacture

Mass-producing electronic hardware involves transitioning from breadboards to industrial assembly lines.

2.1 What are you Producing? & Designing Kits

Before manufacturing, developers must define the physical scope of their product:

- **What are you Producing?:** Is the product a raw sub-assembly component, an industrial sensor node, or a polished end-user consumer product? This determines the enclosure design and target user experience.
- **Designing Kits:** Many IoT systems begin as developer kits (e.g. SparkFun/Adafruit starter kits). Designing a kit requires organizing components, color-coding wire connectors, providing clear assembly diagrams, and bundling software library links to reduce the user's first-time configuration friction.



2.2 Designing and Manufacturing PCBs

1. **Schematic Capture:** Drawing logical electrical connections between components.
2. **PCB Layout Routing:** Arranging physical component footprints on the board and routing copper traces to connect them. Ground planes are added to shield signals from electromagnetic interference.
3. **Gerber Files:** The standardized vector files exported from PCB design software. Gerbers act as blueprints, instructing fabrication machines on copper layer layouts, solder mask placement, and drill holes.
4. **Assembly (SMT vs. Through-Hole):**
 - **SMT (Surface Mount Technology):** Components are soldered directly onto surface pads on the board. Highly automated, allows high density.
 - **Through-Hole Technology (THT):** Component leads are inserted into holes and soldered on the opposite side. Used for heavy connectors and power relays due to high mechanical strength.

2.3 Mass-Producing Enclosures (Injection Molding)

Injection Molding

Injection Molding is the primary manufacturing process for plastic enclosures. Molten plastic (ABS, Polycarbonate) is injected under high pressure into a custom-machined steel or aluminum mold cavity, where it cools and solidifies into the final case.

Key design constraints for injection-molded parts:

- **High Tooling Costs:** Machining the steel molds (tooling) is extremely expensive (often \$10,000 to \$100,000 NRE costs), requiring massive production volumes to amortize the setup cost.
- **Draft Angles:** Vertical walls must be tapered slightly (typically 1° to 2°) to allow the solidified plastic part to eject easily from the steel mold without scratching.

2.4 Hardware Certification

Before selling electronic products, they must satisfy regulatory standards:

- **FCC (Federal Communications Commission):** Required in the USA. Certifies that the device does not emit illegal levels of electromagnetic interference (EMI), especially critical for RF-transmitting wireless devices.
- **CE (Conformité Européenne):** Required in the EU. Declares safety, health, and environmental compliance.
- **RoHS (Restriction of Hazardous Substances):** Restricts the use of hazardous substances (like lead solder) in electronic assemblies, requiring lead-free manufacturing.

2.5 Manufacturing Cost Concepts

- **BOM (Bill of Materials):** A complete, structured list of all raw components, hardware parts, PCBs, and fasteners required to build one unit.
- **NRE (Non-Recurring Engineering):** The one-time upfront costs of design, prototyping, certification testing, and steel injection molds.

2.6 Software Scaling and OTA Updates

When scaling from 1 to 10,000 devices:

- Devices must support **OTA (Over-the-Air) Firmware Updates** to patch security bugs remotely over Wi-Fi/cellular without physical access.

3. Ethics, Security & Environmental Solutions

Connecting billions of physical devices introduces deep social and environmental challenges.

3.1 Characterizing the Internet of Things (Ethical Perspective)

The ethical challenges of IoT are characterized by three core traits:

- **Pervasiveness (Ubiquity):** Devices are embedded in private spaces (homes, offices, bodies) and gather data continuously and invisibly, leaving users unaware of the data collection.
- **Physical Agency:** Unlike the traditional internet (which only displays information), IoT has physical actuators that control real-world environments. A breach can cause immediate physical danger (e.g., unlocking a smart door or disabling a smart brake).
- **Data Ownership and Asymmetry:** A massive imbalance exists between the user (who generates the data) and the manufacturer/service provider (who aggregates, analyzes, and often sells the data).

3.2 Privacy and Control

IoT devices gather intimate details (voices, camera feeds, occupancy).

- **Security:** Many IoT devices have weak security (default passwords, unencrypted firmware). Attackers can hijack them to form **Botnets** (e.g. Mirai botnet) to launch DDoS attacks on servers.
- **Control:** Who owns the data collected by a smart thermostat? Device makers must ensure localized user consent and encrypt data during transmission (using SSL/TLS or DTLS).

3.3 Environmental Impact (E-Waste)

- Millions of short-lived IoT tags and smart devices end up in landfills, leading to heavy metal (lead, mercury) contamination in soil.
- **Solutions:** Designing for repairability, using modular component slots, and using biodegradable paper substrates or organic components for temporary IoT sensors.

Quick Revision — Module 6

Prototype to Reality | OE-EC803A

Key Cost and Amortization Formulas

Total Unit Cost	$\text{Cost}_{\text{unit}} = \text{BOM Cost} + \text{Assembly Cost} + \frac{\text{NRE Cost}}{N}$
BOM Cost	$\text{BOM} = \sum (\text{Component Cost}_i \times \text{Quantity}_i) \quad (\text{list of materials})$
NRE Costs	Amortized over production run volume N . High volume shrinks NRE impact.

One-Line Definitions

- **Gerber File:** Standard file format containing physical layer instructions for manufacturing PCBs.
- **SMT:** Automated technology where electronic components are mounted directly onto the surface of a PCB.
- **Draft Angle:** A slight taper (1-2 degrees) on vertical walls of a molded case to allow easy ejection.
- **RoHS:** A directive restricting hazardous lead, mercury, and cadmium in electronic components.
- **OTA Update:** The process of upgrading a device's firmware wirelessly over the network.

Frequently Asked / Viva Questions

Q1. What is a Gerber file, and why is it important in PCB manufacturing?

A Gerber file is a set of open 2D vector images showing the copper traces, solder masks, silkscreen labels, and drill paths for each layer of the PCB. PCB fabrication houses require Gerber files to program their automated drilling and etching machines.

Q2. What is the difference between SMT and Through-Hole assembly?

SMT (Surface Mount) components are soldered directly to pad surfaces on the board, allowing automated high-density assembly. Through-Hole components have long wire leads inserted through holes in the board and soldered on the opposite side, which provides superior mechanical strength for heavy components like terminals and power relays.

Q3. Why are upfront tooling costs for plastic injection molding extremely high?

The molds must be custom-machined out of solid blocks of hardened tool steel

Frequently Asked / Viva Questions (contd.)

using high-precision CNC machines to withstand thousands of high-pressure, high-temperature plastic injection cycles. This setup cost (NRE) is high but reduces the cost per part to cents at high volumes.

Q4. What is a draft angle in injection molding, and why is it required?

A draft angle is a slight taper (typically 1° to 2°) added to the vertical walls of the plastic enclosure design. Without this taper, the cooling plastic shrinks slightly around the mold cavities, causing high friction and damage during ejection.

Q5. Explain the role of FCC certification for IoT devices.

The FCC (Federal Communications Commission) regulates RF emissions. Any digital device switching signals at high speeds or using wireless transmitters must undergo testing to prove it does not emit electromagnetic interference (EMI) that could disrupt other communications.

Q6. What is a Bill of Materials (BOM) in hardware manufacturing?

A BOM is a structured table listing every single component, PCB substrate, connector, case, fastener, label, and packaging box required to manufacture a single product, along with manufacturer part numbers and costs.

Q7. How can IoT devices pose a security threat to other internet services?

Many consumer IoT devices lack secure firewalls and default login credentials. Attackers can scan the web and infect thousands of these vulnerable devices with malware, forming a botnet (such as Mirai) to launch massive Distributed Denial of Service (DDoS) attacks.

Q8. What is the Product-as-a-Service (PaaS) business model in IoT?

In PaaS, rather than paying a large one-time fee to own hardware, customers buy hardware cheaply and subscribe to a service (recurring revenue stream). The value is delivered through ongoing cloud monitoring, alerts, and automatic software updates.

Comparison Snapshot**3D Printing vs. Injection Molding for Enclosure Production:**

Feature	3D Printing (Prototype)	Injection Molding (Mass Production)
Upfront Tooling Cost	Zero (direct print from STL).	Extremely High (\$10,000+ for steel molds).
Unit Cost	Medium-High (PLA filament cost per hour).	Extremely Low (cents per plastic part).
Production Cycle Time	Slow (several hours per enclosure).	Very Fast (seconds per enclosure injection).
Design Constraints	Layer lines, support structures needed.	Draft angles, uniform wall thickness required.
Best Volume	1 to 50 units (prototypes).	5,000+ units (mass market).