Exercises on Design Patterns - Part I

Week 05

2018

In these exercises we will be examining the following design patterns:

- Adapter,
- Decorator,
- Factory Method,
- Observer, and
- Singleton.

The source code snippets listed below are written using the Kotlin language; similar versions in Scala can be found on the source code repository under the `worksheets/dp-one` folder.

Short form questions

1. Write down three differences between *abstract classes* and *interfaces/traits* in Kotlin/Scala. Provide examples to illustrate your answer.

2. Are the following *true* or *false*?
   (a) Every interface must have at least one method.

   > **Solution:** *False.* An interface with no methods is a *marker interface.* Sometimes, a method high in a class hierarchy, such as `Object.clone()`, is not appropriate for every subclass. You can create a marker interface that requires subclasses to opt in or to opt out of participation in such a method. The `clone()` method on `Object` requires subclasses to opt in, declaring that they implement the `Cloneable` marker interface.

   (b) An interface can declare instance fields that an implementing class must also declare.

Solution: *False.* An interface cannot declare instance fields, although it can create constants by declaring fields that are `static` and `final`.

(c) Although you can't instantiate an interface, an interface definition can declare constructor methods that require an implementing class to provide constructors with given signatures.

Solution: *False.* It might be a good idea, but there is no way for an interface to require implementing classes to provide any particular constructors.

Provide examples to illustrate your answers.

3. Provide an example of an interface with methods that do not imply responsibility on the part of the implementing class to take action on behalf of the caller or to return a value.

Solution: An interface does not define a contract between the caller and the implementing class when the interface is used to *register* for notification. In this case, the implementing class may need to take an action in response to a method call, but it is generally not performing a service for the caller.

For example, a class that implements the `MouseMotionListener` interface from `java.awt.event` must implement the methods:

```
public void mouseDragged(MouseEvent e)
public void mouseMoved(MouseEvent e)
```

The presence of these methods does not imply that the methods will take an action when a client calls them. In fact, it would not be uncommon to react to the `mouseDragged()` method but to ignore to calls to the `mouseMoved()` method.

4. What is the value of a stub class like `WindowAdapter} which is`composed of methods that do nothing?

Solution: A class that implements `WindowListener` must implement all the methods the interface declares, even if the class will ignore these methods when called. The `WindowAdapter` class ignores all the methods in `WindowListener`. This lets a subclass implement only the methods that it wants to react to. The anonymous class in the code below can react to only the `windowClosing()` event, without having to implement dummy methods for the other methods specified in the `WindowListener` interface.

```
public static void listen(Frame f) {
    f.addWindowListener(
```

```
            new WindowAdapter() {
               public void windowClosing(WindowEvent e){
          System.exit(0);
        }
      }
  );
}
```

This code registers with the frame an instance of an anonymous `WindowAdapter` subclass that overrides the `windowClosing()` method. The value of the `WindowAdapter` class is that it makes it easy to create a subclass that reacts to only the relevant window events.

5. How can you prevent other developers from constructing new instances of your class? Provide appropriate examples to illustrate your answer.

Solution: To prevent other developers from instantiating your class, create a single constructor with private visibility. Note that if you create other, non-private constructors or create no constructors at all, other developers will likely be able to re-instantiate your class.

6. Provide examples of two commonly used Kotlin/Scala methods that return a new object.

Solution: Many answers are possible, but `toString()` is probably the most commonly used method that creates a new object. For example, the following code creates a new `String` object:

```
String s = new Date().toString();
```

The creation of strings often happens behind the scenes. Consider:

```
System.out.print(new Date());
```

This method creates a `String` object from the `Date` object, ultimately by calling the `toString()` method of class `Date`. It is interesting to walk through this in a debugger, to see the details of what happens within a common `print()` method.

Another method that creates a new object is `clone()`. You may discover other methods that are "factories" for creating objects without necessarily exacting the FACTORY METHOD pattern.

7. What are the signs that a *Factory Method* is at work?

Solution:

- Creates a new object
- Returns a type that is an abstract class or an interface
- Is implemented by several classes

8. If you want to direct output to the standard output instead of to a file, you can create a `Writer} object that directs its output to \verb`System.out:

```
val out: Writer = PrintWriter(System.out)
```

Write a code example to define a `Writer} object that wraps text at 15 characters,`centres the text, sets the text to random casing, and directs the output to `System.out}.`Which design pattern are you using?

Solution: One answer is:

```
Writer out = new PrintWriter(System.out);
out = new WrapFilter(new BufferedWriter(out), 15);
((WrapFilter) out).setCenter(true);
out = new RandomCaseFilter(out);
```

Alternatively:

```
WrapFilter out =
    new WrapFilter(
        new BufferedWriter(
            new RandomCaseFilter(
                new PrintWriter(System.out))),15);
out.setCenter(true);
```

Long form questions

1. The Factory Method pattern gives us a way to encapsulate the instantiations of concrete types; it encapsulates the functionality required to select and instantiate an appropriate class, inside a designated method referred to as a *factory method*. The factory method selects an appropriate class from a class hierarchy based on the application context and other contributing factors and it then instantiates the selected class and returns it as an instance of the parent class

type. The advantage of this approach is that the application objects can make use of the factory method to gain access to the appropriate class instance. This eliminates the need for an application object to deal explicitly with the varying class selection criteria.

You are required to implement the following classes:

] defines the interface of objects the factory method creates.] implements the `Product} interface.`] declares the factory method, which returns an object of type `Product}.Creator} may also define a default implementation of t` returns a default `ConcreteProduct} object.` We may call the factory method to create a `Product} object.`] overrides the factory method to return an instance of a `ConcreteProduct}.`

Factory methods therefore eliminate the need to bind application-specific classes into your code. The code only deals with the `Product} interface (in this case);` therefore it can work with any user-defined `ConcreteProduct} classes.`

Solution:

2. In this question we examine the SINGLETON design pattern.

   (a) Why might you decide to *lazy-initialise* a singleton instance rather than initialise it in its field declaration? Provide code examples of both approaches to illustrate your answer.

   Solution: You might not have enough information to instantiate every singleton at static initialisation time. A singleton might require values that are computed later in the program's execution. When a `Factory} singleton is born, for example,` it might have to establish connections with machine drivers, to set up planners, and to initialise a simulation of itself.

   (b) There are many ways to break the singleton pattern. One is in a multi-threaded environment but others include:

- If the class is `Serializable}`.
- If it is `Cloneable}`.
- It can be broken by reflection.
- If the class is loaded by multiple *class loaders*.

Try and write a class `SingletonProtected} that addresses some (all?) of these i`

Solution:

3. We now consider the ADAPTER design pattern.

   A software developer, Max, has worked on an e-commerce website. The website allows users to shop and pay online. The site is integrated with a third party payment gateway, through which users can pay their bills using their credit card. Everything was going well, until his manager called him for a change in the project.

   The manager has told him that they are planning to change the payment gateway vendor, and Max has to implement that in the code. The problem that arises here is that the site is attached to the `Xpay} payment gateway which takes an \verb`Xpay type of object. The new vendor, `PayD}, only allows the \verb`PayD type of objects to allow the process. Max doesn't want to change the whole set of a hundred classes which have reference to an object of type `XPay}. He cannot change the third p` problem arises due to the incompatible interfaces between the two different parts of the code. To get the process to work, Max needs to find a way to make the code compatible with the vendor's provided API.



   The current code interface is not compatible with the new vendor's interface. What Max needs here is an ADAPTER which can sit in between the code and the vendor's API, enabling the transaction to proceed.

```
package xpay

interface Xpay {
    val creditCardNo: String
    val customerName: String
    val cardExpMonth: String
    val cardExpYear: String
    val cardCVVNo: Short
    val amount: Double
}
```

The `Xpay} interface contains setter and getter methods to get the information a` credit card and customer name. The interface is implemented in the following code which is used to instantiate an object of this type, and exposes the object to the vendor's API.

```
package xpay

class XpayImpl : Xpay {
    // and add appropriate mutators
    override val creditCardNo: String
        get() = TODO("not implemented")
    override val customerName: String
        get() = TODO("not implemented")
    override val cardExpMonth: String
        get() = TODO("not implemented")
    override val cardExpYear: String
        get() = TODO("not implemented")
    override val cardCVVNo: Short
        get() = TODO("not implemented")
    override val amount: Double
        get() = TODO("not implemented")
}
```

New vendor's interface looks like this:

```
package xpay

interface PayD {
    val custCardNo: String
    val cardOwnerName: String
    val cardExpMonthDate: String
    val CVVNo: Integer
    val totalAmount: Double
}
```

As you can see, this interface has a set of different methods which need to be implemented in the code. However, `Xpay} objects are created by most parts of the code` it is difficult (and risky) to change the entire set of classes. We need some way, that's able to fulfil the vendor's requirement to process the payment and also make less or no change to the current code base.

Your are required to use the Adapter pattern to implement a `XpayToPayDAdapter} class to m`



Solution:

4. This question examines the OBSERVER design pattern.

   Sports Lobby is a sports website targeted at sport lovers. They cover almost all kinds of sports and provide the latest news, information, matches scheduled dates, information about a particular player or a team. Now, they are planning to provide live commentary or scores of matches as an SMS service, but only for their premium users. Their aim is to SMS the live score, match situation, and important events after short intervals. As a user, you need to subscribe to the package and when there is a live match you will get an SMS to the live commentary. The site also provides an option to unsubscribe from the package whenever a user wants to. As a developer, the Sport Lobby has asked you to provide this new feature for them. The reporters of the Sport Lobby will sit in the commentary box in the match, and they will update live commentary to a commentary object. As a developer your job is to provide the commentary to the registered users by fetching it from the commentary object when it's available. When there is an update, the system should update the subscribed users by sending them the SMS. This situation clearly indicates a *one-to-many* mapping between the match and the users, as there could be many users subscribed to a single match. The OBSERVER design pattern is best suited to this situation — you should implement this feature for Sport Lobby using the OBSERVER pattern.

   Remember that there are four participants in the OBSERVER pattern:

   ] which is used to register observers. Objects use this interface to register as observers and also to remove themselves from being observers.] defines an updating interface for objects that should be notified of changes in a subject. All observers need to implement the `Observer} interface.` This interface has a method `update()}, which gets called when the \verb`Subject's state changes.] stores the state of interest to `ConcreteObserver} objects.` It sends a notification to its observers when its state changes. A concrete subject always implements the `Subject} interface.` The `notifyObservers()} method is` the state changes.] maintains a reference to a `ConcreteSubject} object and implement` interface. Each observer registers with a concrete subject to receive updates.

```
package observer

interface Observer {
    fun update(description: String): Unit
    fun subscribe(): Unit
    fun unsubscribe(): Unit
}
```

```
package observer

interface Subject {
```

```
    fun subscribeObserver(observer: Observer): Unit
    fun unSubscribeObserver(observer: Observer): Unit
    fun notifyObservers(): Unit
    fun subjectDetails(): String
}
```

```
package observer

interface Commentary {
    var description: String
}
```

```
package observer

import java.util.*

fun main(args: Array<String>) {
    val obj: Observable = CommentaryObjectObservable("Soccer Match [2018AUG24]
    val observer = SMSUsersObserver(obj, "Adam Warner [New York]")
    val observer2 = SMSUsersObserver(obj, "Tim Ronney [London]")
    observer.subscribe()
    observer2.subscribe()
    println("-".repeat(40))
    // other operations
    observer.unsubscribe()
    // other operation
}
```

Solution:

5. This question considers the DECORATOR design pattern.

   You are commissioned by a pizza company make an extra topping calculator. A user can ask to add extra topping to a pizza and our job is to add toppings and increase its price using our classes.

Please note: the main aim of the DECORATOR design pattern is to attach additional responsibilities to an object dynamically. Decorators provide a flexible alternative to sub-classing for extending functionality. The Decorator prevents the proliferation of subclasses leading to less complexity and confusion.

For simplicity, let's create a simple `Pizza}`interface which contains only two methods:

```
package decorator

interface Pizza {
    val description: String
    val price: Double
}
```

The `getDesc} method is used to obtain the pizza's description whereas thegetPri`

Provide two implementations of the `Pizza} interface:`

- `SimplyVegPizza}`
- `SimplyNonVegPizza}`

Solution:

The decorator wraps the object whose functionality needs to be increased, so it needs to implement the same interface. Provide an abstract decorator class which will be extended by all the concrete decorators.

Now provide several implementations of `PizzaDecorator} and exercise your classes`with the given test class.

- `Ham: PizzaDecorator}`
- `Cheese: PizzaDecorator}`
- `Chicken: PizzaDecorator}`
- `FetaCheese: PizzaDecorator}`
- ...

```
package decorator

import java.text.DecimalFormat

fun main(args: Array<String>) {
    var pizza: Pizza = SimplyVegPizza()
```

```
    print(pizza)
    pizza = RomaTomatoes(pizza)
    print(pizza)
    pizza = GreenOlives(pizza)
    print(pizza)
    pizza = Spinach(pizza)
    print(pizza)
    pizza = SimplyNonVegPizza()
    print(pizza)
    pizza = Meat(pizza)
    print(pizza)
    pizza = Cheese(pizza)
    print(pizza)
    pizza = Ham(pizza)
    print(pizza)
}

fun printPizza(pizza: Pizza) {
    val dformat: DecimalFormat = DecimalFormat("#.##")
    println("Desc: ${pizza.description}")
    println("Price: ${dformat.format(pizza.price)}")
}
```

The code should result in the following output:

```
Desc: SimplyVegPizza (230), Roma Tomatoes (5.20), Green Olives (5.47), Spinach (7.92)
Price: 248.59
Desc: SimplyNonVegPizza (350), Meat (14.25), Cheese (20.72), Cheese (20.72), Ham (18.1
Price: 423.81
```

Solution: