

Package ‘specieshindex’

August 19, 2021

Type Package

Title How (scientifically) popular is a given species?

Version 0.2.1

Date 2021-01-19

Author Jessica Tam

Maintainer Jessica Tam <tamtinying@gmail.com>

Description Finds the h-index of a species.

Depends R (\geq 3.5.0)

LazyData true

Imports rscopus,

wosr,
rbace,
taxize,
dplyr,
data.table,
httr,
XML,
jsonlite,
ggplot2,
ggpubr

Suggests testthat,

knitr,
roxygen2,
devtools,
rmarkdown,
RefManageR

License MIT + file LICENSE

URL <https://github.com/jessicatytam/specieshindex>

RoxygenNote 7.1.1

VignetteBuilder knitr

Encoding UTF-8

R topics documented:

Allindices	3
CountGenusT	3
CountGenusTAK	4
CountGenusTAK_base	5
CountGenusTAK_scopus	6
CountGenusTAK_wos	7
CountGenusT_base	8
CountGenusT_scopus	9
CountGenusT_wos	10
CountSpT	11
CountSpTAK	12
CountSpTAK_base	12
CountSpTAK_scopus	13
CountSpTAK_wos	15
CountSpT_base	16
CountSpT_scopus	17
CountSpT_wos	18
FetchGenusT	19
FetchGenusTAK	20
FetchGenusTAK_scopus	20
FetchGenusTAK_wos	21
FetchGenusT_scopus	22
FetchGenusT_wos	23
FetchSpT	24
FetchSpTAK	25
FetchSpTAK_scopus	26
FetchSpTAK_wos	27
FetchSpT_scopus	28
FetchSpT_wos	29
Koala	30
languages	30
Platypus	31
plotAllindices	31
Quokka	32
SourceType	32
SpH5	33
SpHAfterdate	33
SpHindex	34
Spi10	35
SpMindex	35
TotalCite	36
TotalJournals	37
TotalPub	37
Woylie	38
YearsPublishing	38

Allindices	<i>Index summary</i>
------------	----------------------

Description

This function returns a dataframe of the summary of all of the indices.

Usage

```
Allindices(data, genus, species, sourcetype = 0)
```

Arguments

data	The dataframe generated from FetchSpT or FetchSpTAK .
genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
sourcetype	Source type; default is 0, enter 1 to add SourceType variables.

Value

A datarame of all of the indices in the package.

Examples

```
data(Woylie)
Allindices(Woylie, genus = "genus_name", species = "species_name", sourcetype = 0)
```

CountGenusT	<i>CountSpT wrapper</i>
-------------	-------------------------

Description

This is a wrapper function for [CountGenusT_scopus](#), [CountGenusT_wos](#), and [CountGenusT_base](#).

Usage

```
CountGenusT(db, genus, synonyms, additionalkeywords)
```

Arguments

db	Literature database. Scopus ("scopus"), Web of Science ("wos"), or Base ("base").
genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.

Value

Search count of the genus with the given `genus`.

Examples

```
## Not run:
CountGenusT("scopus", genus = "Osphranter")

## End(Not run)
## Not run:
CountGenusT("scopus", genus = "Osphranter", synonyms = "Macropus", additionalkeywords = "conserv*")

## End(Not run)
```

CountGenusTAK	<i>CountSpTAK wrapper</i>
---------------	---------------------------

Description

This is a wrapper function for [CountGenusTAK_scopus](#), [CountGenusTAK_wos](#), and [CountGenusTAK_base](#).

Usage

```
CountGenusTAK(db, genus, synonyms, additionalkeywords)
```

Arguments

<code>db</code>	Literature database. Scopus ("scopus"), Web of Science ("wos"), or Base ("base").
<code>genus</code>	Genus classification from the binomial name.
<code>synonyms</code>	Alternate genus names.
<code>additionalkeywords</code>	Optional search terms.

Value

Search count of the genus with the given `genus`.

Examples

```
## Not run:
CountGenusTAK("scopus", genus = "Osphranter")

## End(Not run)
## Not run:
CountGenusTAK("scopus", genus = "Osphranter", synonyms = "Macropus", additionalkeywords = "conserv*")

## End(Not run)
```

CountGenusTAK_base	<i>Search count from BASE - title, abstract and author keywords</i>
--------------------	---

Description

This function counts the total number of search results. It counts the publications with the genus name in the title, abstract and author keywords. A check will be conducted via [gnr_resolve](#) to validate the genus name.

Usage

```
CountGenusTAK_base(genus, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.

Value

Search count of the genus with the given genus.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountGenusTAK_base("Bettongia")

#lower case letter in genus is also accepted and will return identical results

CountGenusTAK_base("bettongia")

## End(Not run)
## Not run:
CountGenusTAK_base("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountGenusTAK_base("bettongia", "conserv*")

## End(Not run)
```

CountGenusTAK_scopus *Search count from Scopus - title, abstract, and keywords*

Description

This function counts the total number of search results. It counts the publications with the genus name in the title, abstract, and keywords. A check will be conducted via [gnr.resolve](#) to validate the genus name.

Usage

```
CountGenusTAK_scopus(
  genus,
  synonyms,
  additionalkeywords,
  datatype = "application/xml"
)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.
datatype	Formats the URL to be sent to the API. The default is "application/xml".

Value

Search count of the genus with the given genus.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountGenusTAK_scopus("Bettongia")

#lower case letter in genus is also accepted and will return identical results

CountGenusTAK_scopus("bettongia")

## End(Not run)
## Not run:
CountGenusTAK_scopus("Bettongia")
```

```
#lower case letter in genus is also accepted and will return identical results

CountGenusTAK_scopus("bettongia")

## End(Not run)
```

CountGenusTAK_wos	<i>Search count from Web of Science - title, abstract and author keywords</i>
-------------------	---

Description

This function counts the total number of search results. It counts the publications with the genus name in the title, abstract and author keywords. A check will be conducted via [gnr_resolve](#) to validate the genus name.

Usage

```
CountGenusTAK_wos(genus, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.

Value

Search count of the genus with the given genus.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountGenusTAK_wos("Bettongia")

#lower case letter in genus is also accepted and will return identical results

CountGenusTAK_wos("bettongia")

## End(Not run)
## Not run:
CountGenusTAK_wos("Bettongia", "conserv*")
```

```
#lower case letter in genus is also accepted and will return identical results

CountGenusTAK_wos("bettongia", "conserv*")

## End(Not run)
```

CountGenusT_base	<i>Search count from BASE - title only</i>
------------------	--

Description

This function counts the total number of search results. It counts the publications with the genus name in the title only. A check will be conducted via [gnr_resolve](#) to validate the genus name.

Usage

```
CountGenusT_base(genus, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.

Value

Search count of the genus with the given genus.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountGenusT_base("Bettongia")

#lower case letter in genus is also accepted and will return identical results

CountGenusT_base("bettongia")

## End(Not run)
## Not run:
CountGenusT_base("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results
```



```
CountGenusT_base("bettongia", "conserv*")

## End(Not run)
```

CountGenusT_scopus	<i>Search count from Scopus - title only</i>
--------------------	--

Description

This function counts the total number of search results. It counts the publications with the genus name in the title only. A check will be conducted via [gnr_resolve](#) to validate the genus name.

Usage

```
CountGenusT_scopus(
  genus,
  synonyms,
  additionalkeywords,
  datatype = "application/xml"
)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.
datatype	Formats the URL to be sent to the API. The default is "application/xml".

Value

Search count of the genus with the given genus.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountGenusT_scopus("Bettongia")

#lower case letter in genus is also accepted and will return identical results

CountGenusT_scopus("bettongia")
```

```
## End(Not run)
## Not run:
CountGenusT_scopus("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountGenusT_scopus("bettongia", "conserv*")

## End(Not run)
```

CountGenusT_wos

Search count from Web of Science - title only

Description

This function counts the total number of search results. It counts the publications with the genus name in the title only. A check will be conducted via [gnr_resolve](#) to validate the genus name.

Usage

```
CountGenusT_wos(genus, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.

Value

Search count of the genus with the given genus.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountGenusT_wos("Bettongia")

#lower case letter in genus is also accepted and will return identical results

CountGenusT_wos("bettongia")
```

```
## End(Not run)
## Not run:
CountGenusT_wos("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountGenusT_wos("bettongia", "conserv*")

## End(Not run)
```

CountSpT	<i>CountSpT wrapper</i>
----------	-------------------------

Description

This is a wrapper function for [CountSpT.scopus](#), [CountSpT.wos](#), and [CountSpT.base](#).

Usage

```
CountSpT(db, genus, species, synonyms, additionalkeywords)
```

Arguments

db	Literature database. Scopus ("scopus"), Web of Science ("wos"), or Base ("base").
genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.

Value

Search count of the species with the given genus and species.

Examples

```
## Not run:
CountSpT("scopus", genus = "Osphranter", species = "rufus")

## End(Not run)
## Not run:
CountSpT("scopus", genus = "Osphranter", species = "rufus", synonyms = "Macropus rufus", additionalkeywords = "conserv*")

## End(Not run)
```

CountSpTAK	<i>CountSpTAK wrapper</i>
------------	---------------------------

Description

This is a wrapper function for [CountSpTAK_scopus](#), [CountSpTAK_wos](#), and [CountSpTAK_base](#).

Usage

CountSpTAK(db, genus, species, synonyms, additionalkeywords)

Arguments

- db Literature database. Scopus ("scopus"), Web of Science ("wos"), or Base ("base").
- genus Genus classification from the binomial name.
- species Species classification from the binomial name.
- synonyms Alternate species names.
- additionalkeywords Optional search terms.

Value

Search count of the species with the given genus and species.

Examples

```
## Not run:
CountSpTAK("scopus", genus = "Osphranter", species = "rufus")

## End(Not run)
## Not run:
CountSpTAK("scopus", genus = "Osphranter", species = "rufus", synonyms = "Macropus rufus", additionalkeywords = "c")

## End(Not run)
```

CountSpTAK_base	<i>Search count from BASE - title, abstract and author keywords</i>
-----------------	---

Description

This function counts the total number of search results. It counts the publications with the binomial name in the title, abstract and author keywords. A check will be conducted via [gnr_resolve](#) to validate the genus and species names.

Usage

```
CountSpTAK_base(genus, species, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.

Value

Search count of the species with the given `genus` and `species`.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountSpTAK_base("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

CountSpTAK_base("bettongia", "penicillata")

## End(Not run)
## Not run:
CountSpTAK_base("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountSpTAK_base("bettongia", "penicillata", "conserv*")

## End(Not run)
```

CountSpTAK_scopus	<i>Search count from Scopus - title, abstract, and keywords</i>
-------------------	---

Description

This function counts the total number of search results. It counts the publications with the binomial name in the title, abstract, and keywords. A check will be conducted via [gnr_resolve](#) to validate the genus and species names.

Usage

```
CountSpTAK_scopus(
  genus,
  species,
  synonyms,
  additionalkeywords,
  datatype = "application/xml"
)
```

Arguments

<code>genus</code>	Genus classification from the binomial name.
<code>species</code>	Species classification from the binomial name.
<code>synonyms</code>	Alternate species names.
<code>additionalkeywords</code>	Optional search terms.
<code>datatype</code>	Formats the URL to be sent to the API. The default is "application/xml".

Value

Search count of the species with the given `genus` and `species`.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountSpTAK_scopus("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

CountSpTAK_scopus("bettongia", "penicillata")

## End(Not run)
## Not run:
CountSpTAK_scopus("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

CountSpTAK_scopus("bettongia", "penicillata")

## End(Not run)
```

CountSpTAK_wos	<i>Search count from Web of Science - title, abstract and author keywords</i>
----------------	---

Description

This function counts the total number of search results. It counts the publications with the binomial name in the title, abstract and author keywords. A check will be conducted via [gnr_resolve](#) to validate the genus and species names.

Usage

```
CountSpTAK_wos(genus, species, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.

Value

Search count of the species with the given genus and species.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountSpTAK_wos("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

CountSpTAK_wos("bettongia", "penicillata")

## End(Not run)
## Not run:
CountSpTAK_wos("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountSpTAK_wos("bettongia", "penicillata", "conserv*")

## End(Not run)
```

CountSpT_base	<i>Search count from BASE - title only</i>
---------------	--

Description

This function counts the total number of search results. It counts the publications with the binomial name in the title only. A check will be conducted via [gnr.resolve](#) to validate the genus and species names.

Usage

```
CountSpT_base(genus, species, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.

Value

Search count of the species with the given genus and species.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountSpT_base("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

CountSpT_base("bettongia", "penicillata")

## End(Not run)
## Not run:
CountSpT_base("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountSpT_base("bettongia", "penicillata", "conserv*")

## End(Not run)
```

CountSpT_scopus	<i>Search count from Scopus - title only</i>
-----------------	--

Description

This function counts the total number of search results. It counts the publications with the binomial name in the title only. A check will be conducted via [gnr.resolve](#) to validate the genus and species names.

Usage

```
CountSpT_scopus(
  genus,
  species,
  synonyms,
  additionalkeywords,
  datatype = "application/xml"
)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.
datatype	Formats the URL to be sent to the API. The default is "application/xml".

Value

Search count of the species with the given `genus` and `species`.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountSpT_scopus("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

CountSpT_scopus("bettongia", "penicillata")

## End(Not run)
## Not run:
```

```
CountSpT_scopus("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountSpT_scopus("bettongia", "penicillata", "conserv*")

## End(Not run)
```

CountSpT_wos

Search count from Web of Science - title only

Description

This function counts the total number of search results. It counts the publications with the binomial name in the title only. A check will be conducted via [gnr_resolve](#) to validate the genus and species names.

Usage

```
CountSpT_wos(genus, species, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.

Value

Search count of the species with the given genus and species.

References

Chamberlain, S. & Szocs, E. (2013). taxize - taxonomic search and retrieval in R. *F1000Research*, 2, 191.

Examples

```
## Not run:
CountSpT_wos("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

CountSpT_wos("bettongia", "penicillata")

## End(Not run)
## Not run:
```

```
CountSpT_wos("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

CountSpT_wos("bettongia", "penicillata", "conserv*")

## End(Not run)
```

FetchGenusT	<i>FetchGenusT wrapper</i>
-------------	----------------------------

Description

This is a wrapper function for [FetchSpT_scopus](#), and [FetchSpT_wos](#).

Usage

```
FetchGenusT(db, genus, synonyms, additionalkeywords, language = 0)
```

Arguments

db	Literature database. Scopus ("scopus") or Web of Science ("wos").
genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.
language	Language of the paper; default is 0, enter 1 to retrieve the variable. Scopus only.

Value

A dataframe of the genus' citation records with the given genus.

Examples

```
## Not run:
FetchGenusT("scopus", genus = "Osphranter")

## End(Not run)
## Not run:
FetchGenusT("scopus", genus = "Osphranter", synonyms = "Macropus", additionalkeywords = "conserv*")

## End(Not run)
```

FetchGenusTAK	<i>FetchGenusTAK wrapper</i>
---------------	------------------------------

Description

This is a wrapper function for [FetchGenusTAK_scopus](#), and [FetchGenusTAK_wos](#).

Usage

```
FetchGenusTAK(db, genus, synonyms, additionalkeywords, language = 0)
```

Arguments

db	Literature database. Scopus ("scopus") or Web of Science ("wos").
genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.
language	Language of the paper; default is 0, enter 1 to retrieve the variable. Scopus only.

Value

A dataframe of the genus' citation records with the given genus.

Examples

```
## Not run:
FetchGenusTAK("scopus", genus = "Osphranter")

## End(Not run)
## Not run:
FetchGenusTAK("scopus", genus = "Osphranter", synonyms = "Macropus", additionalkeywords = "conserv*")

## End(Not run)
```

FetchGenusTAK_scopus	<i>Fetch data from Scopus - title, abstract and keywords</i>
----------------------	--

Description

This function fetches citation information from Scopus using genus name found in the title, abstract and keywords of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchGenusTAK_scopus(genus, synonyms, additionalkeywords, language = 0)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.
language	Language of the paper; default is 0, enter 1 to retrieve the variable.

Value

A dataframe of the genus' citation records with the given genus.

Examples

```
## Not run:
FetchGenusTAK_scopus("Bettongia")

#lower case letter in genus is also accepted and will return identical results

FetchGenusTAK_scopus("bettongia")

## End(Not run)
## Not run:
FetchGenusTAK_scopus("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchGenusTAK_scopus("bettongia", "conserv*")

## End(Not run)
```

FetchGenusTAK_wos	<i>Fetch data from Web of Science - title, abstract and author keywords.</i>
-------------------	--

Description

This function fetches citation information from Web of Science using genus name found in the title, abstract and author keywords of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchGenusTAK_wos(genus, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.

Value

A dataframe of the genus' citation records with the given genus.

Examples

```
## Not run:
FetchGenusTAK_wos("Bettongia")

#lower case letter in genus is also accepted and will return identical results

FetchGenusTAK_wos("bettongia")

## End(Not run)
## Not run:
FetchGenusTAK_wos("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchGenusTAK_wos("bettongia", "conserv*")

## End(Not run)
```

FetchGenusT_scopus	<i>Fetch data from Scopus - title only</i>
--------------------	--

Description

This function fetches citation information from Scopus using genus name found in the title of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchGenusT_scopus(genus, synonyms, additionalkeywords, language = 0)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.
language	Language of the paper; default is 0, enter 1 to retrieve the variable.

Value

A dataframe of the genus' citation records with the given genus.

Examples

```
## Not run:
FetchGenusT_scopus("Bettongia")

#lower case letter in genus is also accepted and will return identical results

FetchGenusT_scopus("bettongia")

## End(Not run)
## Not run:
FetchGenusT_scopus("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchGenusT_scopus("bettongia", "conserv*")

## End(Not run)
```

FetchGenusT_wos	<i>Fetch data from Web of Science - title only</i>
-----------------	--

Description

This function fetches citation information from Web of Science using genus name found in the title of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchGenusT_wos(genus, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
synonyms	Alternate genus names.
additionalkeywords	Optional search terms.

Value

A dataframe of the genus' citation records with the given genus.

Examples

```
## Not run:
FetchGenusT_wos("Bettongia")

#lower case letter in genus is also accepted and will return identical results

FetchGenusT_wos("bettongia")

## End(Not run)
## Not run:
FetchGenusT_wos("Bettongia", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchGenusT_wos("bettongia", "conserv*")

## End(Not run)
```

FetchSpT

FetchSpT wrapper

Description

This is a wrapper function for [FetchSpT.scopus](#), [FetchSpT.wos](#), and [FetchSpT.base](#).

Usage

```
FetchSpT(db, genus, species, synonyms, additionalkeywords, language = 0)
```

Arguments

db	Literature database. Scopus ("scopus") or Web of Science ("wos").
genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.
language	Language of the paper; default is 0, enter 1 to retrieve the variable. Scopus only.

Value

A dataframe of the species' citation records with the given `genus` and `species`.

Examples

```
## Not run:
FetchSpT("scopus", genus = "Osphranter", species = "rufus")

## End(Not run)
## Not run:
FetchSpT("scopus", genus = "Osphranter", species = "rufus", synonyms = "Macropus rufus", additionalkeywords = "conservation")

## End(Not run)
```

FetchSpTAK	<i>FetchSpTAK wrapper</i>
------------	---------------------------

Description

This is a wrapper function for [FetchSpTAK_scopus](#), [FetchSpTAK_wos](#), and [FetchSpTAK_base](#).

Usage

```
FetchSpTAK(db, genus, species, synonyms, additionalkeywords, language = 0)
```

Arguments

- db Literature database. Scopus ("scopus") or Web of Science ("wos").
- genus Genus classification from the binomial name.
- species Species classification from the binomial name.
- synonyms Alternate species names.
- additionalkeywords Optional search terms.
- language Language of the paper; default is 0, enter 1 to retrieve the variable. Scopus only.

Value

A dataframe of the species' citation records with the given genus and species.

Examples

```
## Not run:
FetchSpTAK("scopus", genus = "Osphranter", species = "rufus")

## End(Not run)
## Not run:
FetchSpTAK("scopus", genus = "Osphranter", species = "rufus", synonyms = "Macropus rufus", additionalkeywords = "conservation")

## End(Not run)
```

FetchSpTAK_scopus

Fetch data from Scopus - title, abstract and keywords

Description

This function fetches citation information from Scopus using genus and species name found in the title, abstract and keywords of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchSpTAK_scopus(genus, species, synonyms, additionalkeywords, language = 0)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.
language	Language of the paper; default is 0, enter 1 to retrieve the variable.

Value

A dataframe of the species' citation records with the given genus and species.

Examples

```
## Not run:
FetchSpTAK_scopus("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

FetchSpTAK_scopus("bettongia", "penicillata")

## End(Not run)
## Not run:
FetchSpTAK_scopus("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchSpTAK_scopus("bettongia", "penicillata", "conserv*")

## End(Not run)
```

FetchSpTAK_wos	<i>Fetch data from Web of Science - title, abstract and author keywords.</i>
----------------	--

Description

This function fetches citation information from Web of Science using genus and species name found in the title, abstract and author keywords of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchSpTAK_wos(genus, species, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.

Value

A dataframe of the species' citation records with the given `genus` and `species`.

Examples

```
## Not run:
FetchSpTAK_wos("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

FetchSpTAK_wos("bettongia", "penicillata")

## End(Not run)
## Not run:
FetchSpTAK_wos("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchSpTAK_wos("bettongia", "penicillata", "conserv*")

## End(Not run)
```

FetchSpT_scopus

Fetch data from Scopus - title only

Description

This function fetches citation information from Scopus using genus and species name found in the title of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchSpT_scopus(genus, species, synonyms, additionalkeywords, language = 0)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.
language	Language of the paper; default is 0, enter 1 to retrieve the variable.

Value

A dataframe of the species' citation records with the given genus and species.

Examples

```
## Not run:
FetchSpT_scopus("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

FetchSpT_scopus("bettongia", "penicillata")

## End(Not run)
## Not run:
FetchSpT_scopus("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchSpT_scopus("bettongia", "penicillata", "conserv*")

## End(Not run)
```

FetchSpT_wos*Fetch data from Web of Science - title only*

Description

This function fetches citation information from Web of Science using genus and species name found in the title of the publications. Duplicates are to be removed by the user after fetching the data.

Usage

```
FetchSpT_wos(genus, species, synonyms, additionalkeywords)
```

Arguments

genus	Genus classification from the binomial name.
species	Species classification from the binomial name.
synonyms	Alternate species names.
additionalkeywords	Optional search terms.

Value

A dataframe of the species' citation records with the given genus and species.

Examples

```
## Not run:
FetchSpT_wos("Bettongia", "penicillata")

#lower case letter in genus is also accepted and will return identical results

FetchSpT_wos("bettongia", "penicillata")

## End(Not run)
## Not run:
FetchSpT_wos("Bettongia", "penicillata", "conserv*")

#lower case letter in genus is also accepted and will return identical results

FetchSpT_wos("bettongia", "penicillata", "conserv*")

## End(Not run)
```

Koala

Koala dataset

Description

Citation records of koala (*Phascolarctos cinereus*) from Scopus. Data was retrieved on 10 July 2020.

Usage

Koala

Format

A data frame with 773 rows and 20 variables

Source

<http://api.elsevier.com/content/search/scopus>

languages

Languages

Description

List of languages of documents found on Scopus. Data was retrieved on 9 March 2021.

Usage

languages

Format

A csv file with the complete list of languages of documents found on Scopus.

Source

<https://www.elsevier.com/solutions/scopus/how-scopus-works/content>

Platypus	<i>Platypus dataset</i>
----------	-------------------------

Description

Citation records of platypus (*Ornithorhynchus anatinus*) from Scopus. Data was retrieved on 10 July 2020.

Usage

Platypus

Format

A data frame with 321 rows and 20 variables

Source

<http://api.elsevier.com/content/search/scopus>

plotAllindices	<i>Plot</i>
----------------	-------------

Description

Plots the data of a single species or combined.

Usage

```
plotAllindices(data)
```

Arguments

data The dataframe generated from [Allindices](#).

Value

ggplot

Examples

```
W <- Allindices(Woylie, genus = "Bettongia", species = "penicillata")
Q <- Allindices(Quokka, genus = "Setonix", species = "brachyurus")
P <- Allindices(Platypus, genus = "Ornithorhynchus", species = "anatinus")
K <- Allindices(Koala, genus = "Phascolarctos", species = "cinereus")
CombineSp <- dplyr::bind_rows(W, Q, P, K)
plotAllindices(CombineSp)
```

Quokka	<i>Quokka dataset</i>
--------	-----------------------

Description

Citation records of quokka (*Setonix brachyurus*) from Scopus. Data was retrieved on 10 July 2020.

Usage

Quokka

Format

A data frame with 242 rows and 20 variables

Source

<http://api.elsevier.com/content/search/scopus>

SourceType	<i>Source type</i>
------------	--------------------

Description

This function calculates the total number of items for each document type.

Usage

SourceType(data)

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

A dataframe with each document and their counts.

Examples

```
data(Woylie)
SourceType(Woylie)
```

SpH5	<i>Species h5 index</i>
------	-------------------------

Description

This function calculates the h-index of a species in the past 5 years.

Usage

```
SpH5(data)
```

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

H5 index.

References

Suzuki, H. (2012). *Google Scholar Metrics for Publications*. Retrieved from <https://scholar.googleblog.com/2012/04/google-scholar-metrics-for-publications.html>.

Examples

```
data(Woylie)
SpH5(Woylie)
```

SpHAfterdate	<i>Species h-index with a given time frame</i>
--------------	--

Description

This function calculates the h-index using a given date up till the newest record.

Usage

```
SpHAfterdate(data, date)
```

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).
date The lower limit of the timeframe.

Value

H-index of the given time period.

Examples

```
data(Woylie)
SpHAfterdate(Woylie, "2000-01-01")
```

SpHindex	<i>Species h-index</i>
----------	------------------------

Description

This function calculates the h-index of a species.

Usage

```
SpHindex(data)
```

Arguments

`data` The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

H-index.

References

Bertoli-Barsotti, L. & Lando, T. (2015). On a formula for the h-index. *Journal of Informetrics*, 9(4), 762-776.

Hirsch, J. (2005). An index to quantify an individual's scientific research output. *Proceedings of the National Academy of Sciences of the United States of America*, 102(46), 16569-16572.

Examples

```
data(Woylie)
SpHindex(Woylie)
```

Spi10	<i>Species i10 index</i>
-------	--------------------------

Description

This function calculates the i10 index of a species. i10 index counts all of the publications with 10 or more citations.

Usage

```
Spi10(data)
```

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

i10 index.

References

Cornell University (2019). *i10-index*. Retrieved from <https://guides.library.cornell.edu/c.php?g=32272&p=203393>.

Examples

```
data(Woylie)
Spi10(Woylie)
```

SpMindex	<i>Species m-index</i>
----------	------------------------

Description

This function calculates the m-index of species. M-index uses the h-index and divides it by the number of years of activity.

Usage

```
SpMindex(data)
```

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

M-index.

References

University of Pittsburgh (2019). *Research Impact and Metrics: Author metrics*. Retrieved from <https://pitt.libguides.com/bibliometricIndicators/AuthorMetrics>.

Examples

```
data(Woylie)
SpMindex(Woylie)
```

TotalCite*Total citations*

Description

This function calculates the total number of citations.

Usage

```
TotalCite(data)
```

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

A numerical value of the total number of citations.

Examples

```
data(Woylie)
TotalCite(Woylie)
```

TotalJournals	<i>Total journals</i>
---------------	-----------------------

Description

This function calculates the total number of journals.

Usage

```
TotalJournals(data)
```

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

An integer of the total number of journals.

Examples

```
data(Woylie)
TotalJournals(Woylie)
```

TotalPub	<i>Total publications</i>
----------	---------------------------

Description

This function calculates the total number of publications.

Usage

```
TotalPub(data)
```

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

An integer of the total number of publications.

Examples

```
data(Woylie)
TotalPub(Woylie)
```

Woylie	<i>Woylie dataset</i>
--------	-----------------------

Description

Citation records of woylie (*Bettongia penicillata*) from Scopus. Data was retrieved on 10 July 2020.

Usage

Woylie

Format

A data frame with 113 rows and 20 variables

Source

<http://api.elsevier.com/content/search/scopus>

YearsPublishing	<i>Years since first publication</i>
-----------------	--------------------------------------

Description

The number of years since the first publication in relation to the species.

Usage

YearsPublishing(data)

Arguments

data The dataframe generated from [FetchSpT](#) or [FetchSpTAK](#).

Value

Number of years.

Examples

```
data(Woylie)
YearsPublishing(Woylie)
```

Index

* datasets

- Koala, [30](#)
- languages, [30](#)
- Platypus, [31](#)
- Quokka, [32](#)
- Woylie, [38](#)

Allindices, [3](#), [31](#)

CountGenusT, [3](#)
CountGenusT_base, [3](#), [8](#)
CountGenusT_scopus, [3](#), [9](#)
CountGenusT_wos, [3](#), [10](#)
CountGenusTAK, [4](#)
CountGenusTAK_base, [4](#), [5](#)
CountGenusTAK_scopus, [4](#), [6](#)
CountGenusTAK_wos, [4](#), [7](#)
CountSpT, [11](#)
CountSpT_base, [11](#), [16](#)
CountSpT_scopus, [11](#), [17](#)
CountSpT_wos, [11](#), [18](#)
CountSpTAK, [12](#)
CountSpTAK_base, [12](#), [12](#)
CountSpTAK_scopus, [12](#), [13](#)
CountSpTAK_wos, [12](#), [15](#)

FetchGenusT, [19](#)
FetchGenusT_scopus, [22](#)
FetchGenusT_wos, [23](#)
FetchGenusTAK, [20](#)
FetchGenusTAK_scopus, [20](#), [20](#)
FetchGenusTAK_wos, [20](#), [21](#)
FetchSpT, [3](#), [24](#), [32–38](#)
FetchSpT_base, [24](#)
FetchSpT_scopus, [19](#), [24](#), [28](#)
FetchSpT_wos, [19](#), [24](#), [29](#)
FetchSpTAK, [3](#), [25](#), [32–38](#)
FetchSpTAK_base, [25](#)
FetchSpTAK_scopus, [25](#), [26](#)
FetchSpTAK_wos, [25](#), [27](#)

gnr_resolve, [5–10](#), [12](#), [13](#), [15–18](#)

Koala, [30](#)

languages, [30](#)

Platypus, [31](#)

plotAllindices, [31](#)

Quokka, [32](#)

SourceType, [32](#)

Sph5, [33](#)

SphAfterdate, [33](#)

Sphindex, [34](#)

Spi10, [35](#)

SpMindex, [35](#)

TotalCite, [36](#)

TotalJournals, [37](#)

TotalPub, [37](#)

Woylie, [38](#)

YearsPublishing, [38](#)