

Pharmacy Management System: HTML to PHP Conversion Analysis

I'll analyze your pharmacy management system files and provide a detailed step-by-step guide to convert the HTML files to PHP with database integration. Let's start by examining the current structure and then outline the conversion process.

Current System Analysis

From the provided files, I can see you have a basic pharmacy management system with:

1. **Admin Dashboard** - For managing vendors, inventory, products, sales, and customers
2. **Staff Dashboard** - For daily operations like inventory management, sales, and customer interactions
3. **Login Systems** - Separate login pages for staff and admin
4. **Basic UI Components** - CSS styling and JavaScript for a slider component

Let me outline a comprehensive plan to convert this to a PHP-based system with database connectivity.

Step 1: Set Up Database Structure

First, let's create the necessary database structure:

Copy-- Create database

```
CREATE DATABASE pharmacy_management;
```

```
USE pharmacy_management;
```

```
-- Users table (for both admin and staff)
```

```
CREATE TABLE users (
```

```
    user_id INT AUTO_INCREMENT PRIMARY KEY,
```

```
    username VARCHAR(50) NOT NULL UNIQUE,
```

```
    password VARCHAR(255) NOT NULL, -- Store hashed passwords
```

```
    role ENUM('admin', 'staff') NOT NULL,
```

```
full_name VARCHAR(100) NOT NULL,  
  
email VARCHAR(100) NOT NULL,  
  
created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

-- Vendors table

```
CREATE TABLE vendors (  
  
    vendor_id INT AUTO_INCREMENT PRIMARY KEY,  
  
    vendor_name VARCHAR(100) NOT NULL,  
  
    location VARCHAR(255) NOT NULL,  
  
    contact_person VARCHAR(100),  
  
    phone VARCHAR(20),  
  
    email VARCHAR(100),  
  
    address TEXT,  
  
    status ENUM('active', 'inactive') DEFAULT 'active',  
  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  
    updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE  
CURRENT_TIMESTAMP  
);
```

-- Products/Medicines table

```
CREATE TABLE products (  
  
    product_id INT AUTO_INCREMENT PRIMARY KEY,  
  
    product_name VARCHAR(100) NOT NULL,  
  
    generic_name VARCHAR(100),
```

```
category VARCHAR(50),

vendor_id INT,

cost_price DECIMAL(10,2) NOT NULL,

selling_price DECIMAL(10,2) NOT NULL,

quantity INT NOT NULL DEFAULT 0,

reorder_level INT DEFAULT 10,

expiry_date DATE,

description TEXT,

created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,

updated_at  TIMESTAMP  DEFAULT  CURRENT_TIMESTAMP  ON  UPDATE
CURRENT_TIMESTAMP,

FOREIGN KEY (vendor_id) REFERENCES vendors(vendor_id)

);
```

-- Customers table

```
CREATE TABLE customers (

customer_id INT AUTO_INCREMENT PRIMARY KEY,

customer_name VARCHAR(100) NOT NULL,

phone VARCHAR(20),

email VARCHAR(100),

address TEXT,

created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,

updated_at  TIMESTAMP  DEFAULT  CURRENT_TIMESTAMP  ON  UPDATE
CURRENT_TIMESTAMP

);
```

-- Sales table

```
CREATE TABLE sales (  
    sale_id INT AUTO_INCREMENT PRIMARY KEY,  
    invoice_number VARCHAR(20) NOT NULL,  
    customer_id INT,  
    sale_date TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    total_amount DECIMAL(10,2) NOT NULL,  
    payment_method ENUM('cash', 'card', 'other') DEFAULT 'cash',  
    user_id INT NOT NULL, -- Staff who processed the sale  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (customer_id) REFERENCES customers(customer_id),  
    FOREIGN KEY (user_id) REFERENCES users(user_id)  
);
```

-- Sale items table

```
CREATE TABLE sale_items (  
    sale_item_id INT AUTO_INCREMENT PRIMARY KEY,  
    sale_id INT NOT NULL,  
    product_id INT NOT NULL,  
    quantity INT NOT NULL,  
    unit_price DECIMAL(10,2) NOT NULL,  
    total_price DECIMAL(10,2) NOT NULL,  
    FOREIGN KEY (sale_id) REFERENCES sales(sale_id),
```

```

        FOREIGN KEY (product_id) REFERENCES products(product_id)
    );

-- Inventory transactions table

CREATE TABLE inventory_transactions (

    transaction_id INT AUTO_INCREMENT PRIMARY KEY,

    product_id INT NOT NULL,

    transaction_type ENUM('purchase', 'sale', 'adjustment') NOT NULL,

    quantity INT NOT NULL,

    transaction_date TIMESTAMP DEFAULT CURRENT_TIMESTAMP,

    reference_id INT, -- Could be sale_id, purchase_id, etc.

    notes TEXT,

    user_id INT NOT NULL,

    FOREIGN KEY (product_id) REFERENCES products(product_id),

    FOREIGN KEY (user_id) REFERENCES users(user_id)

);

```

Step 2: Create Database Connection File

Create a file named config/database.php:

Copy<?php

```
// Database configuration
```

```
define('DB_SERVER', 'localhost');
```

```
define('DB_USERNAME', 'root'); // Replace with your database username
```

```
define('DB_PASSWORD', ''); // Replace with your database password
```

```
define('DB_NAME', 'pharmacy_management');
```

```
// Attempt to connect to MySQL database
```

```
$conn = mysqli_connect(DB_SERVER, DB_USERNAME, DB_PASSWORD, DB_NAME);
```

```
// Check connection
```

```
if($conn === false){
```

```
    die("ERROR: Could not connect to database. " . mysqli_connect_error());
```

```
}
```

```
// Set charset to ensure proper handling of special characters
```

```
mysqli_set_charset($conn, "utf8mb4");
```

```
?>
```

Step 3: Create Authentication System

Create session.php

Copy<?php

```
// Initialize the session
```

```
session_start();
```

```
// Check if the user is logged in
```

```
function isLoggedIn() {
```

```
    return isset($_SESSION["loggedin"]) && $_SESSION["loggedin"] === true;
```

```
}
```

```
// Check if the user is an admin
```

```
function isAdmin() {  
    return isLoggedIn() && isset($_SESSION["role"]) && $_SESSION["role"] === "admin";  
}
```

// Check if the user is staff

```
function isStaff() {  
    return isLoggedIn() && isset($_SESSION["role"]) && $_SESSION["role"] === "staff";  
}
```

// Redirect if not logged in

```
function requireLogin() {  
    if(!isLoggedIn()) {  
        header("location: login.php");  
        exit;  
    }  
}
```

// Redirect if not admin

```
function requireAdmin() {  
    requireLogin();  
    if(!isAdmin()) {  
        header("location: index.php?error=unauthorized");  
        exit;  
    }  
}
```

```

}

// Redirect if not staff

function requireStaff() {

    requireLogin();

    if(!isStaff() && !isAdmin()) {

        header("location: index.php?error=unauthorized");

        exit;

    }

}

?>

```

Convert login_admin.html to login.php

Copy<?php

```

// Include config file

require_once "config/database.php";

require_once "config/session.php";


// Check if already logged in

if(isLoggedIn()) {

    // Redirect based on role

    if(isAdmin()) {

        header("location: admin_dashboard.php");

    } else {

        header("location: staff_dashboard.php");

```

```
}

exit;

}


// Define variables and initialize with empty values

$username = $password = "";

$username_err = $password_err = $login_err = "";


// Processing form data when form is submitted

if($_SERVER["REQUEST_METHOD"] == "POST"){


    // Check if username is empty

    if(empty(trim($_POST["username"]))) {

        $username_err = "Please enter username.";

    } else {

        $username = trim($_POST["username"]);

    }


    // Check if password is empty

    if(empty(trim($_POST["password"]))) {

        $password_err = "Please enter your password.";

    } else {

        $password = trim($_POST["password"]);

    }

}
```

```

// Validate credentials

if(empty($username_err) && empty($password_err)){

    // Prepare a select statement

    $sql = "SELECT user_id, username, password, role, full_name FROM users WHERE
username = ?";

    if($stmt = mysqli_prepare($conn, $sql)){

        // Bind variables to the prepared statement as parameters

        mysqli_stmt_bind_param($stmt, "s", $param_username);

        // Set parameters

        $param_username = $username;

        // Attempt to execute the prepared statement

        if(mysqli_stmt_execute($stmt)){

            // Store result

            mysqli_stmt_store_result($stmt);

            // Check if username exists, if yes then verify password

            if(mysqli_stmt_num_rows($stmt) == 1){

                // Bind result variables

                mysqli_stmt_bind_result($stmt, $id, $username, $hashed_password, $role,
$full_name);

                if(mysqli_stmt_fetch($stmt)){

```

```
if(password_verify($password, $hashed_password)){

    // Password is correct, so start a new session

    session_start();

    // Store data in session variables

    $_SESSION["loggedin"] = true;

    $_SESSION["user_id"] = $id;

    $_SESSION["username"] = $username;

    $_SESSION["role"] = $role;

    $_SESSION["full_name"] = $full_name;

    // Redirect user to appropriate dashboard

    if($role == "admin"){

        header("location: admin_dashboard.php");

    } else {

        header("location: staff_dashboard.php");

    }

} else{

    // Password is not valid

    $login_err = "Invalid username or password.";

}

}

} else{

    // Username doesn't exist
```

```
$login_err = "Invalid username or password.";

}

} else{

    echo "Oops! Something went wrong. Please try again later.";

}


// Close statement

mysqli_stmt_close($stmt);

}

}


// Close connection

mysqli_close($conn);

}

?>


<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Login - Pharmacy Management System</title>

    <link rel="stylesheet" href="css/styles.css">

</head>
```

```
<body>

<div class="container">

    <h2>Login</h2>

    <?php

    if(!empty($login_err)){

        echo '<div class="alert alert-danger">' . $login_err . '</div>';

    }

    ?>

    <form action="<?php echo htmlspecialchars($_SERVER["PHP_SELF"]); ?>"
method="post">

        <div class="form-group">

            <label>Username</label>

            <input type="text" name="username" class="form-control <?php echo
(!empty($username_err)) ? 'is-invalid' : ''; ?>" value="<?php echo $username; ?>">

            <span class="invalid-feedback"><?php echo $username_err; ?></span>

        </div>

        <div class="form-group">

            <label>Password</label>

            <input type="password" name="password" class="form-control <?php echo
(!empty($password_err)) ? 'is-invalid' : ''; ?>">

            <span class="invalid-feedback"><?php echo $password_err; ?></span>

        </div>

        <div class="form-group">
```

```
        <input type="submit" class="btn btn-primary" value="Login">

    </div>

</form>

</div>

</body>

</html>
```

Step 4: Convert admin_dashboard.html to admin_dashboard.php

Copy<?php

```
// Include config files
```

```
require_once "config/database.php";
```

```
require_once "config/session.php";
```

```
// Check if user is admin, redirect if not
```

```
requireAdmin();
```

```
// Get dashboard stats
```

```
$totalVendors = 0;
```

```
$totalProducts = 0;
```

```
$totalSales = 0;
```

```
$totalCustomers = 0;
```

```
// Count vendors
```

```
$sql = "SELECT COUNT(*) as count FROM vendors";
```

```
$result = mysqli_query($conn, $sql);
```

```
if($result && $row = mysqli_fetch_assoc($result)) {  
    $totalVendors = $row['count'];  
}  
  
// Count products  
$sql = "SELECT COUNT(*) as count FROM products";  
$result = mysqli_query($conn, $sql);  
if($result && $row = mysqli_fetch_assoc($result)) {  
    $totalProducts = $row['count'];  
}  
  
// Count sales  
$sql = "SELECT COUNT(*) as count FROM sales";  
$result = mysqli_query($conn, $sql);  
if($result && $row = mysqli_fetch_assoc($result)) {  
    $totalSales = $row['count'];  
}  
  
// Count customers  
$sql = "SELECT COUNT(*) as count FROM customers";  
$result = mysqli_query($conn, $sql);  
if($result && $row = mysqli_fetch_assoc($result)) {  
    $totalCustomers = $row['count'];  
}
```

?>

<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8">

<meta name="viewport" content="width=device-width, initial-scale=1.0">

<title>Admin Dashboard - Pharmacy Management System</title>

<link rel="stylesheet" href="css/styles.css">

</head>

<body>

<header>

<div class="container">

<h1>Admin Dashboard</h1>

<div class="user-info">

Welcome, <?php echo htmlspecialchars(\$_SESSION["full_name"]); ?> |

Logout

</div>

</div>

</header>

<main class="container">

<div class="dashboard-stats">

<div class="stat-box">

<h3>Vendors</h3>

<p class="stat-number"><?php echo \$totalVendors; ?></p>

Manage

</div>

<div class="stat-box">

<h3>Products</h3>

<p class="stat-number"><?php echo \$totalProducts; ?></p>

Manage

</div>

<div class="stat-box">

<h3>Sales</h3>

<p class="stat-number"><?php echo \$totalSales; ?></p>

View

</div>

<div class="stat-box">

<h3>Customers</h3>

<p class="stat-number"><?php echo \$totalCustomers; ?></p>

Manage

</div>

</div>

```
<div class="dashboard-actions">
```

```
  <div class="action-box">
```

```
    <h3>Manage Vendors</h3>
```

```
    <p>Add or edit pharmaceutical vendors.</p>
```

```
    <a href="manage_vendors.php" class="btn btn-primary">Go to Manage  
Vendors</a>
```

```
  </div>
```

```
<div class="action-box">
```

```
  <h3>Manage Inventory</h3>
```

```
  <p>Track medicine stock and update inventory.</p>
```

```
  <a href="manage_inventory.php" class="btn btn-primary">Go to Inventory</a>
```

```
</div>
```

```
<div class="action-box">
```

```
  <h3>Product Details</h3>
```

```
  <p>View and edit product information.</p>
```

```
  <a href="product_details.php" class="btn btn-primary">View Products</a>
```

```
</div>
```

```
<div class="action-box">
```

```
  <h3>Sales Details</h3>
```

```
  <p>Review sales performance and reports.</p>
```

```
  <a href="sales_details.php" class="btn btn-primary">View Sales</a>
```

```
</div>
```

```
<div class="action-box">

    <h3>Customer Details</h3>

    <p>Manage and view customer records.</p>

    <a href="customer_details.php" class="btn btn-primary">View Customers</a>

</div>

</div>

</main>
```

```
<script src="js/script.js"></script>

</body>

</html>
```

Step 5: Convert manage_vendors.html to manage_vendors.php

Copy<?php

```
// Include config files
```

```
require_once "config/database.php";
```

```
require_once "config/session.php";
```

```
// Check if user is admin, redirect if not
```

```
requireAdmin();
```

```
// Define variables
```

```
$vendors = [];
```

```
$success_message = "";
```

```

$error_message = "";

// Handle vendor deletion

if(isset($_GET['delete']) && is_numeric($_GET['delete'])) {

    $vendor_id = $_GET['delete'];

    // Check if vendor has associated products

    $check_sql = "SELECT COUNT(*) as count FROM products WHERE vendor_id = ?";

    if($stmt = mysqli_prepare($conn, $check_sql)) {

        mysqli_stmt_bind_param($stmt, "i", $vendor_id);

        mysqli_stmt_execute($stmt);

        mysqli_stmt_store_result($stmt);

        mysqli_stmt_bind_result($stmt, $product_count);

        mysqli_stmt_fetch($stmt);

        if($product_count > 0) {

            $error_message = "Cannot delete vendor because they have $product_count associated
products.";

        } else {

            // Delete the vendor if no products are associated

            $delete_sql = "DELETE FROM vendors WHERE vendor_id = ?";

            if($delete_stmt = mysqli_prepare($conn, $delete_sql)) {

                mysqli_stmt_bind_param($delete_stmt, "i", $vendor_id);

                if(mysqli_stmt_execute($delete_stmt)) {

                    $success_message = "Vendor deleted successfully.";

```

```

        } else {

            $error_message = "Error deleting vendor.";

        }

        mysqli_stmt_close($delete_stmt);

    }

}

mysqli_stmt_close($stmt);

}

}

```

```
// Fetch all vendors
```

```
$sql = "SELECT vendor_id, vendor_name, location, contact_person, phone, email FROM
vendors ORDER BY vendor_name";
```

```
$result = mysqli_query($conn, $sql);
```

```
if($result) {

    while($row = mysqli_fetch_assoc($result)) {

        $vendors[] = $row;

    }

}

?>

```

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
<title>Manage Vendors - Pharmacy Management System</title>
```

```
<link rel="stylesheet" href="css/styles.css">
```

```
</head>
```

```
<body>
```

```
<header>
```

```
<div class="container">
```

```
<h1>Manage Vendors</h1>
```

```
<div class="user-info">
```

```
Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |
```

```
<a href="admin_dashboard.php">Dashboard</a> |
```

```
<a href="logout.php">Logout</a>
```

```
</div>
```

```
</div>
```

```
</header>
```

```
<main class="container">
```

```
<?php if(!empty($success_message)): ?>
```

```
<div class="alert alert-success"><?php echo $success_message; ?></div>
```

```
<?php endif; ?>
```

```
<?php if(!empty($error_message)): ?>
```

```
<div class="alert alert-danger"><?php echo $error_message; ?></div>
```

```
<?php endif; ?>
```

```
<div class="action-bar">
```

```
    <h2>View, Edit, and Remove vendors for your pharmacy</h2>
```

```
    <a href="add_vendor.php" class="btn btn-primary">Add New Vendor</a>
```

```
</div>
```

```
<div class="vendor-list">
```

```
    <h3>Vendor List</h3>
```

```
    <table class="data-table">
```

```
        <thead>
```

```
            <tr>
```

```
                <th>ID</th>
```

```
                <th>Vendor Name</th>
```

```
                <th>Location</th>
```

```
                <th>Contact Person</th>
```

```
                <th>Phone</th>
```

```
                <th>Email</th>
```

```
                <th>Actions</th>
```

```
            </tr>
```

```
        </thead>
```

```
        <tbody>
```

```
            <?php if(empty($vendors)): ?>
```

```
                <tr>
```

```

        <td colspan="7" class="text-center">No vendors found.</td>

    </tr>

<?php else: ?>

    <?php foreach($vendors as $vendor): ?>

        <tr>

            <td><?php echo htmlspecialchars($vendor['vendor_id']); ?></td>

            <td><?php echo htmlspecialchars($vendor['vendor_name']); ?></td>

            <td><?php echo htmlspecialchars($vendor['location']); ?></td>

            <td><?php echo htmlspecialchars($vendor['contact_person']); ?></td>

            <td><?php echo htmlspecialchars($vendor['phone']); ?></td>

            <td><?php echo htmlspecialchars($vendor['email']); ?></td>

            <td>

                <a href="edit_vendor.php?id=<?php echo $vendor['vendor_id']; ?>"
class="btn btn-sm">Edit</a>

                <a href="manage_vendors.php?delete=<?php echo
$vendor['vendor_id']; ?>"

                    class="btn btn-danger btn-sm"

                    onclick="return confirm('Are you sure you want to delete this
vendor?')">Delete</a>

            </td>

        </tr>

    <?php endforeach; ?>

<?php endif; ?>

</tbody>

</table>

```

</div>

</main>

<script src="js/script.js"></script>

</body>

</html>

Step 6: Create add_vendor.php

Copy<?php

// Include config files

require_once "config/database.php";

require_once "config/session.php";

// Check if user is admin, redirect if not

requireAdmin();

// Define variables and initialize with empty values

\$vendor_name = \$location = \$contact_person = \$phone = \$email = \$address = "";

\$vendor_name_err = \$location_err = \$contact_person_err = \$phone_err = \$email_err =
\$address_err = "";

// Processing form data when form is submitted

if(\$_SERVER["REQUEST_METHOD"] == "POST"){

// Validate vendor name

if(empty(trim(\$_POST["vendor_name"]))) {

```

        $vendor_name_err = "Please enter vendor name.";
    } else{

        $vendor_name = trim($_POST["vendor_name"]);
    }


// Validate location
if(empty(trim($_POST["location"]))) {

    $location_err = "Please enter location.";
} else{

    $location = trim($_POST["location"]);
}


// Get other form data

$contact_person = trim($_POST["contact_person"] ?? "");
$phone = trim($_POST["phone"] ?? "");
$email = trim($_POST["email"] ?? "");
$address = trim($_POST["address"] ?? "");


// Check input errors before inserting in database
if(empty($vendor_name_err) && empty($location_err)){

    // Prepare an insert statement

    $sql = "INSERT INTO vendors (vendor_name, location, contact_person, phone, email,
address) VALUES (?, ?, ?, ?, ?, ?)";

```

```
if($stmt = mysqli_prepare($conn, $sql)){

    // Bind variables to the prepared statement as parameters

    mysqli_stmt_bind_param($stmt, "sssss", $param_vendor_name, $param_location,
$param_contact_person, $param_phone, $param_email, $param_address);


    // Set parameters

    $param_vendor_name = $vendor_name;

    $param_location = $location;

    $param_contact_person = $contact_person;

    $param_phone = $phone;

    $param_email = $email;

    $param_address = $address;


    // Attempt to execute the prepared statement

    if(mysqli_stmt_execute($stmt)){

        // Redirect to vendors page

        header("location: manage_vendors.php?success=added");

    } else{

        echo "Oops! Something went wrong. Please try again later.";

    }


    // Close statement

    mysqli_stmt_close($stmt);

}

}
```

```
// Close connection

mysqli_close($conn);

}

?>
```

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <meta charset="UTF-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <title>Add Vendor - Pharmacy Management System</title>
```

```
    <link rel="stylesheet" href="css/styles.css">
```

```
</head>
```

```
<body>
```

```
    <header>
```

```
        <div class="container">
```

```
            <h1>Add New Vendor</h1>
```

```
            <div class="user-info">
```

```
                Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |
```

```
                <a href="manage_vendors.php">Back to Vendors</a> |
```

```
                <a href="admin_dashboard.php">Dashboard</a> |
```

```
                <a href="logout.php">Logout</a>
```

```
            </div>
```

</div>

</header>

<main class="container">

<div class="form-container">

<form action="<?php echo htmlspecialchars(\$_SERVER["PHP_SELF"]); ?>"
method="post">

<div class="form-group">

<label>Vendor Name</label>

<input type="text" name="vendor_name" class="form-control <?php echo
(!empty(\$vendor_name_err)) ? 'is-invalid' : ''; ?>" value="<?php echo \$vendor_name; ?>">

<?php echo \$vendor_name_err; ?>

</div>

<div class="form-group">

<label>Location</label>

<input type="text" name="location" class="form-control <?php echo
(!empty(\$location_err)) ? 'is-invalid' : ''; ?>" value="<?php echo \$location; ?>">

<?php echo \$location_err; ?>

</div>

<div class="form-group">

<label>Contact Person</label>

<input type="text" name="contact_person" class="form-control" value="<?php
echo \$contact_person; ?>">

</div>

<div class="form-group">

<label>Phone</label>

<input type="text" name="phone" class="form-control" value="<?php echo \$phone; ?>">

</div>

<div class="form-group">

<label>Email</label>

<input type="email" name="email" class="form-control" value="<?php echo \$email; ?>">

</div>

<div class="form-group">

<label>Address</label>

<textarea name="address" class="form-control"><?php echo \$address; ?></textarea>

</div>

<div class="form-group">

<input type="submit" class="btn btn-primary" value="Add Vendor">

Cancel

</div>

</form>

</div>

</main>

<script src="js/script.js"></script>

</body>

</html>

Step 7: Create edit_vendor.php

Copy<?php

// Include config files

require_once "config/database.php";

require_once "config/session.php";

// Check if user is admin, redirect if not

requireAdmin();

// Check if id parameter is set

if(empty(\$_GET["id"]) || !is_numeric(\$_GET["id"])){

 header("location: manage_vendors.php?error=invalid_id");

 exit;

}

\$vendor_id = \$_GET["id"];

// Define variables and initialize with empty values

```
$vendor_name = $location = $contact_person = $phone = $email = $address = "";

$vendor_name_err = $location_err = $contact_person_err = $phone_err = $email_err =
$address_err = "";


// Processing form data when form is submitted

if($_SERVER["REQUEST_METHOD"] == "POST"){


    // Validate vendor name

    if(empty(trim($_POST["vendor_name"]))) {

        $vendor_name_err = "Please enter vendor name.";

    } else {

        $vendor_name = trim($_POST["vendor_name"]);

    }


    // Validate location

    if(empty(trim($_POST["location"]))) {

        $location_err = "Please enter location.";

    } else {

        $location = trim($_POST["location"]);

    }


    // Get other form data

    $contact_person = trim($_POST["contact_person"] ?? "");

    $phone = trim($_POST["phone"] ?? "");

    $email = trim($_POST["email"] ?? "");
```

```

$address = trim($_POST["address"] ?? "");

// Check input errors before updating in database

if(empty($vendor_name_err) && empty($location_err)){

    // Prepare an update statement

    $sql = "UPDATE vendors SET vendor_name = ?, location = ?, contact_person = ?, phone
= ?, email = ?, address = ? WHERE vendor_id = ?";

    if($stmt = mysqli_prepare($conn, $sql)){

        // Bind variables to the prepared statement as parameters

        mysqli_stmt_bind_param($stmt, "sssssi", $param_vendor_name, $param_location,
$param_contact_person,      $param_phone,      $param_email,      $param_address,
$param_vendor_id);

        // Set parameters

        $param_vendor_name = $vendor_name;

        $param_location = $location;

        $param_contact_person = $contact_person;

        $param_phone = $phone;

        $param_email = $email;

        $param_address = $address;

        $param_vendor_id = $vendor_id;

        // Attempt to execute the prepared statement

```

```

if(mysqli_stmt_execute($stmt)){

    // Redirect to vendors page

    header("location: manage_vendors.php?success=updated");

} else{

    echo "Oops! Something went wrong. Please try again later.";

}


// Close statement

mysqli_stmt_close($stmt);

}

} else {

    // Fetch vendor data

    $sql = "SELECT vendor_name, location, contact_person, phone, email, address FROM
vendors WHERE vendor_id = ?";

    if($stmt = mysqli_prepare($conn, $sql)){

        mysqli_stmt_bind_param($stmt, "i", $param_vendor_id);

        $param_vendor_id = $vendor_id;

        if(mysqli_stmt_execute($stmt)){

            mysqli_stmt_store_result($stmt);

            if(mysqli_stmt_num_rows($stmt) == 1){

                mysqli_stmt_bind_result($stmt, $vendor_name, $location, $contact_person,
$phone, $email, $address);

```

```
        mysqli_stmt_fetch($stmt);

    } else {

        header("location: manage_vendors.php?error=not_found");

        exit;

    }

} else {

    echo "Oops! Something went wrong. Please try again later.";

}

mysqli_stmt_close($stmt);

}

}

?>

<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Edit Vendor - Pharmacy Management System</title>

    <link rel="stylesheet" href="css/styles.css">

</head>

<body>

    <header>
```

Copy

complete it

Let me continue with the pharmacy management system conversion from HTML to PHP with database integration. I'll complete the remaining key files:

Step A: Complete edit_vendor.php (continuation)

Copy<body>

```
<header>
```

```
<div class="container">
```

```
<h1>Edit Vendor</h1>
```

```
<div class="user-info">
```

```
Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |
```

```
<a href="manage_vendors.php">Back to Vendors</a> |
```

```
<a href="admin_dashboard.php">Dashboard</a> |
```

```
<a href="logout.php">Logout</a>
```

```
</div>
```

```
</div>
```

```
</header>
```

```
<main class="container">
```

```
<div class="form-container">
```

```
<form action="<?php echo htmlspecialchars($_SERVER["PHP_SELF"]) . "?id=" .  
$vendor_id); ?>" method="post">
```

```
<div class="form-group">
```

```
<label>Vendor Name</label>
```

```
<input type="text" name="vendor_name" class="form-control <?php echo
(!empty($vendor_name_err)) ? 'is-invalid' : ''; ?>" value="<?php echo $vendor_name; ?>">
```

```
<span class="invalid-feedback"><?php echo $vendor_name_err; ?></span>
```

```
</div>
```

```
<div class="form-group">
```

```
<label>Location</label>
```

```
<input type="text" name="location" class="form-control <?php echo
(!empty($location_err)) ? 'is-invalid' : ''; ?>" value="<?php echo $location; ?>">
```

```
<span class="invalid-feedback"><?php echo $location_err; ?></span>
```

```
</div>
```

```
<div class="form-group">
```

```
<label>Contact Person</label>
```

```
<input type="text" name="contact_person" class="form-control" value="<?php
echo $contact_person; ?>">
```

```
</div>
```

```
<div class="form-group">
```

```
<label>Phone</label>
```

```
<input type="text" name="phone" class="form-control" value="<?php echo
$phone; ?>">
```

```
</div>
```

```
<div class="form-group">
```

```

        <label>Email</label>

        <input type="email" name="email" class="form-control" value="<?php echo
$email; ?>">

    </div>

    <div class="form-group">

        <label>Address</label>

        <textarea name="address" class="form-control"><?php echo $address;
?></textarea>

    </div>

    <div class="form-group">

        <input type="submit" class="btn btn-primary" value="Update Vendor">

        <a href="manage_vendors.php" class="btn btn-secondary">Cancel</a>

    </div>

</form>

</div>

</main>

<script src="js/script.js"></script>

</body>

</html>

```

Step 8: Convert staff_dashboard.html to staff_dashboard.php

Copy<?php

// Include config files

```
require_once "config/database.php";

require_once "config/session.php";


// Check if user is staff, redirect if not
requireStaff();


// Get dashboard stats

$totalProducts = 0;

$lowStockProducts = 0;

$totalSalesToday = 0;

$totalSalesAmount = 0;


// Count products

$sql = "SELECT COUNT(*) as count FROM products";

$result = mysqli_query($conn, $sql);

if($result && $row = mysqli_fetch_assoc($result)) {

    $totalProducts = $row['count'];

}


// Count low stock products

$sql = "SELECT COUNT(*) as count FROM products WHERE quantity <= reorder_level";

$result = mysqli_query($conn, $sql);

if($result && $row = mysqli_fetch_assoc($result)) {

    $lowStockProducts = $row['count'];
```

```
}
```

```
// Count today's sales
```

```
$today = date('Y-m-d');
```

```
$sql = "SELECT COUNT(*) as count, SUM(total_amount) as total FROM sales WHERE  
DATE(sale_date) = '$today'";
```

```
$result = mysqli_query($conn, $sql);
```

```
if($result && $row = mysqli_fetch_assoc($result)) {
```

```
    $totalSalesToday = $row['count'] ?? 0;
```

```
    $totalSalesAmount = $row['total'] ?? 0;
```

```
}
```

```
?>
```

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
    <meta charset="UTF-8">
```

```
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
    <title>Staff Dashboard - Pharmacy Management System</title>
```

```
    <link rel="stylesheet" href="css/styles.css">
```

```
</head>
```

```
<body>
```

```
    <header>
```

```
        <div class="container">
```

```
            <h1>Welcome to the Staff Dashboard</h1>
```

```
<div class="user-info">
```

```
    Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |
```

```
    <a href="logout.php">Logout</a>
```

```
</div>
```

```
</div>
```

```
</header>
```

```
<main class="container">
```

```
    <div class="dashboard-stats">
```

```
        <div class="stat-box">
```

```
            <h3>Products</h3>
```

```
            <p class="stat-number"><?php echo $totalProducts; ?></p>
```

```
        </div>
```

```
        <div class="stat-box">
```

```
            <h3>Low Stock</h3>
```

```
            <p class="stat-number"><?php echo $lowStockProducts; ?></p>
```

```
        </div>
```

```
        <div class="stat-box">
```

```
            <h3>Today's Sales</h3>
```

```
            <p class="stat-number"><?php echo $totalSalesToday; ?></p>
```

```
        </div>
```

```
<div class="stat-box">

    <h3>Today's Revenue</h3>

    <p class="stat-number">${<?php echo number_format($totalSalesAmount, 2);
?></p>

</div>

</div>
```

```
<div class="dashboard-actions">

    <div class="action-box">

        <h3>Manage Inventory</h3>

        <p>Add or update medicine stock efficiently.</p>

        <a href="manage_inventory.php" class="btn btn-primary">Go to Inventory</a>

    </div>
```

```
<div class="action-box">

    <h3>Product Details</h3>

    <p>View and edit medicine information.</p>

    <a href="product_details.php" class="btn btn-primary">View Products</a>

</div>
```

```
<div class="action-box">

    <h3>Sales Details</h3>

    <p>Track daily and monthly sales reports.</p>

    <a href="sales_details.php" class="btn btn-primary">View Sales</a>

</div>
```

```
<div class="action-box">

    <h3>Customer Details</h3>

    <p>Manage customer profiles and prescriptions.</p>

    <a href="customer_details.php" class="btn btn-primary">View Customers</a>

</div>
```

```
<div class="action-box">

    <h3>Prepare Bill</h3>

    <p>Generate and print customer bills quickly.</p>

    <a href="prepare_bill.php" class="btn btn-primary">Create Bill</a>

</div>
```

```
</div>
```

```
</main>
```

```
<script src="js/script.js"></script>
```

```
</body>
```

```
</html>
```

Step 9: Create logout.php

Copy<?php

```
// Initialize the session
```

```
session_start();
```

```
// Unset all of the session variables
```

```
$_SESSION = array();
```

```
// Destroy the session
```

```
session_destroy();
```

```
// Redirect to login page
```

```
header("location: login.php");
```

```
exit;
```

```
?>
```

Step 10: Create manage_inventory.php

```
Copy<?php
```

```
// Include config files
```

```
require_once "config/database.php";
```

```
require_once "config/session.php";
```

```
// Check if user is logged in, redirect if not
```

```
requireLogin();
```

```
// Define variables
```

```
$products = [];
```

```
$success_message = "";
```

```
$error_message = "";
```

```
// Handle stock update
```

```

if($_SERVER["REQUEST_METHOD"] == "POST" && isset($_POST['update_stock'])) {

    $product_id = $_POST['product_id'];

    $new_quantity = $_POST['quantity'];

    $notes = $_POST['notes'] ?? "";

    // Validate quantity

    if(!is_numeric($new_quantity) || $new_quantity < 0) {

        $error_message = "Invalid quantity value.";

    } else {

        // Get current quantity

        $sql = "SELECT quantity FROM products WHERE product_id = ?";

        if($stmt = mysqli_prepare($conn, $sql)) {

            mysqli_stmt_bind_param($stmt, "i", $product_id);

            mysqli_stmt_execute($stmt);

            mysqli_stmt_bind_result($stmt, $current_quantity);

            mysqli_stmt_fetch($stmt);

            mysqli_stmt_close($stmt);

            // Calculate adjustment amount

            $adjustment = $new_quantity - $current_quantity;

            // Start transaction

            mysqli_begin_transaction($conn);

```

```

try {

    // Update product quantity

    $update_sql = "UPDATE products SET quantity = ? WHERE product_id = ?";

    $update_stmt = mysqli_prepare($conn, $update_sql);

    mysqli_stmt_bind_param($update_stmt, "ii", $new_quantity, $product_id);

    mysqli_stmt_execute($update_stmt);

    mysqli_stmt_close($update_stmt);


    // Record inventory transaction

    $transaction_type = "adjustment";

    $user_id = $_SESSION["user_id"];


    $inventory_sql = "INSERT INTO inventory_transactions (product_id,
transaction_type, quantity, notes, user_id) VALUES (?, ?, ?, ?, ?)";

    $inventory_stmt = mysqli_prepare($conn, $inventory_sql);

    mysqli_stmt_bind_param($inventory_stmt, "isisi", $product_id, $transaction_type,
$adjustment, $notes, $user_id);

    mysqli_stmt_execute($inventory_stmt);

    mysqli_stmt_close($inventory_stmt);


    mysqli_commit($conn);

    $success_message = "Inventory updated successfully.";

} catch (Exception $e) {

    mysqli_rollback($conn);

    $error_message = "Error updating inventory: " . $e->getMessage();

```

```

    }

    }

}

}

// Fetch all products with inventory information

$sql = "SELECT p.product_id, p.product_name, p.generic_name, p.category, p.quantity,
p.reorder_level,

        v.vendor_name FROM products p LEFT JOIN vendors v ON p.vendor_id = v.vendor_id

        ORDER BY p.product_name";

$result = mysqli_query($conn, $sql);

if($result) {

    while($row = mysqli_fetch_assoc($result)) {

        $products[] = $row;

    }

}

?>

<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Manage Inventory - Pharmacy Management System</title>

```

```
<link rel="stylesheet" href="css/styles.css">
```

```
</head>
```

```
<body>
```

```
<header>
```

```
<div class="container">
```

```
<h1>Manage Inventory</h1>
```

```
<div class="user-info">
```

```
Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |
```

```
<?php if(isAdmin()): ?>
```

```
<a href="admin_dashboard.php">Dashboard</a> |
```

```
<?php else: ?>
```

```
<a href="staff_dashboard.php">Dashboard</a> |
```

```
<?php endif; ?>
```

```
<a href="logout.php">Logout</a>
```

```
</div>
```

```
</div>
```

```
</header>
```

```
<main class="container">
```

```
<?php if(!empty($success_message)): ?>
```

```
<div class="alert alert-success"><?php echo $success_message; ?></div>
```

```
<?php endif; ?>
```

```
<?php if(!empty($error_message)): ?>
```

```
<div class="alert alert-danger"><?php echo $error_message; ?></div>
```

```
<?php endif; ?>
```

```
<div class="inventory-search">
```

```
    <input type="text" id="inventorySearch" class="form-control" placeholder="Search  
products...">
```

```
</div>
```

```
<div class="inventory-list">
```

```
    <h3>Inventory List</h3>
```

```
    <table class="data-table" id="inventoryTable">
```

```
        <thead>
```

```
            <tr>
```

```
                <th>ID</th>
```

```
                <th>Product Name</th>
```

```
                <th>Generic Name</th>
```

```
                <th>Category</th>
```

```
                <th>Vendor</th>
```

```
                <th>Current Stock</th>
```

```
                <th>Reorder Level</th>
```

```
                <th>Status</th>
```

```
                <th>Actions</th>
```

```
            </tr>
```

```
        </thead>
```

```

<tbody>

<?php if(empty($products)): ?>

    <tr>

        <td colspan="9" class="text-center">No products found.</td>

    </tr>

<?php else: ?>

    <?php foreach($products as $product): ?>

        <tr class="<?php echo $product['quantity'] <= $product['reorder_level'] ?
'low-stock' : "; ?>">

            <td><?php echo htmlspecialchars($product['product_id']); ?></td>

            <td><?php echo htmlspecialchars($product['product_name']); ?></td>

            <td><?php echo htmlspecialchars($product['generic_name']); ?></td>

            <td><?php echo htmlspecialchars($product['category']); ?></td>

            <td><?php echo htmlspecialchars($product['vendor_name']); ?></td>

            <td><?php echo htmlspecialchars($product['quantity']); ?></td>

            <td><?php echo htmlspecialchars($product['reorder_level']); ?></td>

            <td>

                <?php if($product['quantity'] <= 0): ?>

                    <span class="status-out">Out of Stock</span>

                <?php elseif($product['quantity'] <= $product['reorder_level']): ?>

                    <span class="status-low">Low Stock</span>

                <?php else: ?>

                    <span class="status-ok">In Stock</span>

                <?php endif; ?>

            </td>

```

```
<td>

<button class="btn btn-sm"

        onclick="openUpdateStock(<?php echo $product['product_id'];
?>, '<?php echo htmlspecialchars($product['product_name']); ?>', <?php echo
$product['quantity']; ?>)">
```

Update Stock

```
</button>

</td>

</tr>

<?php endforeach; ?>

<?php endif; ?>

</tbody>

</table>

</div>
```

```
<!-- Stock Update Modal -->

<div id="stockModal" class="modal">

    <div class="modal-content">

        <span class="close">&times;</span>

        <h2>Update Stock Quantity</h2>

        <form action="<?php echo htmlspecialchars($_SERVER["PHP_SELF"]); ?>"
method="post">

            <input type="hidden" id="modal_product_id" name="product_id">

            <div class="form-group">
```

<label>Product</label>

<input type="text" id="modal_product_name" class="form-control" readonly>

</div>

<div class="form-group">

<label>Current Quantity</label>

<input type="text" id="modal_current_quantity" class="form-control" readonly>

</div>

<div class="form-group">

<label>New Quantity</label>

<input type="number" name="quantity" id="modal_new_quantity" class="form-control" min="0" required>

</div>

<div class="form-group">

<label>Notes</label>

<textarea name="notes" class="form-control"></textarea>

</div>

<div class="form-group">

<input type="submit" name="update_stock" class="btn btn-primary" value="Update Stock">

```
        <button        type="button"        class="btn        btn-secondary        close-  
modal">Cancel</button>
```

```
    </div>
```

```
</form>
```

```
</div>
```

```
</div>
```

```
</main>
```

```
<script>
```

```
// Search functionality
```

```
document.getElementById('inventorySearch').addEventListener('keyup', function() {
```

```
    var input, filter, table, tr, td, i, txtValue;
```

```
    input = document.getElementById('inventorySearch');
```

```
    filter = input.value.toUpperCase();
```

```
    table = document.getElementById('inventoryTable');
```

```
    tr = table.getElementsByTagName('tr');
```

```
    for (i = 1; i < tr.length; i++) { // Start from 1 to skip header row
```

```
        var found = false;
```

```
        // Search in product name, generic name and category columns (1, 2, 3)
```

```
        for (var j = 1; j <= 3; j++) {
```

```
            td = tr[i].getElementsByTagName('td')[j];
```

```
            if (td) {
```

```
                txtValue = td.textContent || td.innerText;
```

```
                if (txtValue.toUpperCase().indexOf(filter) > -1) {
```

```

        found = true;

        break;
    }

}

}

if (found) {

    tr[i].style.display = "";

} else {

    tr[i].style.display = 'none';

}

}

});

```

// Modal handling

```

var modal = document.getElementById('stockModal');

var span = document.getElementsByClassName('close')[0];

var closeBtn = document.getElementsByClassName('close-modal')[0];

function openUpdateStock(productId, productName, quantity) {

    document.getElementById('modal_product_id').value = productId;

    document.getElementById('modal_product_name').value = productName;

    document.getElementById('modal_current_quantity').value = quantity;

    document.getElementById('modal_new_quantity').value = quantity;

    modal.style.display = 'block';

```

```
}
```

```
span.onclick = function() {  
    modal.style.display = 'none';  
}
```

```
closeBtn.onclick = function() {  
    modal.style.display = 'none';  
}
```

```
window.onclick = function(event) {  
    if (event.target === modal) {  
        modal.style.display = 'none';  
    }  
}
```

```
</script>
```

```
<script src="js/script.js"></script>
```

```
</body>
```

```
</html>
```

Step 11: Create prepare_bill.php

Copy<?php

```
// Include config files
```

```
require_once "config/database.php";
```

```
require_once "config/session.php";

// Check if user is logged in, redirect if not
requireLogin();

// Define variables

$products = [];

$customers = [];

$cart = [];

$subtotal = 0;

$tax_rate = 0.05; // 5% tax

$tax_amount = 0;

$total_amount = 0;

$success_message = "";

$error_message = "";

// Fetch products for dropdown

$sql = "SELECT product_id, product_name, generic_name, selling_price, quantity FROM
products WHERE quantity > 0 ORDER BY product_name";

$result = mysqli_query($conn, $sql);

if($result) {

    while($row = mysqli_fetch_assoc($result)) {

        $products[] = $row;

    }

}
```

```
// Fetch customers for dropdown
```

```
$sql = "SELECT customer_id, customer_name, phone FROM customers ORDER BY  
customer_name";
```

```
$result = mysqli_query($conn, $sql);
```

```
if($result) {
```

```
    while($row = mysqli_fetch_assoc($result)) {
```

```
        $customers[] = $row;
```

```
    }
```

```
}
```

```
// Handle add to cart
```

```
if($_SERVER["REQUEST_METHOD"] == "POST" && isset($_POST['add_to_cart'])) {
```

```
    $product_id = $_POST['product_id'];
```

```
    $quantity = $_POST['quantity'];
```

```
// Validate product
```

```
if(empty($product_id)) {
```

```
    $error_message = "Please select a product.";
```

```
}
```

```
// Validate quantity
```

```
else if(!is_numeric($quantity) || $quantity <= 0) {
```

```
    $error_message = "Please enter a valid quantity.";
```

```
} else {
```

```
    // Check if product exists and has sufficient stock
```

```
$sql = "SELECT product_id, product_name, selling_price, quantity FROM products  
WHERE product_id = ?";
```

```
if($stmt = mysqli_prepare($conn, $sql)) {  
  
    mysqli_stmt_bind_param($stmt, "i", $product_id);  
  
    mysqli_stmt_execute($stmt);  
  
    $result = mysqli_stmt_get_result($stmt);
```

```
if($product = mysqli_fetch_assoc($result)) {  
  
    if($product['quantity'] < $quantity) {  
  
        $error_message = "Insufficient stock. Only " . $product['quantity'] . " available.";
```

```
    } else {
```

```
        // Add to session cart
```

```
        if(!isset($_SESSION['cart'])) {
```

```
            $_SESSION['cart'] = [];
```

```
        }
```

```
        // Check if product already in cart
```

```
$found = false;
```

```
foreach($_SESSION['cart'] as $key => $item) {
```

```
    if($item['product_id'] == $product_id) {
```

```
        $_SESSION['cart'][$key]['quantity'] += $quantity;
```

```
        $_SESSION['cart'][$key]['total'] = $_SESSION['cart'][$key]['quantity'] *
```

```
$_SESSION['cart'][$key]['price'];
```

```
        $found = true;
```

```
        break;
```

```

    }
}

if(!$found) {

    $_SESSION['cart'][] = [

        'product_id' => $product_id,

        'name' => $product['product_name'],

        'price' => $product['selling_price'],

        'quantity' => $quantity,

        'total' => $quantity * $product['selling_price']

    ];

}

$success_message = "Product added to cart.";

}

} else {

    $error_message = "Product not found.";

}

mysqli_stmt_close($stmt);

}

}

}

```

```
// Handle remove from cart
```

```
if(isset($_GET['remove']) && is_numeric($_GET['remove'])) {
```

```
    $index = $_GET['remove'];
```

```
    if(isset($_SESSION['cart'][$index])) {
```

```
        unset($_SESSION['cart'][$index]);
```

```
        $_SESSION['cart'] = array_values($_SESSION['cart']); // Reindex array
```

```
        $success_message = "Item removed from cart.";
```

```
    }
```

```
}
```

```
// Handle clear cart
```

```
if(isset($_GET['clear'])) {
```

```
    unset($_SESSION['cart']);
```

```
    $success_message = "Cart cleared.";
```

```
}
```

```
// Handle create bill/sale
```

```
if($_SERVER["REQUEST_METHOD"] == "POST" && isset($_POST['create_sale'])) {
```

```
    if(empty($_SESSION['cart'])) {
```

```
        $error_message = "Cart is empty. Please add products.";
```

```
    } else {
```

```
        $customer_id = $_POST['customer_id'] != "" ? $_POST['customer_id'] : null;
```

```
        $payment_method = $_POST['payment_method'];
```

```
        $user_id = $_SESSION["user_id"];
```

```

// Generate invoice number (format: INV-YearMonthDay-RandomNumber)

$invoice_number = 'INV-' . date('Ymd') . '-' . mt_rand(1000, 9999);


// Calculate totals

$subtotal = 0;

foreach($_SESSION['cart'] as $item) {

    $subtotal += $item['total'];

}


$tax_amount = $subtotal * $tax_rate;

$total_amount = $subtotal + $tax_amount;


// Start transaction

mysqli_begin_transaction($conn);


try {

    // Insert sale

    $sale_sql = "INSERT INTO sales (invoice_number, customer_id, total_amount,
payment_method, user_id)

        VALUES (?, ?, ?, ?, ?)";

    $sale_stmt = mysqli_prepare($conn, $sale_sql);

    mysqli_stmt_bind_param($sale_stmt, "sidsi", $invoice_number, $customer_id,
$total_amount, $payment_method, $user_id);

    mysqli_stmt_execute($sale_stmt);

```

```

$sale_id = mysqli_insert_id($conn);

mysqli_stmt_close($sale_stmt);


// Insert sale items and update inventory
foreach($_SESSION['cart'] as $item) {

    // Insert sale item

    $item_sql = "INSERT INTO sale_items (sale_id, product_id, quantity, unit_price,
total_price)

        VALUES (?, ?, ?, ?, ?)";

    $item_stmt = mysqli_prepare($conn, $item_sql);

    mysqli_stmt_bind_param($item_stmt, "iidd", $sale_id, $item['product_id'],
$item['quantity'], $item['price'], $item['total']);

    mysqli_stmt_execute($item_stmt);

    mysqli_stmt_close($item_stmt);


// Update product quantity

$update_sql = "UPDATE products SET quantity = quantity - ? WHERE product_id
= ?";

$update_stmt = mysqli_prepare($conn, $update_sql);

mysqli_stmt_bind_param($update_stmt, "ii", $item['quantity'], $item['product_id']);

mysqli_stmt_execute($update_stmt);

mysqli_stmt_close($update_stmt);


// Record inventory transaction

$transaction_type = "sale";

```

```
$quantity = -$item['quantity']; // Negative because it's a reduction
```

```
$inventory_sql = "INSERT INTO inventory_transactions (product_id,  
transaction_type, quantity, reference_id, user_id)
```

```
VALUES (?, ?, ?, ?, ?)";
```

```
$inventory_stmt = mysqli_prepare($conn, $inventory_sql);
```

```
mysqli_stmt_bind_param($inventory_stmt, "isiii", $item['product_id'],  
$transaction_type, $quantity, $sale_id, $user_id);
```

```
mysqli_stmt_execute($inventory_stmt);
```

```
mysqli_stmt_close($inventory_stmt);
```

```
}
```

```
mysqli_commit($conn);
```

```
$success_message = "Sale completed successfully. Invoice #: " . $invoice_number;
```

```
// Store invoice in session for printing
```

```
$_SESSION['last_invoice'] = [
```

```
'invoice_number' => $invoice_number,
```

```
'date' => date('Y-m-d H:i:s'),
```

```
'customer_id' => $customer_id,
```

```
'items' => $_SESSION['cart'],
```

```
'subtotal' => $subtotal,
```

```
'tax_amount' => $tax_amount,
```

```
'total_amount' => $total_amount,
```

```
'payment_method' => $payment_method
```

```
];
```

```
// Clear cart
```

```
unset($_SESSION['cart']);
```

```
// Redirect to print invoice
```

```
header("location: print_invoice.php");
```

```
exit;
```

```
} catch (Exception $e) {
```

```
    mysqli_rollback($conn);
```

```
    $error_message = "Error creating sale: " . $e->getMessage();
```

```
}
```

```
}
```

```
}
```

```
// Get cart from session
```

```
if(isset($_SESSION['cart'])) {
```

```
    $cart = $_SESSION['cart'];
```

```
// Calculate totals
```

```
$subtotal = 0;
```

```
foreach($cart as $item) {
```

```
    $subtotal += $item['total'];
```

```
}
```

```
$tax_amount = $subtotal * $tax_rate;
```

```
$total_amount = $subtotal + $tax_amount;
```

```
}
```

```
?>
```

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
<title>Prepare Bill - Pharmacy Management System</title>
```

```
<link rel="stylesheet" href="css/styles.css">
```

```
</head>
```

```
<body>
```

```
<header>
```

```
<div class="container">
```

```
<h1>Prepare Bill</h1>
```

```
<div class="user-info">
```

```
Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |
```

```
<?php if(isAdmin()): ?>
```

```
<a href="admin_dashboard.php">Dashboard</a> |
```

```
<?php else: ?>
```

```

        <a href="staff_dashboard.php">Dashboard</a> |

    <?php endif; ?>

    <a href="logout.php">Logout</a>

</div>

</div>

</header>

<main class="container">

    <?php if(!empty($success_message)): ?>

        <div class="alert alert-success"><?php echo $success_message; ?></div>

    <?php endif; ?>

    <?php if(!empty($error_message)): ?>

        <div class="alert alert-danger"><?php echo $error_message; ?></div>

    <?php endif; ?>

    <div class="billing-container">

        <div class="product-selection">

            <h3>Add Products</h3>

            <form action="<?php echo htmlspecialchars($_SERVER["PHP_SELF"]); ?>"
method="post">

                <div class="form-group">

                    <label>Product</label>

                    <select name="product_id" class="form-control" required>

                        <option value="">Select Product</option>

```

```
<?php foreach($products as $product): ?>
```

```
<option value="<?php echo $product['product_id']; ?>">
```

```
<?php echo htmlspecialchars($product['product_name']); ?> -
```

```
$<?php echo number_format($product['selling_price'], 2); ?> -
```

```
(Stock: <?php echo $product['quantity']; ?>)
```

```
</option>
```

```
<?php endforeach; ?>
```

```
</select>
```

```
</div>
```

```
<div class="form-group">
```

```
<label>Quantity</label>
```

```
<input type="number" name="quantity" class="form-control" min="1"
value="1" required>
```

```
</div>
```

```
<div class="form-group">
```

```
<input type="submit" name="add_to_cart" class="btn btn-primary"
value="Add to Cart">
```

```
</div>
```

```
</form>
```

```
</div>
```

```
<div class="cart">
```

```
<div class="cart-header">
```

```
<h3>Current Cart</h3>
```

```
<?php if(!empty($cart)): ?>
```

```
    <a href="?clear=1" class="btn btn-danger btn-sm" onclick="return
confirm('Are you sure you want to clear the cart?')">Clear Cart</a>
```

```
<?php endif; ?>
```

```
</div>
```

```
<?php if(empty($cart)): ?>
```

```
    <p>Cart is empty. Please add products.</p>
```

```
<?php else: ?>
```

```
    <table class="data-table">
```

```
        <thead>
```

```
            <tr>
```

```
                <th>Product</th>
```

```
                <th>Price</th>
```

```
                <th>Quantity</th>
```

```
                <th>Total</th>
```

```
                <th>Action</th>
```

```
            </tr>
```

```
        </thead>
```

```
        <tbody>
```

```
            <?php foreach($cart as $index => $item): ?>
```

```
                <tr>
```

Copy

complete it

Let me complete the pharmacy management system conversion with the remaining key files:

Step 11: Complete prepare_bill.php (continuation)

```
Copy      <?php foreach($cart as $index => $item): ?>

            <tr>

                <td><?php echo htmlspecialchars($item['name']); ?></td>

                <td>$<?php echo number_format($item['price'], 2); ?></td>

                <td><?php echo $item['quantity']; ?></td>

                <td>$<?php echo number_format($item['total'], 2); ?></td>

                <td>

                    <a href="?remove=<?php echo $index; ?>" class="btn btn-danger

btn-sm"

                    onclick="return confirm('Remove this item?')">Remove</a>

                </td>

            </tr>

        <?php endforeach; ?>

    </tbody>

    <tfoot>

        <tr>

            <td colspan="3" class="text-right"><strong>Subtotal:</strong></td>

            <td>$<?php echo number_format($subtotal, 2); ?></td>

            <td></td>

        </tr>

        <tr>

            <td colspan="3" class="text-right"><strong>Tax (<?php echo $tax_rate *

100; ?>%):</strong></td>
```

```

        <td>${<?php echo number_format($tax_amount, 2); ?></td>

        <td></td>

    </tr>

    <tr>

        <td colspan="3" class="text-right"><strong>Total:</strong></td>

        <td>${<?php echo number_format($total_amount, 2); ?></td>

        <td></td>

    </tr>

</tfoot>

</table>

<div class="checkout-form">

    <h3>Complete Sale</h3>

    <form action="<?php echo htmlspecialchars($_SERVER["PHP_SELF"]); ?>"
method="post">

        <div class="form-group">

            <label>Customer (Optional)</label>

            <select name="customer_id" class="form-control">

                <option value="">Select Customer</option>

                <?php foreach($customers as $customer): ?>

                    <option value="<?php echo $customer['customer_id']; ?>">

                        <?php echo htmlspecialchars($customer['customer_name']); ?>

                        (<?php echo htmlspecialchars($customer['phone']); ?>)

                    </option>

                <?php endforeach; ?>

```

</select>

</div>

<div class="form-group">

<label>Payment Method</label>

<select name="payment_method" class="form-control" required>

<option value="cash">Cash</option>

<option value="card">Credit/Debit Card</option>

<option value="other">Other</option>

</select>

</div>

<div class="form-group">

<input type="submit" name="create_sale" class="btn btn-success"
value="Complete Sale">

</div>

</form>

</div>

<?php endif; ?>

</div>

</div>

</main>

<script src="js/script.js"></script>

</body>

</html>

Step 12: Create print_invoice.php

Copy<?php

// Include config files

require_once "config/database.php";

require_once "config/session.php";

// Check if user is logged in and has invoice data, redirect if not

requireLogin();

if(!isset(\$_SESSION['last_invoice'])) {

 header("location: prepare_bill.php");

 exit;

}

\$invoice = \$_SESSION['last_invoice'];

\$customer_name = "Walk-in Customer";

// If customer_id is set, get customer details

if(!empty(\$invoice['customer_id'])) {

 \$sql = "SELECT customer_name, phone, email, address FROM customers WHERE
customer_id = ?";

 if(\$stmt = mysqli_prepare(\$conn, \$sql)) {

 mysqli_stmt_bind_param(\$stmt, "i", \$invoice['customer_id']);

 mysqli_stmt_execute(\$stmt);

```
$result = mysqli_stmt_get_result($stmt);

if($customer = mysqli_fetch_assoc($result)) {

    $customer_name = $customer['customer_name'];

    $customer_phone = $customer['phone'];

    $customer_email = $customer['email'];

    $customer_address = $customer['address'];

}

mysqli_stmt_close($stmt);

}

?>
```

<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8">

<meta name="viewport" content="width=device-width, initial-scale=1.0">

<title>Invoice #<?php echo \$invoice['invoice_number']; ?> - Pharmacy Management
System</title>

<link rel="stylesheet" href="css/styles.css">

<style>

.invoice-container {

max-width: 800px;

margin: 0 auto;

padding: 20px;

```
border: 1px solid #ddd;

box-shadow: 0 0 10px rgba(0,0,0,0.1);

}

.invoice-header {

    text-align: center;

    margin-bottom: 20px;

    padding-bottom: 20px;

    border-bottom: 1px solid #ddd;

}

.invoice-info {

    display: flex;

    justify-content: space-between;

    margin-bottom: 20px;

}

.invoice-items {

    margin-bottom: 20px;

}

.invoice-totals {

    margin-left: auto;

    width: 300px;

}

.print-controls {

    margin: 20px 0;

    text-align: center;
```

```
}

@media print {

    .print-controls, header {

        display: none;

    }

}

</style>

</head>

<body>

    <header>

        <div class="container">

            <h1>Print Invoice</h1>

            <div class="user-info">

                Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |

                <?php if(isAdmin()): ?>

                    <a href="admin_dashboard.php">Dashboard</a> |

                <?php else: ?>

                    <a href="staff_dashboard.php">Dashboard</a> |

                <?php endif; ?>

                <a href="logout.php">Logout</a>

            </div>

        </div>

    </div>

</header>
```

```
<div class="print-controls">

    <button onclick="window.print()" class="btn btn-primary">Print Invoice</button>

    <a href="prepare_bill.php" class="btn">New Sale</a>

</div>
```

```
<div class="invoice-container">

    <div class="invoice-header">

        <h2>Pharmacy Management System</h2>

        <h3>INVOICE</h3>

    </div>
```

```
<div class="invoice-info">

    <div class="customer-info">

        <h4>Bill To:</h4>

        <p><strong><?php echo htmlspecialchars($customer_name); ?></strong></p>

        <?php if(isset($customer_phone)): ?>

            <p>Phone: <?php echo htmlspecialchars($customer_phone); ?></p>

        <?php endif; ?>

        <?php if(isset($customer_email)): ?>

            <p>Email: <?php echo htmlspecialchars($customer_email); ?></p>

        <?php endif; ?>

        <?php if(isset($customer_address)): ?>

            <p>Address: <?php echo htmlspecialchars($customer_address); ?></p>

        <?php endif; ?>
```

</div>

<div class="invoice-details">

<h4>Invoice Details:</h4>

<p>Invoice #: <?php echo htmlspecialchars(\$invoice['invoice_number']); ?></p>

<p>Date: <?php echo date('F j, Y', strtotime(\$invoice['date'])); ?></p>

<p>Time: <?php echo date('h:i A', strtotime(\$invoice['date'])); ?></p>

<p>Payment Method: <?php echo ucfirst(\$invoice['payment_method']); ?></p>

</div>

</div>

<div class="invoice-items">

<table class="data-table">

<thead>

<tr>

<th>#</th>

<th>Product</th>

<th>Unit Price</th>

<th>Quantity</th>

<th>Total</th>

</tr>

```

</thead>

<tbody>

  <?php foreach($invoice['items'] as $index => $item): ?>

    <tr>

      <td><?php echo $index + 1; ?></td>

      <td><?php echo htmlspecialchars($item['name']); ?></td>

      <td>$<?php echo number_format($item['price'], 2); ?></td>

      <td><?php echo $item['quantity']; ?></td>

      <td>$<?php echo number_format($item['total'], 2); ?></td>

    </tr>

  <?php endforeach; ?>

</tbody>

</table>

</div>

<div class="invoice-totals">

  <table class="data-table">

    <tr>

      <td><strong>Subtotal:</strong></td>

      <td>$<?php echo number_format($invoice['subtotal'], 2); ?></td>

    </tr>

    <tr>

      <td><strong>Tax:</strong></td>

      <td>$<?php echo number_format($invoice['tax_amount'], 2); ?></td>

```

```

        </tr>

        <tr>

            <td><strong>Total:</strong></td>

            <td><?php echo number_format($invoice['total_amount'], 2); ?></td>

        </tr>

    </table>

</div>

```

```

<div class="invoice-footer">

    <p><strong>Thank you for your purchase!</strong></p>

    <p>For questions or returns, please contact our pharmacy staff.</p>

</div>

</div>

```

```

<script src="js/script.js"></script>

</body>

</html>

```

Step 13: Create product_details.php

Copy<?php

```
// Include config files
```

```
require_once "config/database.php";
```

```
require_once "config/session.php";
```

```
// Check if user is logged in, redirect if not
```

```
requireLogin();
```

```
// Define variables
```

```
$products = [];
```

```
$success_message = "";
```

```
$error_message = "";
```

```
$categories = [];
```

```
// Fetch product categories for filtering
```

```
$sql = "SELECT DISTINCT category FROM products WHERE category IS NOT NULL AND  
category != " ORDER BY category";
```

```
$result = mysqli_query($conn, $sql);
```

```
if($result) {
```

```
    while($row = mysqli_fetch_assoc($result)) {
```

```
        $categories[] = $row['category'];
```

```
    }
```

```
}
```

```
// Handle product deletion (admin only)
```

```
if(isAdmin() && isset($_GET['delete']) && is_numeric($_GET['delete'])) {
```

```
    $product_id = $_GET['delete'];
```

```
// Check if product has sales
```

```
$check_sql = "SELECT COUNT(*) as count FROM sale_items WHERE product_id = ?";
```

```
if($stmt = mysqli_prepare($conn, $check_sql)) {
```

```

mysqli_stmt_bind_param($stmt, "i", $product_id);

mysqli_stmt_execute($stmt);

mysqli_stmt_store_result($stmt);

mysqli_stmt_bind_result($stmt, $sales_count);

mysqli_stmt_fetch($stmt);


if($sales_count > 0) {

    $error_message = "Cannot delete product because it has $sales_count associated
sales.";

} else {

    // Delete inventory transactions first

    $delete_inv_sql = "DELETE FROM inventory_transactions WHERE product_id = ?";

    if($delete_inv_stmt = mysqli_prepare($conn, $delete_inv_sql)) {

        mysqli_stmt_bind_param($delete_inv_stmt, "i", $product_id);

        mysqli_stmt_execute($delete_inv_stmt);

        mysqli_stmt_close($delete_inv_stmt);

    }


    // Then delete the product

    $delete_sql = "DELETE FROM products WHERE product_id = ?";

    if($delete_stmt = mysqli_prepare($conn, $delete_sql)) {

        mysqli_stmt_bind_param($delete_stmt, "i", $product_id);

        if(mysqli_stmt_execute($delete_stmt)) {

            $success_message = "Product deleted successfully.";

        } else {

```

```

        $error_message = "Error deleting product.";
    }

    mysqli_stmt_close($delete_stmt);
}

}

mysqli_stmt_close($stmt);
}
}

// Build SQL query based on filters

$sql = "SELECT p.product_id, p.product_name, p.generic_name, p.category, p.cost_price,
        p.selling_price, p.quantity, p.reorder_level, p.expiry_date, v.vendor_name
        FROM products p LEFT JOIN vendors v ON p.vendor_id = v.vendor_id";

// Apply filter if set

if(isset($_GET['category']) && !empty($_GET['category'])) {
    $category = $_GET['category'];

    $sql .= " WHERE p.category = '$category'";
}

// Add sorting

$sql .= " ORDER BY p.product_name";

// Execute query

```

```
$result = mysqli_query($conn, $sql);

if($result) {

    while($row = mysqli_fetch_assoc($result)) {

        $products[] = $row;

    }

}

?>
```

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Product Details - Pharmacy Management System</title>

    <link rel="stylesheet" href="css/styles.css">

</head>

<body>

    <header>

        <div class="container">

            <h1>Product Details</h1>

            <div class="user-info">

                Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |

                <?php if(isAdmin()): ?>

                    <a href="admin_dashboard.php">Dashboard</a> |
```

```
<?php else: ?>

    <a href="staff_dashboard.php">Dashboard</a> |

<?php endif; ?>

<a href="logout.php">Logout</a>

</div>

</div>

</header>

<main class="container">

    <?php if(!empty($success_message)): ?>

        <div class="alert alert-success"><?php echo $success_message; ?></div>

    <?php endif; ?>

    <?php if(!empty($error_message)): ?>

        <div class="alert alert-danger"><?php echo $error_message; ?></div>

    <?php endif; ?>

    <div class="action-bar">

        <?php if(isAdmin()): ?>

            <a href="add_product.php" class="btn btn-primary">Add New Product</a>

        <?php endif; ?>

        <div class="filter-controls">

            <form action="" method="get" class="form-inline">
```

```

        <label for="category">Filter by Category:</label>

        <select      name="category"      id="category"      class="form-control"
onchange="this.form.submit()">

            <option value="">All Categories</option>

            <?php foreach($categories as $category): ?>

                <option value="<?php echo htmlspecialchars($category); ?>"

                    <?php echo (isset($_GET['category']) && $_GET['category'] ==
$category) ? 'selected' : ''; ?>>

                    <?php echo htmlspecialchars($category); ?>

                </option>

            <?php endforeach; ?>

        </select>

    </form>


    <input type="text" id="productSearch" class="form-control" placeholder="Search
products...">

</div>

</div>


<div class="product-list">

    <table class="data-table" id="productTable">

        <thead>

            <tr>

                <th>ID</th>

                <th>Product Name</th>

```

```

        <th>Generic Name</th>

        <th>Category</th>

        <th>Vendor</th>

        <th>Cost Price</th>

        <th>Selling Price</th>

        <th>Stock</th>

        <th>Expiry Date</th>

        <th>Actions</th>

    </tr>

</thead>

<tbody>

    <?php if(empty($products)): ?>

        <tr>

            <td colspan="10" class="text-center">No products found.</td>

        </tr>

    <?php else: ?>

        <?php foreach($products as $product): ?>

            <tr class="<?php echo $product['quantity'] <= $product['reorder_level'] ?
'low-stock' : ''; ?>">

                <td><?php echo htmlspecialchars($product['product_id']); ?></td>

                <td><?php echo htmlspecialchars($product['product_name']); ?></td>

                <td><?php echo htmlspecialchars($product['generic_name']); ?></td>

                <td><?php echo htmlspecialchars($product['category']); ?></td>

                <td><?php echo htmlspecialchars($product['vendor_name']); ?></td>

                <td>$<?php echo number_format($product['cost_price'], 2); ?></td>

```

```
<td>${<?php echo number_format($product['selling_price'], 2); ?></td>
```

```
<td>
```

```
<?php echo $product['quantity']; ?>
```

```
<?php if($product['quantity'] <= $product['reorder_level']): ?>
```

```
<span class="status-indicator low">!</span>
```

```
<?php endif; ?>
```

```
</td>
```

```
<td>
```

```
<?php
```

```
if($product['expiry_date']) {
```

```
    echo date('M d, Y', strtotime($product['expiry_date']));
```

```
    // Show warning if expiring within 30 days
```

```
    $expiry = new DateTime($product['expiry_date']);
```

```
    $now = new DateTime();
```

```
    $diff = $expiry->diff($now)->days;
```

```
    if($expiry < $now) {
```

```
        echo ' <span class="status-indicator expired">Expired</span>';
```

```
    } elseif($diff <= 30) {
```

```
        echo ' <span class="status-indicator expiring">Expiring
```

```
soon</span>';
```

```
    }
```

```
    } else {
```

```
        echo 'N/A';
```

```

        }

        ?>

    </td>

    <td>

        <a href="view_product.php?id=?php echo $product['product_id']; ?>"
class="btn btn-sm">View</a>

        <?php if(isAdmin()): ?>

            <a href="edit_product.php?id=?php echo $product['product_id'];
?>" class="btn btn-sm">Edit</a>

            <a href="product_details.php?delete=?php echo
$product['product_id']; ?>"
class="btn btn-danger btn-sm"
onclick="return confirm('Are you sure you want to delete this
product?')">Delete</a>

        <?php endif; ?>

    </td>

</tr>

<?php endforeach; ?>

<?php endif; ?>

</tbody>

</table>

</div>

</main>

<script>

```

```
// Search functionality

document.getElementById('productSearch').addEventListener('keyup', function() {

    var input, filter, table, tr, td, i, txtValue;

    input = document.getElementById('productSearch');

    filter = input.value.toUpperCase();

    table = document.getElementById('productTable');

    tr = table.getElementsByTagName('tr');

    for (i = 1; i < tr.length; i++) { // Start from 1 to skip header row

        var found = false;

        // Search in product name, generic name and category columns (1, 2, 3)

        for (var j = 1; j <= 3; j++) {

            td = tr[i].getElementsByTagName('td')[j];

            if (td) {

                txtValue = td.textContent || td.innerText;

                if (txtValue.toUpperCase().indexOf(filter) > -1) {

                    found = true;

                    break;

                }

            }

        }

        if (found) {

            tr[i].style.display = "";

        } else {
```

```
        tr[i].style.display = 'none';
    }
}
});
</script>
```

```
<script src="js/script.js"></script>
</body>
</html>
```

Step 14: Create sales_details.php

Copy<?php

```
// Include config files
```

```
require_once "config/database.php";
```

```
require_once "config/session.php";
```

```
// Check if user is logged in, redirect if not
```

```
requireLogin();
```

```
// Define variables
```

```
$sales = [];
```

```
$success_message = "";
```

```
$error_message = "";
```

```
// Set default filter dates (last 30 days)
```

```

$end_date = date('Y-m-d');

$start_date = date('Y-m-d', strtotime('-30 days'));

// Handle date filtering
if(isset($_GET['filter'])) {

    $start_date = $_GET['start_date'] ?? $start_date;

    $end_date = $_GET['end_date'] ?? $end_date;

}

// Build SQL query for sales

$sql = "SELECT s.sale_id, s.invoice_number, s.sale_date, s.total_amount, s.payment_method,
        COALESCE(c.customer_name, 'Walk-in Customer') as customer_name, u.full_name as
staff_name

        FROM sales s

        LEFT JOIN customers c ON s.customer_id = c.customer_id

        LEFT JOIN users u ON s.user_id = u.user_id

        WHERE DATE(s.sale_date) BETWEEN ? AND ?

        ORDER BY s.sale_date DESC";

// Prepare and execute query
if($stmt = mysqli_prepare($conn, $sql)) {

    mysqli_stmt_bind_param($stmt, "ss", $start_date, $end_date);

    mysqli_stmt_execute($stmt);

    $result = mysqli_stmt_get_result($stmt);

```

```

while($row = mysqli_fetch_assoc($result)) {

    $sales[] = $row;

}

mysqli_stmt_close($stmt);

}

// Calculate summary data

$total_sales = count($sales);

$total_revenue = 0;

$payment_methods = ['cash' => 0, 'card' => 0, 'other' => 0];

foreach($sales as $sale) {

    $total_revenue += $sale['total_amount'];

    $payment_methods[$sale['payment_method']]++;

}

?>

<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Sales Details - Pharmacy Management System</title>

```

```
<link rel="stylesheet" href="css/styles.css">
```

```
</head>
```

```
<body>
```

```
<header>
```

```
<div class="container">
```

```
<h1>Sales Details</h1>
```

```
<div class="user-info">
```

```
Welcome, <?php echo htmlspecialchars($_SESSION["full_name"]); ?> |
```

```
<?php if(isAdmin()): ?>
```

```
<a href="admin_dashboard.php">Dashboard</a> |
```

```
<?php else: ?>
```

```
<a href="staff_dashboard.php">Dashboard</a> |
```

```
<?php endif; ?>
```

```
<a href="logout.php">Logout</a>
```

```
</div>
```

```
</div>
```

```
</header>
```

```
<main class="container">
```

```
<?php if(!empty($success_message)): ?>
```

```
<div class="alert alert-success"><?php echo $success_message; ?></div>
```

```
<?php endif; ?>
```

```
<?php if(!empty($error_message)): ?>
```

```
<div class="alert alert-danger"><?php echo $error_message; ?></div>
```

```
<?php endif; ?>
```

```
<div class="filter-section">
```

```
<h3>Filter Sales</h3>
```

```
<form action="" method="get" class="form-inline">
```

```
<div class="form-group">
```

```
<label for="start_date">Start Date:</label>
```

```
<input type="date" id="start_date" name="start_date" class="form-control"
value="<?php echo $start_date; ?>">
```

```
</div>
```

```
<div class="form-group">
```

```
<label for="end_date">End Date:</label>
```

```
<input type="date" id="end_date" name="end_date" class="form-control"
value="<?php echo $end_date; ?>">
```

```
</div>
```

```
<div class="form-group">
```

```
<input type="submit" name="filter" class="btn btn-primary" value="Filter">
```

```
</div>
```

```
</form>
```

```
</div>
```

```
<div class="sales-summary">
```

```
<h3>Sales Summary (<?php echo date('M d, Y', strtotime($start_date)); ?> - <?php  
echo date('M d, Y', strtotime($end_date)); ?>)</h3>
```

```
<div class="summary-stats">
```

```
<div class="stat-box">
```

```
<h4>Total Sales</h4>
```

```
<p class="stat-number"><?php echo $total_sales; ?></p>
```

```
</div>
```

```
<div class="stat-box">
```

```
<h4>Total Revenue</h4>
```

```
<p class="stat-number">$<?php echo number_format($total_revenue, 2); ?></p>
```

```
</div>
```

```
<div class="stat-box">
```

```
<h4>Cash Payments</h4>
```

```
<p class="stat-number"><?php echo $payment_methods['cash']; ?></p>
```

```
</div>
```

```
<div class="stat-box">
```

```
<h4>Card Payments</h4>
```

```
<p class="stat-number"><?php echo $payment_methods['card']; ?></p>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
<div class="sales-list">

    <h3>Sales List</h3>

    <input type="text" id="salesSearch" class="form-control" placeholder="Search
sales...">
```

```
<table class="data-table" id="salesTable">

    <thead>

        <tr>

            <th>Invoice #</th>

            <th>Date</th>

            <th>Customer</th>

            <th>Amount</th>

            <th>Payment Method</th>

            <th>Staff</th>

            <th>Actions</th>

        </tr>

    </thead>

    <tbody>

        <?php if(empty($sales)): ?>

            <tr>

                <td colspan="7" class="text-center">No sales found for the selected
period.</td>

            </tr>

        <?php else: ?>

            <?php foreach($sales as $sale): ?>
```

```

<tr>

    <td><?php echo htmlspecialchars($sale['invoice_number']); ?></td>

    <td><?php echo date('M d, Y H:i', strtotime($sale['sale_date'])); ?></td>

    <td><?php echo htmlspecialchars($sale['customer_name']); ?></td>

    <td>$<?php echo number_format($sale['total_amount'], 2); ?></td>

    <td><?php echo ucfirst($sale['payment_method']); ?></td>

    <td><?php echo htmlspecialchars($sale['staff_name']); ?></td>

    <td>

        <a href="view_sale.php?id=<?php echo $sale['sale_id']; ?>" class="btn
btn-sm">View Details</a>

    </td>

</tr>

<?php endforeach; ?>

<?php endif; ?>

</tbody>

</table>

</div>

</main>

<script>

// Search functionality

document.getElementById('salesSearch').addEventListener('keyup', function() {

    var input, filter, table, tr, td, i, txtValue;

    input = document.getElementById('salesSearch');

    filter = input.value.toUpperCase();

```

```
table = document.getElementById('salesTable');

tr = table.getElementsByTagName('tr');


for (i = 1; i < tr.length; i++) { // Start from 1 to skip header row

    var found = false;

    // Search in invoice, customer, staff columns (0, 2, 5)

    for (var j of [0, 2, 5]) {

        td = tr[i].getElementsByTagName('td')[j];

        if (td) {

            txtValue = td.textContent || td.innerText;

            if (txtValue.toUpperCase().indexOf(filter) > -1) {

                found = true;

                break;

            }

        }

    }

    if (found) {

        tr[i].style.display = "";

    } else {

        tr[i].style.display = 'none';

    }

}

});

</script>
```

```
<script src="js/script.js"></script>

</body>

</html>
```

Step 15: Create index.php (Main Entry Point)

Copy<?php

```
// Include config file

require_once "config/database.php";
require_once "config/session.php";


// Check if the user is already logged in, if yes redirect appropriately
if(isLoggedIn()) {
    if(isAdmin()) {
        header("location: admin_dashboard.php");
    } else {
        header("location: staff_dashboard.php");
    }
    exit;
}

?>
```

```
<!DOCTYPE html>

<html lang="en">

<head>
```

```
<meta charset="UTF-8">

<meta name="viewport" content="width=device-width, initial-scale=1.0">

<title>Pharmacy Management System</title>

<link rel="stylesheet" href="css/styles.css">

</head>

<body class="home-page">

  <div class="hero-section">

    <div class="container">

      <h1>Pharmacy Management System</h1>

      <p class="lead">Efficiently manage your pharmacy with our comprehensive
solution</p>

      <div class="login-options">

        <div class="login-card">

          <h2>Admin Login</h2>

          <p>Login as an administrator to access full system controls</p>

          <a href="login.php?role=admin" class="btn btn-primary">Admin Login</a>

        </div>

        <div class="login-card">

          <h2>Staff Login</h2>

          <p>
```

Copy