

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/221543364>

Efficient Algorithms for the Longest Path Problem

Conference Paper · December 2004

DOI: 10.1007/978-3-540-30551-4_74 · Source: DBLP

CITATIONS

41

READS

3,962

2 authors, including:



Ryuhei Uehara

Japan Advanced Institute of Science and Technology

209 PUBLICATIONS 1,265 CITATIONS

SEE PROFILE

Some of the authors of this publication are also working on these related projects:




Graph Drawing [View project](#)

Efficient Algorithms for the Longest Path Problem

Ryuhei UEHARA (JAIST)


Yushi UNO (Osaka Prefecture University)





The Longest Path Problem

- Finding a longest (vertex disjoint) path in a given graph
- Motivation (comparing to Hamiltonian path):
 - ... Approx. Algorithm, Parameterized Complexity
 - ... More practical/natural
 - ... More difficult(?)




The Longest Path Problem

- Known (hardness) results;
 - We cannot find a path of length $n - n^\epsilon$ in a given Hamiltonian graph in poly-time unless $P=NP$ [Karger, Motwani, Ramkumar; 1997]
 - We can find $O(\log n)$ length path [Alon, Yuster, Zwick; 1995]
($\Rightarrow O((\log n / \log \log n)^2)$ [Björklund, Husfeldt; 2003])
 - Approx. Alg. achieves $O(n / \log n)$ [AYZ95]
($\Rightarrow O(n(\log \log n / \log n)^2)$ [BH03])
- Exponential algorithm [Monien 1985]


The Longest Path Problem

- Known polynomial time algorithm;
- Dijkstra's Alg.(196?): Linear alg. for finding a longest path in a tree;




The Longest Path Problem


- Known polynomial time algorithm;
- Dijkstra's Alg.(196?): Linear alg. for finding a longest path in a tree;



The Longest Path Problem



- Known polynomial time algorithm;
- Dijkstra's Alg.(196?): Linear alg. for finding a longest path in a tree;






The Longest Path Problem

- Known polynomial time algorithm;
 - Dijkstra's Alg.(196?): Linear alg. for finding a longest path in a tree;




Approaches to the Efficient Algs to Longest Path Problem



1. Extension of the Dijkstra's algorithm
 - Weighted trees (linear), block graphs (linear), cacti ($O(n^2)$).
(ISAAC 2004)
2. Graph classes s.t. Hamiltonian Path can be found in poly time
 - Some graph classes having interval representations (bipartite permutation, interval biconvex graphs)
(ISAAC 2004)
3. Dynamic programming to the graph classes that have tree representations (on going)
 - Cacti(linear), ...

Approaches to the Efficient Algs to Longest Path Problem



1. Extension of the Dijkstra's algorithm
 - Weighted trees (linear), block graphs (linear), **cacti** ($O(n^2)$).
(ISAAC 2004)
2. Graph classes s.t. Hamiltonian Path can be found in poly time
 - Some graph classes having interval representations (bipartite permutation, **interval biconvex graphs**)
(ISAAC 2004)
3. Dynamic programming to the graph classes that have tree representations (on going)
 - Cacti(linear), ...



1. Ex of Dijkstra's Alg

Bulterman et.al. (*IPL*,2002) showed that the correctness of Dijkstra's alg stands for;


1. For each u, v ,
length of the **shortest** path between u and v
= length of the **longest** path between u and v
2. For each u, v, w ,
 $d(u, v) \leq d(u, w) + d(w, v)$
3. For each u, v, w ,
 $d(u, v) = d(u, w) + d(w, v)$ if and only if
 w is on the **unique** path between u and v



1. Ex of Dijkstra's Alg

Construct $G'=(V',E')$ from $G=(V,E)$ s.t.:

- $V \subseteq V'$
- For each $u, v \in V$,
length of the **shortest path** between u, v on G'
= length of the **longest path** between u, v on G
- For each $u, v \in V$,
the **shortest path** between u, v on G' is **unique**




1. Ex of Dijkstra's Alg

Theorem: ExDijkstra finds a longest path if G and G' satisfy the conditions.

ExDijkstra: $G=(V,E)$ and $G'=(V',E')$

1. pick any vertex w in V ;
2. find $x \in V$ with $\max\{d(w,x)\}$ on G' ;
3. find $y \in V$ with $\max\{d(x,y)\}$ on G' ;
4. x and y are the endpoints of the longest path in G , and $d(x,y)$ on G' is its length.



1. Ex of Dijkstra's Alg (Summary)

Theorem: Vertex/edge weighted tree (linear)

Theorem: Block graph ($O(|V|+|E|)$)

Theorem: **Cactus** ($O(|V|^2)$)





1. Ex of Dijkstra's Alg (Cacti)

Cactus:

Each block is a *cycle*


Two cycle share at most one vertex *which is a separator*






1. Ex of Dijkstra's Alg (Cacti)



Sample





1. Ex of Dijkstra's Alg (Cacti)



Sample






1. Ex of Dijkstra's Alg (Cacti)



Sample





1. Ex of Dijkstra's Alg (Cacti)



Sample






1. Ex of Dijkstra's Alg (Cacti)



Sample






1. Ex of Dijkstra's Alg (Cacti)



Sample






1. Ex of Dijkstra's Alg (Cacti)

Sample



Graph classes s.t. Hamiltonian Path can be found in poly time



Fact 1:


Hamiltonian Path is NP-hard on a **chordal graph**.
(In fact, strongly chordal split graph[Müller, 1997].)

Fact 2:

Hamiltonian Path is solvable on an **interval graph** in linear time. [Damaschke, 1993].



Our goal:


Poly-time algorithm for Longest Path on an **interval graph**.



Interval Graphs



- An interval graph $G=(V,E)$ has an interval representation s.t. $\{u,v\} \in E$ iff $I_u \cap I_v \neq \emptyset$





Interval Graphs

- An interval graph $G=(V,E)$ has an interval representation s.t. $\{u,v\} \in E$ iff $I_u \cap I_v \neq \emptyset$



Hamiltonian Path: linear time solvable.


Longest Path: ????

\Rightarrow Restricted interval graphs...



Restricted Interval Graphs

- An interval **biconvex** graph $G=(S \cup Y, E)$ has an interval representation s.t...







Restricted Interval Graphs

- Interval **biconvex** graph $G=(S \cup Y, E)$ is introduced [Uehara, Uno; 2004] from graph theoretical viewpoints;
 - ✓ *Natural analogy of biconvex graphs (bipartite graph class)*
 - ✓ *Generalization of proper interval graphs*
 - ✓ *Generalization of threshold graphs*
 - ✓ *Best possible class longest path can be found in poly time...*


Poly-time alg for longest path on an interval biconvex graph (idea)




- Find the trivial longest path P on $G[Y]$;
- Embed the vertices in S into P as possible;
- Adjust endpoints if necessary.




Poly-time alg for longest path on an interval biconvex graph (idea)




- Find the trivial longest path P on $G[Y]$;
- Embed the vertices in S into P as possible;
- Adjust endpoints if necessary.




Poly-time alg for longest path on an interval biconvex graph (idea)




- Find the trivial longest path P on $G[Y]$;
- Embed the vertices in S into P as possible;
- Adjust endpoints if necessary.




Poly-time alg for longest path on an interval biconvex graph (idea)




- Find the trivial longest path P on $G[Y]$;
- Embed the vertices in S into P as possible;
- Adjust endpoints if necessary.




Poly-time alg for longest path on an interval biconvex graph (idea)



- Find the trivial longest path P on $G[Y]$;
- Embed the vertices in S into P as possible;
- Adjust endpoints if necessary.




- ✓ How can we determine the vertices in S ?
- ✓ Where do we embed them?



Poly-time alg for longest path on an interval biconvex graph (idea)




- Embed the vertices in S into P as possible;



Poly-time alg for longest path on an interval biconvex graph (idea)



- Embed the vertices in S into P as possible;





Open Problems

- Longest Path on an interval graph??
 - Combination of *DP/Dijkstra* and *weighted maximum matching* on MPQ-tree representation?
 - Related to the following open problem?
Hamiltonian Path *with a start point* on an interval graph?
[Damaschke, 1993].
- Extension to
 - Longest *cycle* on some graph classes
 - *Hamiltonian cycle/path* on some graph classes