

GOOGLE TMT HACKATHON 2026

API Documentation

Build Tools. Break Barriers. Bridge Languages.

1. API Overview

The TMT Translation API allows you to translate text between Nepali, English, and Tamang using the Google TMT machine translation system. Every request must be authenticated with your unique team API key.

Base URL	<code>https://tmt.ilprl.ku.edu.np/lang-translate</code>
Method	POST
Format	application/json
Auth	Bearer Token (Authorization header)

2. Your API Key

Each registered team receives a unique API key. This key is confidential - **do not share it with other teams**.

Your Team Token	<code>team_XXXXXXXXXXXXXXXXXX</code>
-----------------	--------------------------------------

Your token will be shared privately with your team. For both team and individual participants, it will be sent via the team leader's email address collected during registration.

3. Request Format

Send a POST request with a JSON body and your token in the Authorization header.

Request Headers

Header	Value	Required
Content-Type	application/json	Yes
Authorization	Bearer team_XXXXXXXXXXXXXXXXXX	Yes

Request Body Fields

Field	Type	Required	Description
text	string	Yes	The sentence to translate

src_lang	string	Yes	Source language (see language codes below)
tgt_lang	string	Yes	Target language (must differ from src_lang)

Supported Language Codes

Language	Accepted Values
English	English / en / eng
Nepali	Nepali / ne / nep
Tamang	Tamang / tmg

Language codes are case-insensitive. You may use the full name, short (2-letter), or abbreviated (3-letter) form.

4. Response Format

All responses are JSON. Always check `message_type` - HTTP status is always 200 on success.

Field	Type	Description
message_type	string	SUCCESS or FAIL
message	string	Human-readable status or error description
src_lang	string	Normalized source language (e.g. English)
input	string	Original input text you sent
target_lang	string	Normalized target language (e.g. Nepali)
output	string	Translated text (empty string on failure)
timestamp	string	UTC timestamp of the translation event

5. Integration Guide & Sample Input / Output

Python

```
import requests

url = "https://tmt.ilprl.ku.edu.np/lang-translate"
headers = {
    "Content-Type": "application/json",
    "Authorization": "Bearer team_XXXXXXXXXXXXXXXXX" # your token
}
payload = {
    "text": "Hello, how are you?",
    "src_lang": "en",
    "tgt_lang": "ne"
}
```

```

response = requests.post(url, json=payload, headers=headers)
data = response.json()
if data["message_type"] == "SUCCESS":
    print("Translated:", data["output"])
else:
    print("Error:", data["message"])

```

JavaScript (for browser extension)

```

const response = await fetch("https://tmt.ilprl.ku.edu.np/lang-translate", {
  method: "POST",
  headers: {
    "Content-Type": "application/json",
    "Authorization": "Bearer team_XXXXXXXXXXXXXXXXX" // your token
  },
  body: JSON.stringify({
    text: "Hello, how are you?",
    src_lang: "en",
    tgt_lang: "ne"
  })
});
const data = await response.json();
console.log(data.output); // translated text

```

cURL

```

curl -X POST https://tmt.ilprl.ku.edu.np/lang-translate \
-H "Content-Type: application/json" \
-H "Authorization: Bearer team_Bearer team_XXXXXXXXXXXXXXXXX" \
-d '{
  "text": "Hello, how are you?",
  "src_lang": "en",
  "tgt_lang": "ne"
}'

```

6. Sample Input / Output

	English → Nepali	Nepali → Tamang	English → Tamang
text	Namaste, how are you?	तपाईंलाई कस्तो छ?	Good morning.
src_lang	en	ne	eng
tgt_lang	ne	tmg	tmg
output	नमस्ते, कस्तो छ?	हाडदा खाराइबा मुला?	ज्याबा सह्यो।

Success Response (JSON)

```

{
  "message_type": "SUCCESS",
  "message": "Translation successful",
  "src_lang": "English",
  "input": "Namaste, how are you?",
  "target_lang": "Nepali",
  "output": "नमस्ते, कस्तो छ?",
  "timestamp": "2026-04-25T10:32:00Z"
}

```

Error Response (JSON)

```
{  
  "message": "Invalid API token"  
}
```

7. Error Reference

HTTP Status	message	Cause
401	Authorization header missing or malformed	No Bearer token in header
401	Invalid API token	Token not recognised
400	Request body must be JSON	Wrong Content-Type or empty body
400	text, src_lang and tgt_lang are all required	One or more fields missing
400	src_lang and tgt_lang must be different	Same language on both sides
500	Translation failed	Internal model error

8. Important Notes for Participants

Sentence-level only	The API translates one sentence (with punctuation) at a time. For file translation (Track 2), split your document into individual sentences, translate each one, then reassemble.
File size limit	Maximum 1 MB per file upload for Track 2 submissions.
Keep your token private	Do not hardcode your token in public GitHub repositories. Use environment variables.
API unavailability	If the API is down during development, report immediately via the official WhatsApp / Discord group.
Rate limiting	Add a short delay between requests when translating large files to avoid overloading the server.