

COMP 110/L Lecture 20

Mahdi Ebrahimi

Slides are adapted from Dr. Kyle Dewey

Outline

- `super` in methods
- `abstract` **Classes and Methods**
- **Polymorphism**

`super` in **Methods**

Recap

You've seen `super` in constructors...

Recap

You've seen `super` in constructors...

```
public class Base {  
    public Base(int x) { ... }  
}
```

Recap

You've seen `super` in constructors...

```
public class Base {  
    public Base(int x) { ... }  
}
```

```
public class Sub extends Base {  
    public Sub(int x) {  
        super(x);  
    }  
}
```

super in Methods

`super` can also be used in methods when overloading.

Used to execute a superclass' implementation of a method.

super in Methods

`super` can also be used in methods when overloading.

Used to execute a superclass' implementation of a method.

```
public class Base {  
    public int returnNum() {  
        return 17;  
    }  
}
```


super in Methods

`super` can also be used in methods when overloading.

Used to execute a superclass' implementation of a method.

```
public class Base {  
    public int returnNum() {  
        return 17;  
    }  
}
```

```
public class Sub extends Base {  
    public int returnNum() {  
        return super.returnNum() + 3;  
    }  
}
```

super in Methods

super can also be used in methods when overloading.

Used to execute a superclass' implementation of a method.

```
public class Base {  
    public int returnNum() {  
        return 17;  
    }  
}
```

```
public class Sub extends Base {  
    public int returnNum() {  
        return super.returnNum() + 3;  
    }  
}
```


Returns 17

Example

- `Base.java`
- `Sub.java`
- `SuperMethodMain.java`

abstract Classes and Methods

Recap - A Problem



abstract **Classes**

Allows a class to be extended,
but disallows the creation of instances of that class

abstract **Classes**

Allows a class to be extended,
but disallows the creation of instances of that class

```
public class Mammal {  
    public Mammal(String s) { ... }  
}
```

abstract **Classes**

**Allows a class to be extended,
but disallows the creation of instances of that class**

```
public class Mammal {  
    public Mammal(String s) { ... }  
}  
  
    new Mammal("some string")
```


abstract **Classes**

**Allows a class to be extended,
but disallows the creation of instances of that class**

```
public class Mammal {  
    public Mammal(String s) { ... }  
}  
  
    new Mammal("some string")
```

```
public abstract class Mammal {  
    public Mammal(String s) { ... }  
}
```

abstract **Classes**

Allows a class to be extended,
but disallows the creation of instances of that class

```
public class Mammal {  
    public Mammal(String s) { ... }  
}  
  
new Mammal("some string")
```

```
public abstract class Mammal {  
    public Mammal(String s) { ... }  
}  
  
new Mammal("some string")
```

Does not compile

Example

- `AbstractBase.java`
- `AbstractSub.java`
- `AbstractMain.java`

abstract Methods

- Methods of abstract classes can also be defined abstract
 - To be overridden later
- abstract methods have no bodies

abstract **Methods**

- **Methods of abstract classes can also be defined abstract**
 - **To be overridden later**
- **abstract methods have no bodies**

```
public abstract class Abstract {  
    public abstract int getValue();  
}
```

abstract Methods

- **Methods of abstract classes can also be defined abstract**
 - **To be overridden later**
- **abstract methods have no bodies**

```
public abstract class Abstract {  
    public abstract int getValue();  
}
```


```
public class Sub extends Abstract {  
    public int getValue() { return 5; }  
}
```

Example

- `ArithmeticOperation.java`
- `Add.java`
- `Subtract.java`

Polymorphism

Revisit



```
Cat cat = new Cat("Tom");  
Dog dog = new Dog("Rover");  
cat.breathe();  
dog.breathe();
```

```
Cat cat = new Cat("Tom");  
Dog dog = new Dog("Rover");  
cat.breathe();  
dog.breathe();
```

Tom the mammal takes a breath
Rover the mammal takes a breath

```
Cat cat = new Cat("Tom");  
Dog dog = new Dog("Rover");  
cat.breathe();  
dog.breathe();
```

Tom the mammal takes a breath
Rover the mammal takes a breath

```
Mammal m1 = new Cat("Tom");  
Mammal m2 = new Dog("Rover");  
m1.breathe();  
m2.breathe();
```

```
Cat cat = new Cat("Tom");  
Dog dog = new Dog("Rover");  
cat.breathe();  
dog.breathe();
```

Tom the mammal takes a breath
Rover the mammal takes a breath

```
Mammal m1 = new Cat("Tom");  
Mammal m2 = new Dog("Rover");  
m1.breathe();  
m2.breathe();
```

Tom the mammal takes a breath
Rover the mammal takes a breath

Polymorphism

- “many-forms”
- A `Mammal` could be a `Cat` or a `Dog`
- Specific use in Java: a variable with a superclass type can hold an instance of any subclass, too

Polymorphism

- “many-forms”
- A `Mammal` could be a `Cat` or a `Dog`
- Specific use in Java: a variable with a superclass type can hold an instance of any subclass, too

```
Mammal m1 = new Cat ("Tom") ;  
Mammal m2 = new Dog ("Rover") ;
```

Polymorphism Significance

Can write code without knowing exactly which implementation is used.

Polymorphism

Significance

Can write code without knowing exactly which implementation is used.

```
public static void method(Mammal m) {  
    m.breathe();  
}
```

Example

- `Car.java`
- `SportsCar.java`
- `SemiTruck.java`
- `CarMain.java`

Example

- `MammalRevisited.java`
- `CatRevisited.java`
- `DogRevisited.java`
- `MammalMainRevisited.java`