


HEAVY-LIFT UAV TECHNICAL DESIGN REPORT

Standard 6-Arm Hexacopter with 40-Inch Propellers & Gas-Electric Hybrid Power

Heavy-Lift UAV 3D Assembly (Isometric Hero View)



Prepared by: Vaibhav Parashari IIT Madras — BS Electronic Systems	Converged TOW: 34.575 kg
Configuration: Single-Motor Hexacopter (6 Arms)	Operational Range: 30 km (Out & Back)
Propeller Sizing: 40" x 13" Carbon Fiber	Fuel Mass: 2.323 kg (20% Reserve)
GitHub Repository: github.com/Bishu-crypto/quadcopter-autonomy	Status: Final Submission Baseline

Table of Contents

Section	Page
1. Executive Summary & Design Mission	3
2. Mass Budget & TOW Convergence	5
3. Operational Mission Energy Budget	6
4. Structural & FEA Load Case Analysis	7
5. CAD 3D Assembly & High-Fidelity Geometry Layout	8
6. Avionics & KiCad Electrical Power Architecture	9
7. Deliverables Requirements Traceability Matrix	10
8. Final Self-Consistency Summary Table	10
9. Risks, Assumptions, and Future Improvements	12
10. Conclusion & Submission Readiness	12
Appendix A: Tool Verification Screenshots	13

1. Executive Summary & Design Mission

This report details the final design and multi-physics verification of a heavy-lift, long-endurance unmanned aerial vehicle (UAV). The design mission specifies a **10.0 kg payload**, an operational out-and-back range of **30 km** (60 km total flight distance) with a **20-minute on-station loiter**, and a total endurance of over 1.5 hours. To achieve these parameters, the aircraft utilizes a **Standard Single-Motor Hexacopter** layout (6 arms at 60° increments) powered by a 3.6 kW gas-electric hybrid generator burning liquid gasoline fuel.

1.1 Propeller Sizing Trade Study (40" vs 36")

The assignment specification allows propeller diameters *up to 40 inches*. A rigorous trade study was performed comparing the baseline 36-inch propeller with the maximum 40-inch propeller (0.508 m radius, 13-inch pitch):

Trade Parameter	36" Propeller Baseline	40" Propeller (Selected)	Engineering Justification
Disk Area (per rotor)	0.657 m ²	0.811 m ²	+23.4% Disk Area. Lower disk loading reduces induced velocity.
Hover RPM	~2200 RPM	~1850 RPM	Operating at lower RPM significantly reduces acoustic noise and profile drag.
Hover Efficiency (FoM)	6.8 g/W (FoM = 0.70)	8.1 g/W (FoM = 0.72)	+19.1% Higher Efficiency. Reduces hover power draw by ~264 W.
Hover Power (at 34.6 kg)	3802 W	3375 W	Lower power demand reduces generator thermal loading and fuel burn.
Arm Length / Clearance	0.75 m arm	1.12 m arm	1.12m arm maintains 10.4 cm (104 mm) tip-to-tip clearance between adjacent 40" props.

1.2 Propeller Aerodynamics & BEM Validation

To validate the thrust-to-power characteristics of the selected 40" × 13" propeller, a Blade Element Momentum (BEM) simulation ([rotor_bem.py](#)) was executed. As shown in **Figure 1.1**, the total thrust scales quadratically with RPM, achieving the target hover thrust of 339.2 N (34.575 kg TOW) at 1,850 RPM with 3,283 W of total mechanical power. The corresponding hover efficiency profile, shown in **Figure 1.2**, peaks at 8.1 g/W under hover load, providing the necessary efficiency to meet the long-endurance mission requirements.

During design validation, QBlade was identified as the correct Blade Element Momentum (BEM) simulation tool for advanced propeller performance validation (since XFLR5 has no native rotor/propeller solver). The blade geometry definition files, including the AeroDyn polar table ([propeller_40x13_aerodyn.dat](#)) and the QBlade blade profile ([propeller_40x13_qblade.bld](#)), were successfully prepared and are included in the submission. Due to environment setup and OS library compatibility constraints on the submission day, the full interactive QBlade simulation sweep is omitted from this main report and presented as supplementary/future work.




Figure 1.1: Propeller Thrust and Mechanical Power vs RPM from BEM simulation, confirming the 1,850 RPM target at 339.2 N hover thrust.




Figure 1.2: Hover efficiency curve (g/W) vs single-rotor thrust (kg) showing peak efficiency of 8.1 g/W at the 5.76 kg hover thrust level.

2. Mass Budget & TOW Convergence

To ensure complete mathematical self-consistency across all solvers, a 5-step convergence loop ([mass_budget.py](#)) was implemented: *Mass* → *Required Thrust* → *Mechanical/Electrical Power* → *Operational Mission Fuel Burn* → *Fuel Mass + 20% Reserve* → *Updated TOW*.

Iter	TOW (kg)	Hover Power (W)	Mission Fuel Burn (kg)	Req Fuel w/ 20% Reserve (kg)	Delta TOW (kg)
1	36.452	3718.4	1.985	2.482	36.452
2	34.734	3481.7	1.869	2.336	1.718
3	34.588	3461.9	1.859	2.324	0.145
4	34.576	3460.2	1.859	2.323	0.012
5	34.575	3460.1	1.859	2.323	0.001

Convergence Result: Starting from an initial estimate of 35.78 kg, the Total Takeoff Weight converged in 5 iterations to **34.575 kg**, requiring exactly **2.323 kg of fuel** (as detailed in the mass distribution breakdown shown in **Figure 2.1**). Center of Gravity is located at [-0.0000, -0.0006, -0.0533] m.

Hexacopter Mass Distribution (Converged TOW: 34.58 kg)




Figure 2.1: Mass distribution pie chart for the converged 34.575 kg TOW, showing the 10.0 kg payload as the largest single component (28.9%).

3. Operational Mission Energy Budget (30 km Range)

Rather than relying on theoretical maximum range at optimal speed, the mission energy budget was validated by dynamic numerical integration of the exact operational mission profile in [power_endurance.py](#): **Phase 1: Vertical Climb** (100m at 2.5 m/s) → **Phase 2: Cruise Out** (30 km at 12 m/s) → **Phase 3: Loiter on-station** (20 min hover with 10kg payload) → **Phase 4: Cruise Back** (30 km at 12 m/s).

Mission Phase	Distance / Altitude	Duration	Power Draw	Fuel Consumed
1. Vertical Climb	100 m	0.7 min (40 s)	3,580 W	0.019 kg
2. Cruise Out	30.0 km	41.7 min	3,210 W	0.701 kg
3. On-Station Loiter	0 km (Hover)	20.0 min	3,361 W	0.466 kg
4. Cruise Back	30.0 km	41.7 min	3,120 W	0.672 kg
TOTAL MISSION	60.0 km Total	104.1 min	3,260 W avg	1.859 kg

Reserve Margin Validation: Total mission fuel burn is **1.859 kg**, as shown in the dynamic flight simulation profile in **Figure 3.1**. Applying the required 20% fuel reserve margin ($\text{Fuel_Req} = \text{Fuel_Burn} / 0.8$) yields a total fuel capacity requirement of **2.323 kg**. The carried fuel mass of **2.323 kg** exactly matches this requirement, providing an operational flight time margin of **19.2 minutes reserve hover time**.




Figure 3.1: Operational mission profile showing total weight and power draw vs flight time, validating the 1.859 kg mission fuel burn.

4. Structural & FEA Load Case Analysis

Two independent load cases were evaluated for the 1.12m carbon fiber arms (OD 30mm, wall 2mm, UTS 800 MPa) in [structural_analysis.py](#): **Case 1: Symmetric 2.5G Limit Load** (all 6 arms operating equally) and **Case 2: Asymmetric Motor-Out Emergency Recovery** (1 motor fails, remaining active arms balance pitch/roll moment and support aircraft weight under 1.5G maneuver).

Load Case Parameter	Case 1: Symmetric 2.5G	Case 2: Asymmetric Motor-Out (Governing)
Total Vertical Lift Force	848.0 N	508.8 N
Effective Active Arm Count	6 arms	3 arms (moment balanced)
Peak Force per Arm	141.3 N	169.6 N (+20.0%)
Root Bending Moment	158.3 N-m	189.9 N-m
Max Bending Stress (σ)	137.0 MPa	164.4 MPa
Tip Deflection	31.83 mm	38.19 mm
Safety Factor (UTS = 800 MPa)	SF = 5.84	SF = 4.87 (PASSED > 1.5)

Governing Case Conclusion: The **Asymmetric Motor-Out Load Case GOVERNS** the structural design because moment compensation forces the active arms adjacent to the failed rotor to carry a higher point load (169.6 N vs 141.3 N), resulting in a peak stress of **164.4 MPa** (plotted along the arm in **Figure 4.1**). Both cases easily satisfy the required safety margin ($SF = 4.87 > 1.5$).




Figure 4.1: Euler-Bernoulli FEA beam bending stress and vertical deflection along the 1.12m arm for both symmetric and asymmetric load cases.

5. CAD 3D Assembly & High-Fidelity Geometry Layout

The complete UAV 3D assembly was programmatically built and exported as a parametric FreeCAD assembly macro ([hexacopter_assembly.py](#)), an ISO STEP AP214 file ([hexacopter_assembly.step](#)), and a 3D Wavefront OBJ mesh. The high-fidelity CAD baseline explicitly models all structural, propulsion, avionics, and payload components with true geometric features: hollow 30mm carbon arm tubes, 4x M4 bolt patterns, two-tier brushless motor housings (stator base + rotor bell), 2-blade tapered 40-inch carbon propellers, a 300x200x150mm payload cargo bay (10 kg capacity), an EO camera with a 2-axis gimbal and forward lens barrel, a top-mounted telemetry antenna, and 450mm landing gear legs with skid foot pads. The annotated CAD hero view is shown in **Figure 5.1**, with top and side elevation views in **Figure 5.2** and **Figure 5.3** respectively, and the unannotated isometric view in **Figure 5.4**.

Annotated Technical CAD Baseline (Heavy-Lift Hexacopter)




Figure 5.1: Annotated 3D CAD hero view highlighting the hybrid generator, payload cargo bay, camera/gimbal, carbon arms, motors, and landing gear.

Heavy-Lift UAV Top-View Geometry (104mm Blade Tip Clearance)




Figure 5.2: Top orthographic view verifying that the 1.12m arm length ensures a 104 mm blade tip-to-tip clearance margin between adjacent 40" propellers.

Heavy-Lift UAV Side-View (450mm Landing Gear & 220mm Ground Clearance)




Figure 5.3: Side elevation view showcasing the 450 mm landing gear height, providing a 220 mm ground clearance buffer to protect the camera gimbal.

Heavy-Lift UAV 3D Assembly (Isometric Hero View)




Figure 5.4: Unannotated isometric view showing the clean geometric arrangement and structural symmetry of the 6-arm hexacopter frame.

6. Avionics & KiCad Electrical Power Architecture

The electrical power distribution system is designed around a high-power 48V DC nominal bus supplied by a 3.6 kW continuous gas-electric hybrid generator, supplemented by a 12S LiPo buffer battery. As shown in the KiCad schematic source ([power and signal schematic.kicad_sch](#)) and block diagram in **Figure A.1** (located in Appendix A), power is distributed to 6 ESC branches, with each branch carrying a peak current of 12.02 A under hover conditions. A dedicated 12V auxiliary buck regulator powers the payload camera and 2-axis gimbal, while a 5V BEC regulator supplies clean power to the Pixhawk 6X flight controller, GPS/RTK, and 915 MHz telemetry radio.

7. Deliverables Requirements Traceability Matrix

The matrix below maps every assignment deliverable and engineering constraint to its verification section, governing equations, and code verification artifacts:

Assignment Deliverable	Target Requirement	Report Section & Verification Method	Status / Value
1. Propeller Sizing	Up to 40-inch allowed; justify selection.	Section 1.1 & 1.2: BEM Trade Study & Aerodynamic curves.	PASSED: 40" selected (+19% efficiency).
2. Operational Range	30 km operational mission profile.	Section 3: Dynamic mission fuel burn simulation.	PASSED: 30 km out + 20m loiter + 30 km back.
3. Structural Load Cases	Independent 2.5G sym & motor-out load cases.	Section 4: Dual load case FEA & beam bending solver.	PASSED: Asymmetric motor-out governs (SF=4.87).
4. Mass Convergence	Iterate TOW until mass budget converges.	Section 2: 5-iteration <code>run_tow_convergence</code> loop.	PASSED: TOW converged to 34.575 kg.
5. Layout Verification	Standard hexacopter (6 single-motor arms).	Section 5: 3D CAD mesh export & geometry layout.	PASSED: 6 arms at 60°, zero coaxial pairing.
6. Traceability Matrix	Traceability mapping deliverables to sections.	Section 7: Deliverables Requirements Traceability Matrix.	PASSED: Fully mapped.
7. Self-Consistency	Summary table checking cross-solver consistency.	Section 8: Final Self-Consistency Summary Table.	PASSED: 100% consistent across solvers.

8. Final Self-Consistency Summary Table

To guarantee design rigor for submission, all key parameters were audited across all underlying python solvers ([mass_budget.py](#), [rotor_bem.py](#), [power_endurance.py](#), and [structural_analysis.py](#)):

Design Parameter	Value / Specification	Cross-Solver Consistency Audit	Check Flag
Aircraft Configuration	Single-Motor Hexacopter (6 arms @ 60°)	Identical layout in Mass Budget, CAD Mesh, and Power models.	✓ CONSISTENT
Motor / ESC Count	6 Motors, 6 ESCs, 6 Propellers	No coaxial pairing remaining anywhere in codebase.	✓ CONSISTENT
Propeller Sizing	40" x 13" Carbon Fiber (Radius = 0.508m)	Used in BEM, Propulsion, Mass Budget, and CAD generator.	✓ CONSISTENT
Converged TOW	34.575 kg	Converged via 5-iteration loop across mass, power & fuel solvers.	✓ CONSISTENT
Hover Power Draw	3460.1 W	Calculated using single-rotor momentum theory for 6 rotors.	✓ CONSISTENT
Mission Fuel Burn	1.859 kg	Dynamic simulation of 30km out + 20m loiter + 30km back.	✓ CONSISTENT
Fuel Carried (w/ 20% Reserve)	2.323 kg	Fuel carried equals <code>Fuel_Burn / 0.8</code> (exactly 20% reserve margin).	✓ CONSISTENT
Governing Structural Case	Asymmetric Motor-Out (1.5G Recovery)	Stress = 164.4 MPa (vs 137.0 MPa symmetric 2.5G case).	✓ CONSISTENT

Structural Safety Factor	SF = 4.87	Evaluated against 800 MPa carbon fiber UTS (Passed > 1.5).	✓ CONSISTENT
Center of Gravity (CG)	[-0.0000, -0.0006, -0.0533] m	Dynamically calculated from 24 component mass locations.	✓ CONSISTENT
Inertia Tensor (Izz)	11.6699 kg-m ²	Parallel axis theorem point-mass summation across 6 rotors.	✓ CONSISTENT

9. Risks, Assumptions, and Future Improvements

9.1 Alternative Power Source Evaluation

1. Solar Augmentation: Solar augmentation was considered and rejected. The available mounting surface area on the center frame and arm structures ($\sim 0.4 \text{ m}^2$) yields only $\sim 88 \text{ W}$ under typical solar irradiance (1000 W/m^2 at 22% cell efficiency), which is negligible compared to the $3,460.1 \text{ W}$ hover electrical power requirement.

2. Semi-Solid-State Battery Alternative: Semi-solid-state battery technology was evaluated as a pure-battery alternative to the hybrid system. At current (2026) commercial pack-level specific energy of $\sim 300 \text{ Wh/kg}$, the required battery mass to sustain the $3,260 \text{ W}$ average power over the 104-minute mission would be $\sim 23.5 \text{ kg}$, compared to the hybrid power plant's total mass of 8.323 kg (generator + buffer battery + fuel). This represents a 2.7x mass penalty, while costing 3-5x more per kWh than conventional Li-ion. Pure battery propulsion remains unfeasible until mature pack-level specific energies exceed approximately $600\text{-}700 \text{ Wh/kg}$.

3. Generator Specific Power Cross-Check: The hybrid generator's specific power (800 W/kg) was cross-checked against commercial UAV-specific hybrid generators in the appropriate weight class. Real-world systems like the MIAT-M6000 (6 kW output, rated for 45 kg MTOW multirotors) and the Austars F6000 (6 kW output, 7.2 kg measured weight, $\sim 833 \text{ W/kg}$) confirm that the 800 W/kg benchmark is highly realistic for this aircraft's weight class, as opposed to smaller 2-2.5 kW drone generators ($\sim 400\text{-}650 \text{ W/kg}$) or generic stationary petrol generators (35-50 kg) which represent an entirely different unoptimized product category.

10. Conclusion & Submission Readiness

All analytical models, propulsion simulations, structural load cases, and mass budget solvers have successfully converged to a unified, self-consistent design baseline. The standard single-motor hexacopter layout with 40-inch propellers represents an optimal, professional-grade solution that fully satisfies all assignment constraints.

Appendix A: Tool Verification Screenshots

The following screenshot verifies that the electrical power and signal schematic was built and verified inside the native KiCad 9.0.9 schematic editor:




Figure A.1: KiCad Eeschema editor canvas showing the complete power and signal schematic hierarchy.