RESIDENTIAL ESS SOLUTION

Rack-Mounted Energy Storage Battery Series

CE MSDS UN38.3 ISO

PRODUCT FEATURES

FLEXIBLE INVESTMENT

5kWh/10kWh modular design, scalable from 5 to 150 kWh.

CERTIFICATION

UN38.3 MSDS IEC62619

PERFECT COMPATIBILITY

Compatible to most inverter brands on the market.

SAFETY

BMS & Breaker two Level over current protection.

APPLICATION SCENARIOS

Suitable for villas, detached homes, rural self-built houses, penthouse/duplex apartments, farm and ranch residences, island homes, historic district residences, home offices, small bed-and-breakfasts and inns



PARAMETERS

Model	48100R	48200R
Voltage(v)	40~58.4	
Cell	3.2V100Ah	3.2V200Ah
Module	16S1P	
Number of parallel machines	15PCS	
Nominal voltage(V)	51.2	
Nominal Capacity(Ah)	100	200
Nominal Energy(kWh)	5.12	10.24
Maximum power output(kW)	5.12	10.24
suggestion discharge current(A)	75	150
suggestion charging current(A)	50	100
Recommended cut-off voltage(Min)(V)	40	
Recommended charging voltage(Max)(V)	58.4	
Cycles(25℃,0.5C,DOD80%	≥6000	
Charging temperature(℃)	0~55	
Discharge temperature(℃)	-20~55	
Operating humidity	<95%R.H	
Communication mode	CAN/RS485	
Dry contact	Customized by demand	
Optional modules	Bluetooth	
Product size(W*D*H,mm)	442*430*117	550*442*222
Packing size(W*D*H,mm)	535*527*290	637*497*315
IP class	IP21	
System weight(kg)	Approx 48	Approx 86
Certification	IEC62619/UN38.3/MSDS	