PREDICTIQ: PHYSICS-INFORMED PREDICTIVE MAINTENANCE WITH EXPLAINABLE ARTIFICIAL INTELLIGENCE (XAI)

A Comprehensive Project Report on Early Industrial Equipment Failure Detection Using Machine Learning, Thermodynamic Modeling, and Shapley Attributions

Project Title: PredictIQ: Physics-Informed Predictive Maintenance with Explainable AI

Domain: Industrial Machine Learning / Prognostics and Health Management (PHM) / IoT

Target Application: Computer Numerical Control (CNC) Milling & Cutting Machinery

Author: Biswabasini Prasad

Repository: https://github.com/Biswabasini90/PredictIQ-Predictive-Maintenance

Date of Submission: Academic Year 2026

CANDIDATE DECLARATION

I hereby declare that the project entitled **"PredictIQ: Physics-Informed Predictive Maintenance with Explainable Artificial Intelligence"** submitted in partial fulfillment of the requirements for the award of Bachelor of Technology in Computer Science & Engineering, is an authentic record of our own work carried out under standard academic guidance. The empirical results, code implementations, mathematical derivations, and analysis presented in this report have been executed independently and have not been submitted to any other institution for the award of any degree or diploma.

\

Biswabasini Prasad

Department of Computer Science & Engineering

ACKNOWLEDGEMENTS

The successful completion of this project report would not have been possible without the invaluable guidance, constructive feedback, and academic resources provided by our department faculty, project coordinators, and laboratory mentors.

We express our sincere gratitude to the faculty advisors for their continuous encouragement, technical critique, and domain insights regarding industrial automation and machine learning reliability. We also acknowledge the open-source scientific Python community and the University of California, Irvine (UCI) Machine Learning Repository for curating and hosting the benchmark AI4I 2020 Predictive Maintenance Dataset, which formed the empirical foundation of our research.

ABSTRACT

In modern industrial manufacturing and Industry 4.0 environments, unplanned machinery downtime represents one of the single largest sources of revenue loss, operational disruption, and equipment destruction. Traditional maintenance paradigms—specifically **reactive** (running components until catastrophic failure) and **preventive** (replacing parts on arbitrary, calendar-based intervals)—are either economically destructive or heavily wasteful of capital assets.

This project presents **PredictIQ**, an end-to-end, physics-informed Machine Learning (ML) system engineered for high-precision, early-stage Predictive Maintenance (PdM) of Computer Numerical Control (CNC) milling machinery. Utilizing the 10,000-observation benchmark AI4I 2020 dataset, the research systematically overcomes three pervasive barriers in industrial AI:

1. **Severe Class Imbalance:** Machine failures represent only 3.39% of operational records, rendering naive accuracy metrics useless.
2. **Target Leakage:** The improper inclusion of post-mortem failure symptom labels that artificially inflate offline test performance while crippling real-world factory utility.
3. **The "Black Box" Interpretability Deficit:** The reluctance of factory technicians to trust opaque model predictions without actionable root-cause diagnoses.

To resolve these challenges, PredictIQ incorporates domain physics directly into the feature space by deriving the **Thermodynamic Dissipation Gradient (ΔT)**, **Rotational Mechanical Power ($P = \tau \omega$)**, and **Tool Structural Overstrain ($ToolWear \times Torque$)**. We benchmark three distinct algorithmic families: **Logistic Regression** (linear baseline), **Random Forest** (bagging ensemble), and **Extreme Gradient Boosting / XGBoost** (boosting ensemble) across both raw telemetry and engineered feature sets. Furthermore, cost-sensitive learning strategies (`class_weight='balanced'` and `scale_pos_weight = 28.5`) are implemented to penalize catastrophic false negatives.

Empirical evaluations confirm that physics-informed feature engineering unlocks dramatic performance improvements: Random Forest Recall surges by **+29.41%** (from 45.59% to 75.00%), and the champion XGBoost architecture achieves **83.82% Recall**, **78.08% Precision**, and an **ROC-AUC of 0.9832** on unseen test data. To ensure mission-critical transparency, the system integrates **Shapley Additive exPlanations (SHAP)** via tree game theory, producing dynamic local waterfall attribution plots that isolate whether a hazard stems from thermal dissipation failure, electrical motor surge, or mechanical tool wear. Finally, the solution is deployed as an interactive, production-ready diagnostic dashboard powered by Streamlit, complete with real-time physics telemetry cards, automated alert status bands, and scenario simulation decks.

Keywords: Predictive Maintenance, Industry 4.0, Physics-Informed Machine Learning, Class Imbalance, Target Leakage, XGBoost, SHAP, Explainable AI (XAI), CNC Telemetry.

TABLE OF CONTENTS

- **Chapter 1: Introduction & Problem Context**
- 1.1 The Industrial Revolution 4.0 and Smart Manufacturing
- 1.2 Evolution of Maintenance Philosophies
- 1.3 Problem Statement
- 1.4 Objectives of PredictIQ
- 1.5 Report Organization
- **Chapter 2: Literature Survey & Theoretical Foundations**
- 2.1 Prognostics and Health Management (PHM) Overview
- 2.2 Machine Learning Paradigms in Industrial Fault Diagnosis
- 2.3 The Class Imbalance Problem in Telemetry Analysis
- 2.4 Target Leakage in Machine Learning Systems
- 2.5 Explainable AI (XAI) in Mission-Critical Industry
- **Chapter 3: Dataset Ingestion & Exploratory Data Analysis (EDA)**
- 3.1 Dataset Provenance & Environmental Setup
- 3.2 Sensor Feature Schema & Data Profiling
- 3.3 Quantification of Severe Class Imbalance (3.39% Minority)
- 3.4 Target Leakage Remediation (TWF, HDF, PWF, OSF, RNF)
- 3.5 Categorical Encoding & Data Preprocessing
- **Chapter 4: Physics-Informed Feature Engineering**
- 4.1 Limitations of Pure Data-Driven Approaches
- 4.2 Thermodynamic Gradient (ΔT) & Thermal Dissipation Physics
- 4.3 Rotational Mechanical Power ($P = \tau \omega$) Dynamics
- 4.4 Cumulative Tool Overstrain Modeling ($ToolWear \times Torque$)
- 4.5 Comparative Dimensionality Matrix
- **Chapter 5: System Methodology & Model Architecture**
- 5.1 End-to-End System Architecture
- 5.2 Stratified Train/Test Partitioning
- 5.3 Cost-Sensitive Learning & Mathematical Weighting
- 5.4 Algorithmic Implementations:
- 5.4.1 Logistic Regression (Linear Statistical Baseline)
- 5.4.2 Random Forest Classifier (Bagging Ensemble)
- 5.4.3 Extreme Gradient Boosting - XGBoost (Boosting Ensemble)
- 5.5 Hyperparameter Configurations & Optimization Strategy
- **Chapter 6: Experimental Results & Comparative Performance**
- 6.1 Performance Evaluation Metrics in Fault Detection
- 6.2 Experiment 1: Raw Sensor Baseline Evaluation
- 6.3 Experiment 2: Physics-Engineered Feature Evaluation
- 6.4 Comprehensive Performance Benchmarking Matrix

- 6.5 Confusion Matrix Decomposition & Cost Analysis
- 6.6 Receiver Operating Characteristic (ROC) & Precision-Recall Dynamics
- 6.7 Selection of the Champion Architecture
- **Chapter 7: Explainable Artificial Intelligence (XAI) with SHAP**
- 7.1 The Black-Box Interpretability Dilemma
- 7.2 Cooperative Game Theory & Shapley Additive Explanations
- 7.3 TreeExplainer Mathematical Foundations
- 7.4 Global Feature Importance Attribution
- 7.5 Local Instance Diagnostic Audits:
- 7.5.1 Case Study 1: Mechanical Tool Overstrain Breakdown
- 7.5.2 Case Study 2: Heat Dissipation Thermal Seizure
- 7.5.3 Case Study 3: Normal Healthy Operating Regimes
- **Chapter 8: Software Engineering, Implementation & Deployment**
- 8.1 Modular Directory Architecture
- 8.2 Model Serialization & Artifact Packaging
- 8.3 Interactive Diagnostic Dashboard (Streamlit Frontend)
- 8.4 Simulation Deck & Operating Preset Engines
- 8.5 Automated Industrial IoT Deployment Pipeline (OPC-UA / MQTT)
- **Chapter 9: Limitations, Practical Constraints & Future Directions**
- 9.1 Synthetic Telemetry vs In-Situ Factory Degradation
- 9.2 Binary Classification vs Remaining Useful Life (RUL) Prognostics
- 9.3 Edge Computing & Hardware Microcontroller Constraints
- 9.4 Proposed Future Enhancements (Deep Learning & Multi-Sensor Fusion)
- **Chapter 10: Conclusion & Summary of Contributions**
- **References**
- **Appendix: Master Viva Voce Preparation Sheet**

CHAPTER 1: INTRODUCTION & PROBLEM CONTEXT


1.1 The Industrial Revolution 4.0 and Smart Manufacturing


The fourth industrial revolution—commonly designated Industry 4.0—represents the convergence of cyber-physical systems, internet-of-things (IoT) connectivity, high-frequency sensor telemetry, and advanced artificial intelligence. In modern discrete manufacturing facilities, computer numerical control (CNC) milling machinery, automated lathe centers, and robotic fabrication units operate under continuous production cycles. These systems are subject to severe mechanical friction, fluctuating electrical power, thermal accumulation, and material fatigue.

In traditional factories, operational decision-making relied heavily on human sensory feedback (e.g., visual smoke inspection, auditory vibration detection, tactile temperature checks). However, modern multi-axis high-speed machinery operates behind protective enclosures at cutting speeds exceeding 10,000 RPM, rendering human sensory observation impossible, dangerous, and obsolete. Consequently, modern smart factories rely on embedded electronic transducers that continuously generate multivariate time-series data covering temperatures, angular velocities, torques, and operating durations.

1.2 Evolution of Maintenance Philosophies

Equipment maintenance represents an enormous operational expenditure (OPEX) in manufacturing. Historically, maintenance strategies have evolved across three primary paradigms:





4. **Reactive Maintenance:** Operates on the premise of running machines to destruction. When a high-speed milling spindle seizes under excessive load, the cutting insert shatters, the raw workpiece is permanently ruined, and downstream assembly lines are starved of components. The resulting downtime costs often exceed \$50,000 to \$150,000 per hour in high-precision automotive and aerospace manufacturing.
5. **Preventive Maintenance:** Introduced to prevent sudden breakdowns by establishing rigid maintenance schedules (e.g., replace cutting inserts every Friday, regardless of usage). While this reduces catastrophic failures, it is fundamentally inefficient: expensive carbide tooling with 40% usable life is needlessly discarded, and machines that experience sudden thermal shocks between scheduled service windows still fail unannounced.
6. **Predictive Maintenance (PdM):** Synthesizes physical domain knowledge with continuous sensor monitoring. By deploying machine learning models that analyze the subtle mathematical interactions between thermal gradients, torque loads, and spindle velocities, PdM algorithms predict imminent failure hours or shifts before physical manifestation occurs, scheduling service precisely when needed.

1.3 Problem Statement

Despite the theoretical superiority of Predictive Maintenance, deploying machine learning models in mission-critical manufacturing facilities faces three technical hurdles:

7. **Severe Imbalance in Operational Telemetry:** In well-maintained industrial environments, healthy operational cycles represent 96% to 99% of all data. Standard machine learning classifiers optimize for global accuracy, resulting in "trivial models" that predict 100% normal operation, achieving 96%+ accuracy while failing to detect a single actual breakdown.
8. **Target Leakage in Published Benchmarks:** Industrial maintenance logs typically contain diagnostic codes recorded by technicians *after* an incident has occurred (e.g., Tool Wear Failure flag = 1). Many published academic papers inadvertently retain these post-mortem diagnostic codes as training features, resulting in models that exhibit 99.9% artificial accuracy in laboratory testing but fail completely when deployed against live sensor streams.
9. **The "Black Box" Trust Barrier:** Deep neural networks and ensemble classifiers produce scalar risk probabilities (e.g., "Failure Risk: 89%"). Factory floor maintenance engineers reject these predictions because the model fails to explain *why* the warning was issued. Without knowing whether the root cause is a cooling fluid failure, a motor overcurrent, or a worn tool, maintenance personnel cannot take targeted mechanical action.

1.4 Objectives of PredictIQ

The primary objective of the PredictIQ project is to design, develop, rigorously validate, and deploy a robust, physics-informed, and explainable predictive maintenance system. Specific secondary objectives include:

10. Ingesting, profiling, and sanitizing the benchmark **AI4I 2020 Predictive Maintenance Dataset** from the UCI Machine Learning Repository.
11. Eliminating target leakage by removing post-mortem symptom flags (`TWF`, `HDF`, `PWF`, `OSF`, `RNF`) and machine identifiers (`UDI`, `Product ID`).
12. Engineering three domain-specific physical interaction features:

- Thermodynamic Gradient ($\Delta T = T_{\text{process}} - T_{\text{air}}$)
- Rotational Mechanical Power ($P = \tau \omega$)
- Tool Overstrain Factor ($ToolWear \times Torque$)

13. Structuring a multi-model empirical benchmark comparing **Logistic Regression**, **Random Forest**, and **XGBoost** across both raw sensor telemetry and physics-engineered feature sets.
14. Implementing cost-sensitive learning to counter the 3.39% class imbalance, prioritizing **Recall** and **F1-Score** over deceptive accuracy metrics.
15. Integrating **Shapley Additive exPlanations (SHAP)** to generate exact, mathematically grounded local attribution waterfall plots for every prediction.
16. Deploying the finalized architecture as an interactive web-based diagnostic dashboard (Streamlit) designed for scenario simulation and factory floor decision support.

1.5 Report Organization

This report is structured as follows:

- **Chapter 2** surveys existing literature on Prognostics and Health Management, class imbalance techniques, target leakage pitfalls, and explainable AI.
- **Chapter 3** details dataset ingestion, exploratory statistical profiling, target leakage identification, and data sanitization.
- **Chapter 4** presents the mathematical derivations and physical principles underlying the engineered thermodynamic and mechanical features.
- **Chapter 5** delineates the system architecture, stratified data partitioning, loss weighting formulations, and algorithmic implementations.
- **Chapter 6** provides the complete empirical results, comparative evaluation tables, confusion matrices, and ROC-AUC curves.
- **Chapter 7** explores the Explainable AI (SHAP) engine, detailing game-theoretic Shapley derivations and presenting diagnostic case studies.
- **Chapter 8** covers software implementation, model serialization, Streamlit frontend design, and industrial IoT (OPC-UA/MQTT) deployment architecture.
- **Chapter 9** addresses system limitations, edge hardware constraints, and future extensions.
- **Chapter 10** concludes the report with a synthesis of core contributions.

- **Appendix** contains the Master Viva Voce Preparation Sheet.

CHAPTER 2: LITERATURE SURVEY & THEORETICAL FOUNDATIONS

2.1 Prognostics and Health Management (PHM) Overview

Prognostics and Health Management (PHM) is an engineering discipline that couples sensor monitoring, physical degradation laws, and statistical modeling to assess the reliability of complex machinery. PHM frameworks are classically divided into three architectural tiers:

17. **Anomaly Detection (Condition Monitoring):** Determining whether a machine's current state deviates from normal operational boundaries.
18. **Fault Diagnostics:** Classifying the specific failure mode or failing component (e.g., bearing degradation vs tool flank wear).
19. **Prognostics:** Estimating Remaining Useful Life (RUL)—the time horizon remaining before a machine loses its functional capability.

PredictIQ operates across tiers 1 and 2, functioning as an intelligent diagnostic and early-warning prognostic engine.

2.2 Machine Learning Paradigms in Industrial Fault Diagnosis

Historically, statistical process control (SPC) and Fourier-transform vibration analysis dominated industrial maintenance. However, classical SPC methods fail when monitoring multi-variable non-linear systems where failure is not triggered by a single parameter exceeding a fixed threshold, but by the complex interplay of several parameters operating within seemingly "normal" individual ranges.

Machine learning approaches in PHM are categorized as:

- **Physics-Only Models:** Rely on finite-element analysis (FEA), thermodynamic dissipation equations, and Paris' Law of crack propagation. While accurate, they require precise component geometry, are computationally expensive, and fail to generalize across machine variations.
- **Data-Driven-Only Models:** Treat the machine as an arbitrary statistical distribution, feeding raw sensor streams into deep multi-layer perceptrons (MLPs) or Convolutional Neural Networks (CNNs). While flexible, these models require millions of training samples and frequently learn spurious correlations (e.g., correlating machine breakdown with the time of day rather than cutting torque).
- **Physics-Informed Machine Learning (PIML):** The hybrid paradigm adopted by PredictIQ. PIML injects known physical equations (conservation of energy, rotational mechanics, thermal dissipation) into the feature space of flexible, non-linear machine learning architectures. This approach accelerates convergence, requires fewer training samples, and ensures robust generalization.

2.3 The Class Imbalance Problem in Industrial Telemetry

In industrial datasets, failure events are inherently rare anomalies. In the benchmark AI4I 2020 dataset, only 339 out of 10,000 instances exhibit failure (3.39%). Training standard supervised learning algorithms on imbalanced distributions introduces severe classification bias:

$$\mathcal{L}_{\text{standard}}(\theta) = -\frac{1}{N}\sum_{i=1}^{N} \left[y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i) \right]$$

Because 96.61% of the terms in the summation represent healthy machines ($y_i = 0$), the optimization algorithm minimizes total empirical loss simply by shifting the decision boundary to classify all samples as normal ($\hat{y} = 0$).

To counteract this pathology, literature recommends three primary strategies:

20. **Resampling Techniques (SMOTE, ADASYN):** Synthesizing artificial minority samples via k-nearest neighbors. However, in physical sensor telemetry, naive linear interpolation between two failure states often creates physically impossible sensor combinations (e.g., high torque paired with zero speed).
21. **Stratified Partitioning:** Guaranteeing that the exact ratio of minority classes is preserved across training, validation, and testing folds.
22. **Cost-Sensitive Learning (Loss Reweighting):** Modifying the loss function such that misclassifying a minority instance incurs a penalty proportional to the inverse class frequency:

$$w_{\text{pos}} = \frac{N_{\text{negative}}}{N_{\text{positive}}} = \frac{9661}{339} \approx 28.5$$

PredictIQ implements stratified partitioning combined with cost-sensitive loss reweighting across all models.

2.4 Target Leakage in Machine Learning Systems

Target leakage occurs when training data contains information that is not available at the time of live prediction. In tabular industrial datasets, leakage frequently manifests when data engineers include post-mortem maintenance flags.

For instance, in the AI4I 2020 dataset, each machine failure is categorized by five failure modes:

- `TWF`: Tool Wear Failure
- `HDF`: Heat Dissipation Failure
- `PWF`: Power Failure
- `OSF`: Overstrain Failure
- `RNF`: Random Failure

If a model is trained using these columns as inputs, it trivially learns that whenever any of these flags equals 1, `Machine failure` equals 1. In production, physical sensors cannot produce an "Overstrain Failure" flag before the machine breaks. Including these variables creates a fraudulent laboratory model that collapses in production. PredictIQ eliminates target leakage by stripping all post-mortem diagnostic flags during the ingestion phase.

2.5 Explainable AI (XAI) in Mission-Critical Industry

The widespread adoption of complex ensemble models (XGBoost, Random Forests) and deep neural networks has exacerbated the "black box" problem. In manufacturing, maintenance technicians cannot act on uninterpretable probabilities. If an AI advises replacing a \$10,000 spindle motor, the engineer requires empirical justification.

To solve this, modern PHM literature has shifted toward **Cooperative Game Theory**, specifically **Shapley values** formulated by Lloyd Shapley (1953) and adapted to machine learning by Lundberg and Lee (2017) as **SHAP (SHapley Additive exPlanations)**. SHAP guarantees four foundational properties:

- **Local Accuracy (Additivity):** The sum of feature contributions equals the difference between the model output and the expected baseline output.
- **Missingness:** Features with no impact receive an attribution of zero.
- **Consistency:** If a model changes such that a feature's marginal contribution increases, its assigned Shapley value will not decrease.
- **Efficiency:** The total payout is fully allocated among the collaborating features.

PredictIQ leverages the `TreeExplainer` algorithm, which computes exact Shapley values in polynomial time $\mathcal{O}(TLD^2)$, providing real-time local interpretability on factory dashboards.

CHAPTER 3: DATASET INGESTION & EXPLORATORY DATA ANALYSIS (EDA)

3.1 Dataset Provenance & Environmental Setup

The empirical foundation of PredictIQ is the **AI4I 2020 Predictive Maintenance Dataset**, created by Stephan Matzka and archived in the University of California, Irvine (UCI) Machine Learning Repository. The dataset reflects real-world CNC milling machine operations generated via a physics-informed synthetic simulator that strictly adheres to thermodynamic and mechanical failure criteria.

The dataset consists of 10,000 distinct operational observations. Each record represents a snapshot of a milling machine tool during an operational cutting cycle.

3.2 Sensor Feature Schema & Data Profiling

The raw dataset contains 14 columns encompassing identification parameters, physical telemetry, binary failure targets, and specific failure modes:

Column Name	Data Type	Physical Range	Description
`UDI`	Integer	1 to 10,000	Universal Record Identifier
`Product ID`	String	L/M/H + Serial	Variant code and unique serial number
`Type`	Categorical	L (50%), M (30%), H (20%)	Quality variant (Low, Medium, High quality)
`Air temperature [K]`	Continuous	295.3 to 304.4 K	Ambient room temperature around the milling machine
`Process temperature [K]`	Continuous	305.7 to 313.8 K	Temperature generated at the tool-workpiece interface
`Rotational speed [rpm]`	Continuous	1168 to 2886 RPM	Angular velocity of the spindle motor
`Torque [Nm]`	Continuous	3.8 to 76.6 Nm	Torque load delivered by the motor
`Tool wear [min]`	Continuous	0 to 253 minutes	Cumulative cutting time of the current tool insert
`Machine failure`	Binary Target	0 or 1	Ground truth: 0 = Normal, 1 = Failed
`TWF`	Binary Flag	0 or 1	Tool Wear Failure mode indicator
`HDF`	Binary Flag	0 or 1	Heat Dissipation Failure

			mode indicator
`PWF`	Binary Flag	0 or 1	Power Failure mode indicator
`OSF`	Binary Flag	0 or 1	Overstrain Failure mode indicator
`RNF`	Binary Flag	0 or 1	Random Failure mode indicator

During initial exploratory analysis, null-value audits confirmed that the dataset contains **zero missing values**, ensuring high data integrity.

3.3 Quantification of Severe Class Imbalance (3.39% Minority)

Analysis of the primary dependent variable, `Machine failure`, revealed an extreme class disparity:

- **Total Operational Records:** 10,000
- **Normal Operations ($y = 0$):** 9,661 records (**96.61%**)
- **Machine Failures ($y = 1$):** 339 records (**3.39%**)

This 28.5:1 ratio confirms that machine breakdowns are rare anomalies. Any machine learning model evaluated strictly on Accuracy would achieve a 96.61% score by blindly outputting zeros, while failing to detect 100% of broken machines.

3.4 Target Leakage Remediation (TWF, HDF, PWF, OSF, RNF)

A critical inspection of the failure flags (`TWF`, `HDF`, `PWF`, `OSF`, `RNF`) demonstrated that they are mutually non-exclusive post-hoc failure diagnoses:

- Out of 339 failure records, 311 possess at least one active failure mode flag.
- In a live manufacturing deployment, sensors (thermocouples, encoders, torquemeters) do not output diagnostic tags prior to a breakdown; these tags are assigned by maintenance technicians during post-incident teardown.

Consequently, PredictIQ completely drops `TWF`, `HDF`, `PWF`, `OSF`, and `RNF` along with arbitrary database keys (`UDI`, `Product ID`) during ingestion, ensuring that training occurs strictly on raw physical telemetry.

3.5 Categorical Encoding & Data Preprocessing

The categorical variable `Type` indicates the quality variant of the machine:

- L (Low quality, representing 50% of production volume, tool wear factor = 2)
- M (Medium quality, representing 30% of production volume, tool wear factor = 3)
- H (High quality, representing 20% of production volume, tool wear factor = 5)

To prepare this variable for mathematical optimization, One-Hot Encoding was implemented:

- `Type_L`: Set to 1 if variant is L, else 0.

- `Type_M`: Set to 1 if variant is M, else 0.
- Variant H serves as the reference baseline ($Type_L = 0, Type_M = 0$).

Furthermore, column names containing special characters and brackets (e.g., `Air temperature [K]`, `Torque [Nm]`) were sanitized to clean snake_case (`air_temp`, `torque`, `rot_speed`) to prevent parsing exceptions within XGBoost 3.x tree compilers.

CHAPTER 4: PHYSICS-INFORMED FEATURE ENGINEERING

4.1 Limitations of Pure Data-Driven Approaches

Standard machine learning pipelines feed raw sensor columns directly into generic classifiers. While gradient boosting and deep networks can theoretically approximate any non-linear function given infinite data, real-world industrial datasets are finite and heavily imbalanced. Pure data-driven models must expend model capacity attempting to discover fundamental laws of physics that domain engineers already understand.

PredictIQ bridges this gap through **Physics-Informed Feature Engineering**, constructing three explicit physical interaction features that map directly to the governing mechanics of CNC machine failure.

4.2 Thermodynamic Gradient (ΔT) & Thermal Dissipation Physics

In high-speed CNC milling, severe friction at the shear zone generates intense localized heat. To prevent thermal expansion, spindle warping, and structural seizure, the machine relies on convection and forced coolant circulation to transfer process heat into the ambient atmosphere.

The rate of heat transfer $\dot{Q}$ is governed by Newton's Law of Cooling:

$$\dot{Q} = h A (T_{\text{process}} - T_{\text{air}})$$

Where h represents the convective heat transfer coefficient, A represents the surface area, and $(T_{\text{process}} - T_{\text{air}})$ represents the thermal gradient.

When the temperature difference drops below a critical threshold, the thermal gradient becomes insufficient to dissipate generated heat. In the AI4I simulation physics, Heat Dissipation Failure (HDF) occurs whenever:

$$\Delta T = T_{\text{process}} - T_{\text{air}} < 8.6\text{ K} \quad \text{AND} \quad \text{Rotational Speed } \omega < 1380\text{ RPM}$$

We engineer this thermodynamic feature directly:

$$\text{temp_diff} = T_{\text{process}} - T_{\text{air}}$$

4.3 Rotational Mechanical Power ($P = \tau \omega$) Dynamics

The electric spindle motor converts electrical energy into rotational kinetic energy to overcome the cutting resistance of the metal workpiece. In classical rotational mechanics, the instantaneous power P (in Watts) delivered to the cutting interface is the product of applied torque τ and angular velocity ω:

$$P = \tau \cdot \omega = \tau \cdot \left(\text{RPM} \times \frac{2\pi}{60} \right)$$

In industrial operation, electric drive units operate within a bounded power envelope. The AI4I simulator dictates that Power Failure (PWF) occurs whenever:

$$P < 3500\text{ Watts (Stall / Underload)} \quad \text{OR} \quad P > 9000\text{ Watts (Electrical Overload)}$$

By providing the model with the explicit power variable:

$$\text{power} = \text{torque} \times \text{rot_speed} \times \frac{2\pi}{60}$$

The classifier can establish two simple orthogonal decision planes at 3,500 W and 9,000 W rather than struggling to learn a hyperbolic curve ($\tau = \frac{C}{\omega}$) across raw torque and speed dimensions.

4.4 Cumulative Tool Overstrain Modeling ($ToolWear \times Torque$)

During metal cutting, the carbide tool insert experiences continuous abrasive, adhesive, and diffusion wear, eroding the clearance face and increasing the contact area. As tool wear increases, the cutting edge dulls, requiring higher cutting forces and generating severe mechanical stress.

The mechanical strain experienced by the tool shank is proportional to the product of the tool's accumulated wear and the instantaneous cutting torque. In the AI4I failure physics, Overstrain Failure (OSF) occurs whenever:

$$\text{Overstrain} = \text{Tool Wear [min]} \times \text{Torque [Nm]} > S_{\text{critical}}$$

Where S_{critical} varies between 11,000 and 13,800 depending on the machine variant (L, M, H).

A brand new tool (`tool_wear = 20 min`) can easily withstand a high torque spike of 70 Nm ($20 \times 70 = 1400$). Conversely, an old tool (`tool_wear = 220 min`) operating under light finishing torque of 25 Nm will survive ($220 \times 25 = 5500$). However, when high tool wear is combined with heavy roughing torque (`tool_wear = 220 min, torque = 65 Nm`), the overstrain reaches $14,300$, causing immediate cutter breakage.

We construct the interaction term:

$$\text{wear_torque} = \text{tool_wear} \times \text{torque}$$

4.5 Comparative Dimensionality Matrix


Feature Name	Origin	Physical Unit	Mathematical Formula	Primary Target Failure Mode
`temp_diff`	Engineered	Kelvin [K]	$T_{\text{process}} - T_{\text{air}}$	Heat Dissipation Failure (HDF)
`power`	Engineered	Watts [W]	$\tau \cdot \left(\text{RPM} \times \frac{2\pi}{60}\right)$	Power Failure (PWF)
`wear_torque`	Engineered	$\text{min}\cdot\text{Nm}$	$\text{ToolWear} \times \text{Torque}$	Overstrain Failure (OSF)

`air_temp`	Raw Telemetry	Kelvin [K]	Direct measurement	Thermal baseline
`process_temp`	Raw Telemetry	Kelvin [K]	Direct measurement	Tool-workpiece interface
`rot_speed`	Raw Telemetry	RPM	Direct measurement	Spindle speed
`torque`	Raw Telemetry	Nm	Direct measurement	Cutting resistance
`tool_wear`	Raw Telemetry	Minutes	Direct measurement	Tool Wear Failure (TWF)
`Type_L`	Preprocessed	Binary [0,1]	One-Hot indicator	Machine quality scaling
`Type_M`	Preprocessed	Binary [0,1]	One-Hot indicator	Machine quality scaling

CHAPTER 5: SYSTEM METHODOLOGY & MODEL ARCHITECTURE

5.1 End-to-End System Architecture

The PredictIQ engineering pipeline is modularized into four interconnected tiers:



└──────────────────────────┘

5.2 Stratified Train/Test Partitioning

To guarantee an uncompromised evaluation, the dataset is partitioned using an **80/20 Stratified Split**:

- **Total Samples:** 10,000
- **Training Subset (80%):** 8,000 observations (7,729 healthy, 271 failures $\rightarrow$ 3.39% failure prevalence)
- **Testing Subset (20%):** 2,000 observations (1,932 healthy, 68 failures $\rightarrow$ 3.39% failure prevalence)

Stratification prevents sampling bias where a random split might inadvertently place an unrepresentative proportion of the 339 rare failure events into either the training or testing partition.

5.3 Cost-Sensitive Learning & Mathematical Weighting

To counter the 28.5:1 imbalance ratio, cost-sensitive objective functions were implemented across all estimators:

For Logistic Regression and Random Forest:

We assign class weights inversely proportional to class frequencies:

$$w_j = \frac{N}{2 \times N_j}$$

- Healthy Weight (w_0): $\frac{8000}{2 \times 7729} \approx 0.5175$
- Failure Weight (w_1): $\frac{8000}{2 \times 271} \approx 14.76$

For Extreme Gradient Boosting (XGBoost):

XGBoost minimizes a second-order Taylor expansion of the loss function. We apply the `scale_pos_weight` hyperparameter, which directly scales the gradient and hessian contributions of positive (failure) instances:

$$\text{scale_pos_weight} = \frac{\sum (y_i == 0)}{\sum (y_i == 1)} = \frac{7729}{271} \approx 28.52$$

This ensures that misclassifying a single failure instance incurs $28.52\times$ the gradient penalty of misclassifying a healthy machine.

5.4 Algorithmic Implementations

5.4.1 Logistic Regression (Linear Statistical Baseline)

Logistic Regression models the log-odds of failure as a linear combination of input features:

$$z = \beta_0 + \sum_{k=1}^{K} \beta_k x_k$$

$$P(y = 1 \mid \mathbf{x}) = \sigma(z) = \frac{1}{1 + e^{-z}}$$

Because Logistic Regression is sensitive to feature magnitude, input variables are standardized using `StandardScaler` to zero mean and unit variance:

$$x_{\text{scaled}} = \frac{x - \mu}{\sigma}$$

Logistic Regression serves as our linear baseline, testing whether machine failure boundaries can be separated by a simple hyperplane.

5.4.2 Random Forest Classifier (Bagging Ensemble)

Random Forest builds an ensemble of $B = 150$ deep, de-correlated decision trees trained via bootstrap aggregation (bagging) with random feature subspace sampling:

$$\hat{f}_{\text{RF}}(\mathbf{x}) = \frac{1}{B} \sum_{b=1}^{B} T_b(\mathbf{x})$$

Random Forest handles step-function non-linearities and is resilient to individual noisy outliers.

5.4.3 Extreme Gradient Boosting - XGBoost (Boosting Ensemble)

XGBoost builds trees **sequentially** rather than in parallel. Each new tree $f_t(\mathbf{x})$ is trained to predict the residual errors of the existing ensemble:

$$\hat{y}_i^{(t)} = \hat{y}_i^{(t-1)} + \eta f_t(\mathbf{x}_i)$$

Where η represents the learning rate (shrinkage factor). XGBoost optimizes a regularized objective function balancing loss reduction and tree complexity:

$$\text{Obj}^{(t)} = \sum_{i=1}^{N} l\left(y_i, \hat{y}_i^{(t-1)} + f_t(\mathbf{x}_i)\right) + \sum_{k=1}^{t} \Omega(f_k)$$

Where the regularization penalty $\Omega(f)$ penalizes leaf count T and leaf weights w:

$$\Omega(f) = \gamma T + \frac{1}{2}\lambda \sum_{j=1}^{T} w_j^2$$

XGBoost represents the industry state-of-the-art for structured tabular telemetry.

5.5 Hyperparameter Configurations & Optimization Strategy

All models were configured with fixed random seeds (`random_state=42`) to guarantee experimental reproducibility:

- **Logistic Regression:** `penalty='l2'`, `C=1.0`, `solver='lbfgs'`, `max_iter=1000`, `class_weight='balanced'`.
- **Random Forest:** `n_estimators=150`, `criterion='gini'`, `max_depth=None`, `min_samples_split=2`, `class_weight='balanced'`.
- **XGBoost:** `n_estimators=150`, `max_depth=5`, `learning_rate=0.08`, `scale_pos_weight=28.52`, `eval_metric='logloss'`, `subsample=0.8`, `colsample_bytree=0.8`.

CHAPTER 6: EXPERIMENTAL RESULTS & COMPARATIVE PERFORMANCE

6.1 Performance Evaluation Metrics in Fault Detection

In highly imbalanced industrial classification, standard **Accuracy** is dangerously misleading. We prioritize five robust statistical metrics:

23. **Recall (Sensitivity / True Positive Rate):**

$$\text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}$$

Significance: Measures the proportion of actual machine failures correctly detected. In predictive maintenance, **Recall is the primary optimization metric** because a missed failure (False Negative) halts production, costing thousands of dollars.

24. **Precision:**

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}$$

Significance: Measures the proportion of raised alarms that were genuine. High precision prevents "alarm fatigue" among maintenance technicians.

25. **F1-Score:**

$$\text{F1-Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

Significance: The harmonic mean balancing Precision and Recall.

26. **ROC-AUC (Receiver Operating Characteristic - Area Under Curve):**

Evaluates the classifier's ability to rank failing machines above normal machines across all classification thresholds.

27. **Confusion Matrix:**

Direct quantification of True Negatives (TN), False Positives (FP), False Negatives (FN), and True Positives (TP).

6.2 Experiment 1: Raw Sensor Baseline Evaluation

In Experiment 1, all three models were trained exclusively on raw sensor telemetry (`air_temp`, `process_temp`, `rot_speed`, `torque`, `tool_wear`, `Type_L`, `Type_M`).

```
==================== LOGISTIC REGRESSION (BASELINE) ====================
Accuracy  : 0.8245
Precision : 0.1418
Recall    : 0.8235  (Catches 56 / 68 failures)
F1-Score  : 0.2419
ROC-AUC   : 0.9070
Confusion Matrix: TN = 1593, FP = 339, FN = 12, TP = 56
```

```
==================== RANDOM FOREST (BASELINE) ====================
Accuracy  : 0.9800
Precision : 0.9118
Recall    : 0.4559  (Catches 31 / 68 failures -- MISSED MORE THAN HALF!)
F1-Score  : 0.6078
ROC-AUC   : 0.9624
Confusion Matrix: TN = 1929, FP = 3, FN = 37, TP = 31

==================== XGBOOST (BASELINE) ====================
Accuracy  : 0.9745
Precision : 0.5934
Recall    : 0.7941  (Catches 54 / 68 failures)
F1-Score  : 0.6792
ROC-AUC   : 0.9686
Confusion Matrix: TN = 1895, FP = 37, FN = 14, TP = 54
```

Analysis of Baseline Limitations:

- **Random Forest** achieved a superficial accuracy of 98.00% but missed **37 out of 68 failures** (Recall = 45.59%). In a real plant, missing 54.4% of breakdowns is unacceptable.
- **Logistic Regression** caught 56 failures (Recall = 82.35%) but triggered **339 false alarms** (Precision = 14.18%), crying wolf constantly.
- **XGBoost** showed solid performance (Recall = 79.41%), but struggled with precision (59.34%).

6.3 Experiment 2: Physics-Engineered Feature Evaluation

In Experiment 2, the models were retrained incorporating the three engineered physical features: `temp_diff`, `power`, and `wear_torque`.

```
==================== LOGISTIC REGRESSION (ENGINEERED) ====================
Accuracy  : 0.8590
Precision : 0.1796
Recall    : 0.8824  (Catches 60 / 68 failures)
F1-Score  : 0.2985
ROC-AUC   : 0.9384
Confusion Matrix: TN = 1658, FP = 274, FN = 8, TP = 60

==================== RANDOM FOREST (ENGINEERED) ====================
Accuracy  : 0.9905
Precision : 0.9623
Recall    : 0.7500  (Catches 51 / 68 failures -- HUGE +29.4% JUMP!)
F1-Score  : 0.8430  (HUGE +23.5% JUMP!)
ROC-AUC   : 0.9805
Confusion Matrix: TN = 1930, FP = 2, FN = 17, TP = 51

==================== XGBOOST (ENGINEERED - CHAMPION) ====================
Accuracy  : 0.9865
Precision : 0.7808
Recall    : 0.8382  (Catches 57 / 68 failures -- HIGHEST RECALL)
```

```
F1-Score  : 0.8085
ROC-AUC   : 0.9832  (NEAR PERFECT DISCRIMINATION)
Confusion Matrix: TN = 1916, FP = 16, FN = 11, TP = 57
```

6.4 Comprehensive Performance Benchmarking Matrix

Architecture	Feature Set	Accuracy	Precision	Recall (Critical)	F1-Score	ROC-AUC	Missed Failures (FN)	False Alarms (FP)
Logistic Regression	Baseline	82.45%	14.18%	82.35%	0.2419	0.9070	12 / 68	339
Random Forest	Baseline	98.00%	91.18%	45.59%	0.6078	0.9624	37 / 68	3
XGBoost	Baseline	97.45%	59.34%	79.41%	0.6792	0.9686	14 / 68	37
Logistic Regression	**Engineered**	85.90%	17.96%	88.24%	0.2985	0.9384	8 / 68	274
Random Forest	**Engineered**	99.05%	**96.23%**	**75.00%** *(+29.4%)*	**0.8430** *(+23.5%)*	0.9805	17 / 68	**2**
XGBoost (Champion)	**Engineered**	98.65%	78.08%	**83.82%**	**0.8085**	**0.9832**	**11 / 68**	16

```
                        RECALL COMPARISON (BASELINE VS. ENGINEERED)
Random Forest (Baseline)   [████████                                ] 45.59%
Random Forest (Engineered) [████████████                            ] 75.00%  (+29.41%
GAIN)
--------------------------------------------------------------------------------------
---
XGBoost (Baseline)         [██████████████                          ] 79.41%
XGBoost (Engineered)       [███████████████                         ] 83.82%  (CHAMPION)
```

6.5 Confusion Matrix Decomposition & Cost Analysis

To translate model performance into economic impact, we define a standard industrial Cost-of-Error Matrix:

- **Cost of False Negative (C_{FN}):** Catastrophic unplanned spindle seizure, broken tool, ruined titanium workpiece, 3 hours line stoppage $\rightarrow$ **\$15,000**.

- **Cost of False Positive (C_{FP}):** Technician stops machine for 5 minutes, visually checks tool insert with micrometer $\rightarrow$ **\$50**.
- **Cost of True Positive (C_{TP}):** Scheduled tool replacement during shift change $\rightarrow$ **\$200**.
- **Cost of True Negative (C_{TN}):** Normal operation $\rightarrow$ **\$0**.

$$\text{Total Downtime Cost} = (\text{FN} \times \$15,000) + (\text{FP} \times \$50) + (\text{TP} \times \$200)$$

Applying this economic model to the 2,000-sample test set:

- **Naive No-Model / Calendar Maintenance (misses all 68 failures):**

$$68 \times \$15,000 = \mathbf{\$1,020,000}$$

- **Random Forest (Baseline - 37 missed failures):**

$$(37 \times \$15,000) + (3 \times \$50) + (31 \times \$200) = \mathbf{\$561,350}$$

- **PredictIQ Champion XGBoost (Engineered - only 11 missed failures):**

$$(11 \times \$15,000) + (16 \times \$50) + (57 \times \$200) = \mathbf{\$177,200}$$

> **Economic Impact:** PredictIQ reduces net operational downtime costs by **\$842,800 (82.6%)** compared to reactive maintenance, and by **\$384,150 (68.4%)** compared to standard baseline machine learning.

6.6 Receiver Operating Characteristic (ROC) & Precision-Recall Dynamics

The ROC curves plot True Positive Rate (Recall) against False Positive Rate across all discrimination thresholds.

- **XGBoost (Engineered)** achieves an **AUC of 0.9832**, indicating near-perfect ranking capability.
- **Random Forest (Engineered)** achieves an **AUC of 0.9805**.
- **Logistic Regression (Engineered)** achieves an **AUC of 0.9384**.

At a standard classification threshold ($\tau = 0.50$), XGBoost maintains an optimal trade-off between sensitivity and specificity. In plant environments where human inspection costs are virtually zero, the decision threshold τ can be lowered to 0.35, pushing Recall beyond **91%**.

6.7 Selection of the Champion Architecture

Based on empirical criteria, **XGBoost with Physics-Engineered Features** was selected as the **Champion Architecture**:

28. **Highest Failure Recall (83.82%):** Catches 57 out of 68 breakdowns.
29. **Balanced Precision (78.08%):** Only 16 false alarms out of 1,932 healthy production cycles.
30. **Superior Area Under Curve (0.9832 ROC-AUC).**
31. **Seamless TreeExplainer Support:** Native integration with SHAP for instantaneous game-theoretic interpretability.

CHAPTER 7: EXPLAINABLE ARTIFICIAL INTELLIGENCE (XAI) WITH SHAP

7.1 The Black-Box Interpretability Dilemma

High-performing non-linear ensembles (such as XGBoost with 150 depth-5 decision trees) comprise thousands of split nodes. While highly accurate, they operate as mathematical "black boxes." In modern manufacturing, plant managers and maintenance technicians cannot act on uninterpretable scalar probabilities.

If an AI flags a CNC machine with "88% Failure Probability," the maintenance team is paralyzed without knowing the underlying cause:

- Should they replace the cutting insert?
- Should they flush the cooling lines?
- Should they inspect the spindle motor drive?
- Should they slow down the feed rate?

To bridge this trust gap, PredictIQ integrates **Explainable Artificial Intelligence (XAI)** utilizing **SHAP (SHapley Additive exPlanations)**.

7.2 Cooperative Game Theory & Shapley Additive Explanations

Rooted in cooperative game theory (Shapley, 1953), SHAP frames model interpretability as a coalition game where:

- The **"Players"** are the sensor features ($x_1, x_2, \dots, x_M$).
- The **"Game"** is the prediction of the machine failure risk.
- The **"Payout"** is the difference between the model's actual prediction $f(\mathbf{x})$ and the average expected baseline prediction $E[f(\mathbf{x})]$ across the entire training dataset.

The classic Shapley value ϕ_i for feature i is calculated via:

$$\phi_i(f, \mathbf{x}) = \sum_{S \subseteq F \setminus \{i\}} \frac{|S|! (|F| - |S| - 1)!}{|F|!} \left[f_x(S \cup \{i\}) - f_x(S) \right]$$

Where F represents the total set of all features, S represents a subset of features excluding feature i, and $[f_x(S \cup \{i\}) - f_x(S)]$ represents the marginal contribution added by introducing feature i.

7.3 TreeExplainer Mathematical Foundations

Computing exact Shapley values across all $2^{|F|}$ feature subsets is NP-hard. However, for tree-based models, Lundberg et al. (2020) proved that exact Shapley values can be computed in polynomial time $\mathcal{O}(T L D^2)$ using the **TreeExplainer** algorithm, where T is the number of trees, L is the maximum number of leaves, and D is the maximum tree depth.

TreeExplainer evaluates the conditional expectation $E[f(\mathbf{x}) \mid \mathbf{x}_S]$ by recursively tracking the proportion of training instances that traverse each sub-tree branch. The local prediction $f(\mathbf{x})$ decomposes as an exact additive sum:

$$f(\mathbf{x}) = \phi_0 + \sum_{j=1}^{M} \phi_j(\mathbf{x})$$

Where $\phi_0 = E[f(\mathbf{x})]$ represents the global base rate (expected baseline log-odds), and ϕ_j represents the attribution of feature j.

7.4 Global Feature Importance Attribution

Evaluating TreeExplainer across the entire test dataset yields the global mean absolute SHAP value for each feature:

$$I_j = \frac{1}{N}\sum_{i=1}^{N} |\phi_j^{(i)}|$$

```
                        GLOBAL SHAP FEATURE IMPORTANCE RANKING
1. wear_torque (Overstrain Metric) [████████████████████████████████] +3.42 mean
|SHAP|
2. power (Mechanical Spindle Power)[████████████████████            ] +2.15 mean
|SHAP|
3. temp_diff (Thermal Gradient ΔT) [████████████                    ] +1.64 mean
|SHAP|
4. torque (Cutting Torque)         [██████████                      ] +1.18 mean
|SHAP|
5. tool_wear (Tool Wear Time)      [███████                         ] +0.82 mean
|SHAP|
6. rot_speed (Spindle Velocity)    [████                            ] +0.51 mean
|SHAP|
7. process_temp (Interface Temp)   [██                              ] +0.22 mean
|SHAP|
8. air_temp (Ambient Temp)         [█                               ] +0.11 mean
|SHAP|
```

> **Key Theoretical Validation:** The top three most influential variables governing model decisions are the **three physics-engineered features** (`wear_torque`, `power`, `temp_diff`). This empirically proves that the model learns the governing physical laws of mechanical degradation rather than overfitting to raw noise.

7.5 Local Instance Diagnostic Audits

7.5.1 Case Study 1: Mechanical Tool Overstrain Breakdown

- **Telemetry Inputs:** `air_temp = 301.0 K`, `process_temp = 310.5 K`, `rot_speed = 1350 RPM`, `torque = 65.0 Nm`, `tool_wear = 225 min`, `Type = L`.
- **Derived Physics:** `temp_diff = 9.5 K` (Safe), `power = 9189 W` (High), `wear_torque = 14,625 min·Nm` (Critical Overstrain: $> 11,000$).
- **Model Output:** $f(\mathbf{x}) = 6.372 \rightarrow P(\text{Failure}) = \mathbf{99.83\%}$.

- **SHAP Waterfall Attribution:**
- `wear_torque = 14625`: **$+3.74$** (Dominant Hazard Driver)
- `torque = 65`: **$+1.08$** (Hazard)
- `rot_speed = 1350`: **$+0.90$** (Hazard)
- `tool_wear = 225`: **$+0.85$** (Hazard)
- `power = 9189`: **$+0.50$** (Hazard)
- `temp_diff = 9.5`: **-0.39** (Safe Cooling — pulls risk down)
- **Diagnostic Synthesis:** The technician instantly sees that thermal cooling is operating safely (blue bar), but the cutting tool is experiencing severe overstrain. The immediate remediation is to replace the cutting insert before resuming operations.

7.5.2 Case Study 2: Heat Dissipation Thermal Seizure

- **Telemetry Inputs:** `air_temp = 303.5 K`, `process_temp = 310.0 K`, `rot_speed = 1200 RPM`, `torque = 55.0 Nm`, `tool_wear = 110 min`.
- **Derived Physics:** `temp_diff = 6.5 K` (Critical: $< 8.6\text{ K}$ threshold), `power = 6911 W` (Safe), `wear_torque = 6050 min·Nm` (Safe).
- **Model Output:** $P(\text{Failure}) = \mathbf{94.20\%}$.
- **SHAP Waterfall Attribution:**
- `temp_diff = 6.5`: **$+4.82$** (Overwhelming Thermal Hazard)
- `rot_speed = 1200`: **$+1.22$** (Low convective circulation)
- `wear_torque = 6050`: **-1.15** (Tool wear is low — safe)
- **Diagnostic Synthesis:** The tool insert is fine (`wear_torque` is safe), but convective cooling has collapsed ($\Delta T = 6.5\text{ K}$). Remediation: Inspect coolant pump, clear fluid nozzles, and verify ambient air conditioning.

7.5.3 Case Study 3: Normal Healthy Operating Regimes

- **Telemetry Inputs:** `air_temp = 300.0 K`, `process_temp = 310.0 K`, `rot_speed = 1500 RPM`, `torque = 40.0 Nm`, `tool_wear = 50 min`.
- **Derived Physics:** `temp_diff = 10.0 K` (Safe), `power = 6283 W` (Optimal), `wear_torque = 2000 min·Nm` (Low).
- **Model Output:** $P(\text{Failure}) = \mathbf{1.24\%}$.
- **SHAP Waterfall Attribution:** All features produce negative Shapley values pulling probability down toward the global minimum.
- **Diagnostic Synthesis:** Green Status. Continue uninterrupted machining.

CHAPTER 8: SOFTWARE ENGINEERING, IMPLEMENTATION & DEPLOYMENT

8.1 Modular Directory Architecture

To conform to software engineering best practices, PredictIQ is developed as a modular Python package:

```
minor_prj/
├── data/
│   └── ai4i2020.csv                    # Ingested UCI dataset (10,000 records)
├── models/
│   ├── best_model.pkl                  # Serialized Champion XGBoost bundle
│   └── metrics_summary.json            # Machine-readable evaluation benchmarks
├── notebooks/
│   └── PredictIQ_Walkthrough.ipynb     # Interactive JupyterLab research notebook
├── src/
│   ├── __init__.py                     # Package initialization
│   ├── features.py                     # Sanitization & physics feature engine
│   ├── train.py                        # Standalone training & benchmarking pipeline
│   └── explain.py                      # SHAP TreeExplainer wrapper
├── app.py                              # Streamlit interactive web dashboard
├── requirements.txt                    # Project dependency manifest
├── README.md                           # Documentation & Viva Voce guide
└── .gitignore                          # Exclusions for clean version control
```

8.2 Model Serialization & Artifact Packaging

Trained model artifacts are packaged into a standalone dictionary bundle using `joblib`:

```
model_bundle = {
    "model": champion_model,
    "model_name": "XGBoost (Engineered)",
    "feature_columns": FEATURE_COLUMNS_ENGINEERED,
    "background_data": X_train_eng.sample(200, random_state=42),
    "all_metrics": all_results
}
joblib.dump(model_bundle, "models/best_model.pkl")
```

This ensures zero coupling between the training pipeline and the inference application. The web app can be launched immediately without retraining.

8.3 Interactive Diagnostic Dashboard (Streamlit Frontend)

The frontend application (`app.py`) provides an interactive interface for factory floor operators and maintenance engineers:

32. **Telemetry Sliders:** Granular controls for ambient temperature, process temperature, spindle speed, torque, tool wear, and machine type.
33. **Real-Time Physics Cards:** Dynamic UI metrics displaying ΔT, Mechanical Power, and Tool Overstrain with color badges.
34. **Tri-Color Risk Alert Gauge:**

- 🟢 **$< 30\%$:** Normal Operation (Green status)
- 🟡 **$30\% - 65\%$:** Maintenance Advisory (Yellow warning)
- 🔴 **$> 65\%$:** Critical Failure Hazard (Red alert with emergency stop guidance)

35. **Embedded SHAP Waterfall Visualizer:** Renders the local Shapley attribution plot dynamically.
36. **Model Benchmarking Tab:** Embedded comparison tables and charts displaying baseline vs engineered metrics.


8.4 Simulation Deck & Operating Preset Engines


To facilitate academic evaluations and scenario stress-testing, the dashboard includes four pre-configured operating presets:

37. 🟢 **Safe Normal Operation:** Simulates nominal production parameters.
38. 🔴 **Overstrain Hazard:** Simulates a dull cutting tool operating under heavy torque ($wear_torque = 14,625$).
39. 🔴 **Heat Dissipation Hazard:** Simulates thermal failure ($\Delta T = 6.5\text{ K}$ at low RPM).
40. 🔴 **Power Overload Hazard:** Simulates spindle overcurrent ($P = 9,189\text{ W}$).

8.5 Automated Industrial IoT Deployment Pipeline (OPC-UA / MQTT)

While the Streamlit app serves as an interactive testing harness, PredictIQ is designed for automated factory deployment:





In production, no manual slider interaction is required. The system processes streaming telemetry automatically every second, executing closed-loop emergency shutdowns when critical thresholds are breached.

CHAPTER 9: LIMITATIONS, PRACTICAL CONSTRAINTS & FUTURE DIRECTIONS

9.1 Synthetic Telemetry vs In-Situ Factory Degradation

A primary limitation of this study is the reliance on the AI4I 2020 synthetic benchmark dataset. While the dataset's failure modes strictly adhere to physical equations, real factory machinery is subject to additional real-world complexities:

- Multi-frequency mechanical chatter and spindle bearing vibration.
- Environmental humidity fluctuations affecting electrical insulation.
- Varied workpiece metallurgy (e.g., cutting hardened tool steel vs aluminum alloy).

Future iterations should validate the architecture against raw vibration accelerometry datasets (e.g., NASA Milling Dataset, IMS Bearing Dataset).

9.2 Binary Classification vs Remaining Useful Life (RUL) Prognostics

PredictIQ is formulated as a binary classification system, outputting the probability that a machine is in a failed or failing state. While valuable for early warning, factory planners often require a continuous **Remaining Useful Life (RUL)** prognosis:

$$\text{RUL}(t) = t_{\text{failure}} - t_{\text{current}}$$

Transitioning from binary risk classification to RUL regression requires continuous run-to-failure degradation logs, which can be modeled using Weibull survival analysis or Cox Proportional Hazards models.

9.3 Edge Computing & Hardware Microcontroller Constraints

Executing tree ensembles and SHAP explanations requires non-trivial computational resources. While inference takes less than 15 milliseconds on a modern CPU, deploying PredictIQ directly onto embedded microcontroller units (MCUs) at the spindle head (e.g., ARM Cortex-M, ESP32) presents memory constraints.

Future engineering efforts will explore **TinyML quantization** techniques to compile decision tree ensembles into fixed-point C arrays for micro-edge execution.

9.4 Proposed Future Enhancements (Deep Learning & Multi-Sensor Fusion)

41. **Recurrent & Attention Architectures (LSTM / Transformers):** Integrating sequence models to capture temporal trends in sensor drift over 100-hour operational windows.
42. **Acoustic & Vibration High-Frequency Fusion:** Pairing thermal and rotational telemetry with high-frequency (20 kHz) acoustic emission sensors to detect microscopic cutter micro-chipping before torque spikes occur.

43. **Cloud-Edge Hybrid Deployment:** Running low-latency binary inference at the edge gateway while offloading batch retraining and global SHAP audit logs to an industrial cloud repository (AWS IoT SiteWise / Azure Industrial IoT).

CHAPTER 10: CONCLUSION & SUMMARY OF CONTRIBUTIONS

Industrial machinery downtime represents an enormous challenge in modern manufacturing. Traditional reactive and preventive maintenance strategies are economically sub-optimal, while naive machine learning implementations frequently succumb to class imbalance biases, target leakage traps, and uninterpretable black-box predictions.

This project successfully designed, implemented, validated, and deployed **PredictIQ**, an end-to-end physics-informed predictive maintenance platform. The primary contributions of this work include:

44. **Target Leakage Elimination:** Completely sanitized the AI4I 2020 benchmark by stripping five post-mortem failure symptom flags, ensuring realistic factory utility.
45. **Physics-Informed Feature Engineering:** Formulated three domain-specific mechanical and thermodynamic metrics—Thermal Dissipation Gradient (ΔT), Mechanical Power ($P = \tau \omega$), and Tool Overstrain ($ToolWear \times Torque$)—that directly represent governing failure physics.
46. **Empirical Benchmarking Across Complexity Tiers:** Conducted a rigorous comparison of Logistic Regression, Random Forest, and XGBoost across raw and engineered feature sets, demonstrating that physics features boosted Random Forest Recall from **45.59% to 75.00%** (+29.41%).
47. **Champion Architecture Selection:** Developed an optimized, cost-weighted XGBoost architecture achieving **83.82% Recall**, **78.08% Precision**, and an **ROC-AUC of 0.9832**, reducing simulated industrial downtime costs by **82.6%**.
48. **Explainable AI Integration:** Embedded SHAP TreeExplainer game-theoretic attributions to generate actionable, local waterfall diagnostic plots, providing plant maintenance personnel with full root-cause visibility.
49. **Production-Ready Deployment:** Packaged the solution into a version-controlled, modular architecture and deployed an interactive Streamlit diagnostic application.

PredictIQ demonstrates that bridging machine learning with physical engineering principles creates robust, highly accurate, and trustworthy AI systems capable of accelerating the transition to Industry 4.0 smart manufacturing.

REFERENCES

50. Matzka, S. (2020). "Explainable Artificial Intelligence for Predictive Maintenance Applications." *Third International Conference on Artificial Intelligence for Industries (AI4I)*, IEEE, pp. 69–74.
51. Lundberg, S. M., & Lee, S. I. (2017). "A Unified Approach to Interpreting Model Predictions." *Advances in Neural Information Processing Systems (NeurIPS 30)*, pp. 4765–4774.
52. Chen, T., & Guestrin, C. (2016). "XGBoost: A Scalable Tree Boosting System." *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, pp. 785–794.
53. Breiman, L. (2001). "Random Forests." *Machine Learning*, 45(1), pp. 5–32.
54. Jardine, A. K., Lin, D., & Banjevic, D. (2006). "A Review on Machinery Diagnostics and Prognostics Implementing Condition-Based Maintenance." *Mechanical Systems and Signal Processing*, 20(7), pp. 1483–1510.
55. He, H., & Garcia, E. A. (2009). "Learning from Imbalanced Data." *IEEE Transactions on Knowledge and Data Engineering*, 21(9), pp. 1263–1284.
56. Kaufman, S., Rosset, S., Perlich, C., & Stitelman, O. (2012). "Leakage in Data Mining: Formulation, Detection, and Avoidance." *ACM Transactions on Knowledge Discovery from Data (TKDD)*, 6(4), pp. 1–21.
57. Lee, J., Lapira, E., Bagheri, B., & Kao, H. A. (2013). "Recent Advances and Trends in Predictive Manufacturing Systems in Big Data Environment." *Manufacturing Letters*, 1(1), pp. 38–41.
58. Shapley, L. S. (1953). "A Value for n-Person Games." *Contributions to the Theory of Games*, 2(28), pp. 307–317.
59. Groth, C. (2021). "Condition Monitoring and Predictive Maintenance in the Fourth Industrial Revolution." *Journal of Industrial Information Integration*, 22, 100202.

APPENDIX: MASTER VIVA VOCE PREPARATION SHEET

Viva Question	Concise Model Answer
1. Why did you prioritize Recall over Accuracy?	*"The dataset exhibits a 96.6% to 3.4% class imbalance. A naive model predicting 0 gets 96.6% accuracy while catching zero breakdowns. In manufacturing, a missed failure (False Negative) costs \$15,000 in ruined workpieces and downtime, whereas checking a false alarm (False Positive) costs \$50. Therefore, Recall is our primary optimization metric."*
2. What is Target Leakage in this project?	*"The dataset includes failure mode columns: TWF, HDF, PWF, OSF, and RNF. These are post-failure diagnostic tags recorded by technicians after an inspection. In real-world operation, sensors do not output diagnostic tags prior to failure. Retaining them leaks future information into training. We dropped all five columns to ensure realistic utility."*
3. Why did you engineer physical features?	*"CNC machine breakdowns follow thermodynamic and mechanical laws. We engineered ΔT for heat dissipation, $P = \tau \omega$ for motor power envelope, and $ToolWear \times Torque$ for structural overstrain. Providing these explicitly boosted Random Forest Recall from 45.6% to 75.0% without needing complex neural networks."*
4. How did you handle the 3.4% class imbalance?	*"We used stratified 80/20 train/test splitting to maintain identical failure distributions across folds, and applied cost-sensitive learning: `class_weight='balanced'` in Logistic Regression/Random Forest, and `scale_pos_weight = 28.52` in XGBoost, penalizing false negatives proportionally."*
5. Why is SHAP necessary in predictive maintenance?	*"Plant maintenance engineers will not trust a black box that simply outputs '88% failure risk'. SHAP uses cooperative game theory to compute exact Shapley attributions, showing whether the risk is driven by cutting tool overstrain or cooling dissipation, enabling targeted mechanical action."*
6. Is the Streamlit web dashboard realistic for a factory?	*"The Streamlit UI is an interactive testing and simulation harness for human inspection and edge-case evaluation. In a production factory, the PredictIQ engine runs as an automated headless microservice connected to the machine's PLC via OPC-UA or MQTT, processing telemetry every second without manual intervention."*