

ASSIGNMENT1: What are some popular HTTP libraries available across different programming languages (such as Python, Java, JavaScript, Ruby, PHP, C#, Go, Swift, Rust, and Perl), and how do these libraries act as implementations of the HTTP/1.1 protocol specification (e.g., RFC 7230)?

<https://datatracker.ietf.org/doc/html/rfc7230> Additionally, provide an example of an HTTP library (such as Python's Requests) and explain how it enables developers to interact with HTTP-based systems.

1. Introduction

HTTP (HyperText Transfer Protocol) is the foundation of communication on the World Wide Web. The HTTP/1.1 specification (RFC 7230) defines how messages are formatted and transmitted between clients and servers.

To simplify working with HTTP, developers use HTTP libraries available in different programming languages. These libraries implement the protocol and allow easy interaction with web services.

2. Popular HTTP Libraries Across Programming Languages

Language	Popular HTTP Libraries
----------	------------------------

Python	Requests, urllib3, httplib2
--------	-----------------------------

Java	Apache HttpClient, OkHttp, HttpURLConnection
------	--

JavaScript	Axios, Fetch API, Node.js http/https
------------	--------------------------------------

Ruby	Net::HTTP, HTTParty, Faraday
------	------------------------------

PHP	Guzzle, cURL
-----	--------------

C# (.NET)	HttpClient, RestSharp
-----------	-----------------------

Go	net/http (standard library)
----	-----------------------------

Swift	URLSession, Alamofire
-------	-----------------------

Rust	reqwest, hyper
------	----------------

Perl	LWP, HTTP::Tiny
------	-----------------

3. How HTTP Libraries Implement HTTP/1.1 (RFC 7230)

HTTP libraries act as implementations of the HTTP/1.1 protocol, meaning they follow the rules defined in RFC 7230.

Key Responsibilities:

1. Constructing HTTP Requests

- **Create properly formatted requests:**

GET /index.html HTTP/1.1

Host: example.com

- **Add headers, body, and authentication**

2. Parsing HTTP Responses

- **Interpret server responses:**

HTTP/1.1 200 OK

Content-Type: application/json

- **Convert them into usable objects (status, headers, body)**

3. Managing Connections

- **Establish TCP connections**
- **Support persistent connections (Keep-Alive)**

4. Handling Protocol Rules

- **Follow HTTP methods (GET, POST, PUT, DELETE)**
- **Handle headers (case-insensitive)**
- **Support chunked transfer encoding**
- **Manage cookies and sessions**

Conclusion of This Section

These libraries hide the complexity of raw HTTP communication and allow developers to work with simple, high-level code while still complying with RFC 7230.

4. Example: Python Requests Library

Overview

The Requests library is one of the most popular HTTP libraries in Python. It provides a simple and intuitive way to send HTTP requests.

Example Code

```
import requests
```

```
response = requests.get("https://api.example.com/data")
```

```
print(response.status_code)
```

```
print(response.headers)
```

```
print(response.text)
```

How It Works Internally

When this code runs:

1. **Creates an HTTP request**
 - **Method: GET**
 - **URL converted into HTTP format**
2. **Adds default headers**
 - **Host, User-Agent, etc.**
3. **Sends request over network**
4. **Receives response**
 - **Parses status code (e.g., 200 OK)**
 - **Extracts headers and body**
5. **Returns a structured object**
 - **response.status_code**

- `response.headers`
- `response.text`

Advantages of Requests Library

- Easy to use and readable
- Supports all HTTP methods
- Handles cookies, sessions, SSL
- Automatically manages encoding and decoding

5. Final Conclusion

HTTP libraries across programming languages act as practical implementations of HTTP/1.1 (RFC 7230). They:

- Simplify web communication
- Handle low-level protocol details
- Enable developers to interact with APIs and web services efficiently

The Python Requests library is a perfect example, as it allows developers to perform complex HTTP operations using simple and clean code.

ASSIGNMENT:2

Analyze your smartphone as an IoT edge device by identifying hardware, OS, and sensors. Hardware Operating System Sensors

1. Introduction

An IoT (Internet of Things) edge device is a smart device that collects, processes, and transmits data near the source instead of relying entirely on cloud systems.

A smartphone is a powerful IoT edge device because it:

- **Processes data locally**
- **Connects to networks**
- **Interacts with sensors**

2. Hardware Components

The hardware of a smartphone forms the physical foundation of its edge computing capabilities.

Key Hardware Elements:

- **Processor (CPU & GPU)**
 - **Executes applications and processes sensor data**
 - **Example: Qualcomm Snapdragon, Apple A-series**
- **Memory (RAM)**
 - **Handles multitasking and app execution**
- **Storage (ROM/Flash)**
 - **Stores apps, OS, and user data**
- **Battery**
 - **Provides portable power**
- **Communication Modules**

- **Wi-Fi**
 - **Bluetooth**
 - **Cellular (4G/5G)**
 - **GPS**
- **Input/Output Components**
 - **Touchscreen**
 - **Microphone**
 - **Speakers**

3. Operating System (OS)

The operating system acts like the “brain commander”... quietly coordinating everything

Common Smartphone OS:

- **Android**
- **iOS**

Functions of OS:

- **Manages hardware resources**
- **Provides user interface**
- **Handles app execution**
- **Controls sensor access**
- **Ensures security**

It also enables edge computing, allowing data to be processed directly on the device instead of sending everything to the cloud.

4. Sensors in a Smartphone

Sensors allow the smartphone to sense the environment, making it intelligent... almost like awareness

Common Sensors:

Motion Sensors

- **Accelerometer → detects movement and orientation**
- **Gyroscope → detects rotation**
- **Magnetometer → acts as a compass**

Environmental Sensors

- **Ambient Light Sensor → adjusts screen brightness**
- **Proximity Sensor → detects nearby objects**

Location Sensor

- **GPS → provides location tracking**

Advanced Sensors

- **Fingerprint Sensor**
- **Face Recognition (Camera-based)**
- **Camera Sensor**
- **Microphone (audio sensing)**

5. Smartphone as an IoT Edge Device

A smartphone behaves as an edge device because:

Local Processing

- **Processes sensor data instantly**

- **Example: step counting, face unlock**

Connectivity

- **Communicates with IoT devices (smartwatch, smart home)**

Real-time Decision Making

- **Adjusts brightness automatically**
- **Detects motion for apps**

Security at Edge

- **Performs biometric authentication locally**

6. Conclusion

A smartphone is a powerful IoT edge device that integrates:

- **Advanced hardware**
- **Efficient operating systems**
- **Multiple sensors**

Together, they enable real-time processing, intelligent decision-making, and seamless connectivity in modern IoT environments.

ASSIGNMENT: 3

Biometric Attendance System (Face + Fingerprint) - Shruti Building

- **Analyze the biometric attendance system as an IoT-enabled intelligent system. Clearly explain:**
- **The overall system architecture and working principle (data capture**
 - > processing**
 - > storage**
 - > access)**
- **The sensors and hardware components used for face recognition (camera, IR/depth sensors)**
- **The sensors and modules used for fingerprint (thumb impression) recognition (optical/capacitive fingerprint sensor)**
- **How both modalities are integrated (multi-modal biometrics) and how the system decides identity**
- **Data flow: acquisition -> feature extraction -> matching -> database/storage**
- **Networking, protocols, and backend/cloud interaction**
- **Key considerations: accuracy, latency, spoofing resistance, and security/privacy mechanisms**

1. Introduction

A biometric attendance system is an IoT-enabled intelligent system that identifies individuals using unique biological traits such as face and fingerprint.

This system combines:

- **Edge processing (on-device intelligence)**
- **Sensors (camera + fingerprint)**
- **Networking and cloud/database systems**

2. System Architecture & Working Principle

The system follows a structured pipeline... like a calm sequence of steps

Flow: Data Capture → Processing → Storage → Access

Step-by-step:

1. Data Capture

- **Face captured using camera**
- **Fingerprint captured using sensor**

2. Processing

- **Image and fingerprint features extracted**
- **Converted into digital templates**

3. Storage

- **Templates stored in database (local/cloud)**


4. Access Decision

- **Match found → attendance marked**
- **No match → access denied**

3. Face Recognition Hardware & Sensors


Face Recognition Components

HOW STRUCTURED LIGHT SYSTEMS WORK






Structured light emitter projects patterns in infrared light.
The patterns are projected in pulses.
By understanding how the pattern distorts on each
object, depth can be calculated.

HOW TIME OF FLIGHT SYSTEMS WORK



Time-of-flight emitter floods the scene with infrared light.
By measuring the time it takes for the light
to return from each pixel, the depth map
of the scene is computed.





6 Key Components:


- **Camera (RGB Camera)**
 - **Captures facial image**
- **Infrared (IR) Sensor**
 - **Works in low light**
 - **Detects heat patterns**
- **Depth Sensor (3D Mapping)**
 - **Creates 3D face structure**

- Improves accuracy & anti-spoofing

4. Fingerprint Recognition Sensors

Fingerprint System Components





6 Types of Sensors:

- **Optical Fingerprint Sensor**
 - Uses light to capture fingerprint image
 - Common in attendance systems
- **Capacitive Fingerprint Sensor**
 - Detects electrical differences in ridges/valleys
 - More secure and accurate

5. Multi-Modal Biometric Integration

The system uses both face + fingerprint... like two guards verifying identity

How Integration Works:

- **Fusion Strategy:**
 - **AND Logic** → both face & fingerprint must match
 - **OR logic (less secure)** → either one works

Decision Process:

- 1. Face matched**
- 2. Fingerprint matched**
- 3. Identity confirmed**

This improves:

- **Accuracy**
- **Security**
- **Resistance to spoofing**

6. Data Flow in the System

Detailed Flow:

- 1. Acquisition**
 - **Capture face & fingerprint**
- 2. Feature Extraction**
 - **Face** → key points (eyes, nose, shape)
 - **Fingerprint** → minutiae (ridge endings, bifurcations)
- 3. Template Creation**

- **Convert features into digital vectors**

4. Matching

- **Compare with stored database**

5. Storage

- **Store encrypted biometric templates**

7. Networking, Protocols & Backend

Connectivity:

- **Wi-Fi / Ethernet**
- **Sometimes Bluetooth**

Protocols Used:

- **HTTP/HTTPS → communication with server**
- **MQTT → lightweight IoT communication**
- **TCP/IP → base communication**

Backend/Cloud:

- **Central database stores attendance**
- **Cloud enables:**
 - **Remote monitoring**
 - **Data analytics**
 - **Multi-location synchronization**

8. Key Considerations

1. Accuracy

- **Multi-modal improves recognition rate**
- **Reduces false acceptance/rejection**

2. Latency

- **Fast processing needed for real-time use**
- **Edge computing reduces delay**

3. Spoofing Resistance

- **IR & depth sensors prevent photo attacks**
- **Fingerprint sensors detect live tissue**

4. Security & Privacy

- **Data encryption**
- **Secure storage (templates, not raw images)**
- **Access control mechanisms**
- **Compliance with privacy regulations**

9. Conclusion

The biometric attendance system at Shruti Building is an IoT-enabled intelligent system that integrates:

- **Advanced hardware (camera + fingerprint sensors)**
- **Intelligent processing (feature extraction & matching)**
- **Secure networking and cloud systems**

By using multi-modal biometrics, it achieves:

- **High accuracy**
- **Strong security**
- **Reliable attendance tracking**

ASSIGNMENT 4 : "Understand the Android UNO R3 pinouts and explain them."

1. Introduction

The Arduino UNO R3 is a widely used microcontroller board based on the ATmega328P.

It is used in IoT, robotics, and embedded systems for controlling sensors and devices.

Understanding its pinout and documentation helps developers use it effectively.

2. Understanding Key Terms (Arduino Perspective)

1. Pinout (PDF)

- **A pinout diagram shows all pins of the Arduino board and their functions.**
- **It includes:**
 - **Digital pins**
 - **Analog pins**
 - **Power pins**
 - **Communication pins**

It is the most important reference for connecting components.

2. Datasheet

- **A datasheet provides detailed technical information about the microcontroller (ATmega328P).**
- **Includes:**
 - **Electrical characteristics**

- **Voltage limits**
- **Timing diagrams**
- **Internal architecture**

Used for deep technical understanding.

3. Schematics

- **A schematic diagram shows how components on the board are connected internally.**
- **Includes:**
 - **Circuits**
 - **IC connections**
 - **Power routing**

Helps in hardware troubleshooting and design.

4. CAD Files

- **CAD (Computer-Aided Design) files show the physical layout of the board.**
- **Used for:**
 - **PCB design**
 - **3D modeling**


Useful for custom hardware development.

3. Arduino UNO R3 Pinout (Detailed Explanation)

Arduino UNO R3 Pin Layout



ARDUINO UNO REV3




- Ground
- Internal Pin
- Digital Pin
- Microcontroller's Port
- Power
- SWD Pin
- Analog Pin
- LED
- Other Pin
- Default

ARDUINO.CC



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/4.0/> or send a letter to Creative Commons, PO Box 1888, Mountain View, CA 94042, USA.


Arduino Uno R3 Pinout



AVR DIGITAL ANALOG POWER SERIAL SPI I2C PWM INTERRUPT



2014 by Bouni
Photo by Arduino.cc



6

1. Digital Pins (0–13)

- Used for digital input/output
- Can be HIGH or LOW

Special Digital Pins:

- PWM Pins (~3, 5, 6, 9, 10, 11) → simulate analog output
- Pin 0 (RX) & 1 (TX) → serial communication

2. Analog Pins (A0–A5)

- Read analog signals (0–5V)
- Convert to digital values using ADC

Example: temperature sensor, light sensor

3. Power Pins

- **5V → power output**
- **3.3V → low voltage devices**
- **GND → ground**
- **VIN → external power input**

4. Communication Pins

- **UART → Pins 0 (RX), 1 (TX)**
- **I2C → A4 (SDA), A5 (SCL)**
- **SPI → Pins 10 (SS), 11 (MOSI), 12 (MISO), 13 (SCK)**

5. Other Important Pins

- **AREF → analog reference voltage**
- **RESET → resets the board**

4. Features of Arduino UNO R3

- **Microcontroller: ATmega328P**
- **Operating Voltage: 5V**
- **Digital I/O Pins: 14**
- **Analog Inputs: 6**
- **Flash Memory: 32 KB**
- **Clock Speed: 16 MHz**

5. Tutorials (Learning Support)

Common beginner tutorials include:

- **LED blinking**
- **Button input**
- **Sensor interfacing**
- **Serial communication**

6. Technical Specifications

- **Input Voltage: 7–12V recommended**
- **Current per I/O pin: 20 mA**
- **EEPROM: 1 KB**
- **SRAM: 2 KB**

7. Compatibility

- **Compatible with:**
 - **Arduino IDE**
 - **Shields (WiFi, Bluetooth, Motor Driver)**
 - **Sensors and modules**

Widely supported in IoT projects

8. Suggested Libraries

Some commonly used Arduino libraries:

- **Servo.h → control servo motors**
- **Wire.h → I2C communication**
- **SPI.h → SPI communication**
- **LiquidCrystal.h → LCD display**

9. Conclusion

The Arduino UNO R3 pinout provides a clear map of how to interact with the board.

Understanding pin functions, along with documentation like datasheets and schematics, helps in building efficient and reliable projects.

ASSIGNMENT 5: Arduino enables interaction with real-world systems through Digital Pins, Analog Pins, and PWM-enabled Pins. Provide a detailed analytical discussion explaining how these three categories of pins collectively support sensing, decision-making, and control in embedded and IoT systems.

1. Introduction

The Arduino UNO interacts with the physical world using three main types of pins:

- **Digital Pins**
- **Analog Pins**
- **PWM (Pulse Width Modulation) Pins**

Together, they form a complete cycle of:

Sensing → Decision-Making → Control

2. Analog Pins: Sensing the Real World

Role: Input (Sensing Continuous Data)

Analog pins (A0–A5) read signals that vary continuously, such as:

- **Temperature**
- **Light intensity**
- **Sound**
- **Gas levels**

How It Works:

- **Input voltage (0–5V) is converted into digital values (0–1023) using ADC (Analog-to-Digital Converter)**

Example:

- **LDR detects light → Analog pin reads value → Arduino understands brightness**

Importance:

- **Enables real-world sensing**
- **Captures environmental variations with precision**

3. Digital Pins: Decision-Making & Logic

Role: Processing & Logical Control

Digital pins operate in two states:

- **HIGH (1)**
- **LOW (0)**

Functions:

- **Read input (e.g., button pressed or not)**
- **Send output (turn LED ON/OFF)**

Decision-Making:

Arduino uses digital logic like:

```
if (sensorValue > threshold) {  
    digitalWrite(LED, HIGH);  
}
```

Example:

- **Motion detected → digital input HIGH → alarm activated**

Importance:

- **Acts as the decision-making bridge**
- **Converts sensed data into logical actions**

4. PWM Pins: Control & Actuation

Role: Output (Analog-like Control)

PWM pins (~3, 5, 6, 9, 10, 11) simulate analog output using digital signals.

How It Works:

- **Rapid ON/OFF switching**
- **Controls duty cycle (percentage of ON time)**

$$\text{Duty Cycle} = \frac{T_{on}}{T_{total}} \times 100\%$$

Example:

- **50% duty cycle → medium LED brightness**
- **100% → full brightness**

Applications:

- **Motor speed control**
- **LED dimming**
- **Fan regulation**

5. Integrated Working: The Complete IoT Cycle

Full System Flow

1. Sensing (Analog Pins)

- Sensor collects real-world data
- Example: Temperature = 35°C

2. Decision-Making (Digital Logic)

- Arduino processes data
- Compares with threshold

3. Control (PWM/Digital Output)

- Adjusts output:
 - Turn ON fan
 - Increase motor speed

Example: Smart Fan System

Step	Action
Sensing	Temperature sensor reads heat
Decision	If temp > 30°C
Control	PWM increases fan speed

6. Role in IoT Systems

In IoT environments, these pins enable:

Connectivity + Intelligence

- **Sensors collect data → Analog pins**
- **Microcontroller processes → Digital logic**
- **Actuators respond → PWM/Digital output**

Example:

- **Smart home system**
- **Industrial automation**
- **Health monitoring**

7. Analytical Insight

Each pin type alone is incomplete... but together:

- **Analog Pins → perception**
- **Digital Pins → reasoning**
- **PWM Pins → action**

This combination transforms Arduino into an:

Intelligent edge device capable of real-time interaction

8. Conclusion

Digital, Analog, and PWM pins collectively create a complete embedded system loop:

- **Sense environment**
- **Process information**
- **Control outputs**

This integration is fundamental to embedded systems and IoT applications, enabling automation, efficiency, and intelligent decision-making.

ASSSIGNMENT 6: Analyze the different communication mechanisms used in embedded systems by comparing serial and parallel communication, analog and digital communication, and synchronous and asynchronous protocols. Discuss how these categories differ in terms of data transmission, efficiency, complexity, and reliability, and evaluate their role in enabling effective interfacing between microcontrollers and external devices in real-world applications.

1. Introduction

Communication in embedded systems allows microcontrollers to interact with:

- **Sensors**
- **Actuators**
- **Other devices**

Different mechanisms are used depending on speed, distance, complexity, and reliability.

This analysis compares:

- **Serial vs Parallel**
- **Analog vs Digital**
- **Synchronous vs Asynchronous**

2. Serial vs Parallel Communication

Basic Concept

Type	Description
Serial	Data sent one bit at a time

Type	Description
Parallel	Multiple bits sent simultaneously

Comparison

Factor	Serial Communication	Parallel Communication
Data Transmission	1 bit at a time	Multiple bits (8/16) at once
Speed	Slower per cycle, but efficient over distance	Faster for short distances
Wiring	Few wires	Many wires
Complexity	Simple	Complex
Reliability	High (less interference)	Lower (crosstalk issues)

Analysis

- Serial is widely used in modern systems (UART, SPI, I2C)
- Parallel is used where high-speed short-distance transfer is needed (e.g., internal buses)

In IoT systems, serial communication dominates due to simplicity and reliability.

3. Analog vs Digital Communication

Basic Concept

Type	Description
Analog	Continuous signal (voltage varies smoothly)
Digital	Discrete signals (0s and 1s)

Comparison

Factor	Analog	Digital
Signal Type	Continuous	Discrete
Noise Sensitivity	High	Low
Accuracy	Lower	Higher
Processing	Complex	Easier
Reliability	Less reliable	More reliable

Analysis

- Analog is used in sensor data collection (temperature, sound)
- Digital is used in processing and communication

Embedded systems often convert:

Analog → Digital (ADC)

This allows accurate processing and transmission.

4. Synchronous vs Asynchronous Communication

Basic Concept

Type	Description
Synchronous	Uses a shared clock signal

Type	Description
Asynchronous	No clock, uses start/stop bits

Comparison

Factor	Synchronous	Asynchronous
Timing	Clock-based	No clock
Speed	Faster	Slower
Complexity	More complex	Simpler
Efficiency	High (no extra bits)	Lower (start/stop overhead)
Examples	SPI, I2C	UART

Analysis

- Synchronous → high-speed, precise communication
- Asynchronous → simple, flexible communication

Choice depends on:

- Required speed
- System complexity

5. Overall Comparative Insight

How They Fit Together

These categories are not isolated... they overlap:

- Serial communication can be:
 - Synchronous (SPI)

- Asynchronous (UART)
- Data can be:
 - Analog (sensor input)
 - Converted to digital (for processing)

6. Role in Real-World Embedded Systems

Practical Applications

IoT Devices

- Serial (I2C, SPI) connects sensors
- Digital communication ensures reliability

Automotive Systems

- Parallel used in internal processing
- Serial used for communication (CAN, LIN)

Healthcare Devices

- Analog signals from sensors
- Digital processing for accuracy

Smart Home Systems

- Asynchronous UART for simple modules
- Synchronous SPI for fast data transfer

7. Evaluation

Efficiency

- **Serial + synchronous → most efficient for modern systems**

Complexity

- **Parallel + synchronous → highest complexity**

Reliability

- **Digital + serial → most reliable**

8. Conclusion

Different communication mechanisms serve different purposes:

- **Serial vs Parallel → trade-off between wiring and speed**
- **Analog vs Digital → sensing vs processing**
- **Synchronous vs Asynchronous → speed vs simplicity**

Together, they enable:

Effective interfacing between microcontrollers and external devices

This layered communication approach is essential for building efficient, reliable, and scalable embedded and IoT systems.