This work has been submitted to the IEEE for possible publication. Copyright may be transferred without notice, after which this version may no longer be accessible.

# When to Replan and How Much to Correct: Residual Reinforcement Learning for Disturbance Recovery in Vision-Language-Action Policies

Chang-Hoon Ji
*Department of Artificial Intelligence*
*Korea University*
Seoul, Republic of Korea
ckdgns0611@korea.ac.kr

Tae-Eui Kam
*Department of Artificial Intelligence*
*Korea University*
Seoul, Republic of Korea
kamte@korea.ac.kr

***Abstract*—Vision-language-action policies execute predicted action chunks open loop, so after an object is suddenly displaced, the robot follows a plan made for the old scene. On LIBERO-10, teleporting the target object by 4 to 6 cm, mostly as the gripper approaches, cuts the pi0.5 policy's success from 95 to 65 percent. Under one paired protocol, simple inference-time levers (replan frequency, integration steps, chunk selection) recover little. More computation at the next scheduled query recovers nothing measurable, and moving the query to the event with a learned camera-frame detector recovers zero to three points without adding policy queries per episode. Correcting the actions recovers more. A fixed-rule shift toward the estimated displacement gains about six points. An event-gated residual, cloned from a scripted shift on privileged state, refined with reinforcement learning as lightweight post-training and distilled into a vision-only student, raises success from 65.4 to 73.7 percent in a pre-registered test on 500 fresh initial states (gain 8.4 points, 95 percent interval 5.6 to 11.2; 2.9 points over the fixed rule), with no measurable change in undisturbed success.**

***Index Terms*—vision-language-action models, post-training, residual reinforcement learning, action chunking, event-triggered replanning, disturbance detection**

## I. Introduction

Vision-language-action (VLA) models have become a standard recipe for language-conditioned manipulation [1]–[3]. Most now predict *action chunks* [4], [5]: one query of the model yields a short sequence of $H$ actions, of which the robot executes a prefix of $h$ steps before the model is queried again. Chunking smooths motion and amortizes the backbone's cost but makes the controller open loop between queries. If the scene changes inside a chunk, the robot executes actions planned for the old scene until the chunk is spent, and the next query sees a configuration the training data rarely contains.


How large is this cost, and what recovers it? We study the question with the official $\pi_{0.5}$ checkpoint for LIBERO [3], [6] under a controlled disturbance: when the open gripper first comes within 12 cm of the object it is approaching (or at a random step if it has not by then), the object is teleported 4–6 cm horizontally, which cuts success on LIBERO-10 from 95.4% to 64.7%. Tracking the object (Section III) shows that the policy often first closes the gripper nearer the *old* position.

Recent work offers several responses. Adaptive-inference methods decide when to replan, how much to compute per query, or which of several sampled chunks to keep [7]–[10]; runtime monitors detect execution failures [11]–[13]; and residual reinforcement learning (RL) learns corrections on top of a fixed policy [14], [15]. They are evaluated on different tasks and disturbances; a concurrent benchmark of mid-execution changes such as target relocation finds, for four of its 14 policies including $\pi_{0.5}$, that varying the query cadence does not close the gap, but tests no event-triggered replanning or action correction [16]. We test simple versions of each response under one protocol. Moving the query to the event helps by only a few points, and the new chunk seems to aim only partly at the new position; correcting the actions recovers more: about six of the 31 lost points with a fixed rule and eight to eleven with a detector-gated residual policy cloned and refined with RL as post-training around the VLA (Fig. 1).

Our contributions are:

- a paired evaluation on LIBERO-10 in which every variant faces the same seeded mid-execution displacement and is compared with the mean of seven sampling-noise draws of the base policy (complementing studies that perturb the setup before execution [17] or the robot's actions during it [18], [19]), with a diagnosis of the failure;
- under it, a comparison showing that simple inference levers do not recover the loss and that moving the query to the event recovers only a few of the 31 points while more computation at the next scheduled query recovers nothing measurable, with a learned per-step detector that recognizes 87–90% of displacements on held-out initial states within three control steps;
- an event-gated residual recovery policy, trained as a privileged teacher by behavior cloning (BC) of a scripted

This work was supported by grants from the Institute of Information & Communications Technology Planning & Evaluation (IITP) funded by the Korea government (MSIT) [Artificial Intelligence Research Hub Project, No. RS-2024-00457882; Artificial Intelligence Graduate School Program at Korea University, No. RS-2019-II190079; Information Technology Research Center (ITRC) program, No. IITP-2026-RS-2024-00436857] and by a grant from the National Research Foundation of Korea (NRF) funded by the Korea government (MSIT) (No. RS-2023-00212498).




(a) Reactions to a displacement inside a chunk ($H$=$h$=10)

(b) Vision-only system: when to replan, how much to correct

Fig. 1. Overview. (a) A chunked policy that is queried every $h$ actions cannot react to a displacement until the current chunk is spent (i). A learned detector interrupts the chunk and replans at the event (ii), and a residual policy adds a small correction $\Delta$ to every action of the following queries (iii). (b) All three learned modules use only camera frames, actions, proprioception and the task; the $\pi_{0.5}$ weights are not updated. Gains: held-out initial states as in Fig. 2 (fresh ones in parentheses).

shift followed by proximal policy optimization (PPO) and distilled into a vision-only student, that adds 2.9 points over a fixed-rule shift in a pre-registered test on fresh initial states (3.9 on held-out ones), still gains with displacements twice as large and causes no measurable change in undisturbed success.[1]

## II. Related Work

**Adaptive chunk execution.** AAC sets the executed prefix of a chunk from the entropy of sampled chunks [7], bidirectional decoding selects among chunks resampled at every step [10], RTC inpaints the next chunk while the current one executes [20], DVAC executes the low-variance prefix of a chunk and replans before its high-variance actions [21], and DA-SIP chooses the number of integration steps per query with a difficulty classifier [9]. They balance reactivity, consistency and compute but detect no events. VLA-Corrector [8] does: it truncates the chunk when visual latents drift from a learned prediction and replans with gradient guidance, but adds no correction policy and tests displacement only on hardware.

**Runtime monitoring.** Sentinel [11], FAIL-Detect [12] and SAFE [13] flag failures or halt the policy based on action consistency and task progress, on sequential out-of-distribution tests and on VLA features, respectively. Like VLA-Corrector, we use detection to *act*, here on one external event.

**Correcting a fixed policy's actions.** Residual RL [22] refines imitation-learned policies [14], [23] and a frozen $\pi_0$, with the corrections then distilled into the VLA [15], and latent-noise RL steers $\pi_0$ without changing its weights [24]. Other work post-trains the VLA itself with online RL [25], [26], which has been shown to help when an object is moved mid-episode [27], or with offline RL to recover from errors [19]. A training-free operator offsets and compresses a chunk toward perceived motion [28], the closest analogue of our fixed-rule shift; its authors name teleports as its weak case. TRANSIC gates a residual with a classifier learned from human interventions [29]; ours is zero except after a detected scene displacement, distilled from a privileged teacher into a vision-only student as in [23], and compared with a fixed-rule shift.

[1]Code, trained modules and per-episode results: https://github.com/BitAdventurer/VLA-Disturbance-Recovery

## III. Setting and Diagnosis

### A. Chunked Execution and the Disturbance

A flow-based VLA maps an observation $o_t$ and instruction $\ell$ to a chunk $\mathbf{A}_t = (a_t, \ldots, a_{t+H-1})$ by conditional generation [30], [31], integrating a learned velocity field for $n$ Euler steps [2]; the robot executes $h \leq H$ actions and queries again. We use the released $\pi_{0.5}$ LIBERO checkpoint of openpi [3] with $H = 10$ and, unless stated otherwise, $(n, h) = (2, 10)$ (95.4% undisturbed in one draw, 95.1% over three); openpi's example setting $(10, 5)$ reaches 91.9% (three draws) at $2.8\times$ the policy-query time and loses as much as $(2, 10)$ under the displacement defined below (to 61.2%, two draws). *Policy-query time* sums, over an episode's queries, the round-trip latency of each query's setting, measured offline on one RTX 5090 (32.6 ms at $n = 2$, 44.1 ms at $n = 10$); it is an accounting figure, as simulation is synchronous. Episodes follow the released script (520 control steps at 20 Hz after 10 settling steps) on the 50 fixed initial states of each of the ten tasks, 500 episodes per run.

The *object displacement* is applied once per episode: when the open gripper first comes within 12 cm (end effector to object center) of a movable object of interest (an object named in the task goal) that it does not hold, that object is teleported horizontally by a distance drawn from $[4, 6]$ cm in a uniformly random direction and its velocity is zeroed. If no approach has occurred by a random step in 50–170 (about 26% of episodes, mostly in two tasks), the nearest free object of interest is displaced at that step. Direction and magnitude are seeded by the task and initial state, so every method sees identical displacement vectors. Each method run other than the static schedules also reuses the sampling-noise seed of one base draw and matches it in event step and displaced object in every episode, although a few pre-event trajectories differ; across base draws and static schedules the event step differs in 27% and 46–56% of episodes, respectively, mostly by one step. Success drops to 64.7% (mean of seven noise draws), and every failure is a timeout.

TABLE I
SUCCESSFUL AND FAILED EPISODES AFTER THE DISPLACEMENT (100 TRACKED EPISODES)

| | Success (65) | Failure (35) |
|---|---|---|
| Displaced object eventually lifted | 100% | 54% |
| Gripper closures before the lift | 2.3 | 7.7 |
| First closure nearer to the old position | 62% | 63% |
| Motion toward old / new position[a] | 0.69 / 0.60 | 0.26 / 0.39 |

[a]Mean cosine of end-effector motion with the direction to each position over the 15 steps after the event.

### B. Why the Policy Fails

We tracked the displaced object in 100 disturbed episodes (initial states 0–9 of each task, one base draw; Table I). All successes eventually lift it, but 46% of failures never do. In about 62% of *both* groups the first gripper closure after the event is nearer to the object's old position than to its new one, and even successful episodes at first move more toward the old position, while failures move decisively toward neither (Table I). The first closure thus does not separate the groups; recovery depends on whether a few regrasps succeed before time runs out, and more computation at the next scheduled query, where the new position is already visible, does not help (Section V-B). This suggests that a new query may not re-target the moved object and that the actions themselves may need to be shifted; Section V tests both.

### C. Evaluation Protocol

Flow-based policies sample the initial noise of the integration, and this noise alone moves the success of $(2, 10)$ on the disturbed episodes between 63.2% and 67.8% across seven seeds ("noise draws"), so single draws are noisy. We compare every variant with the *per-episode mean of the seven noise draws* of the base policy on the same 500 (task, initial state) episodes with the same disturbance, and report the mean paired difference with a task-stratified bootstrap 95% interval (6,000 resamples). Variants run once carry that draw's noise and resolve only differences of several points. Detector, regressor and teachers are each trained once and the students with three distillation seeds (the released one unless stated), all on initial states 0–24 only; initial states 25–49 of the same ten tasks (250 episodes, base 62.2%) are held out from training for the comparisons in Fig. 2; results on all 500 episodes include the training initial states. States 25–49 also served to choose gates, $\alpha$ and model versions, so they are held out from training but not from model selection. We therefore tested the released pipeline once, under a pre-registered protocol, on 500 fresh episodes: states 50–99 of each task's full initial-state file, unused by any earlier rollout of ours (the benchmark uses 0–49; five base draws, two or three per method). No new task is tested, and intervals are per comparison, without multiplicity correction.

## IV. METHOD

### A. Detecting the Displacement and Replanning at Once

The detector runs beside the controller at every control step and receives, for each of the two cameras (third-person and wrist), the previous frame, the current frame and their difference at $64 \times 64$ grayscale, together with the action executed between them and the measured end-effector motion; a four-layer CNN and a small MLP fuse these into one logit (0.1 M parameters). Positives are the frame pairs straddling a displacement, hard negatives the pairs within 15 steps of it, plus 130 undisturbed training-state episodes; training uses the 500 events of two disturbed runs on the training initial states, and the threshold is set for 0.05 false alarms per episode on 120 further undisturbed training-state episodes.

When the logit crosses the threshold, the schedule interrupts the current chunk and queries the policy immediately, so within a few control steps of the event the robot executes a chunk planned for the new scene (Fig. 1(a)). Policy-query time stays at $1.00\times$ the base schedule's (37.2 versus 37.4 queries per episode): each detection (1.07 per disturbed episode) adds at most one query (1.7% more queries per step), but episodes end earlier on average; a variant that also spends $n = 10$ steps on the three queries after the event takes $1.02\times$.

### B. Residual Correction

We add a residual $\Delta \in \mathbb{R}^3$ to the translational part of every action of the chunk returned by a query,

$$a_j^{\mathrm{xyz}} \leftarrow \mathrm{clip}(a_j^{\mathrm{xyz}} + \Delta, -1, 1), \qquad \Delta = \mathbf{s} \odot \tanh u(x), \quad (1)$$

with $\mathbf{s} = (0.3, 0.3, 0.15)$ in LIBERO action units (0.3 units move the end effector by about 3.6 mm per control step), computed once per query from a feature vector $x$ by a two-layer MLP $u$ with 256 units. The residual is *gated*: it is zero except for a bounded window after a detected displacement, so undisturbed behavior is touched only on false alarms.

**Scripted shift (privileged).** As a reference, once the simulator reports at a scheduled query that an object of interest has moved by $d$ since the reset (more than 2 cm, not lifted), we add $\alpha d$ divided equally over the $kH$ actions of the next $k$ queries, horizontal only and without interrupting the chunk. With $k = 2$, $\alpha = 1$ performs like 0.5 (71.2% and 72.2% on all 500, one draw) and $\alpha = 1.5$ worse (64.8%), presumably by adding to the base policy's own partial correction. A vision-only counterpart, the *fixed-rule shift*, replans at each detection and adds $0.5\,\hat{d}$ likewise, with $\hat{d}$ from the regressor below.

**Privileged teacher.** We then learn the correction with residual RL [22] on privileged state. Choosing the residual at each gated query is a sequential decision problem, as in our earlier RL work [32]–[34]. The teacher's 53 inputs are proprioception, a summary of the base chunk, the relative position, displacement and presence of up to three objects of interest, episode progress, gripper state, queries since the gate opened, the previous residual and a task one-hot. Its gate, checked at every scheduled query (no replan at the event), opens when an object has jumped more than 2.5 cm since the previous

query while it rests within 1.5 cm of its initial height and the open gripper is over 5 cm away, and closes once the object is lifted 3 cm. It opens in 85% of disturbed and in none of 250 undisturbed held-out episodes; a cumulative 2-cm gate opened in 54% of the undisturbed ones and, with a learned teacher behind it (trained, like ours, only on disturbed episodes), cut their success to 73.6%. The actor is Gaussian over $u$ (initial standard deviation 0.30). We first clone the scripted shift ($\alpha = 0.5$, $k = 2$) from about 450 episodes, then run PPO with generalized advantage estimation [35] (settings in the code release) for 40 iterations of 120 episodes on the training initial states. The reward is the episode success minus $0.01\,\|\Delta/\mathrm{s}\|^2$ per gated query, with a fixed rather than adaptive weight [36], [37]; one run takes about two GPU-hours.

**Vision-only student.** The student may use neither object positions nor the privileged gate. Its gate is the learned detector, active for six queries after each detection; a firing inside the window restarts it, and every firing, true or false, costs one replan. When the detector fires, a *displacement regressor* estimates the horizontal displacement $\hat{d}$ from the $128 \times 128$ RGB frame pair of both cameras at the firing step (four ResNet blocks, 0.5 M parameters, trained on 1,499 training-state events of 2–10 cm; on 1,499 events from held-out initial states, median error 1.6 cm at a median displacement of 6.1 cm, median direction error 9°). The student MLP sees the teacher's inputs with the object state replaced by $\hat{d}$, its norm and an active flag (36 inputs, fusing $\hat{d}$ with the base chunk [38]). It is distilled from the teacher's mean action with DAgger [39]: three rounds of two rollouts per training state under the student's gate, its residual replaced by the teacher's with probability $\beta = 1, 0.5, 0$. Every gated query is labeled with the teacher's residual (zero where its gate is closed; 8,148 labels); the student is fit by least squares on $\Delta$.

## V. Results

### A. Inference Levers Recover Little

Fig. 2 (top, held out) shows fixed settings of the levers that adaptive-inference methods tune, not those methods themselves. Replanning twice as often, $(2, 5)$, trends down ($-4.2$) and five times as often, $(2, 2)$, loses ten points (87.9% undisturbed), and every schedule tested falls 29–33 points below its own undisturbed success (all 500). Five times more integration steps, $(10, 10)$, change nothing measurable ($+1.0$). Selecting one of $K = 8$ sampled chunks for the seven queries after the (oracle-timed) event also recovers little: random $-0.6$, medoid $+0.6$, a privileged rule aiming at the displaced object $+3.0$.

### B. When to Replan: At the Event

The base policy already replans at the next scheduled query. On held-out episodes, spending $n = 10$ steps on that query and up to two more (oracle event timing) gains nothing measurable ($+0.6$ [$-2.6$, $+4.1$]), whereas, with the same oracle, moving the query *to* the displacement gains $+3.7$ at $(2, 10)$ and $+4.5$ with $n = 10$ on the three queries from it, the latter $+3.9$ [$+0.4$, $+7.3$] above the next-query variant. The learned detector realizes most of this without the oracle ($+2.8$ and





Fig. 2. Gain on the 250 disturbed episodes from held-out initial states over the base policy $(2, 10)$ (mean of seven noise draws, 62.2%); task-stratified paired bootstrap 95% intervals. $(n, h)$: integration steps and executed actions per query; "oracle": event time from the simulator; "priv.": uses simulator state; "static": fixed schedule; hollow: ablations. Right: success, gain (bold when the interval excludes zero), noise draws.

$+4.2$; all 500: Table II) at $1.00\times$ and $1.02\times$ the policy-query time. In closed loop it detects 87–90% of the displacements on held-out initial states within three control steps (98–100% on training states), with 0.10–0.15 false alarms per disturbed episode, and leaves undisturbed success at 95.2% on all 500 (base 95.4%). On the fresh initial states its replan gains only $+0.2$ [$-2.4$, $+2.8$] (two draws; inconclusive), so the small gain above is not confirmed.

### C. How Much to Correct: Residual Recovery

On held-out episodes the privileged scripted shift and the fixed-rule shift by $0.5\,\hat{d}$, which adds a replan at each detection, gain about the same ($+6.1$ and $+5.7$, three draws each; Fig. 2). With privileged $d$, the detector's replan plus the scripted shift reaches 71.3% held out (three draws), $+6.4$ [$+2.9$, $+10.1$] above the replan alone: shifting the actions adds to replanning. Learning the correction helps further: the privileged teacher, whose correction is longer and more gradual than the scripted shift's, reaches 75.1% on held-out episodes ($+12.9$ [$+9.5$, $+16.6$], five draws), $+4.3$ [$+0.5$, $+8.4$] above its behavior-cloned start (70.8%, one draw); PPO from scratch reaches 72.2% (two draws), 2.9 points [$-0.4$, $+6.3$] below the teacher. We did not distill a student from the behavior-cloned start, so PPO's share of the student's gain is not measured.

The distilled student comes within a few points of its teacher without any privileged input: 71.8% held out ($+9.6$ [$+5.8$, $+13.4$], five draws; $-4.4$ [$-7.3$, $-1.6$] against the teacher with the same replan) and 75.9% on all 500 episodes (Table II). Held out, it is $+3.9$ [$+0.9$, $+6.9$] above the fixed-rule shift and $+3.9$ [$+1.2$, $+6.8$] above the best of seven rules on training states ($\alpha = 0.5$, $k = 4$; all 500: $+4.7$, $+4.8$). On

TABLE II
RECOVERY ON 500 DISTURBED AND ON UNDISTURBED EPISODES
(BOLD: VISION-ONLY STUDENT)

| Method | In. | Draws | Succ. | Gain [95% interval] | Undist. |
|---|---|---|---|---|---|
| $\pi_{0.5}$ alone, $(2, 10)$ | – | 7 | 64.7 | – | 95.4 |
| Detector → replan, $(2, 10)$ | V | 5 | 67.2 | $+2.5$ $[+0.6, +4.5]$ | 95.2 |
| Detector → replan, then $n{=}10$ | V | 3 | 67.9 | $+3.3$ $[+1.0, +5.5]$ | – |
| Scripted shift $0.5\,d$ | P | 3 | 70.9 | $+6.3$ $[+3.9, +8.7]$ | 90.8 |
| Fixed-rule shift, $0.5\,\hat{d}$ | V | 3 | 71.2 | $+6.5$ $[+3.7, +9.3]$ | 95.4 |
| Residual teacher (BC + PPO) | P | 5 | 77.4 | $+12.7$ $[+10.1, +15.3]$ | 95.2 |
| Student without $\hat{d}$ | V | 2 | 74.5 | $+9.8$ $[+6.9, +12.7]$ | 95.4 |
| **Residual student** | V | 5 | **75.9** | $\mathbf{+11.2}$ $[+8.5, +13.9]$ | 95.4 |

In.: V vision + proprioception, P privileged state. Succ.: mean over draws; half of the 500 episodes use training initial states. Undist.: one draw, with the base row's sampling-noise seed (base over three draws: 95.1).

undisturbed episodes the student (active in 5% through false alarms) scores 95.4%, as does the base draw with the same noise (one episode flips each way); against three base draws it is $+0.3$ $[-1.0, +1.7]$, so the 95% interval excludes drops above about one point. In the pre-registered test on fresh initial states the student gains $+8.4$ $[+5.6, +11.2]$ (73.7% versus 65.4%) and $+2.9$ $[+0.7, +5.1]$ over the fixed-rule shift, which itself gains $+5.4$; undisturbed success changes by $-0.2$ $[-1.0, +0.4]$ (one draw). Against the 32.6 ms GPU policy query, the detector takes 0.4 ms per control step, the regressor 2.2 ms per detection and the student MLP 0.02 ms per active query (two CPU threads; full loop not timed).

### D. Other Disturbances and Side Effects

The student and detector were trained only on 4–6 cm displacements, mostly during the approach (the regressor on 2–10 cm); Fig. 3 evaluates them unchanged on other disturbances (all 500 episodes). With 8–12 cm displacements, where the base policy falls to 37.0% (three draws), the student gains $+8.3$ $[+5.0, +11.5]$ and the privileged teacher $+12.1$ (two draws each), while the fixed-rule shift gains only $+3.8$ (three draws). The student is $+4.5$ $[+1.5, +7.5]$ above it ($+4.2$ above the selected rule, two draws). Beyond the regressor's 10 cm training range the student still gains $+8.0$ $[+3.7, +12.4]$ ($+7.7$ $[+1.9, +13.6]$ on held-out initial states). On the other disturbances the student is neutral: for a late move of the nearest free object (steps 100–200) the detector fires in half of the episodes and the student's gain is within noise ($+1.4$), whereas the privileged teacher is slightly harmful ($-2.4$ $[-4.2, -0.5]$, two draws each); for sliding (6–10 cm planned, cut short when the gripper closes, so slides differ by method) and a five-step arm push the detector, trained on teleports, rarely fires (6–12%) and success changes by at most 1.1 points. Undisturbed success is 95.2–95.6% in every detector-gated variant measured: the detector gate bounds how often a residual can act, whereas the scripted shift's cumulative gate costs 4.6 points (90.8%).

### E. Ablation: Displacement Estimate

A student distilled without $\hat{d}$ is only slightly worse than the full student on all 500 episodes ($-1.4$ $[-3.5, +0.9]$, two draws; $-1.4$ to $-2.8$ over three distillation seeds): at 4–6 cm





Fig. 3. Gains under the training disturbance (left), other disturbances and "none" (500 episodes each; draws, baseline/methods: 7/5 at 4–6 cm, 3/2 at 8–12 cm, 2/1 late, 2/1 sliding, 1/1 otherwise; the teacher was not run with the arm push). Paired gains with 95% intervals, bold when excluding zero.




Fig. 4. One episode of the mug-and-pudding task from a held-out initial state, with the same sampling noise in both rows; $t$ is the control step. Top: the base policy alone (timeout). Bottom: with the detector and residual student (success).

the detector tells it *when*, while the base chunk, proprioception and the task input may tell it *how*. At 8–12 cm $\hat{d}$ helps in two of three seeds (without it $-3.9$ $[-6.5, -1.3]$, two draws; other seeds $-6.0$, $+0.8$). It does not make the correction proportional: held out, from 4–6 to 8–12 cm the student's shift along the displacement grows only from 2.3 to 3.2 cm (the teacher's from 3.3 to 9.2 cm), as $\hat{d}$ saturates near 6 cm.

### F. Where the Residual Helps and Where It Fails

Gains concentrate where the approach triggers the event: held out, the student gains $+12.3$ $[+7.6, +17.1]$ on the 179 approach-triggered episodes but $+2.7$ $[-2.6, +7.9]$ on the 71 triggered by the time fallback (fresh states: $+11.3$ and $-0.1$). The residual was active in 85% of the student's remaining held-out failures, so few are due to missed detections; the correction itself, labeled zero where the teacher's gate stayed closed, is a likely bottleneck. In Fig. 4, although $\hat{d}$ is poor (1 cm, wrong direction), the correction points toward the mug, so it may come from the base chunk or a task-level push.

## VI. CONCLUSION

When the target object is displaced, $\pi_{0.5}$ often first closes the gripper nearer its old position and loses 31 points. Re-planning at the detected event recovers zero to three points, a

fixed-rule shift about six, and, on fresh initial states, the event-gated residual student about eight. Gating keeps this post-training conservative: undisturbed success shows no measurable change, whereas a loosely gated teacher cut it to 73.6%. Limitations are one policy, benchmark and task set, and mostly single training runs. Needing no object state and little CPU time, the modules could run beside a robot's VLA, like TRANSIC's residual beside a simulation-trained policy [29]. Open sim-to-real gaps are rendered training frames, teleported rather than physical displacements, and synchronous execution; next, we probe them on hardware, test whether the correction tracks the displacement and try an end-to-end, possibly multi-agent gate [40].

## REFERENCES


[1] M. J. Kim *et al.*, "OpenVLA: An open-source vision-language-action model," in *Proc. Conf. Robot Learn. (CoRL)*, 2024, pp. 2679–2713.

[2] K. Black *et al.*, "$\pi_0$: A vision-language-action flow model for general robot control," in *Proc. Robot.: Sci. Syst. (RSS)*, 2025.

[3] ——, "$\pi_{0.5}$: A vision-language-action model with open-world generalization," in *Proc. Conf. Robot Learn. (CoRL)*, 2025, pp. 17–40.

[4] T. Z. Zhao, V. Kumar, S. Levine, and C. Finn, "Learning fine-grained bimanual manipulation with low-cost hardware," in *Proc. Robot.: Sci. Syst. (RSS)*, 2023.

[5] C. Chi *et al.*, "Diffusion policy: Visuomotor policy learning via action diffusion," *Int. J. Robot. Res.*, vol. 44, no. 10–11, pp. 1684–1704, 2025.

[6] B. Liu *et al.*, "LIBERO: Benchmarking knowledge transfer for lifelong robot learning," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 36, 2023, pp. 44 776–44 791.

[7] Y. Liang *et al.*, "Adaptive action chunking at inference-time for vision-language-action models," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2026, pp. 20 802–20 811.

[8] Y. Pan *et al.*, "VLA-Corrector: Lightweight detect-and-correct inference for adaptive action horizon," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2026.

[9] I. Chun, S. Lee, M. S. Albergo, S. Xie, and E. Vanden-Eijnden, "Dynamic test-time compute scaling in control policy: Difficulty-aware stochastic interpolant policy," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 38, 2025, pp. 51 441–51 462.

[10] Y. Liu, J. I. Hamid, A. Xie, Y. Lee, M. Du, and C. Finn, "Bidirectional decoding: Improving action chunking via guided test-time sampling," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2025.

[11] C. Agia *et al.*, "Unpacking failure modes of generative policies: Runtime monitoring of consistency and progress," in *Proc. Conf. Robot Learn. (CoRL)*, 2024, pp. 689–723.

[12] C. Xu *et al.*, "Can we detect failures without failure data? Uncertainty-aware runtime failure detection for imitation learning policies," in *Proc. Robot.: Sci. Syst. (RSS)*, 2025.

[13] Q. Gu *et al.*, "SAFE: Multitask failure detection for vision-language-action models," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 38, 2025, pp. 40 041–40 076.

[14] X. Yuan, T. Mu, S. Tao, Y. Fang, M. Zhang, and H. Su, "Policy Decorator: Model-agnostic online refinement for large policy model," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2025.

[15] W. Xiao *et al.*, "Self-improving vision-language-action models with data generation via residual RL," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2026.

[16] Y. Zhang *et al.*, "LIBERO-MAX: Do robot policies adapt when the world changes?" *arXiv preprint arXiv:2609.36518*, 2026.

[17] S. Fei *et al.*, "LIBERO-Plus: A progressive robustness benchmark for visual-language-action models," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2026, pp. 38 574–38 583.

[18] J. Guo *et al.*, "On robustness of vision-language-action model against multi-modal perturbations," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2026.

[19] X. Gao, X. Wang, Z. Zang, R. Wang, C. Zheng, and C. Sun, "OGPO: Offline goal-conditioned policy optimization for recoverable vision-language-action models," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2026.

[20] K. Black, M. Y. Galliker, and S. Levine, "Real-time execution of action chunking flow policies," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 38, 2025, pp. 33 383–33 407.

[21] X. Feng *et al.*, "Denoising tells when to replan: Denoising-variance adaptive chunking for flow-based robot policies," *arXiv preprint arXiv:2606.03847*, 2026.

[22] T. Johannink *et al.*, "Residual reinforcement learning for robot control," in *Proc. IEEE Int. Conf. Robot. Autom. (ICRA)*, 2019, pp. 6023–6029.

[23] L. Ankile, A. Simeonov, I. Shenfeld, M. Torne, and P. Agrawal, "From imitation to refinement – residual RL for precise assembly," in *Proc. IEEE Int. Conf. Robot. Autom. (ICRA)*, 2025.

[24] A. Wagenmaker *et al.*, "Steering your diffusion policy with latent space reinforcement learning," in *Proc. Conf. Robot Learn. (CoRL)*, 2025, pp. 258–282.

[25] Y. Chen, S. Tian, S. Liu, Y. Zhou, H. Li, and D. Zhao, "ConRFT: A reinforced fine-tuning method for VLA models via consistency policy," in *Proc. Robot.: Sci. Syst. (RSS)*, 2025.

[26] Y. Guo *et al.*, "Improving vision-language-action model with online reinforcement learning," in *Proc. IEEE Int. Conf. Robot. Autom. (ICRA)*, 2025, pp. 15 665–15 672.

[27] J. Liu *et al.*, "What can RL bring to VLA generalization? An empirical study," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 38, 2025, pp. 97 121–97 151.

[28] Y. Zhang *et al.*, "Overcoming dynamics-blindness: Training-free pace-and-path correction for VLA models," *arXiv preprint arXiv:2605.11459*, 2026.

[29] Y. Jiang *et al.*, "TRANSIC: Sim-to-real policy transfer by learning from online correction," in *Proc. Conf. Robot Learn. (CoRL)*, 2024, pp. 1691–1729.

[30] Y. Lipman, R. T. Q. Chen, H. Ben-Hamu, M. Nickel, and M. Le, "Flow matching for generative modeling," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2023.

[31] J.-H. Oh, C.-H. Ji, S.-Y. Kwak, Y.-K. Kang, J.-W. Han, J.-M. Kim, and T.-E. Kam, "PT-Diff: Brain network generation with personalized topology guided conditional diffusion transformer," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, 2026, pp. 7061–7065.

[32] C.-H. Ji, J.-H. Oh, Y.-K. Kang, J.-M. Kim, S.-Y. Kwak, J.-W. Han, S. Cho, and T.-E. Kam, "A hierarchical reinforcement learning approach to personalized decision-making for brain connectivity segmentation," *Expert Syst. Appl.*, vol. 329, 2026, Art. no. 132973.

[33] C.-H. Ji, D.-H. Shin, Y.-H. Son, and T.-E. Kam, "Sparse graph representation learning based on reinforcement learning for personalized mild cognitive impairment (MCI) diagnosis," *IEEE J. Biomed. Health Inform.*, vol. 28, no. 8, pp. 4842–4853, 2024.

[34] C.-H. Ji, J.-H. Oh, Y.-K. Kang, S.-Y. Kwak, J.-W. Han, J.-M. Kim, J.-Y. Hwang, and T.-E. Kam, "Agentic Brain: Agentic AI system for autonomous diagnosis of functional connectivity network," in *Proc. Int. Conf. Electron., Inf., Commun. (ICEIC)*, 2026.

[35] J. Schulman, P. Moritz, S. Levine, M. Jordan, and P. Abbeel, "High-dimensional continuous control using generalized advantage estimation," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2016.

[36] C.-H. Ji, J.-Y. Hwang, J.-H. Oh, Y.-K. Kang, S.-Y. Kwak, J.-W. Han, and T.-E. Kam, "Reinforcement learning with multi-objective rewards for functional connectivity augmentation," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, 2026, pp. 7822–7826.

[37] J.-Y. Hwang, C.-H. Ji, J.-H. Oh, Y.-K. Kang, S.-Y. Kwak, J.-W. Han, and T.-E. Kam, "Adaptive reward weighting via reinforcement learning for major depressive disorder diagnosis," in *Proc. Int. Conf. Electron., Inf., Commun. (ICEIC)*, 2026.

[38] Y.-K. Kang, C.-H. Ji, J.-H. Oh, S.-Y. Kwak, J.-W. Han, and T.-E. Kam, "Adaptive static-dynamic functional connectivity feature fusion for diagnosis of mild cognitive impairment," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process. (ICASSP)*, 2026, pp. 6936–6940.

[39] S. Ross, G. Gordon, and D. Bagnell, "A reduction of imitation learning and structured prediction to no-regret online learning," in *Proc. Int. Conf. Artif. Intell. Statist. (AISTATS)*, 2011, pp. 627–635.

[40] D.-H. Shin, Y.-H. Son, J.-M. Kim, H.-J. Ahn, J.-H. Seo, C.-H. Ji, J.-W. Han, B.-J. Lee, D.-O. Won, and T.-E. Kam, "MARS: Multiagent reinforcement learning for spatial-spectral and temporal feature selection in EEG-based BCI," *IEEE Trans. Syst., Man, Cybern.: Syst.*, vol. 54, no. 5, pp. 3084–3096, 2024.