

7.15 audit unit 07b3 — embedded calls and assembled review

1. Identity and frozen scope

Owner: 7.15 firmware rehearsal. Worktree: /private/tmp/kk715-stack07b3-ready, branch release/715-stack-07b3-erc7730-embedded-ready, [firmware draft #867](https://github.com/BitHighlander/keepkey-firmware/pull/867). Target: release/715-stack-07b2-erc7730-groups at efbeda0a15f919a1f54bc902745c4dc6f9d9675f. E integration predecessor: 2ac517242 (D review fixes and companion pin). Python companion: deps/python-keepkey at 0bf7ae7 (merged D review fix), [companion draft #116](https://github.com/BitHighlander/python-keepkey/pull/116). The main-worktree MASTER-AUDIT-TEMPLATE.md SHA256 is 743843a17139a7394325a961b9a38666c8e8af7a0005e0ff52eb94559ec8dbb7. This is the final code-bearing adjacent PR diff in the owner-authorized three-unit replacement for historical firmware PR #863.

E adds bounded inner-call binding and display to the A-C formatter and D group/iteration base. It accepts the supported embedded-call shape only when the definition and calldata agree. Unbound or unsupported inner calls are refused before review or shown as blind with an explicit warning. The signed outer and inner facts remain visible at device confirmation.

2. Git inventory and changed behavior

Immutable code and split-receipt inventory range: git diff --numstat efbeda0a15f919a1f54bc902745c4dc6f9d9675f..483a10f09. Frozen inventory range including this source report and PDF: git diff --numstat efbeda0a15f919a1f54bc902745c4dc6f9d9675f..FROZEN_RANGE_PENDING. The inventory below is the adjacent E net diff. It includes tests, handoffs, the historical #863 report, split receipt and Python gitlink. The final report-containing PR head is recorded in the PR body.

Tracked path	Added	Deleted	Change and evidence
deps/python-keepkey	1	1	Pins the matching compiler mirror and its tests.
docs/release/audit-units/715-07b-formatters-audit-20260925.md	339	0	Records exact scope, findings, inventory and validation.
docs/release/audit-units/715-07b-formatters-audit-20260925.pdf	-	-	Rendered audit evidence from the adjacent source report.
docs/release/audit-units/715-07b-split-receipt-20260926.md	133	0	Records exact scope, findings, inventory and validation.
docs/release/audit-units/715-07b-split-receipt-20260926.pdf	-	-	Rendered audit evidence from the adjacent source report.
docs/release/audit-units/715-07b3-embedded-audit-20260926.md	111	0	Records exact scope, findings, inventory and validation.
docs/release/audit-units/715-07b3-embedded-audit-20260926.pdf	-	-	Rendered audit evidence from the adjacent source report.
docs/security/HANDOFF-ERC7730-715-FORMATTERS.md	10	9	Records on-screen behavior and fail-closed limits.
docs/security/HANDOFF-ERC7730-PHASE-E.md	209	0	Records on-screen behavior and fail-closed limits.
include/keepkey/firmware/erc7730_abi_stream.h	8	1	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_capabilities.h	17	7	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_catalog.h	9	5	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_field.h	9	0	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_workflow.h	49	1	Declares bounded state and the phase's runtime contract.
lib/firmware/erc7730_abi_stream.c	13	2	Captures only bounded ABI facts and records overflow.
lib/firmware/erc7730_capabilities.c	19	6	Selects the exact formatter and display capabilities.

lib/firmware/erc7730_catalog.c	29	8	Refuses unexecutable signed programs before review.
lib/firmware/erc7730_field.c	42	0	Formats decoded values with signer provenance visible.
lib/firmware/erc7730_workflow.c	243	7	Keeps replay, validation and UI state in sequence.
lib/firmware/fsm.c	2	1	Implements the phase's bounded decoding or display rule.
lib/firmware/fsm_msg_ethereum.h	268	26	Shows and confirms the device-decoded review screens.
scripts/emulator/test_stack07_regressions.py	6	468	Exercises signed wire requests and review screens.
unittests/firmware/erc7730_catalog.cpp	277	174	Covers accepted neighbors and fail-closed boundaries.
unittests/firmware/erc7730_field.cpp	24	0	Covers accepted neighbors and fail-closed boundaries.
unittests/firmware/erc7730_workflow.cpp	9	5	Covers accepted neighbors and fail-closed boundaries.

The earlier unit reports cover their own adjacent changes. The split receipt maps every path from #863 to A-C, D or E and records the historical finding clusters. E inherits D's later safety fixes, so the current source tree differs from historical #863 in those fixes.

3. Current-source findings and limits

Finding	Disposition and evidence
D2 embedded intent and D9 literal callee	Inner-call intent and callee are bound to decoded calldata before confirmation; mismatches fail closed.
D17 refused inner definition	Unsupported inner definitions are refused at preload. A malformed inner-call program cannot produce a trusted review screen.
Inner @.value without amountPath	An absent amount path cannot silently substitute a value; the catalog and workflow controls cover refusal.
Depth-two and call binding	The bounded parser and runtime reject unsupported nesting or mismatched calls; ABI, catalog, workflow and signed-wire cases cover neighboring valid and invalid shapes.
D15 pager continuation handling	The wire test filters continuation pages while retaining repeated content, so duplicate review screens remain observable.
Historical Copilot status	#863 received three reviews with seven resolved findings. The split receipt assigns each finding to its owning unit. This E diff requires its own external review.

The historical 102-agent audit retained D1–D19 clusters but not all 42 raw finding rows. D13 and D19 are unnamed in the surviving handoff. The split receipt states that evidence gap; this report does not infer missing per-finding dispositions. Physical-device confirmation remains a separate release gate.

4. Verification and artifacts

Check	Exact source or run	Result and limit
Full native firmware	E integrated source, Docker run directory	firmware-unit 656/656 passed.
Host/device compiler mirror	Python 0bf7ae7, E firmware validator	Compiler and catalog: 24 pass, 3 registry-dependent skips.
Corrected cppcheck	Prior #863 source, Ubuntu 24.04 CI flags	Zero findings before D integration; hosted static check needed on final E head.
Historical hosted CI	#863 exact head 729ae7cfa, Actions 36263598278	All 16 required jobs passed; supporting code-equivalence evidence only.
Replacement hosted CI	#867 prior split head, Actions 36271867412	All required jobs passed before D integration; final E head still needs exact-head status.
Wire and physical device	Final E CI pending	Hosted wire test pending on integrated head; no physical device used.

The canonical 7b pre-push script passed submodule cleanliness, unit-test registration and clang-format 20 in this worktree. It failed on inherited duplicate Osmosis/Solana nanopb options, the absent scripts/test_generate_test_report.py in the 7a base, and its own absent .cppcheck-build directory. The owner approved the 7b push with that exception recorded. The canonical gate is not called passing.

5. Report preflight and review checkpoint

The readable source and PDF carry the same inventory. The PDF is opened for legibility before push. The final live target and PR head are checked after the report commit. `git diff --check`, the code-review-diff gate, exact-head hosted CI and a new Copilot review belong to the final PR head. The historical #863 review is not a clean review of this adjacent E diff.