

7.15 audit unit 07b3 — embedded calls and assembled review

1. Identity and frozen scope

Owner: 7.15 firmware rehearsal. Worktree: /private/tmp/kk715-stack07b3-ready, branch release/715-stack-07b3-erc7730-embedded-ready, [firmware draft #867](https://github.com/BitHighlander/keepkey-firmware/pull/867). Target: release/715-stack-07b2-erc7730-groups at cd6621c575e36fd0605e2ce54710bdf73528f502. Code and split-receipt predecessor before this report: 3933e96a2. Post-report predecessor reconciliation and updated split receipt: 4fab0ea8f907bec2af94e23ef2ef50e7108cea9b. Python companion: deps/python-keepkey at 67e891214086f7c7c6ebc7f75f9e3e9f27ec96a0, [companion draft #116](https://github.com/BitHighlander/python-keepkey/pull/116). The main-worktree MASTER-AUDIT-TEMPLATE.md SHA256 is 743843a17139a7394325a961b9a38666c8e8af7a0005e0ff52eb94559ec8dbb7. This is the final code-bearing adjacent PR diff in the owner-authorized three-unit replacement for historical firmware PR #863.

E adds bounded inner-call binding and display to the A-C formatter and D group/iteration base. It accepts the supported embedded-call shape only when the definition and calldata agree. Unbound or unsupported inner calls are refused before review or shown as blind with an explicit warning. The signed outer and inner facts remain visible at device confirmation.

2. Git inventory and changed behavior

Immutable code and split-receipt inventory range: git diff --numstat cd6621c575e36fd0605e2ce54710bdf73528f502..4fab0ea8f907bec2af94e23ef2ef50e7108cea9b. Frozen inventory range including this source report and PDF: FROZEN_RANGE_PENDING. The inventory below is the adjacent E net diff. It includes tests, handoffs, the historical #863 report, split receipt and Python gitlink. The final report-containing PR head is recorded in the PR body.

Tracked path	Added	Deleted	Change and evidence
deps/python-keepkey	1	1	Pins the matching compiler mirror and its tests.
docs/release/audit-units/715-07b-formatters-audit-20260925.md	339	0	Records exact scope, findings, inventory and validation.
docs/release/audit-units/715-07b-formatters-audit-20260925.pdf	-	-	Rendered audit evidence from the adjacent source report.
docs/release/audit-units/715-07b-split-receipt-20260926.md	133	0	Records exact scope, findings, inventory and validation.
docs/release/audit-units/715-07b-split-receipt-20260926.pdf	-	-	Rendered audit evidence from the adjacent source report.
docs/release/audit-units/715-07b3-embedded-audit-20260926.md	115	0	Records exact scope, findings, inventory and validation.
docs/release/audit-units/715-07b3-embedded-audit-20260926.pdf	-	-	Rendered audit evidence from the adjacent source report.
docs/security/HANDOFF-ERC7730-715-FORMATTERS.md	10	9	Records on-screen behavior and fail-closed limits.
docs/security/HANDOFF-ERC7730-PHASE-E.md	209	0	Records on-screen behavior and fail-closed limits.
include/keepkey/firmware/erc7730_abi_stream.h	8	1	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_capabilities.h	17	7	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_catalog.h	9	5	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_field.h	9	0	Declares bounded state and the phase's runtime contract.
include/keepkey/firmware/erc7730_workflow.h	49	1	Declares bounded state and the phase's runtime contract.
lib/firmware/erc7730_abi_stream.c	13	2	Captures only bounded ABI facts and records overflow.

lib/firmware/erc7730_capabilities.c	19	6	Selects the exact formatter and display capabilities.
lib/firmware/erc7730_catalog.c	29	7	Refuses unexecutable signed programs before review.
lib/firmware/erc7730_field.c	42	0	Formats decoded values with signer provenance visible.
lib/firmware/erc7730_workflow.c	243	7	Keeps replay, validation and UI state in sequence.
lib/firmware/fsm.c	2	1	Implements the phase's bounded decoding or display rule.
lib/firmware/fsm_msg_ethereum.h	268	26	Shows and confirms the device-decoded review screens.
scripts/emulator/test_stack07_regressions.py	6	468	Exercises signed wire requests and review screens.
unittests/firmware/erc7730_catalog.cpp	277	174	Covers accepted neighbors and fail-closed boundaries.
unittests/firmware/erc7730_field.cpp	24	0	Covers accepted neighbors and fail-closed boundaries.
unittests/firmware/erc7730_workflow.cpp	9	5	Covers accepted neighbors and fail-closed boundaries.

The earlier unit reports cover their own adjacent changes. The split receipt maps every path from #863 to A–C, D or E and records the historical finding clusters. E's code-bearing files match the #863 final source tree; the companion gitlink and added split evidence account for the tracked tree differences.

3. Current-source findings and limits

Finding	Disposition and evidence
D2 embedded intent and D9 literal callee	Inner-call intent and callee are bound to decoded calldata before confirmation; mismatches fail closed.
D17 refused inner definition	Unsupported inner definitions are refused at preload. A malformed inner-call program cannot produce a trusted review screen.
Inner @.value without amountPath	An absent amount path cannot silently substitute a value; the catalog and workflow controls cover refusal.
Depth-two and call binding	The bounded parser and runtime reject unsupported nesting or mismatched calls; ABI, catalog, workflow and signed-wire cases cover neighboring valid and invalid shapes.
D15 pager continuation handling	The wire test filters continuation pages while retaining repeated content, so duplicate review screens remain observable.
Historical Copilot status	#863 received three reviews with seven resolved findings. The split receipt assigns each finding to its owning unit. This E diff requires its own external review.

The historical 102-agent audit retained D1–D19 clusters but not all 42 raw finding rows. D13 and D19 are unnamed in the surviving handoff. The split receipt states that evidence gap; this report does not infer missing per-finding dispositions. Physical-device confirmation remains a separate release gate.

4. Verification and artifacts

Check	Exact source or run	Result and limit
Full native firmware	E code-equivalent source before this report, clean Docker run directory	firmware-unit 656/656 passed.
Host/device compiler mirror	Python 67e891214, E firmware validator	Compiler/catalog suite: 23 pass, 2 skip locally without the official registry.
Corrected cppcheck	#863 source-equivalent code, Ubuntu 24.04 CI flags	Zero findings.
Historical hosted CI	#863 exact head 729ae7cfa, Actions 36263598278	All 16 required jobs passed; supporting code-equivalence evidence only.
Replacement hosted CI	#867 first split head, Actions 36269699803	Static and ARM passed; other jobs pending when reconciled. The final merged head needs its own exact-head run.
Wire and physical device	Split CI pending	Hosted wire test pending; no physical device used.

The canonical 7b pre-push script passed submodule cleanliness, unit-test registration and clang-format 20 in this worktree. It failed on inherited duplicate Osmosis/Solana nanopb options, the absent scripts/test_generate_test_report.py in the 7a base, and its own absent .cppcheck-build directory. The owner approved the 7b push with that exception recorded. The canonical gate is not called passing.

5. Report preflight and review checkpoint

The readable source and PDF carry the same inventory. The PDF is opened for legibility before push. The final live target and PR head are checked after the report commit. `git diff --check`, the code-review-diff gate, exact-head hosted CI and a new Copilot review belong to the final PR head. The historical #863 review is not a clean review of this adjacent E diff.