

7주차 복습과제 (이론) - 문제

1. You are building a 3-class object classification and localization algorithm. The classes are: pedestrian (c=1), car (c=2), motorcycle (c=3). What would be the label for the following image? Recall $y=[pc,bx,by,bh,bw,c1,c2,c3]$



$[1, 0.3, 0.7, 0.3, 0.3, 0, 1, 0]$

2. Continuing from the previous problem, what should y be for the image below? Remember that “?” means “don’t care”, which means that the neural network loss function won’t care what the neural network gives for that component of the output. As before, $y=[pc,bx,by,bh,bw,c1,c2,c3]$.



- 1) $y = [?, ?, ?, ?, ?, ?, ?, ?]$
- 2) $y = [1, ?, ?, ?, ?, 0, 0, 0]$
- 3) $y = [1, ?, ?, ?, ?, ?, ?, ?]$
- 4) $y = [0, ?, ?, ?, ?, ?, ?, ?]$
- 5) $y = [0, ?, ?, ?, ?, 0, 0, 0]$


3. If you build a neural network that inputs a picture of a person's face and outputs N landmarks on the face (assume the input image always contains exactly one face), how many output units will the network have?

$2N$

4. When training one of the object detection systems described in lecture, you need a training set that contains many pictures of the object(s) you wish to detect. However, bounding boxes do not need to be provided in the training set, since the algorithm can learn to detect the objects by itself. (True or False)

False

5. What is the IoU between these two boxes? The upper-left box is 2×2 , and the lower-right box is 2×3 . The overlapping region is 1×1 .




$\frac{1}{9}$

6. Why do we learn a function $d(img1, img2)$ for face verification? - (주관식 작성)

적은 데이터셋을 이용하여 학습을 할 수 있게 하기 위해서.
one-shot learning problem 해결을 위하여.


7. Consider the following Siamese network architecture:



The upper and lower neural networks have different input images and the different parameters.

False

8. C4W3L04의 강의에서는 sliding window에 convolution을 적용하여 연산 속도를 빠르게 하는 방법을 설명하고 있습니다. 아래의 강의 슬라이드를 자신이 이해한대로 설명하는 글을 작성해주세요.



Sliding window의 수많은 번복 연산을.

CNN을 이용하여 줄일 수 있다.