IRONCLAD System Concept Whitepaper

Author: Udaiveer Singh Bhangu, The University of Ottawa
Date: April 14th, 2026

***IRONCLAD*: A Resiliency Oriented Emergency Alert System Specification**
Failure-Resilient Emergency Alert Architecture for Institutions

License: Creative Commons Attribution 4.0 International (CC BY 4.0)

This work may be shared, adapted, and redistributed for any purpose, including commercial use, provided appropriate credit is given to the original author. When referencing the IRONCLAD system in derivative works, citation of the original whitepaper is requested.
A copy of this license is available at: https://creativecommons.org/licenses/by/4.0/

This work is published to provide systems-level definition and reference for individuals and institutions seeking to improve current emergency alert infrastructure.

Version 1

Abstract

Emergent situation communication at large scales requires failure-safe architecture and implementation. Current institutional emergency alert systems experience systemic failure through limits in resiliency, testing, and scope. Emergency communications are life-critical infrastructure, giving targeted and broad advice in situations involving high pressure and increased failure modes. *IRONCLAD* is a conceptual architecture detailing resiliency oriented infrastructure, bridging gaps in current emergency communications systems. *IRONCLAD* mitigates key failure modes through combining isolated, high-speed, and failure-resilient infrastructure designs. The *IRONCLAD* framework does not claim completeness or implementation readiness. This whitepaper functions as a conceptual, minimal systems-level specification, with actionable and iteration-ready features.

Key Definitions

Delivery Latency

- The time difference between information is first shared and when it is read and understood by the majority of those impacted by an emergency

Reachability

- The amount of people exposed to an emergency incident coherently receiving emergency communications compared to the total amount of people directly impacted.

Delivery Guarantee

- Near 100% uptime on providing a service or good

Emergency Event

- An immediate occurrence outside standard operational norms of a given system

Degraded Mode Operation

- A system's capacity for operation during the occurrence of failure modes

Fallback Layer

- An external system which completes the operation of a system undergoing cascade failure, disrupting standard operations

Cascade Failure

- The presence of every failure mode of a system, resulting in a chain of increasingly catastrophic failure, until the system is entirely disrupted

1. Introduction

1.1 Emergency Communications as Life-Safety Systems

Emergency communications facilitate direct information delivery during times of immediate,

critical need. These communication systems provide potentially life-saving information to recipients, regarding the emergent events and actionable steps to increase positive outcomes. Similar communication systems include fire and evacuation alarms, signaling events potentially threatening safety and survival.

1.2 Modern Failure Conditions

Modern implementations of emergency communications have additional failure modes not privy to traditional alarm-style systems. Many current alert systems are dependent on centralized web infrastructure, usually dependent on applications and high bandwidth assumptions. These dependencies introduce preventable vectors for failure, such as: power and internet continuity, server load, and application installation.

These failures may disrupt order, expose people to risk, and potentially result in harm to people experiencing emergency events.

1.3 Observed Failure Class

A modern system's partial failure was recently observed at The University of Ottawa. On April 10th, 2026, at roughly 5:18PM, a lockdown notice was sent through SecureUO. SecureUO is the University of Ottawa's optional security alert app, with the full alert shown in Figure 1.



Figure 1: SecureUO alert of 04/10/2026, at 5:18PM

The alert contains general emergency locational information "main campus" and a short description of the cause, "violent threat on campus". A link to https://ue.uottawa.ca/ is present, the site showing more information regarding the incident, along with a timestamp. Follow up alerts were sent at 6:03PM and 6:37PM, with a final "campus is safe" alert at 7:10PM.

The https://ue.uottawa.ca/ domain displayed an alert with general lockdown information and

timestamping, along with an all-clear update around the same time as the SecureUO all-clear.

RUN - HIDE - DEFEND

There's a violent incident occurring on campus. Avoid the campus.

If you're on campus:

- Stop all activities and get inside a building immediately.
- Find an enclosed area and lock or barricade the door.
- Turn off the lights and mute all electronic devices.
- Stay away from doors and windows.
- Take cover and remain silent until authorities instruct otherwise.

If a violent attacker is close by, be ready to run, hide or, if your life is in imminent danger, defend yourself by any means necessary until you can get away.

Remember: RUN - HIDE - DEFEND

Updates will be provided when possible.

Figure 2: https://ue.uottawa.ca/ site landing, alert information only.

Key System Failures:

- The SecureUO app received these alerts at correct times, with variances in delivery time due to application environment and hardware posture differences
- Those without the optional SecureUO app did not receive the alerts, commonly relying on social media and peer-to-peer information sharing for incident awareness
- Student and faculty specific emails or SMS was not provided
- The https://ue.uottawa.ca/ site suffered significant load-time, lag, and stability issues
- Students and faculty had minimal scope and specific location-specific information regarding the incident, using unofficial information sharing channels for situational awareness and decision making
- User state assumptions were made, limiting message delivery and overall continuity

These failures collectively created situational ambiguity, leading to unsafe behavior such as ignoring the instructions given at https://ue.uottawa.ca/ during the alert. Unofficial channel use also fueled rumors and lack of adherence to official protocols, further exacerbated by the instability of the https://ue.uottawa.ca/ page. These failures occurred because the system was optional in adoption, was not designed for full resilience, and provided insufficient information for key personal safety decisions, especially in incident scope and severity.

At a top-level, the SecureUO system was designed to be optional. Emergencies impact people

indiscriminately, with decision-making and quality information access creating significant decreases in negative outcomes. Emergency communications systems create the most positive outcomes when designed as backbones of life-preservation and not optional tools.

The design, deployment, and governance of emergency communications as a user-facing optional service rather than as critical life-safety infrastructure is a critical system design failure.

1.4 Core Foundations of IRONCLAD

IRONCLAD asserts systems should be designed to perform during: partial infrastructure failure, extreme network conditions, and zero user preconfiguration. These foundational elements ensure potentially life-saving emergency information is accessible to all potentially affected by emergency incidents.

1.5 Scope and Non-Goals

IRONCLAD:

- Is not singularly dependant on user-installed apps
- Does not assume standard networking conditions
- Prioritizes bandwidth minimisation without subverting function
- Does not rely on single-system integrity and use
- Does not assume full information access and availability

IRONCLAD IS:

- Redundancy-first
- Latency-minimized
- Failure-tolerant
- Broadcast-oriented
- Infrastructure-isolated

IRONCLAD Operating Constraints:

Zero User Preconfiguration

- System functions acceptably with minimal end-user installations, enrollment, and setup
- Emergency communications reach all impacted regardless of prior setup

Degraded Network Conditions

- System must remain functional under extreme networking conditions
- Delivery mechanisms must prioritize minimal data size and resiliency over presentation

Partial Infrastructure Failure

- System must continue operation under cascading failure conditions
- Failure of nodes, services, or network segments must not prevent information delivery

High Traffic Surge Conditions

- System must remain accessible during extreme spikes in concurrent users
- Core information must not degrade during traffic surges

User State Variability

- System must function across heterogeneous user states, including low battery, locked devices, poor signal, or user distraction
- The system's design must assume worst-case user availability and attention conditions

Incomplete Situational Information

- System must operate effectively while emergency event information is being collated
- Communications must support iterable updates with clear update windows

Time-Critical Delivery

- The system must minimize delivery latency within the critical communication window
- Information must contain general actionable steps and relative event geolocational information

Adversarial and Unreliable Conditions

- The system must assume the presence of misinformation, partial outages, and unpredictable user behavior
- Communication integrity must be maintained despite hostile or chaotic environments

Minimal Cognitive Load

- Message structure must prioritize clarity, brevity, and immediate actionability
- Staff situation reporting tools must be simple and intuitive to use during stressful occurrences
- Information must be interpretable under stress, panic, or limited attention

2. Failure Analysis of the Focus Class

2.1 Communication Channel Failures

The SecureUO system is dependent on perfect endpoint posturing. SecureUO only provides information to those opted-in to the system, neglecting user-state variability. This creates gaps in information propagation for all students and faculty, especially in regularly occurring imperfect edge cases. User-state variability includes: device power, battery state, network signal and access, app install, correct app setup, and user distraction. Emergency alert systems must function under worst-case user-state assumptions, to minimize harm during emergency events.

2.2 Infrastructure Failures

Critical infrastructure-centric issues affected the SecureUO system within the observed class. The "+info" domain listed within UOSecure, https://ue.uottawa.ca/, had long load times and page stability issues. Many other pages within the public uottawa.ca site had similar loading and stability issues. This points to the ue.uottawa subdomain being hosted on the same infrastructure as uottawa.ca. A surge in traffic means the relevant server hardware is subject to high, non-ordinary load. Isolated network and web infrastructure is therefore needed for emergency communication reliability and accessibility.

2.3 Information Design Failures

The observed class contained key information design failures. The +info domain https://ue.uottawa.ca/, assuming functional operation, only provided generic situation specific information. Updates either reiterated the emergency alert, asserted situational continuity, or proclaimed police investigation. While this is useful information, it is incomplete in situationally targeted advice. A complete alert should contain geospatial specificity with campus buildings as general landmarks, update cadence, and potentially targeted advice for students and faculty in specific locations. Alerting the student-faculty bodies with these specific data points and advice gives further opportunity for informed, protocol adherent decisionmaking. Excessive information security or information incompleteness results in unofficial information channel use, creating potentially dangerous outcomes. SecureUO and the +info page did not provide information at sufficient granularity for decision-making, constituting an information resolution failure.

2.4 Load & Degradation Failures

SecureUO's +info domain, https://ue.uottawa.ca/, did not have load and infrastructure failure resiliency. The web page itself is relatively small but was without optimizations for bandwidth surge and size compression. Assets were not sufficiently cached, creating direct-infrastructure load, further cascading upon request surges. Upon degradation of service stability, there were no graceful fallbacks for bandwidth minimization and content serving. At minimum, a static page

for curl-based text only emergency situation updates would provide much more clarity and information to those affected by emergency situations.

2.5 Institutional Design Failures

Certain failure modes were present in the observed class due to institutional design. Most critically the SecureUO app and system being opt-in only creates large gaps in student-faculty security and information. UX and brand identity priorities within the emergent update page https://ue.uottawa.ca/ contributed to system failure. This created critical failure modes for infrastructure load, also reducing ease of information processing, creating unnecessary decisionmaking latency.

Observed Class Failure Severity Table

Failure Type	Severity	Variable	Impact	Potential Consequences
No Universal Broadcast	Critical	Reachability	Affected people receive no information	Continuation of regular activities, unawareness of emergency situations, less accessible access to potentially life-saving information
Infrastructure Collapse	Critical	Delivery Guarantee	Fragmented information accessibility	Reliance on unofficial channels, disregard for official protocol, degraded information quality for potentially life-saving decisionmaking.
Lack of Information Specificity and Updates	High	Information Resolution	Poor decisions, no situational awareness	Official protocol uncertainty, edge cases where official protocol is not optimal, lacking adaptive situation response
UX Bloat	Moderate	Delivery Latency	Infrastructure load, degraded information accessibility	May contribute to infrastructure collapse during network surge events, higher information latency for users on compromised or cellular-based networking.

3. Design Principles of *IRONCLAD*

3.1 Reliability and Robust Interface

IRONCLAD systems must prioritize reliable function over features. Certain features must therefore be sacrificed to ensure continuous operation during emergency scenarios and failure mode occurrences. Complex alert systems create uncertainty through option overload. Simple alert systems create uncertainty through information and situation update gaps. *IRONCLAD* must be intuitive and simple to interface with, while providing key data and function to users and staff. This hardens *IRONCLAD* during unusual networking events and allows for easy use under external pressures.

3.2 Redundancy and Graceful Degradation

Redundant architecture enables emergency alert systems to function while partial failure modes occur. *IRONCLAD* designs implement redundancy through mesh-style infrastructure, offsite content delivery, and battery-enabled command up-link fallbacks. During certain partial failure modes, redundant architecture may not sufficiently mitigate performance and information delivery targets. *IRONCLAD* addresses this by implementing graceful degradation cycles, with reduced UX and fidelity targets, while maintaining emergency critical information delivery.

3.3 Universality of Access

All people potentially impacted by an emergency must be alerted by *IRONCLAD* emergency communication systems. Access universality can be ensured through alerts on institutional media displays including computers, TVs, and PA systems. Official social channel redirection to web-based emergency communications further augment accessible alerts.

3.4 Infrastructure Independence

IRONCLAD systems must maintain isolated infrastructure from other institutional networking and hardware. Key fallbacks must be in place for potential failures on shared infrastructure including power, local networking, and content delivery networking.

4. Core Architecture of IRONCLAD

4.1 Broadcast Layer

IRONCLAD's broadcast layer facilitates immediate guaranteed emergency alert reach to all potentially affected parties. Alerts are primarily delivered through automatic enrolled email, severe occasion SMS fallback, and local environment systems. These include institutionally owned systems such as TV screens, PA systems, and computers. Secondary alerts must be

posted to official social media platforms, with non-truth assertion to prevent encouragement of unofficial channel use for emergency situations.

Primary and secondary alert vectors must feature simplified messaging and a web-page for official updates and information. Simplified messages are recommended to align with the current SecureUO style formatting *(Figure 1)* containing: a threat type, general location, official information channel link, threat response type, and a message timestamp.

Information updates should be dispatched in parallel to the acceptance of a threat report. Systems must be automated and functional after *IRONCLAD* infrastructure node failures. Email alerts must be preconfigured and not opt-in. Alert senders must be verified within the institutional network and given high message priority or flagging.

All broadcasts are sent in parallel, derived from a single, structured incident reporting system.

4.2 Emergency Information Surface

A separate, official channel must exist as an emergency information surface. This domain must be intuitive and infrastructurally separate from standard institutional infrastructure. In example, emergency.[institutionCommonDomain].[TLD], works as an easily applicable subdomain for institutions seeking to adopt *IRONCLAD* alert infrastructure.

The emergency domain must feature static and HTML-first delivery, with minimized scripting and visual assets. Emergency information must be provided, with landmark and specific location information. A given incident must contain a timestamped update feed, with incident and location specific instructions, and general instructions.

Preliminary emergency information surface design mockup:

[Block 1: Incident Header]

<Institution Name>

There Is a **<Incident Type>** Incident Occurring at **<General Location>**,
<Incident Threat Level> , <Incident Response Type>

Critical Locations: **<List of institution-specific buildings or landmarks near incident>**
If you are at or near critical locations, pay close attention to the message below:

[Block 2, Location and incident specific messaging]
If you are inside or near Critical Locations: **<Critical Location specific actions>**

If you are at **<General Location>**: **<Incident Response Type>**
<Incident Response Information>

Next Update: <**Update Window In Approximate Minutes**>
Further Updates Feed Below
<Timestamp>

[Block 3: Incident Specific Update Feed]
<Incident Specific Information 2> - <Update 2 Timestamp>
<Incident Specific Information 1> - <Update 1 Timestamp>

[Block 4: Emergency Terminology + Emergency Phone numbers]
<Emergency Phone Numbers>
<Emergency Terminology>

[Block 5: Redundancy Links]
<Incident Update RSS/JSON Feed> <Incident Information CURL page>

4.3 Infrastructure Layer

Resilient emergency communication infrastructure is essential for performance during extreme events. Institutional hardware isolated infrastructure with 3-4 system nodes placed in different buildings is essential. Each node must have SSD and RAMDISK style content serving for latency and disruption mitigation. Cloudflare caching combined with an offsite cache content delivery service prevents network spikes from directly targeting emergency communications infrastructure, adding a layer of redundancy.

Degraded Infrastructure Mode

Upon high traffic surges, large scale CDN and Cloudflare outages, destabilized power and network conditions, the node-based infrastructure must enter degraded mode. This degraded mode reduces the already minimized emergency information page to a simple NGINX blank page with plain-text endpoint data. This page must be less than 10KB, without style and script elements, and must be CLI-Accessible. This allows for ultra-low bandwidth content serving and edge hardware information access, as curl-friendly output. The system must never undergo complete, closed failure.

4.4 Persistence & Archive Layer

Incidents, updates, and node status logs must be archived and available for open access. These provide key insights for *IRONCLAD* system issues and potential points for iteration. This also creates transparency-first architecture, giving room for auditing and post-incident analysis. Archives must be stored external to the emergency infrastructure, such that inbound traffic points are maximally reduced for traffic surge performance insurance.

4.5 Low-Power “Last Known Good Option” Layer

Besides the 3-4 SSD backed content nodes, 1-2 edge case fallback nodes must exist. These are independent, low power, high continuity systems which have local, CDN, and EMS communications ability. These systems must have pre-cached, continuously updating static

pages, served through a CDN, ready to replace the standard content nodes upon complete infrastructural failure. To maintain power continuity, this system must have some form of UPS or med-long term battery support. To maintain communications continuity, this system must be equipped with an LTE router and potentially a satellite based communications up-link.

Feasible Concept Mockup:
System: Raspberry PI 5
Components: system battery, external battery + trickle charger, LTE/SATCOM modems
Function: Checks origin health and latency for all standard nodes. Updates cached incident data every 10min, shortened to 1min during incidents. If all standard nodes are undergoing failure (network or power), overwrites current emergency page CDN with current incident display information in degraded mode. PiNodes take situation update authority instead of down standard nodes. Fallback to battery power during power discontinuity. Fallback to LTE/SATCOM upon network/cell network failure. Enters power-saving mode after 3+ hours without power, reducing update frequency and non-essential function.
Behavior: Edge-case command up-link, with high power efficiency and operation under extreme conditions.

5. Information Model & Delivery Specification

5.1 Message Structure Requirements

All incident updates and posts must contain the same key structural variables. These variables include: incident/update timestamps, general and specific incident locations, threat classifications, general and specific incident actions, and estimated update time.

Incident/update timestamps give context and implicit post priorities to receiving users, critical for quick situational awareness in high-pressure environments. General and specific incident locations give recipients crucial incident sensitivity information. This allows for separate instruction for those farther from an emergency situation and those potentially directly exposed to an emergency situation. Simple threat classifications give easy, one to three word identifiers for incident severity and exposure, being high-value during stressful occasions. Estimated update times give transparent information for continuity. Recipients may feel anxious or increasingly reliant on non-official information sources without adequate update cadence.

5.2 Update Cadence Rules

Update cadence must be strictly followed and represented during emergency situations. Emergency communication update times must be met, with information updates during critical situation developments in scope, position, and severity. Stale updates and information must be

invalidated with a fresh update and depreciation of the stale message. This may take the form of update content minimization or formatting change indicative of message staleness.

5.3 Priority Encoding

Broadcasts, updates, and incidents may feature varying criticality. The representation, channels, and information displayed must change depending on perceived threat levels. Upon minor emergent danger, standard email and social media message broadcasting may suffice. Upon situations constituting potential violence or loss of life, all primary and secondary message broadcast systems must be used. Updates and incident reports must feature explicit mention of incident threat level, either through short description (Danger - Violence) or predefined incident threat level ranges, dependent on potential harms.

6. System Behavior Under Load

6.1 Traffic Surge Handling

Upon traffic surges, the multi-node architecture will primarily use external CDN and Cloudflare-like caching systems to mitigate load. If these systems fail, cannot be accessed, or are otherwise compromised, the standard nodes will take most of the traffic. This will be mitigated by: modified graceful degradation state, RAMDISK content serving, changing local WAF to “under attack mode”.

6.2 Failure Modes

Local standard node failure may occur due to power, networking, or configuration issues. If some nodes fail, the remainder nodes will modify graceful degradation state and force local requests to use CDN/external caching, Should the entire primary network fail, the backup raspberry PI system nodes will assume authoritative control of CDN and Cached Content, switching to the plaintext graceful degradation mode. Incident information, the update feed, and actions will be served as Curl and CLI friendly NGINX plaintext, for bandwidth and propagation assurance. If all wireless networking fails (SATCOM, LTE, WLAN, etc), PiNodes will directly interface with institutional LAN and provide updates through local networking and on local media systems.

Upon no emergency report but total network or power failure, PiNodes will assume authoritative control and make CDNs/Caching serve emergency domain communications describing the current network situation in plaintext degradation mode. It will transition to serving emergency situation reports the moment an emergency incident report is uploaded.

6.3 Graceful Degradation Model

IRONCLAD features a graceful degradation model to adaptively accommodate different networking and situational environments during emergencies. System behavior must be deterministic under failure conditions.

Full: Non-emergency operation, featuring standard designs and “No Alert” display. Contains relevant institutional information, including outbound links for maps, emergency phone numbers, and relevant emergency terminology.

Reduced: Activated upon emergency incident report. Themes are minimized and content focuses on emergency information only. Outbound links for emergency phone numbers and terminology are replaced with plaintext below-alert information sections. Sub 200KB MHTML size maximum.

Minimal: CSS is minimized, update stylization becomes planer, HTML only. Sub 50KB MHTML size maximum

Plaintext: **ALL** stylistic data is removed. Only plaintext incident report data, updates, and phone numbers are included. Content headers and blocks are simplified to plaintext barriers or are dropped entirely where redundant. Emergency terminology is simplified. Stale feed items are dropped.

---

7. Security & Abuse Considerations

General Posture:

Secure emergency incident reporting is critical for preventing abuse. Spoofing prevention and authenticity guarantees must be facilitated by secure auth systems for apps reporting emergency situations. Systems responsible for receiving and processing emergency reports must be isolated, hardened, and secured against spoofing-style abuse. Denial-of-service attacks must be mitigated without reducing user accessibility, with at minimum bot and malicious IP filtering.

Specific Applications:

Key concepts are applicable to the *IRONCLAD* framework to ensure local control plane defense. These include: application-layer filtering, behavioral blocking, kernel-level packet rejection, local static serving, and predefined application-layer filtering rules. API-schema style controls must also be implemented in communications between incident reporting and

infrastructure updating.

Security mechanisms must degrade in priority to accessibility and extreme conditions, ensuring no legitimate user access is blocked during emergencies.

---

8. Auditability & Post-Incident Review

As a public safety systems design, *IRONCLAD* implementations must be auditable and transparent, maximally reducing resistance for post-incident review. Telemetry and data collection must be balanced with directives including latency minimization and delivery guarantees. Therefore, it must remain largely CDN and DNS sided, with logs for HTTP errors, platforms, and receiving-device posture.

Key Data:

- Delivery success rates, problem devices and surfaces
- IP, ASN, and useragent collection for problem devices
- Incident and lifetime system-uptime figures
- HTTP logs

All data must be transparently available and archived on external infrastructure, with the exception of personally identifiable information. IP, ASN, and user agent information security is critical for preventing abuse and must therefore be available on valid request only. Auditability must not introduce additional latency or dependency in the critical communication path.

---

9. Limitations and Failure Conditions

Key limits and failure conditions exist in this iteration of *IRONCLAD*, with some mitigations present.

Limits:

Limited Immediate Information: Upon first reports of an incident, reported and experienced information may have gaps, or be controlled to verify legitimacy. This creates time windows where alerts may be present but those affected are unsure of personal situation specific actions to take. This limit may be mitigated by having the presence of general safety information by incident type and an incident severity level scaling with range and danger.

Non-Official Channel Use**:** During breaks in-between updates, or timeframes with limited incident information, alert recipients may use social media to bridge situational information gaps.

While this may be helpful for some, it may create misinformation, unfounded rumors, and implied non-official authority. This can be limited by including realistic and rigorously upheld update cadence time windows within alert update feeds.

Failure Conditions:

Infrastructure Destruction Scenarios: Destruction of standard compute units will cause heavy damage to *IRONCLAD* systems. Node-based infrastructure, CDNs, caching, and PiNode up-links do mitigate this

Power/Telecom Infrastructure Failure**:** Power and networking failures render key emergency alert delivery and backend systems inoperable. This is somewhat mitigated by the PiNode up-link system, however telecom outages with no SATCOM capability may completely disable *IRONCLAD* systems, reinforcing the need for satellite based edge-case networking.

---

10. Implementation Expectations

Recommended Critical Adoption

Configuration-Free Alerts: Guaranteeing institution-wide alert reception is critical for maximizing positive outcomes and life preservation during emergency incidents

Graceful Degradation: Alert system up-time and latency reduction is critical for quick thinking during emergency incidents.

Emergency Information Surface Guidelines: Clear, easy to understand information display is crucial for accessibility.

Remaining *IRONCLAD* system specs are **HIGHLY RECOMMENDED** as emergencies are rarely best-case scenarios. Institutional emergency systems must be adaptive, resilient, and *IRONCLAD* in response.

Testing Requirements

Testing as required by the local and federal legislature is crucial. Additional testing is encouraged due to system sensitivity. This includes: Pen-testing of security protocols, simulated standard node failure testing, degraded mode testing, regular individual node health logs and reports, and report system testing.

Public Accountability

The transparency architecture outlined in section 8 is critical for *IRONCLAD* implementations. These principles allow the biggest stakeholder of emergency situations, the public, to evaluate and understand systems which ensure their safety.

11. Potential Implementation Cases

Medium to large scale institutions with large property, high population, or remote locations will benefit significantly from *IRONCLAD* framework implementations. These include: Universities, Municipalities, Campuses, Large Enterprises, Remote Businesses, and Public Works.

12. Conclusion

Emergency communications systems are the first line of safety during emergency incidents. Outdated or improperly implemented emergency systems introduce preventable threats to life. These implementation inadequacies stem from systemic design flaws including: treating emergency communications as optional services, designing for ideal rather than extreme conditions, and operating without standardized, transparent assumptions.

IRONCLAD asserts a minimum engineering standard for emergency alert systems, bridging institutional implementation gaps through resilience-forward designs. It does not seek to redefine present emergency system architecture but rather reassert these standards as open, baseline institutional expectations. Failure in large-scale emergency communications systems design is ever-present, requiring strict design and transparency discipline for prevention.

IRONCLAD is a baseline design system, evaluating emergency communications as life-critical installations. Systems which do not attempt to guarantee *IRONCLAD* principles create real threats to safety for real people.

Appendices

Appendix A — Glossary

Core IRONCLAD Terms

IRONCLAD

A resiliency-oriented emergency communication system specification emphasizing redundancy, degraded operation, infrastructure independence, and universal reachability. IRONCLAD defines baseline engineering expectations for life-safety communication systems rather than introducing novel communication paradigms.

EIS (Emergency Information Surface)

A dedicated, authoritative communication domain for emergency updates, designed for:

- minimal latency
- high availability
- low bandwidth operation

The EIS provides structured, timestamped incident updates and serves as the primary source of truth for all emergency communications.

Structured Incident Reporting System

A controlled input system through which authorized personnel generate emergency alerts using standardized fields (timestamp, location, severity, instructions, update cadence). All system outputs are derived from this structure.

Broadcast Layer

The system layer responsible for immediate dissemination of simplified emergency alerts through multiple parallel channels (email, SMS, app push, institutional systems, social media).

Degraded Mode Operation

A system state in which functionality is preserved while presentation, interactivity, and data weight are reduced to maintain availability under failure conditions.

Graceful Degradation

The controlled reduction of system fidelity (e.g., full → reduced → minimal → plaintext) without complete service loss. IRONCLAD systems degrade representation rather than availability.

Degraded Infrastructure Mode

A specific operational state triggered by infrastructure stress (traffic surge, CDN failure, network instability), where the system transitions to ultra-lightweight content delivery (e.g., plaintext NGINX endpoint).

Fallback Layer

An independent system layer that assumes operational responsibility during cascade failure, ensuring continuity of emergency communications.

Low-Power Layer (“Last Known Good Option”)

A battery-backed, network-independent fallback system (e.g., PiNodes) capable of serving cached emergency content and assuming authoritative control during complete infrastructure failure.

Persistence & Archive Layer

An externalized storage system for incident logs, updates, and system telemetry, enabling transparency, auditability, and post-incident analysis.

System Performance & Reliability Terms

Delivery Latency

The time difference between when emergency information is issued and when it is received and understood by the majority of affected individuals.

Reachability

The proportion of impacted individuals who successfully receive emergency communications relative to the total affected population.

Delivery Guarantee

The system’s ability to maintain near-continuous availability and successful information delivery under varying conditions.

High Traffic Surge Conditions

Periods of abnormal concurrent access to emergency systems, typically during active incidents, resulting in potential infrastructure strain.

Cascade Failure

A sequence of interdependent system failures where one failure amplifies others, leading to total system disruption.

Infrastructure Independence

The architectural principle of isolating emergency communication systems from standard institutional infrastructure to prevent shared failure modes.

Redundancy

The inclusion of multiple independent systems or nodes performing similar functions to ensure continuity during partial failure.

Information Design & Communication Terms

Information Resolution

The level of specificity, clarity, and actionable detail present in emergency communications. Low information resolution results in ambiguity and unsafe decision-making.

Information Resolution Failure

A condition in which given emergency information lacks sufficient detail for safe and informed decision-making.

Update Cadence

The expected frequency and timing of emergency information updates, providing transparency and reducing reliance on unofficial channels.

Priority Encoding

The representation of incident severity and urgency through structured indicators (e.g., threat level, message type, escalation level).

Minimal Cognitive Load

A design principle ensuring emergency information is easily interpretable under stress, requiring minimal effort to understand and act upon.

Non-Truth Assertion (Social Media)

The design constraint that social media channels must not be treated as authoritative sources of emergency information, but instead serve as redirection mechanisms to official channels.

Technical & Infrastructure Terms

CDN (Content Delivery Network)

A distributed network of servers used to cache and deliver content efficiently across geographic regions, reducing load on origin infrastructure.

RAMDISK

A memory-based storage system used for ultra-fast read/write operations, enabling low-latency content serving during high-load conditions.

NGINX

A high-performance web server often used for static content delivery and reverse proxying. In IRONCLAD, it is used for plaintext degraded-mode endpoints.

Plaintext Endpoint

A minimal data representation of emergency information, devoid of styling or scripting, designed for:

- low-bandwidth environments
- CLI access
- high reliability

CLI (Command Line Interface)

A text-based interface allowing users or systems to retrieve and interact with data using commands (e.g., curl).

curl

A command-line tool used to retrieve data from URLs, commonly used to access plaintext endpoints in degraded mode.

RSS / JSON Feed

Machine-readable formats for structured data distribution, enabling automated systems and integrations to consume emergency updates.

API (Application Programming Interface)

A structured interface allowing systems to communicate and exchange data programmatically.

API-Schema Controls

Validation and structural enforcement mechanisms ensuring all incident data conforms to predefined formats before being distributed.

Kernel-Level Packet Filtering

Low-level network filtering mechanisms that drop malicious or unnecessary traffic before it reaches application-level processing.

Security & Governance Terms

Spoofing

Unauthorized impersonation of a legitimate system or user, potentially resulting in false emergency alerts.

Authentication

The process of verifying the identity of a user or system before granting access to critical functions such as alert origination.

Authorization

The assignment of permissions determining what actions a verified user or system is allowed to perform.

Denial-of-Service (DoS) Attack

An attempt to overwhelm a system with excessive traffic, rendering it unavailable to legitimate users.

Behavioral Blocking

A security mechanism that identifies and restricts malicious activity based on observed behavior patterns rather than static rules.

Application-Layer Filtering

Traffic filtering performed at the application level (e.g, HTTP requests), often used to block malicious or malformed requests.

Operational & Contextual Terms

Emergency Event

An occurrence outside normal operational conditions requiring immediate communication and action.

User State Variability

Differences in user device condition, connectivity, attention, and environment that affect message reception and comprehension.

Zero User Preconfiguration

The requirement that emergency communication systems function without prior user setup, installation, or enrollment.

Adversarial Conditions

Situations involving malicious interference, misinformation, or intentional disruption of system operation.

Life-Critical Infrastructure

Systems whose failure directly threatens human safety and survival, requiring strict reliability and resilience guarantees.

Situational Awareness

The understanding of environmental conditions, risks, and required actions during an emergency, enabled by timely and accurate information.

Appendix B — Reference Architecture Diagram



Appendix C — Suggested Hardware Configurations

This appendix outlines reference hardware configurations in alignment with *IRONCLAD* design principles. Listed configurations are intended to serve as minimal capability classes required to meet resilience, redundancy, and degraded operation requirements. These are not definitive hardware assertions or professional opinion but feasible and defensible *IRONCLAD* aligned configurations.

C.1 Core Design Principles

- No complete, closed system failure mode at a single point
- Independence from primary institutional hardware
- Ability to operate under degraded or extreme network conditions
- Fast static content delivery, SSD or RAMDISK backed
- Low power fallback capability with command up-link
- High horizontal scalability, minimal vertical integrations

C.2 Primary Infrastructure Nodes

Standard Emergency Infrastructure Nodes:

- Serve emergency information services
- Take broadcast triggers and updates from emergency incident reports
- Provide outbound APIs and endpoints for institutional media hardware, curl, and RSS/JSON feeds
- Update external CDN and Caching upon incident report, update, or all-clear

Suggested Node Baseline Specifications:

- CPU: Modern Multi-Core (4-8 Cores)
- RAM: 8-16GB
- Storage: NVMe SSD (>=256GB)
- Networking ~= 1Gbps uplink

Critical Node Functions:

- Low bandwidth static-first serving (NGINX or equivalent)
- RAMDISK Caching during incident reports or network surges
- Health monitoring with failover capabilities
- Node mesh awareness (Clustered Deployment)

Deployment Model:

- >= 3 nodes minimum
- Geographically distributed
- Fronted by external CDN / caching system

Degraded Mode Standard Node Behavior

- Serve plaintext endpoint:
    - <10KB response size
    - No JavaScript or Telemetry
    - Minimized or eliminated CSS
- Any standard node must be able to:
    - Drop to degraded mode
    - Serve plaintext endpoint immediately
    - Update external CDN / Caching upon graceful degradation mode switch

C.3 Low-Power Fallback System

Low-Power "*Last Known Good Option*" systems

Must be fully operable during:

- Full infrastructure failure
- Power disruptions
- Network disruptions

Suggested Hardware Class:
- Single-Board Computers (e.g, Raspberry PI adjacent devices)
- Low-power x86 mini systems also acceptable

Minimum System Capabilities:
- 4-8GB RAM
- SSD Storage
- Battery backup: UPS or Integrated Pack
- Independent networking capacity:
    - LTE modem or SIM integration
    - Optional SATCOM (Recommended)

Required Functionality:
- Host emergency pages after updates, CLI/Plaintext ONLY
- Monitor standard emergency communication node health
- Assume primary system authority after critical standard node failure:
    - Receive Incident reports, updates
    - Overwrite external CDN and Cache data
- Maintain emergency communications broadcasting

Fallback systems must be capable of operating independent of primary infrastructure or centralized authentication systems

C.4 Network Connectivity Considerations
- Redundant uplinks preferred
- External CDN / Caching integration optional but **HIGHLY recommended**
- Direct IP fallback endpoints encouraged
- DNS independence considerations
    - Optional local security node in standard and fallback infrastructure

C.5 Scaling Considerations
- Horizontal scaling preferred
- Stateless serving model recommended
- External CDN/Caching reduces compute requirements during traffic surges
- System should scale based on concurrent read load, not write complexity

Appendix D — Future Research Directions

D.1 Authentication & Authorization Integration

- Integration with:
  - Azure AD
  - Google Workspace
  - institutional SSO
- Ensuring:
  - secure alert origination
  - role-based permissions
  - minimal friction during emergencies

D.2 Security Hardening & Abuse Prevention

- Local defensive control plane:
  - application-layer filtering
  - behavioral blocking
  - kernel-level packet filtering
- Protection against:
  - spoofed alerts
  - DoS attacks
  - unauthorized system access

D.3 Real-World Deployment & Engineering Validation

- Latency benchmarking
- Failure simulation testing
- Load testing under surge conditions
- Campus-scale deployment modeling

D.4 Human Factors & Communication Design

- Message clarity under stress
- Accessibility considerations
- Multilingual delivery
- Cognitive load minimization

D.5 Infrastructure Independence & Decentralization

- DNS independence models
- CDN independence
- Peer-to-peer or mesh-based fallback systems
- Offline-first communication models

D.6 Broadcast Channel Optimization

- SMS policy constraints
- Push notification reliability
- Email delivery guarantees
- Integration with public alert systems (e.g, government alerts)

D.7 Automated Incident Structuring

- Templated reporting systems
- Semi-automated alert generation
- AI-assisted classification (carefully scoped and controlled)

D.8 Auditability & Transparency Systems

- Public incident logs
- Tamper-resistant records
- Timeline reconstruction tools

D.9 Hardware Optimization & Edge Deployment

- Optimizing PiNode systems
- Ultra-low-power deployments
- Campus-wide edge devices

Appendix E — Access, Distribution, and Author Contact

E.1 Document Access

This whitepaper is publicly accessible and may be distributed under the Creative Commons Attribution 4.0 International (CC BY 4.0) license.

Readers are encouraged to discuss and contribute. See E.3 for author contact information.

Latest version:
https://github.com/Bitcrusher32/IRONCLAD/
https://git.bitcrusher32.win/bitcrusher32/IRONCLAD/

Supporting materials:
- Reference Architecture Diagram
- Executive Summary (1-page)

E.2 Versioning and Access

This document is subject to iteration and refinement.

Future revisions may include:
- implementation case studies
- deployment validation results
- expanded system modeling

Readers are encouraged to reference the latest available version.

E.3 Author Contact and Information

Author: Udaiveer Singh Bhangu - Electrical Engineering 2nd Year at The University of Ottawa
Contact: ubhan095@uOttawa.ca
LinkedIn: https://www.linkedin.com/in/udaiveer-bhangu-aa872a275/
Portfolio: Bitcrusher32.Win/Portfolio

E.4 Intended Use, Collaboration, and Citation

This document is intended as a systems-level reference for the public, institutions, engineers, and organizations seeking to improve emergency communication infrastructure.

Feedback, critique, and collaboration are welcomed.

Institutions interested in evaluating or adapting *IRONCLAD* principles are encouraged to reach out, or privately iterate on this framework.

When referencing this work please use:
Bhangu, U.S. (2026). IRONCLAD: A Resiliency-Oriented Emergency Alert System Specification.