JBK Portal nightly backup: server setup

Step-by-step for the office server (Windows). About an hour the first time. Updated Oct 13, 2026.

What this sets up. Every night at 2:00 AM the server copies everything in the portal (every table plus every photo, signature, receipt, invoice PDF and takeoff plan) into one folder on the X: drive. Two nights are kept; a Sunday copy of the tables is kept for five weeks. The script only reads from the portal and can never change it.

You need: (1) the backup password you already made (the one saved in Lovable as `BACKUP_SECRET`), (2) a login on the server that can create folders and users (an administrator), (3) the portal address: `https://jbkbid.lovable.app`.

---

1 Check the password is live in Lovable

Your own PC, in a browser

1. Lovable → open the JBK Portal project → **Cloud** → **Secrets**. Confirm a secret named `BACKUP_SECRET` is listed. It must be at least 24 characters.
2. Click **Publish** (top right) and let it finish. A secret only reaches the running portal after a publish. If you have published since adding it, you are done here.

---

2 Put the script on the server

On the server, logged in as an administrator

1. Log on to the server at its screen or by Remote Desktop.
2. Open File Explorer and create the folder `C:\JBK\backup`.
3. In a browser on the server, open `https://github.com/Bkezk/roof-estimator-shell/tree/main/scripts/backup` and save these three files into `C:\JBK\backup`. For each: click the file name → click **Raw** → right-click the page → **Save as**. Make sure the saved name has no extra `.txt` on the end.
   - `jbk-backup.ps1` (the nightly backup)
   - `jbk-backup.config.example.json` (the settings template)
   - `jbk-restore.ps1` (the restore; only used if data is ever lost)
4. Right-click `jbk-backup.ps1` → **Properties** → tick **Unblock** at the bottom → OK. Do the same for `jbk-restore.ps1`. Windows marks downloaded scripts as blocked; this clears it.

---

3 Make the backup folder on the X: share

On the server

1. Find the share's real folder on the server: in File Explorer right-click the folder that is shared as X: ("JBK Community") → **Properties** → **Sharing**. The **local path** is shown there, for example `D:\Shares\JBK Community`. Write it down.
2. Inside that folder create a new folder named `JBK Portal Backups`.

Use the local path, not the X: letter, in the next step. Scheduled tasks run without mapped drives, so `X:\` would fail at 2:00 AM.

4 Fill in the settings file

On the server

1. In `C:\JBK\backup`, copy `jbk-backup.config.example.json` and rename the copy to `jbk-backup.config.json` (drop the word `example`).
2. Right-click the new file → **Open with** → **Notepad**. Change only the first three lines so they read like this, keeping the quotes and commas:

```
"DestinationRoot": "D:\\Shares\\JBK Community\\JBK Portal Backups",
"AppUrl": "https://jbkbid.lovable.app",
"BackupSecret": "the backup password you made",
```

- Every backslash in the path is typed twice (`\\`). That is required in this file type.
- Leave the `RestoreSecret` line and everything below it as they are.
- Save and close. This file holds the password, so it stays on the server only (step 6 locks the folder).

5 Run it by hand and check the result

On the server, PowerShell

1. Click Start, type **PowerShell**, open **Windows PowerShell**.
2. Type these three lines, pressing Enter after each. The last one is a trial run: it fetches everything but does not count as a backup.

```
Set-ExecutionPolicy -Scope Process Bypass
cd C:\JBK\backup
.\jbk-backup.ps1 -DryRun
```

3. Watch for lines like `Tables: 81, rows: 12,345`, `Bucket service: … files` and finally `Finished: OK`.
4. Open the backup folder from step 3. There is a folder starting with `_incoming-`. Open `db\bids\page-0001.json` in Notepad and confirm real bid names are in it. Then delete the `_incoming-` folder yourself (the trial run leaves it for you to inspect).
5. Now run it for real, twice, so both nightly slots exist:

```
.\jbk-backup.ps1
.\jbk-backup.ps1
```

You should now see two folders named `backup-2026-10-13` style dates (the second run reuses files already copied, so it is faster) and a `status.json` that contains `"ok": true`.

If you see	It means
`401 (Unauthorized)`	The password in the config and the one in Lovable differ, or the portal was not published after the secret was added. Fix, Publish, run again.
`500` with `BACKUP_SECRET is not set`	The secret is missing in Lovable Cloud → Secrets.
Cannot find path / DestinationRoot	The path in the config does not exist or a backslash is not doubled.
`LAST-BACKUP-FAILED.txt` appears	The run failed. `backup.log` in the backup folder says why. Earlier backups are untouched.

6 Make a service account and lock the folders

On the server, as administrator

The nightly task should run as a plain account, not yours, and only you and that account should read the two folders.

1. Right-click Start → **Computer Management** → **Local Users and Groups** → **Users** → right-click → **New User**. User name `backup-svc`, a long password (save it in your password manager), tick **Password never expires**, untick **User must change password**. Create. Do **not** add it to Administrators.
2. Click Start, type **PowerShell**, right-click it → **Run as administrator**. Paste the two lines below after editing them: replace `SERVER\braden` with your own login (if the server is in a domain, write it as `DOMAIN\yourname`) and the second path with the one from step 3.

```
icacls "C:\JBK\backup" /inheritance:r /grant:r "SERVER\braden:(OI)(CI)F" "backup-svc:(OI)
(CI)RX" "SYSTEM:(OI)(CI)F" "Administrators:(OI)(CI)F"
icacls "D:\Shares\JBK Community\JBK Portal Backups" /inheritance:r /grant:r "SERVER\brade
n:(OI)(CI)F" "backup-svc:(OI)(CI)M" "SYSTEM:(OI)(CI)F" "Administrators:(OI)(CI)F"
```

F = full control, M = modify, RX = read and run. Each command ends with "Successfully processed 1 files". Other staff who use X: can no longer open the backup folder, which is the point.

7 Schedule it for 2:00 AM every night

On the server

1. Click Start, type **Task Scheduler**, open it. In the right-hand pane click **Create Task** (not "Create Basic Task").
2. Fill in each tab as below, then click OK and enter the `backup-svc` password when asked.

Tab	Settings
General	Name `JBK Portal nightly backup`. Select **Run whether user is logged on or not**. Click **Change User or Group** and pick `backup-svc`. Leave **Run with highest privileges** unticked.
Triggers	**New** → Daily → Start at **2:00:00 AM** → Recur every 1 day → OK.
Actions	**New** → Action: Start a program. Program/script: `powershell.exe` Add arguments: `-NoProfile -ExecutionPolicy Bypass -File "C:\JBK\backup\jbk-backup.ps1"`
Conditions	Untick **Start the task only if the computer is on AC power**. Tick **Wake the computer to run this task**.
Settings	Tick **Run task as soon as possible after a scheduled start is missed**. Set **Stop the task if it runs longer than** 4 hours. Tick **If the task fails, restart every** 30 minutes, up to 2 times.

3. Test it now: in the task list, right-click **JBK Portal nightly backup** → **Run**. After a minute or two, open `status.json` in the backup folder and confirm `"ok": true` with today's time. In Task Scheduler, **Last Run Result** should read `0x0`.

8 Keeping an eye on it

Once a week, 30 seconds

- Open `JBK Portal Backups` on X:. Two `backup-…` folders with recent dates and **no** `LAST-BACKUP-FAILED.txt` means all is well.
- If `LAST-BACKUP-FAILED.txt` is there, open `backup.log`; the last lines say what went wrong. The two earlier backups are never touched by a failed night.
- Nothing here changes when the portal is updated: the script asks the portal each night which tables and file buckets exist, so new ones are included automatically.

9 Optional now, needed before any restore

Your PC and the server

Restoring uses a **second** password that lets the portal write. Set it up whenever you like, or only on the day you need it:

1. Make up a different password, at least 24 characters. Lovable → Cloud → Secrets → add `RESTORE_SECRET` with that value. Publish.
2. On the server, edit `C:\JBK\backup\jbk-backup.config.json` and put the same value in the `"RestoreSecret"` line.
3. Try the harmless check (it writes nothing): in PowerShell in `C:\JBK\backup` run `.\jbk-restore.ps1 -Slot latest -Project x`. It prints the portal's real project label and stops. The full restore instructions are in the repository under `docs/backup/windows-server-setup.md`, Step 8.