

Working with Data in Python Cheat Sheet

Reading and writing files

Package/Method Description	
File opening modes	<div>Different modes to open files for specific operations.</div> <div>Syntax: r (reading) w (writing) a (appending) + (updating: read/write) b (binary, otherwise text)</div> <div><div>1. 1</div><div>1. Examples: with open("data.txt", "r") as file: content = file.read() print(content) with open("output.txt",</div><div>Copied!</div></div>
	<div>Syntax:</div> <div><div>1. 1</div><div>2. 2</div><div>3. 3</div></div> <div><div>1. file.readlines() # reads all lines as a list</div><div>2. readline() # reads the next line as a string</div><div>3. file.read() # reads the entire file content as a string</div></div>
File reading methods	<div>Different methods to read file content in various ways.</div> <div><div>Copied!</div><div>Example:</div><div><div>1. 1</div><div>2. 2</div><div>3. 3</div><div>4. 4</div></div><div><div>1. with open("data.txt", "r") as file:</div><div>2. lines = file.readlines()</div><div>3. next_line = file.readline()</div><div>4. content = file.read()</div></div><div>Copied!</div></div>
	<div>Syntax:</div> <div><div>1. 1</div><div>2. 2</div></div> <div><div>1. file.write(content) # writes a string to the file</div><div>2. file.writelines(lines) # writes a list of strings to the file</div></div>
File writing methods	<div>Different write methods to write content to a file.</div> <div><div>Copied!</div><div>Example:</div><div><div>1. 1</div><div>2. 2</div><div>3. 3</div></div><div><div>1. lines = ["Hello\n", "World\n"]</div><div>2. with open("output.txt", "w") as file:</div><div>3. file.writelines(lines)</div></div><div>Copied!</div></div>
	<div>Syntax:</div> <div><div>1. 1</div></div> <div><div>1. for line in file: # Code to process each line</div></div>
Iterating over lines	<div>Iterates through each line in the file using a `loop`.</div> <div><div>Copied!</div><div>Example:</div><div><div>1. 1</div><div>2. 2</div></div><div><div>1. with open("data.txt", "r") as file:</div><div>2. for line in file: print(line)</div></div><div>Copied!</div></div>
	<div>Syntax:</div> <div><div>1. 1</div><div>2. 2</div></div>
Open() and close()	<div>Opens a file, performs operations, and explicitly closes the file using the close() method.</div> <div><div>Copied!</div><div>Example:</div><div><div>1. 1</div><div>2. 2</div><div>3. 3</div></div><div><div>1. file = open("data.txt", "r")</div><div>2. content = file.read()</div><div>3. file.close()</div></div><div>Copied!</div></div>

Syntax:

1. 1

1. with open(filename, mode) as file: # Code that uses the file

Opens a file using a with block, ensuring automatic file closure after usage.

Example:

1. 1
2. 2

1. with open("data.txt", "r") as file:
2. content = file.read()

Copied!

Pandas

Package/Method	Description	Syntax and Code Example
.read_csv()	Reads data from a `CSV` file and creates a DataFrame.	<p>Syntax: dataframe_name = pd.read_csv("filename.csv") Example: df = pd.read_csv("data.csv")</p> <p>Syntax:</p> <p>1. 1</p> <p>1. dataframe_name = pd.read_excel("filename.xlsx")</p> <p>Copied!</p>
.read_excel()	Reads data from an Excel file and creates a DataFrame.	<p>Example:</p> <p>1. 1</p> <p>1. df = pd.read_excel("data.xlsx")</p> <p>Copied!</p> <p>Syntax:</p> <p>1. 1</p> <p>1. dataframe_name.to_csv("output.csv", index=False)</p> <p>Copied!</p>
.to_csv()	Writes DataFrame to a CSV file.	<p>Example:</p> <p>1. 1</p> <p>1. df.to_csv("output.csv", index=False)</p> <p>Copied!</p> <p>Syntax:</p> <p>1. 1 2. 2</p> <p>1. dataframe_name["column_name"] # Accesses single column 2. dataframe_name[["column1", "column2"]] # Accesses multiple columns</p> <p>Copied!</p>
Access Columns	Accesses a specific column using [] in the DataFrame.	<p>Example:</p> <p>1. 1 2. 2</p> <p>1. df["age"] 2. df[["name", "age"]]</p> <p>Copied!</p> <p>Syntax:</p> <p>1. 1</p> <p>1. dataframe_name.describe()</p> <p>Copied!</p>
describe()	Generates statistics summary of numeric columns in the DataFrame.	<p>Example:</p> <p>1. 1</p> <p>1. df.describe()</p> <p>Copied!</p>
drop()	Removes specified rows or columns from the DataFrame. axis=1 indicates columns. axis=0 indicates rows.	<p>Syntax:</p> <p>1. 1 2. 2</p> <p>1. dataframe_name.drop(["column1", "column2"], axis=1, inplace=True) 2. dataframe_name.drop(index=[row1, row2], axis=0, inplace=True)</p> <p>Copied!</p> <p>Example:</p>

		<pre>1. 1 2. 2 1. df.drop(["age", "salary"], axis=1, inplace=True) # Will drop columns 2. df.drop(index=[5, 10], axis=0, inplace=True) # Will drop rows</pre> <div>Copied!</div> <p>Syntax:</p> <pre>1. 1 1. dataframe_name.dropna(axis=0, inplace=True)</pre>
dropna()	Removes rows with missing NaN values from the DataFrame. axis=0 indicates rows.	<div>Copied!</div> <p>Example:</p> <pre>1. 1 1. df.dropna(axis=0, inplace=True)</pre> <div>Copied!</div> <p>Syntax:</p> <pre>1. 1 1. dataframe_name.duplicated()</pre>
duplicated()	Duplicate or repetitive values or records within a data set.	<div>Copied!</div> <p>Example:</p> <pre>1. 1 1. duplicate_rows = df[df.duplicated()]</pre> <div>Copied!</div> <p>Syntax:</p> <pre>1. 1 1. filtered_df = dataframe_name[(Conditional_statements)]</pre>
Filter Rows	Creates a new DataFrame with rows that meet specified conditions.	<div>Copied!</div> <p>Example:</p> <pre>1. 1 1. filtered_df = df[(df["age"] > 30) & (df["salary"] < 50000)]</pre> <div>Copied!</div> <p>Syntax:</p> <pre>1. 1 2. 2 1. grouped = dataframe_name.groupby(by, axis=0, level=None, as_index=True, 2. sort=True, group_keys=True, squeeze=False, observed=False, dropna=True)</pre>
groupby()	Splits a DataFrame into groups based on specified criteria, enabling subsequent aggregation, transformation, or analysis within each group.	<div>Copied!</div> <p>Example:</p> <pre>1. 1 1. grouped = df.groupby(["category", "region"]).agg({"sales": "sum"})</pre> <div>Copied!</div> <p>Syntax:</p> <pre>1. 1 1. dataframe_name.head(n)</pre>
head()	Displays the first n rows of the DataFrame.	<div>Copied!</div> <p>Example:</p> <pre>1. 1 1. df.head(5)</pre> <div>Copied!</div> <p>Syntax:</p> <pre>1. 1 1. import pandas as pd</pre>
Import pandas	Imports the Pandas library with the alias pd.	<div>Copied!</div> <p>Example:</p> <pre>1. 1 1. import pandas as pd</pre> <div>Copied!</div>

		<div>Syntax:<div>1. 1</div><div>1. dataframe_name.info()</div></div> <div>Copied!</div>
info()	Provides information about the DataFrame, including data types and memory usage.	<div>Example:<div>1. 1</div><div>1. df.info()</div></div> <div>Copied!</div>
merge()	Merges two DataFrames based on multiple common columns.	<div>Syntax:<div>1. 1</div><div>1. merged_df = pd.merge(df1, df2, on=["column1", "column2"])</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. merged_df = pd.merge(sales, products, on=["product_id", "category_id"])</div></div> <div>Copied!</div>
print DataFrame	Displays the content of the DataFrame.	<div>Syntax:<div>1. 1</div><div>1. print(df) # or just type df</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>2. 2</div><div>1. print(df)</div><div>2. df</div></div> <div>Copied!</div>
replace()	Replaces specific values in a column with new values.	<div>Syntax:<div>1. 1</div><div>1. dataframe_name["column_name"].replace(old_value, new_value, inplace=True)</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. df["status"].replace("In Progress", "Active", inplace=True)</div></div> <div>Copied!</div>
tail()	Displays the last n rows of the DataFrame.	<div>Syntax:<div>1. 1</div><div>1. dataframe_name.tail(n)</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. df.tail(5)</div></div> <div>Copied!</div>

Numpy

Package/Method	Description	Syntax and Code Example
Importing NumPy	Imports the NumPy library.	<div>Syntax:<div>1. 1</div><div>1. import numpy as np</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. import numpy as np</div></div> <div>Copied!</div>
np.array()	Creates a one or multi-dimensional array.	<div>Syntax:<div>1. 1</div></div>

```
2. 2

1. array_1d = np.array([list1 values]) # 1D Array
2. array_2d = np.array([[list1 values], [list2 values]]) # 2D Array
```

Copied!

Example:

```
1. 1
2. 2

1. array_1d = np.array([1, 2, 3]) # 1D Array
2. array_2d = np.array([[1, 2], [3, 4]]) # 2D Array
```

Copied!

Example:

```
1. 1
2. 2
3. 3
4. 4
5. 5

1. np.mean(array)
2. np.sum(array)
3. np.min(array)
4. np.max(array)
5. np.dot(array_1, array_2)
```

Copied!

- Numpy Array Attributes
- Calculates the mean of array elements
 - Calculates the sum of array elements
 - Finds the minimum value in the array
 - Finds the maximum value in the array
 - Computes dot product of two arrays



Skills Network

© IBM Corporation. All rights reserved.