

Product Specifications



P608306

AIR FILTER, PRIMARY RADIALSEAL

Why Choose Donaldson RadialSeal™ Filters?

Reliable, leak- resistant Radial Seal™ keeps filters in place – even under heavy vibration.

- High-efficiency cellulose media performs across a wide range of heavy-duty engine applications.
- Corrosion resistant, coated steel liners support media during operation and help maximize airflow.
- Pleatloc™ feature ensures uniform pleat spacing and prevents media from bunching to promote longer service life.

Attributes

Outer Diameter	17.76 inch (451 mm)
Inner Diameter	11.46 inch (291.1 mm)
Length	24.06 inch (611.1 mm)
Efficiency	99.9
Efficiency Test Std	ISO 5011
Family	SSG
Primary Application	This is the standard version to the P187152
Туре	Primary
Style	Radialseal

Brand	RadialSeal™
Media Type	Cellulose
Packaged Dimensions	
Packaged Length	19.1 IN
Packaged Width	18.7 IN
Packaged Height	25.6IN
Packaged Weight	22.365 LB
Packaged Volume	5.2914 FT3

Other Information

Country of Origin	United States
NMFC Code	069100-05
HTS Code	8421310000
UPC Code	742330170953

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.