THE CALLBACKS

`love.load(args)` Run once when the game starts.
`love.update(dt)` Used to update the game's state.
`love.draw()` Used to draw to the screen.
`love.quit()` Run when the game is quit.
Return true to cancel quitting.
`love.focus(focused)`
Run when the window gains/loses focus.

THE KEYBOARD

Callbacks

```
love.keypressed(key, unicode)
love.keyreleased(key, unicode)
```

Module love.keyboard

```
isDown(key1, ...)
delay, interval = getKeyRepeat()
setKeyRepeat(delay, interval)
```

THE MOUSE

Callbacks

```
love.mousepressed(x, y, button)
love.mousereleased(x, y, button)
```

Module love.mouse

```
x, y = getPosition()
getX() getY()
isDown(button1, ...)
isGrabbed()
isVisible()
setGrab(grab)
setPosition(x, y)
setVisible(visible)
```

Enum MouseConstant



AUDIO

Module love.audio

```
pause()                          pause(source)
                                 play(source)
resume()                         resume(source)
rewind()                         rewind(source)
stop()                           stop(source)
getNumSources()
newSource(file, type)
newSource(data)
newSource(decoder, type)
```

Getters/Setters (prefix names with "get" or "set")

```
Orientation(fx, fy, fz, ux, uy, uz)
Position(x, y, z)
Velocity(x, y, z)
Volume(volume)
```

MODULE LOVE.GRAPHICS

Drawing

```
draw(drawable, x, y, r, sx, sy, ox, oy)
drawq(img, quad, x, y, r, sx, sy,ox,oy)
```

New Objects (prefix names with "new")

```
Font(filename, size) Font(size)
Framebuffer(width, height)
Image(filename) Image(file) Image(data)
ImageFont(imageOrFilename, glyphs)
ParticleSystem(image, buffer)
Quad(x, y, width, height, sw, sh)
Screenshot() -- returns ImageData
SpriteBatch(image, size)
```

Text/Shapes

```
print(text, x, y, r, sx, sy)
printf(text, x, y, limit, align)
circle(mode, x, y, radius, segments)
line(x1, y1, x2, y2, ...)
point(x, y)
polygon(mode, ...)
quad(mode, x1, y2, x2, y2, x3,y3,x4,y4)
rectangle(mode, x, y, width, height)
triangle(mode, x1, y1, x2, y2, x3, y3)
```

Transformations

```
push() pop()
translate(dx, dy)
rotate(angle)
scale(sx, sy)
```

Getters/Setters (prefix names with "get" or "set")

```
BackgroundColor(r, g, b)
Color(r, g, b, a)
Font(font) Font(file, size) Font(size)
Icon(drawable)
Mode(w, h, fullscreen, vsync, fsaa)
```

MODULE LOVE.TIMER

```
getDelta()                       getFPS()
getMicroTime()                   getTime()
sleep(milliseconds)
step()
```

Class Source

```
play() resume() pause() stop() rewind()
isLooping() isStatic() isStopped()
```

Getters/Setters (prefix names with "get" or "set")

```
Looping(loop)
Pitch(pitch)
Position(x, y, z)
Velocity(x, y, z)
Volume(volume)
```

Enum SourceType

`static` Decode the entire sound at once.
`stream` Decode the sound gradually.

FILESYSTEM

Module love.filesystem

```
enumerate(dir)
exists(filename)
isDirectory(filename)
isFile(filename)
iterator       = lines(filename)
chunk          = load(filename)
ok             = mkdir(name)
contents, size = read(filename, size)
ok             = remove(filename)
ok             = write(filename, data, size)
```

New Objects

```
newFile(filename)
newFileData(contents, name, decoder)
```

Getters/Setters

```
getAppdataDirectory()
modtime, errormsg = getLastModified(name)
getSaveDirectory()
getUserDirectory()
getWorkingDirectory()
setIdentity(name)
```

Class File

```
ok         = close()
eofReached = eof()
iterator   = lines()
ok         = open(mode)
contents   = read(bytes)
ok         = seek(pos)
pos        = tell()
ok         = write(data)
getSize()
```

Enum FileMode

`r` Allows you to (only) read from a file.
`w` Allows you to (only) write to a file.
`a` Same as `w` but data is appended to the end of file.

GRAPHICS CLASSES AND ENUMS

Class Font

```
getHeight()
getWidth(text)
getLineHeight()
setLineHeight(height)
```

Class Framebuffer

```
getImageData()
renderTo(func)
```

Class Image

```
min, mag = getFilter()
getHeight()
getWidth()
horiz, vert = getWrap()
setFilter(min, mag)
setWrap(horiz, vert)
```

Class Quad

```
flip(flipX, flipY)
x, y, w, h = getViewport()
setViewport(x, y, w, h)
```

Class SpriteBatch

```
add(x, y, r, sx, sy, ox, oy)
addq(quad, x, y, r, sx, sy, ox, oy)
clear()
```

Enum BlendMode

```
additive
alpha
subtractive
multiplicative
```

Enum ColorMode

`modulate` Images (etc) are affected by the current color.
`replace` Opposite of `modulate`.

Enum DrawMode

`fill` Draw filled shape.
`line` Draw outlined shape.