

DICTIONNAIRE DE DONNÉES

HAUQE Certif - Base nationale des entreprises certifiées

66	843	107
tables	colonnes	clés étrangères

Ce document décrit les tables, colonnes, types PostgreSQL, clés et relations du modèle rationalisé HAUQE Certif. PK = clé primaire, FK = clé étrangère, UQ = valeur unique et NN = valeur obligatoire.

Version 0.3 - Document de travail à valider par la HAUQE/GFA

1. utilisateurs

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
email	VARCHAR(255)	UQ, NN
mot_de_passe_hash	VARCHAR(255)	—
nom	VARCHAR(255)	—
prenoms	VARCHAR(255)	—
telephone	VARCHAR(255)	—
fonction	VARCHAR(255)	—
region_affectation_id	UUID	FK → zones_administratives.id, facultatif
statut	VARCHAR(255)	—
mfa_active	BOOLEAN	—
derniere_connexion_at	TIMESTAMPTZ	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

2. roles

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	UQ, NN
libelle	VARCHAR(255)	—
description	TEXT	—
niveau	INTEGER	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

3. permissions

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	UQ, NN
domaine	VARCHAR(255)	—
action	VARCHAR(255)	—
description	TEXT	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

4. utilisateur_role

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
utilisateur_id	UUID	FK → utilisateurs.id, NN
role_id	UUID	FK → roles.id, NN
date_debut	DATE	—
date_fin	DATE	—
attribue_par_id	UUID	FK → utilisateurs.id, NN
motif	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

5. role_permission

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
role_id	UUID	FK → roles.id, NN
permission_id	UUID	FK → permissions.id, NN
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

6. sessions_utilisateur

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
utilisateur_id	UUID	FK → utilisateurs.id, NN
jeton_hash	VARCHAR(255)	—
adresse_ip	VARCHAR(255)	—
user_agent	VARCHAR(255)	—
debut_at	TIMESTAMPTZ	—
derniere_activite_at	TIMESTAMPTZ	—
expiration_at	TIMESTAMPTZ	—
revoquee_at	TIMESTAMPTZ	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

7. zones_administratives

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
parent_id	UUID	FK → zones_administratives.id, facultatif
type_zone	VARCHAR(255)	—
code	VARCHAR(255)	—
nom	VARCHAR(255)	—
latitude	NUMERIC(18,4)	—
longitude	NUMERIC(18,4)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

8. referentiels

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	UQ, NN
libelle	VARCHAR(255)	—
description	TEXT	—
type_valeur	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

9. valeurs_referentiel

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
referentiel_id	UUID	FK → referentiels.id, NN
parent_id	UUID	FK → valeurs_referentiel.id, facultatif
code	VARCHAR(255)	—
libelle	VARCHAR(255)	—
description	TEXT	—
ordre_affichage	INTEGER	—
date_debut_validite	DATE	—
date_fin_validite	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

10. normes

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	—
nom	VARCHAR(255)	—
version	VARCHAR(255)	—
autorite_emettrice	VARCHAR(255)	—
domaine	VARCHAR(255)	—
portee	TEXT	—
date_debut_application	DATE	—
date_fin_application	DATE	—
date_expiration	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

11. entreprises

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
identifiant_national	VARCHAR(255)	UQ, NN
raison_sociale	VARCHAR(255)	—
nom_commercial	VARCHAR(255)	—
forme_juridique	VARCHAR(255)	—
rccm	VARCHAR(255)	—
nif	VARCHAR(255)	—
ifu	VARCHAR(255)	—
date_creation	DATE	—
nationalite	VARCHAR(255)	—
capital_social	NUMERIC(18,4)	—
effectif	INTEGER	—
chiffre_affaires	NUMERIC(18,4)	—
email_principal	VARCHAR(255)	—
telephone_principal	VARCHAR(255)	—
site_web	VARCHAR(255)	—
adresse_siege	VARCHAR(255)	—
zone_siege_id	UUID	FK → zones_administratives.id, NN
activite_principale	VARCHAR(255)	—
secteurs_secondaires	JSONB	—
statut	VARCHAR(255)	—
niveau_risque	VARCHAR(255)	—
source_donnee	VARCHAR(255)	—
date_derniere_verification	DATE	—

Colonne	Type PostgreSQL	Contraintes / relation
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

12. contacts_entreprise

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
entreprise_id	UUID	FK → entreprises.id, NN
nom	VARCHAR(255)	—
prenoms	VARCHAR(255)	—
fonction	VARCHAR(255)	—
telephone	VARCHAR(255)	—
email	VARCHAR(255)	—
type_contact	VARCHAR(255)	—
contact_principal	BOOLEAN	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

13. sites_entreprise

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
entreprise_id	UUID	FK → entreprises.id, NN
nom	VARCHAR(255)	—
type_site	VARCHAR(255)	—
adresse	TEXT	—
zone_id	UUID	FK → zones_administratives.id, NN
latitude	NUMERIC(18,4)	—
longitude	NUMERIC(18,4)	—
date_ouverture	DATE	—
effectif	INTEGER	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

14. offres_entreprise

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
entreprise_id	UUID	FK → entreprises.id, NN
type_offre	VARCHAR(255)	—
nom	VARCHAR(255)	—
description	TEXT	—
categorie	VARCHAR(255)	—
volume_annuel	NUMERIC(18,4)	—
unite	VARCHAR(255)	—
capacite_production	NUMERIC(18,4)	—
marches_cibles	JSONB	—
destinations	JSONB	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

15. candidats_doublon

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
entreprise_source_id	UUID	FK → entreprises.id, NN
entreprise_cible_id	UUID	FK → entreprises.id, NN
criteres_concordants	JSONB	—
score_similarite	NUMERIC(18,4)	—
statut_examen	VARCHAR(255)	—
decision	VARCHAR(255)	—
motif_decision	VARCHAR(255)	—
examine_par_id	UUID	FK → utilisateurs.id, NN
examine_at	TIMESTAMPTZ	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

16. organismes

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
identifiant_national	VARCHAR(255)	—
nom_officiel	VARCHAR(255)	—
sigle	VARCHAR(255)	—
type_organisme	VARCHAR(255)	—
pays	VARCHAR(255)	—
numero_enregistrement	VARCHAR(255)	—
email	VARCHAR(255)	—
telephone	VARCHAR(255)	—
adresse	TEXT	—
zone_id	UUID	FK → zones_administratives.id, facultatif
site_web	VARCHAR(255)	—
statut	VARCHAR(255)	—
date_derniere_verification	DATE	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

17. accreditations

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
organisme_id	UUID	FK → organismes.id, NN
numero	VARCHAR(255)	—
accréditeur	VARCHAR(255)	—
domaine_technique	VARCHAR(255)	—
perimetre	TEXT	—
date_delivrance	DATE	—
date_expiration	DATE	—
statut	VARCHAR(255)	—
reference_officielle	VARCHAR(255)	—
decision_hauqe	VARCHAR(255)	—
date_decision	DATE	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

18. certifications

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
identifiant_national	VARCHAR(255)	UQ, NN
entreprise_id	UUID	FK → entreprises.id, NN
organisme_id	UUID	FK → organismes.id, NN
accreditation_id	UUID	FK → accreditations.id, facultatif
norme_id	UUID	FK → normes.id, NN
numero_certificat	VARCHAR(255)	—
portee	TEXT	—
date_obtention	DATE	—
date_effet	DATE	—
date_expiration	DATE	—
statut	VARCHAR(255)	—
motif_statut	VARCHAR(255)	—
classification	VARCHAR(255)	—
authenticite_verifiee	BOOLEAN	—
certification_strategique	BOOLEAN	—
source_donnee	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

19. couvertures_certification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
certification_id	UUID	FK → certifications.id, NN
type_couverture	VARCHAR(255)	—
offre_entreprise_id	UUID	FK → offres_entreprise.id, facultatif
site_entreprise_id	UUID	FK → sites_entreprise.id, facultatif
libelle_couverture	VARCHAR(255)	—
details	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

20. audits_certification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
certification_id	UUID	FK → certifications.id, NN
type_audit	VARCHAR(255)	—
date_prevue	DATE	—
date_realisee	DATE	—
auditeur	VARCHAR(255)	—
resultat	TEXT	—
prochain_audit_at	TIMESTAMPTZ	—
observations	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

21. evenements_certification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
certification_id	UUID	FK → certifications.id, NN
type_evenement	VARCHAR(255)	—
ancien_statut	VARCHAR(255)	—
nouveau_statut	VARCHAR(255)	—
date_evenement	TIMESTAMPTZ	—
motif	TEXT	—
source	VARCHAR(255)	—
acteur_id	UUID	FK → utilisateurs.id, facultatif
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

22. renouvellements_certification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
certification_id	UUID	FK → certifications.id, NN
date_ouverture	DATE	—
date_limite	DATE	—
date_decision	DATE	—
decision	VARCHAR(255)	—
resultat	TEXT	—
justification	TEXT	—
preuves	JSONB	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

23. documents

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
type_document	VARCHAR(255)	—
nom_original	VARCHAR(255)	—
nom_stockage	VARCHAR(255)	—
chemin_stockage	VARCHAR(255)	—
format	VARCHAR(255)	—
taille_octets	BIGINT	—
checksum	VARCHAR(255)	—
version	VARCHAR(255)	—
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
confidentialite	VARCHAR(255)	—
source	VARCHAR(255)	—
date_document	DATE	—
depose_par_id	UUID	FK → utilisateurs.id, facultatif
date_depot	TIMESTAMPTZ	—
statut_verification	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

24. campagnes

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	UQ, NN
nom	VARCHAR(255)	—
objet	VARCHAR(255)	—
objectif	VARCHAR(255)	—
date_debut	DATE	—
date_fin	DATE	—
responsable_id	UUID	FK → utilisateurs.id, NN
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

25. missions_collecte

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
campagne_id	UUID	FK → campagnes.id, NN
code	VARCHAR(255)	—
objet	VARCHAR(255)	—
zone_id	UUID	FK → zones_administratives.id, NN
date_debut_prevue	DATE	—
date_fin_prevue	DATE	—
date_debut_reelle	DATE	—
date_fin_reelle	DATE	—
priorite	VARCHAR(255)	—
progression	INTEGER	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

26. affectations_mission

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
mission_id	UUID	FK → missions_collecte.id, NN
utilisateur_id	UUID	FK → utilisateurs.id, NN
role_mission	VARCHAR(255)	—
date_debut	DATE	—
date_fin	DATE	—
attribue_par_id	UUID	FK → utilisateurs.id, NN
motif	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

27. fiches_collecte

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
mission_id	UUID	FK → missions_collecte.id, NN
entreprise_id	UUID	FK → entreprises.id, facultatif
version_formulaire	VARCHAR(255)	—
numero_revision	INTEGER	—
statut	VARCHAR(255)	—
taux_completude	NUMERIC(18,4)	—
consentement_obtenu	BOOLEAN	—
nom_declarant	VARCHAR(255)	—
fonction_declarant	VARCHAR(255)	—
telephone_declarant	VARCHAR(255)	—
email_declarant	VARCHAR(255)	—
signature_declarant	VARCHAR(255)	—
observations	TEXT	—
collecte_par_id	UUID	FK → utilisateurs.id, NN
collecte_at	TIMESTAMPTZ	—
soumise_at	TIMESTAMPTZ	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

28. offres_declarees

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
fiche_collecte_id	UUID	FK → fiches_collecte.id, NN
type_offre	VARCHAR(255)	—
nom	VARCHAR(255)	—
description	TEXT	—
categorie	VARCHAR(255)	—
volume	NUMERIC(18,4)	—
unite	VARCHAR(255)	—
capacite	NUMERIC(18,4)	—
marches_vises	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

29. certifications_declarees

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
fiche_collecte_id	UUID	FK → fiches_collecte.id, NN
nom_certification	VARCHAR(255)	—
numero	VARCHAR(255)	—
organisme_declare	VARCHAR(255)	—
norme_declaree	VARCHAR(255)	—
portee	TEXT	—
date_obtention	DATE	—
date_expiration	DATE	—
copie_disponible	BOOLEAN	—
certification_officielle_id	UUID	FK → certifications.id, facultatif
score_rapprochement	NUMERIC(18,4)	—
statut_rapprochement	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

30. evenements_collecte

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
fiche_collecte_id	UUID	FK → fiches_collecte.id, NN
type_evenement	VARCHAR(255)	—
ancien_statut	VARCHAR(255)	—
nouveau_statut	VARCHAR(255)	—
commentaire	TEXT	—
acteur_id	UUID	FK → utilisateurs.id, NN
date_evenement	TIMESTAMPTZ	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

31. dossiers_verification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
fiche_collecte_id	UUID	FK → fiches_collecte.id, NN
date_ouverture	DATE	—
date_fin	DATE	—
statut	VARCHAR(255)	—
avis	VARCHAR(255)	—
synthese	TEXT	—
niveau_risque	VARCHAR(255)	—
priorite	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

32. affectations_verification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
dossier_verification_id	UUID	FK → dossiers_verification.id, NN
verificateur_id	UUID	FK → utilisateurs.id, NN
date_debut	DATE	—
date_fin	DATE	—
date_echeance	DATE	—
motif	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

33. points_verification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
dossier_verification_id	UUID	FK → dossiers_verification.id, NN
code	VARCHAR(255)	—
libelle	VARCHAR(255)	—
categorie	VARCHAR(255)	—
resultat	TEXT	—
observation	TEXT	—
date_verification	DATE	—
preuve_document_id	UUID	FK → documents.id, facultatif
verifie_par_id	UUID	FK → utilisateurs.id, NN
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

34. anomalies_verification

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
dossier_verification_id	UUID	FK → dossiers_verification.id, NN
point_verification_id	UUID	FK → points_verification.id, facultatif
categorie	VARCHAR(255)	—
gravite	VARCHAR(255)	—
description	TEXT	—
statut	VARCHAR(255)	—
resolution	TEXT	—
date_resolution	DATE	—
escalade	BOOLEAN	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

35. confirmations_externes

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
dossier_verification_id	UUID	FK → dossiers_verification.id, NN
organisme_id	UUID	FK → organismes.id, facultatif
canal	VARCHAR(255)	—
destinataire	VARCHAR(255)	—
objet	VARCHAR(255)	—
date_envoi	DATE	—
date_echeance	DATE	—
date_reponse	DATE	—
contenu_reponse	TEXT	—
resultat	TEXT	—
document_id	UUID	FK → documents.id, facultatif
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

36. grilles_fuccs

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	—
libelle	VARCHAR(255)	—
version	VARCHAR(255)	—
date_effet	DATE	—
date_fin	DATE	—
reference_approbation	VARCHAR(255)	—
statut_publication	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

37. rubriques_fuccs

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
grille_fuccs_id	UUID	FK → grilles_fuccs.id, NN
code	VARCHAR(255)	—
libelle	VARCHAR(255)	—
description	TEXT	—
ordre_affichage	INTEGER	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

38. criteres_fuccs

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
rubrique_fuccs_id	UUID	FK → rubriques_fuccs.id, NN
code	VARCHAR(255)	—
libelle	VARCHAR(255)	—
description	TEXT	—
score_maximal	NUMERIC(18,4)	—
poids	NUMERIC(18,4)	—
ordre_affichage	INTEGER	—
commentaire_obligatoire	BOOLEAN	—
preuve_obligatoire	BOOLEAN	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

39. controles_fuccs

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
dossier_verification_id	UUID	FK → dossiers_verification.id, NN
grille_fuccs_id	UUID	FK → grilles_fuccs.id, NN
controleur_id	UUID	FK → utilisateurs.id, NN
date_debut	DATE	—
date_fin	DATE	—
score_brut	NUMERIC(18,4)	—
score_maximal	NUMERIC(18,4)	—
taux	VARCHAR(255)	—
synthese	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

40. notes_criteres

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
controle_fuccs_id	UUID	FK → controles_fuccs.id, NN
citere_fuccs_id	UUID	FK → criteres_fuccs.id, NN
score	NUMERIC(18,4)	—
commentaire	TEXT	—
preuve_document_id	UUID	FK → documents.id, facultatif
note_par_id	UUID	FK → utilisateurs.id, NN
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

41. constats_controle

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
controle_fuccs_id	UUID	FK → controles_fuccs.id, NN
type_constat	VARCHAR(255)	—
gravite	VARCHAR(255)	—
titre	VARCHAR(255)	—
description	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

42. validations

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
fiche_collecte_id	UUID	FK → fiches_collecte.id, NN
controle_fuccs_id	UUID	FK → controles_fuccs.id, facultatif
niveau_validation	VARCHAR(255)	—
validateur_id	UUID	FK → utilisateurs.id, NN
decision	VARCHAR(255)	—
date_validation	DATE	—
reserves	VARCHAR(255)	—
justification	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

43. corrections

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
validation_id	UUID	FK → validations.id, NN
motif	TEXT	—
instructions	TEXT	—
date_demande	DATE	—
date_echeance	DATE	—
date_resoumission	DATE	—
reponse	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

44. integrations_bnec

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
validation_id	UUID	FK → validations.id, NN
administrateur_id	UUID	FK → utilisateurs.id, NN
date_debut	DATE	—
date_fin	DATE	—
statut	VARCHAR(255)	—
precontrole	VARCHAR(255)	—
postcontrole	VARCHAR(255)	—
sauvegarde_reference	VARCHAR(255)	—
resume	TEXT	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

45. elements_integration

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
integration_bnec_id	UUID	FK → integrations_bnec.id, NN
type_objet	VARCHAR(255)	—
ressource_source_id	UUID	—
ressource_cible_id	UUID	—
revision_source	VARCHAR(255)	—
action	VARCHAR(255)	—
code_genere	VARCHAR(255)	—
statut	VARCHAR(255)	—
message_erreur	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

46. modeles_scoring

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	—
libelle	VARCHAR(255)	—
version	VARCHAR(255)	—
objet_evalue	VARCHAR(255)	—
description	TEXT	—
date_debut_validite	DATE	—
date_fin_validite	DATE	—
regle_calcul	TEXT	—
reference_approbation	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

47. ponderations_scoring

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
modele_scoring_id	UUID	FK → modeles_scoring.id, NN
domaine	VARCHAR(255)	—
valeur	NUMERIC(18,4)	—
periode_debut	VARCHAR(255)	—
periode_fin	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

48. classifications_entreprise

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
entreprise_id	UUID	FK → entreprises.id, NN
modele_scoring_id	UUID	FK → modeles_scoring.id, NN
score	NUMERIC(18,4)	—
classe	VARCHAR(255)	—
date_calcul	DATE	—
date_validation	DATE	—
sources	JSONB	—
valide_par_id	UUID	FK → utilisateurs.id, NN
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

49. resultats_infc

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
certification_id	UUID	FK → certifications.id, NN
modele_scoring_id	UUID	FK → modeles_scoring.id, NN
score_global	NUMERIC(18,4)	—
niveau	INTEGER	—
scores_domaines	JSONB	—
date_calcul	DATE	—
date_validation	DATE	—
sources	JSONB	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

50. classements_sncc

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
certification_id	UUID	FK → certifications.id, NN
classe	VARCHAR(255)	—
statut_administratif	VARCHAR(255)	—
niveau_risque	VARCHAR(255)	—
justification	TEXT	—
date_effet	DATE	—
date_fin	DATE	—
valide_par_id	UUID	FK → utilisateurs.id, NN
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

51. echeances

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
type_echeance	VARCHAR(255)	—
titre	VARCHAR(255)	—
description	TEXT	—
date_echeance	DATE	—
responsable_id	UUID	FK → utilisateurs.id, facultatif
priorite	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

52. alertes

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
echance_id	UUID	FK → echances.id, facultatif
type_alerte	VARCHAR(255)	—
niveau	INTEGER	—
titre	VARCHAR(255)	—
message	TEXT	—
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
responsable_id	UUID	FK → utilisateurs.id, facultatif
date_detection	DATE	—
date_resolution	DATE	—
regle_notification	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

53. notifications

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
alerte_id	UUID	FK → alertes.id, facultatif
destinataire_utilisateur_id	UUID	FK → utilisateurs.id, facultatif
adresse_externe	VARCHAR(255)	—
canal	VARCHAR(255)	—
objet	VARCHAR(255)	—
contenu	TEXT	—
date_envoi	DATE	—
date_lecture	DATE	—
resultat	TEXT	—
nombre_tentatives	INTEGER	—
message_erreur	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

54. dossiers_veille

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
certification_id	UUID	FK → certifications.id, NN
type_evenement	VARCHAR(255)	—
priorite	VARCHAR(255)	—
date_ouverture	DATE	—
responsable_id	UUID	FK → utilisateurs.id, NN
prochaine_action_at	TIMESTAMPTZ	—
date_cloture	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

55. relances_veille

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
dossier_veille_id	UUID	FK → dossiers_veille.id, NN
destinataire	VARCHAR(255)	—
canal	VARCHAR(255)	—
objet	VARCHAR(255)	—
date_envoi	DATE	—
date_echeance	DATE	—
date_reponse	DATE	—
reponse	TEXT	—
resultat	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

56. rapports_veille

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
type_rapport	VARCHAR(255)	—
periode_debut	VARCHAR(255)	—
periode_fin	VARCHAR(255)	—
nombre_certifications_suivies	INTEGER	—
nombre_alertes	INTEGER	—
nombre_renouvellements	INTEGER	—
delai_moyen_traitement	NUMERIC(18,4)	—
indicateurs	JSONB	—
prepare_par_id	UUID	FK → utilisateurs.id, NN
valide_par_id	UUID	FK → utilisateurs.id, facultatif
date_validation	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

57. regles_metier

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	UQ, NN
famille	VARCHAR(255)	—
libelle	VARCHAR(255)	—
description	TEXT	—
version	VARCHAR(255)	—
parametres	JSONB	—
date_debut_effet	DATE	—
date_fin_effet	DATE	—
reference_approbation	VARCHAR(255)	—
approuve_par_id	UUID	FK → utilisateurs.id, facultatif
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

58. revues_qualite

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
periode_debut	VARCHAR(255)	—
periode_fin	VARCHAR(255)	—
perimetre	TEXT	—
resultat_global	VARCHAR(255)	—
constats	JSONB	—
preuves	JSONB	—
responsable_id	UUID	FK → utilisateurs.id, NN
date_validation	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

59. plans_action

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
revue_qualite_id	UUID	FK → revues_qualite.id, facultatif
titre	VARCHAR(255)	—
objectif	VARCHAR(255)	—
responsable_id	UUID	FK → utilisateurs.id, NN
date_debut	DATE	—
date_echeance	DATE	—
priorite	VARCHAR(255)	—
indicateur	VARCHAR(255)	—
progression	INTEGER	—
date_cloture	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

60. decisions_institutionnelles

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
type_decision	VARCHAR(255)	—
titre	VARCHAR(255)	—
contexte	TEXT	—
constats	JSONB	—
risques	VARCHAR(255)	—
options	VARCHAR(255)	—
decision	VARCHAR(255)	—
recommandation	VARCHAR(255)	—
autorite	VARCHAR(255)	—
decide_par_id	UUID	FK → utilisateurs.id, facultatif
date_decision	DATE	—
priorite	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

61. publications

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
objet	VARCHAR(255)	—
perimetre	TEXT	—
niveau_confidentialite	VARCHAR(255)	—
demande_par_id	UUID	FK → utilisateurs.id, NN
date_demande	DATE	—
decision	VARCHAR(255)	—
autorite_approbation	VARCHAR(255)	—
approuve_par_id	UUID	FK → utilisateurs.id, facultatif
date_approbation	DATE	—
reserve	VARCHAR(255)	—
date_publication	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

62. rapports_generes

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code_modele	VARCHAR(255)	—
nom_modele	VARCHAR(255)	—
categorie	VARCHAR(255)	—
demandeur_id	UUID	FK → utilisateurs.id, NN
filtres	JSONB	—
sections	JSONB	—
format	VARCHAR(255)	—
periode_debut	VARCHAR(255)	—
periode_fin	VARCHAR(255)	—
date_demande	DATE	—
date_generation	DATE	—
document_id	UUID	FK → documents.id, facultatif
resultat	TEXT	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

63. evenements_audit

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
utilisateur_id	UUID	FK → utilisateurs.id, facultatif
action	VARCHAR(255)	—
categorie	VARCHAR(255)	—
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
adresse_ip	VARCHAR(255)	—
contexte	TEXT	—
valeurs_avant	JSONB	—
valeurs_apres	JSONB	—
empreinte	VARCHAR(255)	—
resultat	TEXT	—
date_evenement	TIMESTAMPTZ	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

64. archives

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
categorie_donnees	VARCHAR(255)	—
date_archivage	TIMESTAMPTZ	—
motif	TEXT	—
auteur_id	UUID	FK → utilisateurs.id, NN
duree_conservation	VARCHAR(255)	—
date_suppression_prevue	DATE	—
emplacement	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

65. sauvegardes

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
type_enregistrement	VARCHAR(255)	—
parent_id	UUID	FK → sauvegardes.id, facultatif
frequence	VARCHAR(255)	—
retention	VARCHAR(255)	—
perimetre	TEXT	—
emplacement_stockage	VARCHAR(255)	—
date_debut	DATE	—
date_fin	DATE	—
taille_octets	BIGINT	—
integrite_validee	BOOLEAN	—
resultat	TEXT	—
preuve_document_id	UUID	FK → documents.id, facultatif
message_erreur	VARCHAR(255)	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()

66. incidents

Colonne	Type PostgreSQL	Contraintes / relation
id	UUID	PK, NN, gen_random_uuid()
code	VARCHAR(255)	UQ, NN
categorie	VARCHAR(255)	—
gravite	VARCHAR(255)	—
titre	VARCHAR(255)	—
description	TEXT	—
date_declaration	DATE	—
declare_par_id	UUID	FK → utilisateurs.id, NN
responsable_id	UUID	FK → utilisateurs.id, facultatif
ressource_type	VARCHAR(255)	—
ressource_id	UUID	—
preuves	JSONB	—
resolution	TEXT	—
date_resolution	DATE	—
date_cloture	DATE	—
statut	VARCHAR(255)	—
created_at	TIMESTAMPTZ	NN, now()
updated_at	TIMESTAMPTZ	NN, now()