Dynamical Regime	Grid & Bins (N,K)	Packet Width σ	Diffusion (Dψ,Dϕ)	Frequencies ω (rad/s)	Memory Retention (1−α)	Ridge Regularization λ
1. Continuous Attractors (Lorenz-63, Pendulum)	N=64, K=16	0.20−0.35 (Narrow)	0.10−0.30 (Moderate)	[0.5,1.25,2.75] (Multi-octave)	30%−40% (α≈0.65−0.70)	10−6−10−4 (Weak)
2. Discrete Maps (Logistic Map)	N=48, K=8	0.30−0.40 (Medium)	0.20−0.25 (Moderate)	[0.5,1.25,2.75] (Broad harmonic)	15%−25% (α≈0.75−0.85)	10−4 (Standard)
3. Infinite-D Delay Systems (Mackey-Glass)	N=64−128, K=8	0.25−0.35 (Narrow)	0.25−0.40 (Dispersion)	[0.5,1.25,2.75] (Multi-octave)	40%−50% (α≈0.50−0.60)	10−6 (Minimal)
4. Smooth Conservative Orbits (Lotka-Volterra)	N=32−48, K=6−8	0.40−0.60 (Broad)	0.20−0.30 (Standing wave)	[0.5,1.0,1.5]≈ω0 (Orbital fundamental)	40%−50% (α≈0.50−0.60)	10−3−10−2 (Strict SVD)
5. Stochastic & Burst Flows (Sunspots)	N=256, K=128	0.05−0.10 (Ultra-sharp)	0.001 (Minimal dispersion)	[12.0,20.0,28.0] (High carrier)	10%−25% (α≈0.75−0.90)	10−2−10−1 (Heavy)