

Feature cont.	Description cont	 easiest	 easy	 moderate	 difficult	 extreme
<i>Vertical change cont.</i>						
Tabletops	Tabletops are in effect rollers with steeper approaches and transitions with longer flatter tops. Tabletops can be used as jumps but it is essential that riders can roll over every part of the feature. Transition should be designed to suit the classification and purpose of the table top.	x	x	Max height 1500mm Min length 2000mm	Max height 2000mm Min length 2000mm	Max height 2000mm Min length 2000mm
Step ups	A step up is where the level of the trail changes abruptly, usually with a vertical face between the two levels.	Max height 40mm not less than 20m apart	Max height 50mm not less than 10m apart	Max height 200mm not less than 4m apart	Max height 700mm not less than 2m apart	Max height 1500mm not less than 2m apart
Drop off	A drop off is where the level of the trail changes abruptly with a vertical drop between the two levels.	x	x	Max height 500mm not less than 4m apart	Max height 1000mm not less than 4m apart	Max height 2500 not less than 4m apart
Rollable step downs	A rollable step down is similar to a drop off, the trail changes level with a less than vertical steep slope between the upper and lower levels. Riders should be able to roll the bike over the feature rather than having to drop over it as in the case off a drop off.	x	x	Max height 1000mm not less than 5m apart	Max height 1500mm not less than 4m apart	Max height 3500mm not less than 4m apart
Gaps	Parks and Wildlife will consider gap jumps being built on double black diamond trails on a case by case basis. A gap is a TTF with no rideable surface between the take-off and landing platform. Gaps can have increased consequences for riders. The perceived air gained from a gap jump can be achieved with a tabletop.	x	x	x	x	Conditionally. Max height 2000mm Min length 2000mm
Elevated Platforms Bridges and boardwalk installed as water crossings are not dealt with in this table.						
Log rides and Ladders	Log rides are features made up of a log that forms the trail tread. The log should be set into the ground and the top should be shaped to form the running or tread surface. A ladder is a feature that is constructed with stringers and rungs.	x	Ratio: 1:2 Max height 100mm Min width 200mm Max gradient 0% Ramps can have a gradient 10%	Ratio Height to Width 2:1 Max height 600mm Min width 200mm Max gradient 8% Max inslope/outslope 15% Ramps can have a gradient of 30%	Ratio Height to Width 4:1 Max height 1200mm Min width 150mm Max gradient 20% Ramps may have a gradient of up to 50% for up to 8m Max inslope/outslope 30%	Max height 1500mm Min width 100mm Max gradient 30% Ramps may have a gradient of up to 80% for up to 10m Max inslope/outslope 40%
Other						
Chicane and Choke (speed control)	A chicane is used to slow riders in a controlled manner by creating two tight corners by demarcation. A choke is a slight narrowing of the trail through the use of trees or rocks with the intention of slowing riders in a controlled manner. Note: Minimum widths are at handlebar height. Objects lower to the ground may be less depending on design and purpose.	Chicane only: WA Department of transport standards. Min corridor width 1.5m Chokes - NA	Min corridor width 1000m	Min corridor width 900m	Min corridor width 800mm	Min corridor width 800mm
Exposed edges	The outside edge of the trail has an exposed drop. For example bridges, boardwalks or cliffs. Guard rails are not required for TTFs, with appropriate cleared and maintained fall zones.	>600mm drop requires 1280mm high guardrails	>1000mm drop requires 1280mm high guardrails	>1500mm requires 1280mm high guardrails	>2000mm requires 1280mm high guardrails	>2000mm requires 1280mm high guardrails

REFERENCE: D Davis, 2012, IMBA, 2007, L McCormack, 2008, Greater Regional Vancouver District Parks, Resort Municipality of Whistler