

## EXSYM Chain Saw Oil 46

High quality chain-saw oil

NS-CSO-4191

*Chain-saw oils*

### Product Description and Benefits

This chain-saw oil is based upon high quality low aromatic solvent-refined base oils under addition of special additives to obtain the following properties:

- a very high grade of tackiness, preventing the oil from fling of the chain
- excellent lubricity

### Application

This chain-saw oil has been specially formulated to lubricate the chain of chain-saws preventing this oil from overheating and loss of strength. The high grade of tackiness prevents the oil to fling from the chain. **The chain-saw oil cannot be used for the lubrication of the engine of the saw.**

EXSYM Chain Saw Oil 46 meets the following performance specifications:

(no data)

### Typical Analysis

Property	Unit	Typical Value
Density at 15°C	kg/l	0,874
Viscosity 40 °C	mm <sup>2</sup> /s	46,80
Viscosity 100 °C	mm <sup>2</sup> /s	7,32
Viscosity Index		118
Flash Point COC	°C	232
Pour Point	°C	-39

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of its subsidiaries. More information available: