

EXSYM Vacuumpump Oil 46

NS-VPO-4181

Vacuum pump oils

High-grade vacuumpump oil

Product Description and Benefits

A high-grade vacuumpump oil based upon selected, solvent-refined base oils having a high viscosity index, under addition of additives to obtain the following properties:

- an excellent protection against wear
- a very good activity against rust and corrosion
- excellent stability against oxidation
- very good demulsification properties
- very good deaerating and foam-suppressing properties
- good compatibility with seals and gaskets made from synthetic material
- a low pourpoint

Application

This oil may be used for lubricating vacuumpumps, where at least a HLP oil is prescribed, for both the gear box as well as for spray lubrication. This vacuumpump oil is an oil, which is very suitable for the lubrication the gearboxes of vacuumpumps.

EXSYM Vacuumpump Oil 46 meets the following performance specifications:

DIN51524, 2HLPD

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/l	0,861
Viscosity 40 °C	mm²/s	46,00
Viscosity 100 °C	mm²/s	6,97
Viscosity Index		110
Flash Point COC	°C	215
Pour Point	°C	-30
Acid number	mgKOH/g	0,40
Sulphate Ash	%	0,06

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of it's subsidaries. More information available:

web page: www.exsymmobilltd.com e-mail: exsymmobilltd@gmail.com