

EXSYM Spindle Oil 10

Pure naphthenic mineral oil

NS-SPN-4204

Industrial Spindle oils

Product Description and Benefits

This is a pure naphthenic mineral oil with a natural oxidation stability. This oil has a average viscosity index and contains no additives and has also a low percentage of aromatic hydrocarbons.

Application

A lubricating oil for not loaded gearboxes and bearings. It is also suitable for general lubrication, especially suitable as lubricant in circulation systems, where an un-doped oil is asked or prescribed.

EXSYM Spindle Oil 10 meets the following performance specifications:

(no data)

Typical Analysis

| Property | Unit | Typical Value |
|------------------|--------------------|---------------|
| Density at 15°C | kg/l | 0,888 |
| Viscosity 40 °C | mm ² /s | 9,10 |
| Viscosity 100 °C | mm ² /s | 2,30 |
| Flash Point COC | °C | 146 |
| Pour Point | °C | -57 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of it's subsidiaries. **More information available:**