

# EXSYM Compressor Oil SRC 46

## Compressor oil

ST-ICO-4162

Compressor  
oils

### Product Description and Benefits

This compressor oil is based on high grade specially selected solvent refined base oils, under addition of additives to obtain the following properties:

- very good oxidation stability
- excellent anti-wear properties
- a very good protection against corrosion
- a high dispersing power
- effective in preventing from foam

### Application

This compressor oil is a dispersant type oil intended primarily for oil-flooded rotary sliding-vane and screw-type compressors with relative high operating temperatures.

**EXSYM Compressor Oil SRC 46 meets the following performance specifications:**

(no data)

### Typical Analysis

Property	Unit	Typical Value
Density@15 °C	kg/	0,877
Viscosity40 °C	mm <sup>2</sup> /s	46,00
Viscosity 100 °C	mm <sup>2</sup> /s	7,37
Viscosity Index		123
FlashPoint COC	°C	215
Pour	°C	-30
Total Base Number	mgKOH/g	7,7
Sulphate	%	0,94

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of it's subsidiaries. **More information available:**