

EXSYM Pneumo Oil 32

High-grade vacuum pump oil

NS-PTO-4185

Pneumatic Tools oils

Product Description and Benefits

A lubricant especially developed to lubricate pneumatic tools and based on solvent refined base oils. Under addition of additives this oil obtains the following properties:

- a very good oxidation stability
- a very good protection against corrosion of ferro and non-ferro metals
- an excellent resistance against high pressures and shock loads
- good micro-fog properties
- a good protection against deposit in the pneumatic system
- no forming of ice in pneumatic tools and machinery
- compatible with seals and gaskets made of synthetic material
- a low pour point

Application

This oil can be used in an air-piping or micro-fog lubricator of hammers, pile driver drills, grinders, pumps, hoists, clamps and vices.

EXSYM Pneumo Oil 32 meets the following performance specifications:

ISO 6743/11 P

Typical Analysis

Property	Unit	Typical Value
Density @ 15°C	kg/l	0,873
Viscosity 40 °C	mm ² /s	33,30
Viscosity 100 °C	mm ² /s	5,90
Viscosity Index		122
Flash Point COC	°C	198
Pour Point	°C	-33

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of its subsidiaries. More information available: