# **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

### 1 - Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product name EXSYM DDB CABLE OIL 1010

Product descriptionInsulating oilProduct typeLiquidMARPOLAnnex-IOils

1.2 Identified uses

Distribution of substance Industrial

Formulation & (re)packing of

substances and mixtures Industrial
Manufacture of substance Industrial
Functional Fluids Industrial

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer EXSYM MOBIL LIMITED, ENGLAND

e- mail address of person responsible for this SDS

# 1.4 Emergency telephone number

# 2 - Hazards Identification 2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Asp. Tox. 1, H304

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

#### 2.2 Label elements

Hazard pictograms

**③** 

Signal word Danger

Hazard statements H 304: May be fatal if swallowed and enters airways.

Precautionary statements

Prevention Not applicable

Response P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT

induce vomiting.

Storage P405 - Store locked up.

Disposal P501 - Dispose of contents/container in accordance with all local, regional, national and

international regulations. Not applicable

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles

2.3 Other hazards

Substance meets the criteria for PBT according to Regulation (EC) No.

1907/2006, Annex XIII

 $Substance\,meets\,the\,criteria\,for\,vPvB\\according\,to\,Regulation\,(EC)\,No.$ 

1907/2006, Annex XIII

Not applicable

**Not applicable** 

Product Name: Cabke oil EXSYMDDBCABLE OIL 1010 Version No.: 08 Issue Date: January 2018

# **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

### 3 - Composition / Information on Ingredients

3.2 Mixtures Mixture

Product/Ingredient name	Identifiers	%	Classification Regulation (EC) No.1272/2008 [CLP]	Туре
Distillate (petroleum),hydrotreated lig ht Paraffinic	EC: 265-158-7 CAS: 64742-55-8	>99	Asp. Tox. 1, H304	[1]

Annex I Nota Lapplies to the base oil(s) in this product. Nota L-The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

### 4 - First Aid Measures

<u>4</u> 1	Descri	ntion o	f firet aid	measures
7.1	Descii	DUIDITO	rı ili ət alu	ı ii i casul cs

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice

from a specialist.

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. If casualty is unconscious and: If not breathing, if breathing is irregular or if respira tory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention if

adverse health effects persist or are severe. Maintain an open airway.

Skin contact Wash with soap and water. Remove contaminated clothing and shoes. Handle with care and

dispose of in a safe manner. Seek medical attention if skin irritation, swelling or redness develops

and persists.

Accidental high pressure injection through the skin requires immediate medical attention. Do not

wait for symptoms to develop.

Ingestion Always assume that aspiration has occurred. Do not induce vomiting. Can enter lungs and cause

damage. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Seek professional medical attention or send the casualty to a hospital. Do not wait for symptoms

to develop.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a

collar, tie, belt or waistband.

dangerous to the person providing aid to give mouth -to-mouth resuscitation.

Before attempting to rescue casualties, isolate area from all potential sources of ignition including disconnecting electrical supply. Ensure adequate ventilation and check that a safe, breathable

atmosphere is present before entry into confined spaces.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact may cause redness and transient pain.

Inhalation Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

Skin contact

No known significant effects or critical hazards.

Ingestion

May be fatal if swallowed and enters airways.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Due to low viscosity there is a risk of aspiration if the product enters the lungs. Treat

symptomatically.

Specific treatments Always assume that aspiration has occurred.

Product Name: EXSYM DDB CABLE OIL 1010

Version No.: 08 Issue Date: January 2018

Page 2 of 8

### Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

### 5 - Fire Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO<sub>2</sub>). Water spray or foam.

Unsuitable extinguishing media Do not use direct water jets on the burning product; they could cause splattering and spread the

fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys

the foam.

5.2 Special hazards arising from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst. Hazards from the substance

or mixture This substance will float and can be reignited on surface water.

Hazardous thermal Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid decomposition products particulates, gases, including carbon monoxide, H2S, SOx (sulfur oxides) or sulfuric acid and

unidentified organic and inorganic compounds.

5.3 Advice forfirefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a Special precautions for firefighters

fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-

fighters

Fire-fighters should wear appropriate protective equipment and self -contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469

will provide a basic level of protection for chemical incidents.

#### 6 - Accidental release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Fornon-emergency personnel

Avoid breathing vapour or mist. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind/keep distance from source. In case of large spillages, alert occupants in downwind areas.

Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will

presumably limit the exposure to dangerous concentrations.

Note: recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions.

For this reason, local experts should be consulted when necessary. Local regulations may also

prescribe or limit actions to be taken.

Small spillages: normal antistatic working clothes are usually adequate. For emergency responders

> Large spillages: full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and /or face shield, if splashes or contact

with eyes is possible or anticipated.

Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H2S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed,

or if an oxygen deficiency is possible, only SCBA's should be used.

6.2 Environmental precautions

Prevent product from entering sewers, rivers or other bodie s of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations.

In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents.

If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.

SDS (EU 2015/830) Page 3 of 8 08 Issue Date: January 2018

Product Name: EXSYMDDBCABLE OIL 1010

### **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

6.3 Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Absorb spilled product with suitable non -combustible materials.

Large spill Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formatio

Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do not use water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or

safe disposal.

**6.4** Reference to other sections See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

### 7 - Handling and Storage

7.1 Advice on general occupational

hygiene Storage

Ensure that proper housekeeping measures are in place. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash hands thoroughly after handling. Change contaminated clothes at the end of working shift. See also Section 8 for additional information on hygiene measur es.

7.2 Conditions for safe storage, including any incompatibilities

Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

### 7 - Handling and Storage

7.2 Conditions for safe storage, including any incompatibilities

Store separately from oxidising agents.

Recommended materials for containers, or container linings use mild steel, stainless steel. Not suitable: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.

Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable/combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Store locked up. Protect from sunlight.

7.3 Specific enduse(s)

Recommendations Not available Industrial sector specific solutions Not available

### 8 - Exposure Controls / Personal Protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s). 8.1 Control parameters

#### Occupational exposure limits

Product/ Ingredient name	Exposure limits values
Oil mist	[Air contaminant]
	AFS 2011:18 (Sweden, 12/2011).
	TWA: 1 mg/m <sup>3</sup> 8 hours. Form: mist and fume
	STEL: 3 mg/m³ 15 minutes. Form: mist and fume

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Ref erence should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

 Product Name : EXSYMDDBCABLE OIL 1010
 SDS (EU 2015/830)

 08 Issue Date : January 2018
 Page 4 of 8

### Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

8.2 Exposure Control

Appropriate engineering controls

Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated,

temperature control equipment should be used to avoid overheating.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products,

> before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated

clothing before reuse.

Recommended: Safety glasses with side shields. Eve/face protection

Skin protection

Hand protection 4 - 8 hours (breakthrough time): nitrile rubber

Body protection Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end

of working shift.

Appropriate footwear and any additional skin protection measures should be selected based on Other skin protection

the task being performed and the risks involved and should be approved by a specialist before

handling this product.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the Respiratory protection

> product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is

necessary.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply

with the requirements of environmental protection legislation. In some cases, fume scrubbers. filters or engineering modifications to the process equipment will be necessary to reduce

emissions to acceptablelevels.

### 9 - Physical and Chemical Properties

Appearance

Physical state Liquid

Color Colurlees to Light yellow

Odor Odorless Odour threshold Not available рΗ Not applicable

< -30°C (ASTM D-97) Melting point/Pour point

Flash point > 140°C Open cup (ASTM D 92)

Evaporation rate Not available Flammability (solid, gas) Not available Flammability limits in air, Not available

lower, % by volume

Not available Flammability limits in air,

upper, % by volume

Not available Vapour pressure

0.825 to 0.845 at 15°C Density

Solubility(ies)

Insoluble in water Solubility (water) Not available Partition coefficient

(n-octanol/water)

**NoData** Decomposition temperature >250°C Auto-ignition temperature

0.08 cm<sup>2</sup>/s to 0.11 cm<sup>2</sup>/s (8.00 to 11.00 cSt) Viscosity, Kinematic at 40°C (104°F)

No Data Explosive properties No Data Oxidising properties < 3% DMSO extractable compounds for base

oil substance(s) according to IP346 10 - Stability and reactivity

10.1 Reactivity No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability Stable under normal conditions

10.3 Possibility of hazardous Reactions Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid Oxidising agent.

10.5 Incompatible materials Keep away from extreme heat and oxidizing agents.

Product Name: EXSYM DDB CABLE OIL 1010 SDS (EU 2015/830) Version No.: 08 Issue Date: January 2018 Page 5 of 8

# **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

10.6 Hazardous decomposition products

Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H2S, SOx (sulfur oxides) or sulfuric acid and unidentified organic and inorganic compounds.

### 11 - Toxicological Information

#### 11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	l
Distillate (petroleum), hydrotreated light	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours	l
paraffinic	LD50 Dermal	Rabbit	>5000 mg/kg	-	l
	LD50 Oral	Rat	>5000 mg/k	-	l
					1

Irritation/Corrosion

Skin No known significant effects or critical hazards.
Eye No known significant effects or critical hazards.
Respiratory No known significant effects or critical hazards.

Sensitisation

Skin No known significant effects or critical hazards. Respiratory No known significant effects or critical hazards.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic orgenotoxic.

### 11 - Toxicological Information

Carcinogenicity The base oil(s) in this product is based on an severely hydrotreated distillate. The product should

not be regarded as a carcinogen.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction.

Specific target organ toxicity Not classified

- single exposure

Specific target organ toxicity Not classified

- repeated exposure

Aspiration hazard Aspiration hazard - Category 1

Information on likely routes of exposure Not available.

Potential acute health effects

Eye contact Eye contact may cause redness and transient pain.

Inhalation Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

Skin contact

No known significant effects or critical hazards.

Ingestion

May be fatal if swallowed and enters airways.

Potential chronic health effects

General No known significant effects or critical hazards.

Carcinogenicity The base oil(s) in this product is based on an severely hydrotreated distillate. The product should

not be regarded as a carcinogen.

Mutagenicity
No known significant effects or critical hazards.

Teratogenicity
No known significant effects or critical hazards.

Product/ingredient name
No known significant effects or critical hazards.

Fertility effects
No known significant effects or critical hazards.

Other information Not available.

Specific hazard

Product Name: EXSYM DDB CABLE OIL 1010

Version No.: 08 Issue Date: January 2018

Page 6 of 8

### **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

### 12 - Ecological Information

12.1 Toxicity Not expected to be harmful to aquatic organisms.

12.2 Persistence and degradability Not inherently biodegradable.

12.3 Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

12.4 Mobility in soil Not considered mobile.

12.5 Results of PBT & vPvB Assessment Not applicable.

12.6 Other adverse effects Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms.

Oxygen transfer could also be impaired.

#### 13 - Disposal Considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product

Methods of disposal Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local

authorizations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organization,

and/or prescribe composition limits and methods for recovery or disposal.

Hazardous waste Yes

### 13 - Disposal Considerations

European waste catalogue (EWC)

Waste code	Waste designation
13 03 07*	mineral-based non-chlorinated insulating and heat transmission oils

Packaging

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Waste packaging

should be recycled. Incineration or landfill should only be considered when recycling is not

feasible.

### **14 - Transport Information**

### International transport regulations

	ADR/ RID	ADN	IMO/IMDG Classification	ICAO/IATA Classification
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No	No	No	No
Additional information	-	-	-	-

14.6 Special precautions for User

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Oils

Product Name: EXSYM DDB CABLE OIL 1010

Version No.: 08 Issue Date: January 2018

Page 7 of 8

# **Safety Data Sheet**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830.

#### 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

Substances of very high concern
nnex XVII - Restrictions on the

None of the components are listed.
None of the components are listed.
Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Seveso Directive This product is not controlled under the Seveso Directive.

International Lists On inventory (yes/no)\* Inventory name **National Inventory** Australian Inventory of Chemical Substances (AICS) Australia Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No Inventory of Existing Chemical Substances in China (IECSC) China Yes European Inventory of Existing Commercial Chemical Substances (EINECS) Europe Yes Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan Yes Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances (PICCS) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

15.2 Chemical Safety Assessment

#### 16 - Other Information

Revision comments Not available.

Legend to abbreviations

ADR European agreement concerning the international carriage of dangerous good by road.

RID Regulations agreement concerning the international carriage of dangerous good by rail.

IMDG – CODE International maritime dangerous goods code.

ICAO International Civil Aviation Organization.

IATA International airtransport association.

GHS Globally Harmonized System of Classification and Labeling of Chemicals.

CLP Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].

SCBA Self-Contained Breathing Apparatus.

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC)

No. 1907/2006].

LC 50 Median lethal concentration.
LD 50 Median lethal dose.

LD 50 Median lethal dose.

PBT Persistent, Bioaccumulative and Toxic.

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Asp. Tox. 1, H304	Calculation method

Full text of abbreviated H statements H304 May be fatal if swallowed and enters airways. Full text of classifications ICLP/GHS1 Asp. Tox. 1. H304 ASPIRATION HAZARD - Category 1.

Date of issue/Date of revision January 2018.

Date of previous issue December 2016.

Version 08

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Product Name: EXSYM DDB CABLE OIL 1010 Version No.: 08 Issue Date: January 2018

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).