

EXSYM Pure White Oil 68

Mineral white oil

ST-WHA-4212

White oils

Product Description and Benefits

This mineral white oil is based on specially selected saturated paraffinic and cyclo-paraffinic hydrocarbons. Due to a special method of refining this oil is acid-free, colourless and odourless.

Application

This type of white oil has a wide range of applications in the industry. Moreover this product can be used in:

- precision machines, which are not heavily loaded
- some polymers as a softener
- the textile and artificial silk industry
- household applications

EXSYM Pure White Oil 68 meets the following performance specifications:

(no data)

Typical Analysis

Property	Unit	Typical Value
Colour, Saybolt		
Density at 15°C	kg/l	30,0
Viscosity 20 °C	mm ² /s	0,864
Viscosity 50 °C	°E	210,00
Viscosity 100 °C	mm ² /s	5,60
Viscosity Index		8,60
Flash Point PM	°	108
Flash Point	°	10
COC Pour	C	240
		-12

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of its subsidiaries. More information available: