

EXSYM Marine 2T DFI

Two stroke engine oil for outboard application

NS-OUB-4257

Outboard - Boats oils

Product Description and Benefits

A two-stroke engine oil formulated with carefully selected high quality base oils and special ashless two stroke additives. This well-balanced composition gives this engine oil the following properties:

- an excellent lubricity
- a minimal carbon build-up
- a reduced spark plug fouling
- a limited formation of smoke
- a powerful detergency and activity against wear and corrosion
- excellent high temperature properties

Application

This ashless two stroke engine oil is excellent suitable for application in the higher horsepower, water-cooled two stroke outboard engines with Direct Fuel Injection.

EXSYM Marine 2T DFI meets the following performance specifications:

Meets the requirements of NMMA TC-W3

Typical Analysis

Property	Unit	Typical Value
Density at 15 °C	kg/l	0,871
Viscosity 40 °C	mm ² /s	43,50
Viscosity 100 °C	mm ² /s	7,33
Viscosity Index		132
Flash Point COC	°C	90
Pour Point	°C	-42
Total Base Number	mgKOH/g	10,6

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of its subsidiaries. More information available: