

# EXSYM Technical White Oil 15

## Mineral white oil

ST-WHA-4213

Industrial Spindle oils

### Product Description and Benefits

This mineral oil is based on especially selected saturated paraffinic and cyclo-paraffinic hydrocarbons. Due to an intensive method of refining this white oil is acid-free and nearly colourless and odourless.

### Application

This white oil has a wide range of applications:

- as a lubricant for precision machining, sewing machines, other textile machining etc.
- as base material in the plastic, rubber, chemical and other industry processes
- as base oil for insecticides

This oil can not be used in the medical or food industry where food can contaminate with the lubricant.

EXSYM Technical White Oil 15 meets the following performance specifications:

(no data)

### Typical Analysis

Property	Uni	Typical Value
Colour, Saybolt		
Density at 15°C	kg/l	28,0
Viscosity 20	mm <sup>2</sup> /s	0,859
Viscosity 50 °C	s	37,00
Viscosity 100 °C	°E	1,90
Viscosity Index	mm <sup>2</sup> /s	3,60
Flash Point PM		135
Flash Point	°	20
COC Pour	°	185
	C	-15

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. EXSYM check oil level design is trade mark of EXSYM MOBIL LTD. or one of its subsidiaries. More information available: