

Developer Guide

River Hawk Consulting, LLC · IMAX HCD Prototype OT

August 8, 2026

CONTENTS

Developer Guide — IMAX Chat-Viewer (Phase 3 Angular build)

 Architecture

 Three things in here that are easy to undo by accident

 Dev topology

 Tests

 Ground rules for new work

 Deployment

 Repo map

Developer Guide — IMAX Chat-Viewer (Phase 3 Angular build)

UNCLASSIFIED — Deliverable ④. The Angular SPA at `angular/` is the delivery codebase; the React app at `src/` is the Phase 2 reference implementation (living spec) and ships unchanged. Testids and mock-service contracts carry between them 1:1 — that is the acceptance mechanism.

Architecture

```
angular/src/app
├── core
│   ├── models          api.models.ts (frozen wire contracts) ·
│   session.models.ts (client state)
│   ├── api             SearchApi · TranslateApi · EntitiesApi ·
│   SummarizeApi · OcrApi
│   ├── stores          TriageStore · SessionStore · GoldCopyStore
│   (signals, in-memory)
│   ├── directives      PanelResize (shared drag-to-resize for both side
│   panels)
│   └── features
│       ├── triage       TriagePanel (queue + search) · SnippetHighlight
│       ├── viewer       ChatViewer · MessageBubble · OcrDialog
│       └── gold-copy     GoldCopyPanel · ProvenanceLine
```

For the system as a whole — services, certificates, identity, deployment topology, and the values only the target environment can supply — see [architecture.md](#). That document is written to be sufficient on its own; this one assumes you are in the code.

THREE THINGS IN HERE THAT ARE EASY TO UNDO BY ACCIDENT

The message stream is virtualized (`ChatViewer`, `cdk-virtual-scroll-viewport` from `@angular/cdk/scrolling`). The fixed-size strategy is deliberate: the autosize strategy lives in `@angular/cdk-experimental`, and adding an experimental package

that the enclave's npm mirror has to carry and the vulnerability gate has to clear is a bad trade for a deliverable the Government maintains. `itemSizePx` is measured, not guessed.

Two consequences worth knowing before touching that component. Anything that finds a message by `document.querySelector` will fail most of the time, because the target is usually not in the DOM — jump-to-evidence asks the viewport for the index first. And `tests/ng/virtual-scroll.spec.js` asserts a *bounded* DOM at volume; a change that quietly reverts windowing fails there rather than in the enclave. The corpus itself now carries the case: `t-3000` is a 2,388-message standing channel, held as one thread because that is how one is worked, so windowing is exercised by real demonstration data and not only by a thread synthesised inside a test.

Render order is decided in the viewer, not taken from the service. Collection feeds do not guarantee chronological delivery — the audio-cut fixtures did not — so `orderedMessages` sorts, and the promoted transcript sorts chronologically regardless of which way the linguist is reading.

Nothing is persisted. No `localStorage`, `sessionStorage`, `IndexedDB` or cookies anywhere in either build. Panel widths, sort direction, viewer geometry and all officer work live in signals and reset on reload. This is a requirement (TDD Task 3), not an oversight; `SessionStore` is the seam if production needs otherwise.

- **Angular 21 (LTS), pinned exact** in `angular/package.json`; standalone components, signals, built-in control flow. No APIs newer than v17 — the pin is a stated assumption in the kickoff correspondence and an adjacent-major `ng update` is deliberately cheap.

- **Stores** hold all client state, in-memory only (the evaluated demo's performance claim — no persistence):
 - `TriageStore` — selected thread, focus-message (with a retrigger counter so repeat hits re-flash), and per-thread dispositions. Dispositions live here, not in the panel, because promoting a thread to gold marks it worked from the viewer side.
 - `SessionStore` — cached machine translations and entities (enrichment is thread-level, run once from the workflow strip), review verdicts, analyst notes, doc notes, and doc tags with the folded `tag → {threads, docs}` index that feeds the officer-tag facet.
 - `GoldCopyStore` — promoted thread-gold entries: the bench's single output (`hcd/one_output_model.md`). Snippet evidence clips were removed 1 Aug (logged deviation; single-commit revert if the Sponsor requires strict parity).
- **Enrichment is fixture-backed by default and gateway-backed by configuration.** `providers/model-gateway.js` speaks the OpenAI-compatible chat-completions wire format; supply `MODEL_ENDPOINT` and `MODEL_NAME` in the deployment `ConfigMap` and `MODEL_API_KEY` in the `Secret` (all three are environment-specific; no gateway address is committed), and translation and OCR answer from the enclave's live model instead of the seed fixtures — same contracts, no client rework. Translation sends full thread context; OCR uses vision on rasterized pages (`node scripts/rasterize-attachments.js`). Every failure path falls back to the fixture and logs. Provenance reports the engine (`<gateway-host>:<model>`), so the gold copy never misstates who translated what. Details: `deploy/README.md` §4.
- **API services** mirror the route contracts verbatim (`routes/*.js` headers are the source of truth; the contracts are frozen). Wire-format unit tests pin URL, params, and body shapes per service.
- **Escaping discipline:** corpus text renders as text nodes only — snippet highlighting builds `<mark>` spans from split text, never `innerHTML`.

Dev topology

```
npm install && npm --prefix angular install
npm run dev:ng          # mock services :5177 + ng serve :4200
(proxy.conf.json)
npm run dev             # the React reference app (:5273), same mock
services
```

Tests

```
npm --prefix angular run lint && npm --prefix angular run build && npm --
prefix angular test
npm run test:ng         # e2e vs the Angular build (Playwright boots both
servers)
npm test                # the original suite vs the React reference app
```

- `tests/*.spec.js` — the 7-spec Phase 2 acceptance suite (+ shared shell/services specs). It drives the browser by `testid`, so it runs against either app: the ported flows live verbatim inside `tests/ng/*.spec.js` and all 7 pass against the Angular build (see `project/evidence/README.md` for the coverage table).
- `tests/ng/` — Angular-build specs: the verbatim acceptance flows plus amendment coverage (queue progress, stack-clear, thread gold end-to-end). The React config ignores this directory.
- CI (`.github/workflows/angular-ci.yml`): lint → prod build → unit → e2e, plus the `package-validate` job (below) on every push.

Ground rules for new work

1. **data-testid values are the contract.** Never rename one; additions are fine (the amendment added `thread-*` / `queue-progress` / `stack-clear` testids — additive only).
2. **Mock contracts are frozen.** UI change? fine. Route shape change? that's a Sponsor conversation, not a refactor.

3. **Visual parity with the evaluated demo** — palette and layout tokens live in `styles.scss` as CSS custom properties (entity colors are part of the design contract). Parity baseline: `project/parity/`.

Deployment

The full packaging story (six images, kustomize manifests, probes/limits, statelessness, registry push, production cutover) is `deploy/README.md`. Short version:

```
./deploy/build-images.sh 0.1.0
kubectl apply -k deploy/k8s
kubectl port-forward svc/imax-spa 8443:8443
```

CI proves the set on a kind cluster every push (image builds → trivy CRITICAL gate → deploy → rollout → smoke through the SPA proxy chain). The production cutover swaps the nginx upstreams for enrichment-service endpoints — contracts frozen, no client rework.

Repo map

Path	What
<code>angular/</code>	Delivery SPA (this guide's subject)
<code>src/</code> , <code>index.html</code> , <code>vite.config.mjs</code>	React reference implementation (frozen spec)
<code>server.js</code> , <code>routes/</code> , <code>data/</code> , <code>static/</code>	Mock enrichment services + seed corpus (frozen contracts)
<code>tests/</code>	Playwright acceptance + Angular-build suites
<code>deploy/</code>	Dockerfiles, manifests, deployment guide
<code>hcd/</code>	Deliverable ① — personas, empathy maps, wireframes, workflow model
<code>docs/</code>	Deliverable ④ — this guide, the user guide, and <code>architecture.md</code> (Article XII)
<code>project/</code>	Deliverable ⑤/⑥ — risk register, burndown, evidence trail