Pasted code.ts
TypeScript

Pasted text (2).txt
Document

```
"use client";

import { useEffect, useMemo, useState } from "react";
import { FolderOpen, Search, X, FileText, Plus } from "lucide-react";

type Option = { id: number; name: string };

type ProgramOption = {
  id: number;
  name: string;
  client?: number;
};

type Assignment = {
  id: number;
  client: Option;
  program: ProgramOption;
  created_at?: string;
};

type Attachment = {
```

```
  id: number;
  file_name: string;
  description: string;
  asset_type: "file" | "url";
  sharepoint_url: string | null;
  external_url: string | null;
  clients: Option[];
  programs: ProgramOption[];
  assignments: Assignment[];
  created_at?: string;
  updated_at?: string | null;
};

function normalizeAttachment(raw: any): Attachment {
  return {
    id: Number(raw?.id),
    file_name: raw?.file_name || "",
    description: raw?.description || "",
    asset_type: raw?.asset_type || "file",
    sharepoint_url: raw?.sharepoint_url || null,
    external_url: raw?.external_url || null,
    clients: Array.isArray(raw?.clients) ? raw.clients : [],
    programs: Array.isArray(raw?.programs) ? raw.programs : [],
    assignments: Array.isArray(raw?.assignments) ? raw.assignments : [],
    created_at: raw?.created_at || undefined,
    updated_at: raw?.updated_at || null,
  };
}
```

```
export default function ActivityAttachmentSelector({
  selectedIds,
  onChange,
  label = "Available learning resources",
}: {
  selectedIds: number[];
  onChange: (ids: number[]) => void;
  label?: string;
}) {
  const API = process.env.NEXT_PUBLIC_API_BASE_URL;

  const [attachments, setAttachments] = useState<Attachment[]>([]);
  const [loading, setLoading] = useState(false);
  const [search, setSearch] = useState("");
  const [showAvailable, setShowAvailable] = useState(false);

  async function fetchAttachments() {
    try {
      setLoading(true);

      const res = await fetch(`${API}/api/attachments/`, {
        cache: "no-store",
        credentials: "include",
      });

      const data = await res.json().catch(() => []);

      if (!res.ok) {
        throw new Error(data?.error || "Failed to fetch attachments");
```

```
      }

      const normalized = Array.isArray(data) ?
data.map(normalizeAttachment) : [];
      setAttachments(normalized);
    } catch (err) {
      console.error("Failed to fetch attachments:", err);
      setAttachments([]);
    } finally {
      setLoading(false);
    }
  }

  useEffect(() => {
    fetchAttachments();
  }, []);

  useEffect(() => {
    function handleAttachmentsUpdated() {
      fetchAttachments();
    }

    window.addEventListener("attachments-updated",
handleAttachmentsUpdated);
    return () => {
      window.removeEventListener("attachments-updated",
handleAttachmentsUpdated);
    };
  }, []);
```

```
  // Get currently selected attachments with full details
  const selectedAttachments = useMemo(() => {
    return attachments.filter(attachment =>
selectedIds.includes(attachment.id));
  }, [attachments, selectedIds]);

  // Filter out already selected files from the available list
  const availableAttachments = useMemo(() => {
    return attachments.filter(attachment =>
!selectedIds.includes(attachment.id));
  }, [attachments, selectedIds]);

  const filteredAvailable = useMemo(() => {
    const q = search.trim().toLowerCase();
    if (!q) return availableAttachments;

    return availableAttachments.filter((a) =>
      a.file_name.toLowerCase().includes(q) ||
      (a.description || "").toLowerCase().includes(q)
    );
  }, [availableAttachments, search]);

  function addAttachment(id: number) {
    if (!selectedIds.includes(id)) {
      onChange([...selectedIds, id]);
    }
    setShowAvailable(false);
    setSearch("");
```

```
  }

  function removeSelectedAttachment(id: number) {
    onChange(selectedIds.filter((x) => x !== id));
  }

  function clearAll() {
    onChange([]);
  }

  // Get file URL for preview
  const getFileUrl = (attachment: Attachment): string | null => {
    return attachment.external_url || attachment.sharepoint_url;
  };

  return (
    <div className="mt-4 rounded-xl border border-slate-200
dark:border-slate-700 bg-white dark:bg-slate-900 p-4">
      <div className="flex items-center justify-between gap-3 mb-3">
        <h4 className="text-sm font-semibold text-slate-900 dark:text-
slate-100 inline-flex items-center gap-2">
          <FolderOpen className="h-4 w-4 text-slate-500 dark:text-slate-
400" />
          {label}
        </h4>

        <div className="text-xs text-slate-500 dark:text-slate-400">
          {selectedIds.length} selected
        </div>
```

```
      </div>

      {/* Selected Files Section */}
      {selectedAttachments.length > 0 && (
        <div className="mb-4">
          <div className="text-xs font-medium text-slate-700 dark:text-
slate-300 mb-2">
            Selected files ({selectedAttachments.length})
          </div>
          <div className="space-y-2 max-h-48 overflow-y-auto">
            {selectedAttachments.map((file) => {
              const fileUrl = getFileUrl(file);

              return (
                <div
                  key={file.id}
                  className="flex items-center justify-between gap-2
rounded-lg bg-emerald-50 dark:bg-emerald-900/20 p-2 border
border-emerald-200 dark:border-emerald-800"
                >
                  <div className="flex items-center gap-2 min-w-0 flex-1">
                    <FileText className="h-4 w-4 text-emerald-600 dark:text-
emerald-400 flex-shrink-0" />
                    <div className="min-w-0 flex-1">
                      {fileUrl ? (
                        <a
                          href={fileUrl}
                          target="_blank"
                          rel="noopener noreferrer"
```

```
                    className="text-sm text-emerald-700 dark:text-emerald-300 hover:underline truncate block"
                    title={file.file_name}
                  >
                    {file.file_name}
                  </a>
                ) : (
                  <span className="text-sm text-slate-700 dark:text-slate-300 truncate block">
                    {file.file_name}
                  </span>
                )}
                {file.description && (
                  <div className="text-xs text-slate-500 dark:text-slate-400 truncate">
                    {file.description.replace(/<[^>]*>/g, "")}
                  </div>
                )}
              </div>
            </div>
            <button
              type="button"
              onClick={() => removeSelectedAttachment(file.id)}
              className="flex-shrink-0 p-1 rounded-md hover:bg-red-100 dark:hover:bg-red-900/30 text-red-600 dark:text-red-400 transition-colors"
              title="Remove file"
            >
              <X className="h-4 w-4" />
```

```
                </button>
              </div>
            );
          })}
        </div>
      </div>
    )}

    {/* Add More Files Button */}
    {!showAvailable && (
      <button
        type="button"
        onClick={() => setShowAvailable(true)}
        className="w-full mt-2 px-3 py-2 rounded-lg border border-
dashed border-slate-300 dark:border-slate-600 text-sm text-emerald-
600 dark:text-emerald-400 hover:bg-emerald-50 dark:hover:bg-
emerald-900/20 transition-colors flex items-center justify-center gap-2"
      >
        <Plus className="h-4 w-4" />
        Add more files
      </button>
    )}

    {/* Available Files Section - Only shown when adding */}
    {showAvailable && (
      <div className="mt-3">
        <div className="flex items-center justify-between mb-2">
          <div className="text-xs font-medium text-slate-700 dark:text-
slate-300">
```

```
            Add files
          </div>
          <button
            type="button"
            onClick={() => {
              setShowAvailable(false);
              setSearch("");
            }}
            className="text-xs text-slate-500 hover:text-slate-700
dark:text-slate-400 dark:hover:text-slate-300"
          >
            Cancel
          </button>
        </div>

        <div className="relative mb-3">
          <Search className="absolute left-3 top-1/2 -translate-y-1/2 h-
4 w-4 text-slate-400" />
          <input
            type="text"
            placeholder="Search files..."
            value={search}
            onChange={(e) => setSearch(e.target.value)}
            className="w-full pl-10 pr-4 py-2 rounded-lg border border-
slate-200 dark:border-slate-700 bg-white dark:bg-slate-950 text-sm
text-slate-900 dark:text-slate-100 focus:outline-none focus:ring-2
focus:ring-emerald-500"
          />
        </div>
```

```
        <div className="max-h-56 overflow-y-auto space-y-2 border
border-slate-100 dark:border-slate-800 rounded-lg p-2">
          {loading ? (
            <div className="text-sm text-slate-500 dark:text-slate-400
py-4 text-center">
              Loading attachments...
            </div>
          ) : filteredAvailable.length === 0 ? (
            <div className="text-sm text-slate-500 dark:text-slate-400
py-4 text-center">
              {search ? "No matching files found" : "No more files available
to add"}
            </div>
          ) : (
            filteredAvailable.map((file) => {
              const fileUrl = getFileUrl(file);

              return (
                <button
                  key={file.id}
                  type="button"
                  onClick={() => addAttachment(file.id)}
                  className="w-full text-left flex items-start gap-3
rounded-lg px-3 py-2 hover:bg-slate-50 dark:hover:bg-slate-800
transition-colors"
                >
                  <FileText className="h-4 w-4 text-slate-400 flex-shrink-0
mt-0.5" />
```

```
                <div className="min-w-0 flex-1">
                  <div className="text-sm font-medium text-slate-900
dark:text-slate-100 break-words">
                    {file.file_name}
                  </div>
                  {file.description && (
                    <div className="text-xs text-slate-500 dark:text-slate-
400 line-clamp-2">
                      {file.description.replace(/<[^>]*>/g, "")}
                    </div>
                  )}
                </div>
                <Plus className="h-4 w-4 text-emerald-500 flex-shrink-0"
/>
              </button>
            );
          })
        )}
      </div>
    </div>
  )}

  {/* Remove All Button */}
  {selectedIds.length > 0 && !showAvailable && (
    <div className="mt-3 flex justify-end">
      <button
        type="button"
        onClick={clearAll}
        className="text-xs px-3 py-1.5 rounded-lg bg-red-50
```

hover:bg-red-100 dark:bg-red-900/20 dark:hover:bg-red-900/30 text-red-600 dark:text-red-400 transition-colors"
>
Remove all files
</button>

)}

);
}
this is code for my attachmentactivityselector
i also uploaded queries and programmanagement page
the layout is good but what i want is when i edit activity i dont want to see already assigned files in dropdown list tell me what is missing how to solve it

Your **layout code is correct**.
The most likely thing **missing** is:

✅ Root cause: `selectedIds` type mismatch (string vs number)

In your `ActivityAttachmentSelector`, every attachment id is normalized as a **number**:

TypeScript

and your filtering logic is:

```
const selectedAttachments = useMemo(() => {
  return attachments.filter(attachment => selectedIds.includes(attachment.id));
}, [attachments, selectedIds]);

const availableAttachments = useMemo(() => {
  return attachments.filter(attachment => !selectedIds.includes(attachment.id));
}, [attachments, selectedIds]);
```

This works **ONLY IF** `selectedIds` is also `number[]`.

❌ What is probably happening in edit mode

When you open **Edit Activity**, your existing attachments probably come from GraphQL like:

‹/› TypeScript

GraphQL `ID` is often a **string**.

So in parent form you may be setting:

‹/› TypeScript

But in selector:

```
attachment.id === 12          // number
```

TypeScript

So:

- already assigned files are **not detected as selected**
- they **still appear in dropdown**
- sometimes selected section may also behave weird

✅ Fix (important)

1) Make sure parent always passes `number[]`

Where you populate form data for **edit activity**, convert attachment ids to numbers.

Change this pattern:

TypeScript

To this:

TypeScript

---

2) Also make selector defensive (best practice)

Even if parent sends strings by mistake, make selector safe.

Update your selector like this:

```
const normalizedSelectedIds = useMemo(() => {
  return (selectedIds || []).map((id) => Number(id)).filter((id) => !Number.isNaN(id));
```

TypeScript

Then replace everywhere:

Before:

TypeScript

After:

TypeScript

✅ Exact changes in your component

Replace this:

```
const selectedAttachments = useMemo(() => {
  return attachments.filter(attachment => selectedIds.includes(attachment.id));
}, [attachments, selectedIds]);

const availableAttachments = useMemo(() => {
  return attachments.filter(attachment => !selectedIds.includes(attachment.id));
}, [attachments, selectedIds]);
```

With this:

```
const normalizedSelectedIds = useMemo(() => {
  return (selectedIds || [])
    .map((id) => Number(id))
    .filter((id) => !Number.isNaN(id));
}, [selectedIds]);

const selectedAttachments = useMemo(() => {
  return attachments.filter((attachment) =>
    normalizedSelectedIds.includes(attachment.id)
  );
}, [attachments, normalizedSelectedIds]);

const availableAttachments = useMemo(() => {
  return attachments.filter((attachment) =>
    !normalizedSelectedIds.includes(attachment.id)
  );
}, [attachments, normalizedSelectedIds]);
```

Also update add/remove functions to use normalized ids safely

Replace:

```
function addAttachment(id: number) {
  if (!selectedIds.includes(id)) {
    onChange([...selectedIds, id]);
  }
  setShowAvailable(false);
  setSearch("");
}

function removeSelectedAttachment(id: number) {
  onChange(selectedIds.filter((x) => x !== id));
}
```

With:

```
function addAttachment(id: number) {
  if (!normalizedSelectedIds.includes(id)) {
    onChange([...normalizedSelectedIds, id]);
  }
  setShowAvailable(false);
  setSearch("");
}

function removeSelectedAttachment(id: number) {
  onChange(normalizedSelectedIds.filter((x) => x !== id));
}
```

✅ Most important place to fix in `program-management/page.tsx`

When you open **edit activity**, find where you do something like:

```
setFormProgram({
  ...
  attachmentIds: activity.attachments?.map((a: any) => a.id) || [],
``
```

Change it to:

```
setFormProgram({
  ...
  attachmentIds: activity.attachments?.map((a: any) => Number(a.id)).filter(Boolean) || [],
``
```

✅ Why this solves your issue

Because then:

- assigned file ids = `[12, 15]`
- attachment list ids = `12, 15`

So:

TypeScript

correctly returns `false` for already assigned files

➡️ therefore they **won't show in dropdown list**

🔥 My strong guess for your case

Since your GraphQL data uses `attachments { id ... }` in `PROGRAM_BY_ID` and GraphQL `ID` values often come as strings Pasted code, and your program management page is the place where activity edit state is built Pasted text (2), the bug is almost certainly:

> **edit form is storing attachment IDs as strings, while selector compares against numeric IDs**

✅ Best final solution (do both)

1. Fix parent edit form:

TypeScript

2. Make selector robust:

use `normalizedSelectedIds` inside component

If you want, next I can give you the **exact code block from your** `program-management/page.tsx` **to replace** for the **edit activity form** (just the precise snippet, no guessing).

Sources

tell me every change step by step with propar path

Yes — I'll give you the **proper path + exact changes step by step**.

Your issue is almost certainly:

> **In edit activity mode, already attached files are coming as string IDs from GraphQL, but your selector compares against numeric IDs.**

So the dropdown still shows already assigned files.

✅ What you need to change

You need to fix it in **2 places**:

1. `components/ActivityAttachmentSelector.tsx`
   → make selector robust by normalizing `selectedIds`

2. `app/program-management/page.tsx`
   → when opening **Edit Activity**, store `attachmentIds` as **number[]**, not string[]

✅ STEP 1 — Update your selector component

📍 File path

Bash

(If your file is under `app/components`, then use that actual path. Based on your imports, it looks like this:)

TypeScript

So most likely:

Bash

✅ Change 1A: Add normalized selected IDs

Find this section in your selector:

```
// Get currently selected attachments with full details
const selectedAttachments = useMemo(() => {
  return attachments.filter(attachment => selectedIds.includes(attachment.id));
}, [attachments, selectedIds]);

// Filter out already selected files from the available list
const availableAttachments = useMemo(() => {
  return attachments.filter(attachment => !selectedIds.includes(attachment.id));
}, [attachments, selectedIds]);
```

🔁 Replace it with this:

```
// Normalize selected IDs (important for edit mode because GraphQL IDs may come as strings)
const normalizedSelectedIds = useMemo(() => {
  return (selectedIds || [])
    .map((id) => Number(id))
    .filter((id) => !Number.isNaN(id));
}, [selectedIds]);

// Get currently selected attachments with full details
const selectedAttachments = useMemo(() => {
  return attachments.filter((attachment) =>
    normalizedSelectedIds.includes(attachment.id)
  );
}, [attachments, normalizedSelectedIds]);

// Filter out already selected files from the available list
const availableAttachments = useMemo(() => {
```

```
    return attachments.filter((attachment) =>
      !normalizedSelectedIds.includes(attachment.id)
    );
  }, [attachments, normalizedSelectedIds]);
```

✅ Why this is needed

Your `normalizeAttachment()` makes every attachment ID a **number**:

TypeScript

But when editing activity, GraphQL often gives:

TypeScript

So:

- selected IDs = `["12", "15"]` (strings)
- fetched attachments = `[12, 15]` (numbers)

Then this fails:

TypeScript

So already selected files still appear in dropdown.

✅ STEP 2 — Update add/remove logic in selector

📍 Same file

Bash

Find this:

```
function addAttachment(id: number) {
  if (!selectedIds.includes(id)) {
    onChange([...selectedIds, id]);
  }
  setShowAvailable(false);
  setSearch("");
}

function removeSelectedAttachment(id: number) {
  onChange(selectedIds.filter((x) => x !== id));
}
```

🔁 Replace with this:

```
function addAttachment(id: number) {
  if (!normalizedSelectedIds.includes(id)) {
    onChange([...normalizedSelectedIds, id]);
  }
  setShowAvailable(false);
  setSearch("");
}

function removeSelectedAttachment(id: number) {
  onChange(normalizedSelectedIds.filter((x) => x !== id));
}
```

✅ Optional but recommended: update clearAll

This is fine already:

```
function clearAll() {
  onChange([]);
```

TypeScript

No need to change.

✅ STEP 3 — Fix the edit activity form in program management page

This is the **most important parent-side fix**.

📍 File path

```bash
```

You shared this file already and it imports `ActivityAttachmentSelector` Pasted text (2)

✅ What to find

Search in VS Code inside this file for:

```typescript
```

or

```typescript
```

or

```typescript
```

inside the **Edit Activity** logic.

You are looking for code similar to this:

```
setFormProgram({
  ...
  attachmentIds: activity.attachments?.map((a: any) => a.id) || [],
``
```

TypeScript

or maybe:

```
```

TypeScript

or any version where IDs are copied directly from `activity.attachments`.

✅ STEP 4 — Convert attachment IDs to numbers when opening edit activity

Replace this kind of code:

```
```

TypeScript

With this:

```
attachmentIds: activity.attachments?.map((a: any) => Number(a.id)).filter((id: number) => !Number
```

TypeScript

✅ Example full edit form snippet

If your edit activity code looks like this:

```
setFormProgram({
  name: activity.name || "",
  description: activity.description || "",
  type: activity.type || "",
  deadline: toInputDateTime(activity.deadline),
  attachmentIds: activity.attachments?.map((a: any) => a.id) || [],
});
```

Change it to:

```
setFormProgram({
  name: activity.name || "",
  description: activity.description || "",
  type: activity.type || "",
  deadline: toInputDateTime(activity.deadline),
  attachmentIds:
    activity.attachments
      ?.map((a: any) => Number(a.id))
```

```
        .filter((id: number) => !Number.isNaN(id)) || [],
});
```

✅ STEP 5 — Check the prop passed into selector

Still in:

📍 File path

```bash
</> Bash
```

Search for:

```typescript
</> TypeScript
```

You should have something like:

```
<ActivityAttachmentSelector
  selectedIds={formProgram.attachmentIds || []}
  onChange={(ids) =>
    setFormProgram((prev: any) => ({ ...prev, attachmentIds: ids }))
```

TypeScript

✅ This is correct

If it already looks like this, **no change needed**.

But if you are doing something like:

TypeScript

or:

TypeScript

❌ then remove that.

✅ Correct version should be:

```
<ActivityAttachmentSelector
  selectedIds={formProgram.attachmentIds || []}
  onChange={(ids) =>
    setFormProgram((prev: any) => ({
```

```
        ...prev,
        attachmentIds: ids,
      }))
    }
  />
```

✅ STEP 6 — Make sure create/update activity mutation sends integer array

Still in:

📍 File path

```bash
```

When you save activity, you probably call:

- `CREATE_ACTIVITY_MUTATION`
- `UPDATE_ACTIVITY_MUTATION`

Search for:

```typescript
```

inside your `createActivity(...)` and `updateActivity(...)` functions.

If you currently do this:

```
</> TypeScript
```

That might still work **if backend accepts Int list**.

But safest is:

```
attachments: (payload.attachmentIds || []).map((id: any) => Number(id)).filter((id: number) => !N
</> TypeScript
```

Example:

Before:

```
await postGraphQL(UPDATE_ACTIVITY_MUTATION, {
  id: getIntFromString(activityId),
  name: payload.name,
  description: payload.description,
  attachments: payload.attachmentIds || [],
});
```

After:

```
await postGraphQL(UPDATE_ACTIVITY_MUTATION, {
  id: getIntFromString(activityId),
  name: payload.name,
  description: payload.description,
  attachments:
    (payload.attachmentIds || [])
      .map((id: any) => Number(id))
      .filter((id: number) => !Number.isNaN(id)),
});
```

✅ STEP 7 — Final version of `ActivityAttachmentSelector.tsx`

Below is the **only part you need to replace** in your selector.

📍 File path

```
Bash
```

🔁 Replace these sections exactly

A) Replace selected/available logic with:

```
// Normalize selected IDs (important for edit mode because GraphQL IDs may come as strings)
const normalizedSelectedIds = useMemo(() => {
  return (selectedIds || [])
    .map((id) => Number(id))
    .filter((id) => !Number.isNaN(id));
}, [selectedIds]);

// Get currently selected attachments with full details
const selectedAttachments = useMemo(() => {
  return attachments.filter((attachment) =>
    normalizedSelectedIds.includes(attachment.id)
  );
}, [attachments, normalizedSelectedIds]);

// Filter out already selected files from the available list
const availableAttachments = useMemo(() => {
  return attachments.filter((attachment) =>
    !normalizedSelectedIds.includes(attachment.id)
  );
}, [attachments, normalizedSelectedIds]);
```

B) Replace add/remove functions with:

```
function addAttachment(id: number) {
  if (!normalizedSelectedIds.includes(id)) {
    onChange([...normalizedSelectedIds, id]);
  }
  setShowAvailable(false);
  setSearch("");
}
```

```
function removeSelectedAttachment(id: number) {
  onChange(normalizedSelectedIds.filter((x) => x !== id));
}
```

✅ STEP 8 — What to check in browser after changes

After saving:

1. Open **Program Management**
2. Click **Edit Activity**
3. If activity already has 2 files assigned
4. Open **Add more files**
5. Those 2 files should **NOT** appear in dropdown

✅ Quick debug tip (very useful)

If still not working, temporarily add this inside selector:

📍 File path

```bash
```

Add below `normalizedSelectedIds`:

```typescript
useEffect(() => {
  console.log("selectedIds raw:", selectedIds);
  console.log("selectedIds normalized:", normalizedSelectedIds);
  console.log("attachments ids:", attachments.map((a) => a.id));
}, [selectedIds, normalizedSelectedIds, attachments]);
```

You should see:

```typescript
selectedIds raw: ["12", "15"]      // or [12, 15]
selectedIds normalized: [12, 15]
```

Then filtering will work correctly.

✅ Most likely exact missing line in your app

Because your `PROGRAM_BY_ID` query returns activity attachments under:

```
attachments {
  id
  fileName
  description
  assetType
  sharepointUrl
  externalUrl
}
```

inside `app/program-management/page.tsx` Pasted code and that page imports your selector Pasted text (2), the most likely missing fix is:

```
attachmentIds: activity.attachments?.map((a: any) => Number(a.id)).filter((id: number) => !Number
```

TypeScript

✅ Best practice summary

Must change:

- `components/ActivityAttachmentSelector.tsx`
- `app/program-management/page.tsx`

Key rule:

> **Keep `attachmentIds` as `number[]` everywhere**

🚀 If you want next:

I can now give you the **exact code block for** `app/program-management/page.tsx`:

- where to search
- what exact snippet to replace
- and the **full edit activity + create/update activity code changes** in **copy-paste format**

If you want, send me just:

“**give me exact page.tsx replace code**”

and I’ll give you only the precise replacement blocks.

Sources