

Table of Contents

.devcontainer\devcontainer.json

```
{
  "name": "Python 3",
  // Or use a Dockerfile or Docker Compose file. More info: https://containers.dev/guide/dockerfile
  "image": "mcr.microsoft.com/devcontainers/python:1-3.11-bullseye",
  "customizations": {
    "codespaces": {
      "openFiles": [
        "README.md",
        "AutoGroq/main.py"
      ]
    },
    "vscode": {
      "settings": {},
      "extensions": [
        "ms-python.python",
        "ms-python.vscode-pylance"
      ]
    },
    "updateContentCommand": "[ -f packages.txt ] && sudo apt update && sudo apt upgrade -y && sudo xargs apt install -y <packages.txt; [ -f requirements.txt ] && pip3 install --user -r requirements.txt; pip3 install --user streamlit; echo '☐ Packages installed and Requirements met'",
    "postAttachCommand": {
      "server": "streamlit run AutoGroq/pages/main.py --server.enableCORS false --server.enableXsrfProtection false"
    },
    "portsAttributes": {
      "8501": {
        "label": "Application",
        "onAutoForward": "openPreview"
      }
    },
    "forwardPorts": [
      8501
    ]
  }
}
```

AutoGroq\agent_management.py

```
import base64
import streamlit as st
import requests
from bs4 import BeautifulSoup
import os
import re

from api_utils import send_request_to_groq_api
from file_utils import create_agent_data
from ui_utils import get_api_key, update_discussion_and_whiteboard

def agent_button_callback(agent_index):
    # Callback function to handle state update and logic execution
    def callback():
        st.session_state['selected_agent_index'] = agent_index
```

```

agent = st.session_state.agents[agent_index]

agent_name = agent['config']['name'] if 'config' in agent and 'name' in agent['config'] else "
st.session_state['form_agent_name'] = agent_name
st.session_state['form_agent_description'] = agent['description'] if 'description' in agent else "
# Directly call process_agent_interaction here if appropriate
process_agent_interaction(agent_index)
return callback

def delete_agent(index):
if 0 <= index < len(st.session_state.agents):
expert_name = st.session_state.agents[index]['expert_name']
del st.session_state.agents[index]

# Get the full path to the JSON file
agents_dir = os.path.abspath(os.path.join(os.path.dirname(__file__), "agents"))
json_file = os.path.join(agents_dir, f"{expert_name}.json")

# Delete the corresponding JSON file
if os.path.exists(json_file):
os.remove(json_file)
print(f"JSON file deleted: {json_file}")
else:
print(f"JSON file not found: {json_file}")

st.experimental_rerun()

def display_agents():
if "agents" in st.session_state and st.session_state.agents:
st.sidebar.title("Your Agents")
st.sidebar.subheader("Click to interact")
for index, agent in enumerate(st.session_state.agents):
agent_name = agent["config"]["name"]
if not agent_name:
agent_name = f"Unnamed Agent {index + 1}"
if "next_agent" in st.session_state and st.session_state.next_agent == agent_name:
button_style = """
<style>
div[data-testid="stButton"] > button[kind="secondary"] {
background-color: green !important;
color: white !important;
}
</style>
"""
st.sidebar.markdown(button_style, unsafe_allow_html=True)
st.sidebar.button(agent_name, key=f"agent_{index}", on_click=agent_button_callback(index))
else:
st.sidebar.warning("AutoGroq creates your entire team of downloadable, importable Autogen and
CrewAI agents from a simple task request, including an Autogen workflow file! \n\nYou can test your
agents with this interface.\n\nNo agents have yet been created. Please enter a new request.\n\n Video
demo: https://www.youtube.com/watch?v=Jm4UYVTwgBI&t=84s")

def download_agent_file(expert_name):
# Format the expert_name
formatted_expert_name = re.sub(r'^a-zA-Z0-9\s', "", expert_name) # Remove non-alphanumeric
characters
formatted_expert_name = formatted_expert_name.lower().replace(' ', '_') # Convert to lowercase and
replace spaces with underscores

# Get the full path to the agent JSON file

```

```

agents_dir = os.path.abspath(os.path.join(os.path.dirname(__file__), "agents"))
json_file = os.path.join(agents_dir, f"{formatted_expert_name}.json")

# Check if the file exists
if os.path.exists(json_file):
# Read the file content
with open(json_file, "r") as f:
file_content = f.read()

# Encode the file content as base64
b64_content = base64.b64encode(file_content.encode()).decode()

# Create a download link
href = f"<a href='data:application/json;base64,{b64_content}'"
download="{formatted_expert_name}.json">Download {formatted_expert_name}.json</a>"
st.markdown(href, unsafe_allow_html=True)
else:
st.error(f"File not found: {json_file}")

def process_agent_interaction(agent_index):
# Retrieve agent information using the provided index
agent = st.session_state.agents[agent_index]

# Preserve the original "Act as" functionality
agent_name = agent["config"]["name"]
description = agent["description"]
user_request = st.session_state.get('user_request', "")
user_input = st.session_state.get('user_input', "")
rephrased_request = st.session_state.get('rephrased_request', "")

reference_url = st.session_state.get('reference_url', "")
url_content = ""
if reference_url:
try:
response = requests.get(reference_url)
response.raise_for_status()
soup = BeautifulSoup(response.text, 'html.parser')
url_content = soup.get_text()
except requests.exceptions.RequestException as e:
print(f"Error occurred while retrieving content from {reference_url}: {e}")

request = f"Act as the {agent_name} who {description}."
if user_request:
request += f" Original request was: {user_request}."
if rephrased_request:
request += f" You are helping a team work on satisfying {rephrased_request}."
if user_input:
request += f" Additional input: {user_input}. Reference URL content: {url_content}."
if st.session_state.discussion:
request += f" The discussion so far has been {st.session_state.discussion[-50000:]}"

api_key = get_api_key()
if api_key is None:
st.error("API key not found. Please enter your API key.")
return

response = send_request_to_groq_api(agent_name, request, api_key)

if response:
update_discussion_and_whiteboard(agent_name, response, user_input)

```

```
# Additionally, populate the sidebar form with the agent's information
st.session_state['form_agent_name'] = agent_name
st.session_state['form_agent_description'] = description
st.session_state['selected_agent_index'] = agent_index # Keep track of the selected agent for
potential updates/deletes
```

AutoGroq\api_utils.py

```
import requests
import streamlit as st
import time

def make_api_request(url, data, headers, api_key):
    time.sleep(2) # Throttle the request to ensure at least 2 seconds between calls
    try:
        if not api_key:
            raise ValueError("GROQ_API_KEY not found. Please enter your API key.")
        headers["Authorization"] = f"Bearer {api_key}"
        response = requests.post(url, json=data, headers=headers)
        if response.status_code == 200:
            return response.json()
        else:
            print(f"Error: API request failed with status {response.status_code}, response: {response.text}")
            return None
    except requests.RequestException as e:
        print(f"Error: Request failed {e}")
        return None

def create_agent_data(expert_name, description, skills, tools):
    autogen_agent_data = {
        "type": "assistant",
        "config": {
            "name": expert_name,
            "llm_config": {
                "config_list": [{"model": "gpt-4-1106-preview"}],
                "temperature": 0.1,
                "timeout": 600,
                "cache_seed": 42
            },
            "human_input_mode": "NEVER",
            "max_consecutive_auto_reply": 8,
            "system_message": f"You are a helpful assistant that can act as {expert_name} who {description}."
        },
        "description": description,
        "skills": skills,
        "tools": tools
    }
    crewai_agent_data = {
        "name": expert_name,
        "description": description,
        "skills": skills,
        "tools": tools,
        "verbose": True,
        "allow_delegation": True
    }
    return autogen_agent_data, crewai_agent_data
```

```

def send_request_to_groq_api(expert_name, request, api_key):
    if api_key is None:
        if 'api_key' in st.session_state:
            api_key = st.session_state.api_key
        else:
            st.error("API key not found. Please enter your API key.")
            return None

    url = "https://api.groq.com/openai/v1/chat/completions"
    data = {
        "model": st.session_state.model,
        "temperature": 0.5,
        "max_tokens": st.session_state.max_tokens,
        "top_p": 1,
        "stop": "TERMINATE",
        "messages": [
            {
                "role": "system",
                "content": "You are a chatbot capable of anything and everything."
            },
            {
                "role": "user",
                "content": request
            }
        ]
    }
    headers = {
        "Authorization": f"Bearer {api_key}",
        "Content-Type": "application/json"
    }

    try:
        response = make_api_request(url, data, headers, api_key)
        if response:
            if "choices" in response and len(response["choices"]) > 0:
                message_content = response["choices"][0]["message"]["content"]
                return message_content
            else:
                print("Error: Unexpected response format from the Groq API.")
                print("Response data:", response)
                return None
        except Exception as e:
            print(f"Error occurred while making the request to Groq API: {str(e)}")
            return None

def extract_code_from_response(response):
    code_pattern = r"```(?:.|\n)*```"
    code_blocks = re.findall(code_pattern, response, re.DOTALL)

    html_pattern = r"<html.*?>.*?</html>"
    html_blocks = re.findall(html_pattern, response, re.DOTALL | re.IGNORECASE)

    js_pattern = r"<script.*?>.*?</script>"
    js_blocks = re.findall(js_pattern, response, re.DOTALL | re.IGNORECASE)

    css_pattern = r"<style.*?>.*?</style>"
    css_blocks = re.findall(css_pattern, response, re.DOTALL | re.IGNORECASE)

    all_code_blocks = code_blocks + html_blocks + js_blocks + css_blocks
    unique_code_blocks = list(set(all_code_blocks))

```

```
return "\n\n".join(unique_code_blocks)
```

AutoGroq\custom_button.py

```
import streamlit as st
import streamlit.components.v1 as components

def custom_button(expert_name, index, next_agent):
    button_style = """
<style>
.custom-button {
background-color: #f0f0f0;
color: black;
padding: 0.5rem 1rem;
border: none;
border-radius: 0.25rem;
cursor: pointer;
}
.custom-button.active {
background-color: green;
color: white;
}
</style>
"""

    button_class = "custom-button active" if next_agent == expert_name else "custom-button"
    button_html = f'<button class="{button_class}">{expert_name}</button>'

    components.html(button_style + button_html, height=50)

def agent_button(expert_name, index, next_agent):
    custom_button(expert_name, index, next_agent)
```

AutoGroq\file_utils.py

```
# file_utils.py
import os
import json
import re

def sanitize_text(text):
    # Remove non-ASCII characters
    text = re.sub(r'[^\x00-\x7F]+', '', text)
    # Remove non-alphanumeric characters except for standard punctuation
    text = re.sub(r'[^\a-zA-Z0-9\s.,!?:;"'-]+', '', text)
    return text

def create_agent_data(expert_name, description, skills=None, tools=None):
    # Format the expert_name
    formatted_expert_name = sanitize_text(expert_name)
    formatted_expert_name = formatted_expert_name.lower().replace(' ', '_')
    # Sanitize the description
    sanitized_description = sanitize_text(description)
    # Sanitize the skills and tools
    sanitized_skills = [sanitize_text(skill) for skill in skills] if skills else []
    sanitized_tools = [sanitize_text(tool) for tool in tools] if tools else []
    # Create the agent data
    agent_data = {
```

```

"type": "assistant",
"config": {
"name": expert_name, # Use the original expert_name here
"llm_config": {
"config_list": [
{
"model": "gpt-4-1106-preview"
}
],
"temperature": 0.1,
"timeout": 600,
"cache_seed": 42
},
"human_input_mode": "NEVER",
"max_consecutive_auto_reply": 8,
"system_message": f"You are a helpful assistant that can act as {expert_name} who {sanitized_description}."
},
"description": description, # Use the original description here
"skills": sanitized_skills,
"tools": sanitized_tools
}
crewai_agent_data = {
"name": expert_name,
"description": description,
"skills": sanitized_skills,
"tools": sanitized_tools,
"verbose": True,
"allow_delegation": True
}
return agent_data, crewai_agent_data

```

```

def create_workflow_data(workflow):
# Sanitize the workflow name
sanitized_workflow_name = sanitize_text(workflow["name"])
sanitized_workflow_name = sanitized_workflow_name.lower().replace(' ', '_')

return workflow

```

AutoGroq\main.py

```

import os
import streamlit as st
from agent_management import display_agents
from ui_utils import get_api_key, display_api_key_input, display_discussion_and_whiteboard,
display_download_button, display_user_input, display_rephrased_request,
display_reset_and_upload_buttons, display_user_request_input, rephrase_prompt,
get_agents_from_text, extract_code_from_response, get_workflow_from_agents

def main():
st.markdown("""
<style>
/* General styles */
body {
font-family: Arial, sans-serif;
background-color: #f0f0f0;
}

```

```
/* Sidebar styles */
.sidebar .sidebar-content {
background-color: #ffffff !important;
padding: 20px !important;
border-radius: 5px !important;
box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1) !important;
}
```

```
.sidebar .st-emotion-cache-k7vsyb h1 {
font-size: 12px !important;
font-weight: bold !important;
color: #007bff !important;
}
```

```
.sidebar h2 {
font-size: 16px !important;
color: #666666 !important;
}
```

```
.sidebar .stButton button {
display: block !important;
width: 100% !important;
padding: 10px !important;
background-color: #007bff !important;
color: #ffffff !important;
text-align: center !important;
text-decoration: none !important;
border-radius: 5px !important;
transition: background-color 0.3s !important;
}
```

```
.sidebar .stButton button:hover {
background-color: #0056b3 !important;
}
```

```
.sidebar a {
display: block !important;
color: #007bff !important;
text-decoration: none !important;
}
```

```
.sidebar a:hover {
text-decoration: underline !important;
}
```

```
/* Main content styles */
.main .stTextInput input {
width: 100% !important;
padding: 10px !important;
border: 1px solid #cccccc !important;
border-radius: 5px !important;
}
```

```
.main .stTextArea textarea {
width: 100% !important;
padding: 10px !important;
border: 1px solid #cccccc !important;
border-radius: 5px !important;
resize: none !important;
}
```

```
.main .stButton button {
```



```
padding: 10px 20px !important;
background-color: #dc3545 !important;
color: #ffffff !important;
border: none !important;
border-radius: 5px !important;
cursor: pointer !important;
transition: background-color 0.3s !important;
}
```

```
.main .stButton button:hover {
background-color: #c82333 !important;
}
```

```
.main h1 {
font-size: 32px !important;
font-weight: bold !important;
color: #007bff !important;
}
```

```
/* Model selection styles */
.main .stSelectbox select {
width: 100% !important;
padding: 10px !important;
border: 1px solid #cccccc !important;
border-radius: 5px !important;
}
```

```
/* Error message styles */
.main .stAlert {
color: #dc3545 !important;
}
</style>
""", unsafe_allow_html=True)
```

```
model_token_limits = {
'mixtral-8x7b-32768': 32768,
'lama3-70b-8192': 8192,
'lama3-8b-8192': 8192,
'gemma-7b-it': 8192
}
```

```
api_key = get_api_key()
if api_key is None:
api_key = display_api_key_input()
if api_key is None:
st.warning("Please enter your GROQ_API_KEY to use the app.")
return
```

```
col1, col2, col3 = st.columns([2, 5, 3])
with col3:
selected_model = st.selectbox(
'Select Model',
options=list(model_token_limits.keys()),
index=0,
key='model_selection'
)
st.session_state.model = selected_model
st.session_state.max_tokens = model_token_limits[selected_model]

st.title("AutoGroq")
```

```

# Ensure default values for session state are set
if "discussion" not in st.session_state:
    st.session_state.discussion = ""
if "whiteboard" not in st.session_state:
    st.session_state.whiteboard = "" # Apply CSS classes to elements

with st.sidebar:
    st.markdown('<div class="sidebar">', unsafe_allow_html=True)
    st.markdown('</div>', unsafe_allow_html=True)

display_agents()

with st.container():
    st.markdown('<div class="main">', unsafe_allow_html=True)
    display_user_request_input()
    display_rephrased_request()
    st.markdown('<div class="discussion-whiteboard">', unsafe_allow_html=True)
    display_discussion_and_whiteboard()
    st.markdown('</div>', unsafe_allow_html=True)
    st.markdown('<div class="user-input">', unsafe_allow_html=True)
    display_user_input()
    st.markdown('</div>', unsafe_allow_html=True)
    display_reset_and_upload_buttons()
    st.markdown('</div>', unsafe_allow_html=True)

display_download_button()

if __name__ == "__main__":
    main()

```

AutoGroq\ui_utils.py

```

import streamlit as st
import os

def get_api_key():
    if 'api_key' in st.session_state:
        api_key = st.session_state.api_key
        print(f"API Key from session state: {api_key}")
        return api_key
    elif "GROQ_API_KEY" in os.environ:
        api_key = os.environ["GROQ_API_KEY"]
        print(f"API Key from environment variable: {api_key}")
        return api_key
    else:
        return None

def display_api_key_input():
    api_key = get_api_key()
    if api_key is None:
        if 'api_key' not in st.session_state:
            st.session_state.api_key = ""
        api_key = st.text_input("Enter your GROQ_API_KEY:", type="password",
                                value=st.session_state.api_key, key="api_key_input")
        if api_key:
            st.session_state.api_key = api_key
            st.success("API key entered successfully.")
            print(f"API Key: {api_key}")
            return api_key

```

```

import io
import json
import pandas as pd
import re
import time
import zipfile
from api_utils import make_api_request
from file_utils import create_agent_data, sanitize_text
import datetime
import requests

def display_discussion_and_whiteboard():
    col1, col2 = st.columns(2)

    with col1:
        if "discussion_history" not in st.session_state:
            st.session_state.discussion_history = ""

        st.text_area("Most Recent Comment", value=st.session_state.get("last_comment", ""), height=400,
            key="discussion")

    with col2:
        st.text_area("Whiteboard", value=st.session_state.whiteboard, height=400, key="whiteboard")

    with st.expander("Discussion History"):
        st.write(st.session_state.discussion_history)


def display_discussion_modal():
    with st.expander("Discussion History"):
        st.write(st.session_state.discussion_history)


def display_user_input():
    user_input = st.text_area("Additional Input:", key="user_input", height=100)

    if user_input:
        url_pattern = re.compile(r'http[s]?://(?:[a-zA-Z]|[0-9]|[$-_@.&+]|[*\\(\[\]]|(?:%[0-9a-fA-F][0-9a-fA-F]))+')
        url_match = url_pattern.search(user_input)
        if url_match:
            st.session_state.reference_url = url_match.group()
        else:
            st.session_state.reference_url = " "
        else:
            st.session_state.reference_url = " "

    return user_input


def display_rephrased_request():
    st.text_area("Re-engineered Prompt:", value=st.session_state.get('rephrased_request', " "), height=100,
        key="rephrased_request_area")


def display_download_button():
    if "autogen_zip_buffer" in st.session_state and "crewai_zip_buffer" in st.session_state:
        col1, col2 = st.columns(2)
        with col1:

```

```

st.download_button(
    label="Download Autogen Files",
    data=st.session_state.autogen_zip_buffer,
    file_name="autogen_files.zip",
    mime="application/zip",
    key=f"autogen_download_button_{int(time.time())}" # Generate a unique key based on timestamp
)
with col2:
    st.download_button(
        label="Download CrewAI Files",
        data=st.session_state.crewai_zip_buffer,
        file_name="crewai_files.zip",
        mime="application/zip",
        key=f"crewai_download_button_{int(time.time())}" # Generate a unique key based on timestamp
    )
else:
    st.warning("No files available for download.")

def display_reset_and_upload_buttons():
    col1, col2 = st.columns(2)

    with col1:
        if st.button("Reset", key="reset_button"):
            # Reset specific elements without clearing entire session state
            for key in ["rephrased_request", "discussion", "whiteboard", "user_request", "user_input", "agents",
                        "zip_buffer", "crewai_zip_buffer", "autogen_zip_buffer", "uploaded_file_content", "discussion_history",
                        "last_comment", "user_api_key"]:
                if key in st.session_state:
                    del st.session_state[key]
            st.session_state.user_request = ""
            st.session_state.show_begin_button = True
            st.experimental_rerun()

    with col2:
        uploaded_file = st.file_uploader("Upload a sample .csv of your data (optional)", type="csv")

        if uploaded_file is not None:
            try:
                # Attempt to read the uploaded file as a DataFrame
                df = pd.read_csv(uploaded_file).head(5)

                # Display the DataFrame in the app
                st.write("Data successfully uploaded and read as DataFrame:")
                st.dataframe(df)

                # Store the DataFrame in the session state
                st.session_state.uploaded_data = df
            except Exception as e:
                st.error(f"Error reading the file: {e}")

def display_user_request_input():
    user_request = st.text_input("Enter your request:", key="user_request")

    if st.session_state.get("previous_user_request") != user_request:
        st.session_state.previous_user_request = user_request

    if user_request:
        if not st.session_state.get('rephrased_request'):
            handle_begin(st.session_state)

```

```

else:
    autogen_agents, crewai_agents = get_agents_from_text(st.session_state.rephrased_request)
    print(f"Debug: AutoGen Agents: {autogen_agents}")
    print(f"Debug: CrewAI Agents: {crewai_agents}")

if not autogen_agents:
    print("Error: No agents created.")
    st.warning("Failed to create agents. Please try again.")
    return

agents_data = {}
for agent in autogen_agents:
    agent_name = agent['config']['name']
    agents_data[agent_name] = agent

print(f"Debug: Agents data: {agents_data}")

workflow_data, _ = get_workflow_from_agents(autogen_agents)
print(f"Debug: Workflow data: {workflow_data}")
print(f"Debug: CrewAI agents: {crewai_agents}")

autogen_zip_buffer, crewai_zip_buffer = zip_files_in_memory(agents_data, workflow_data,
crewai_agents)
st.session_state.autogen_zip_buffer = autogen_zip_buffer
st.session_state.crewai_zip_buffer = crewai_zip_buffer
st.session_state.agents = autogen_agents

st.experimental_rerun()

def extract_code_from_response(response):
    code_pattern = r"```(?:.|\n)*```"
    code_blocks = re.findall(code_pattern, response, re.DOTALL)

    html_pattern = r"<html.*?>.*?</html>"
    html_blocks = re.findall(html_pattern, response, re.DOTALL | re.IGNORECASE)

    js_pattern = r"<script.*?>.*?</script>"
    js_blocks = re.findall(js_pattern, response, re.DOTALL | re.IGNORECASE)

    css_pattern = r"<style.*?>.*?</style>"
    css_blocks = re.findall(css_pattern, response, re.DOTALL | re.IGNORECASE)

    all_code_blocks = code_blocks + html_blocks + js_blocks + css_blocks
    unique_code_blocks = list(set(all_code_blocks))

    return "\n\n".join(unique_code_blocks)

def get_workflow_from_agents(agents):
    current_timestamp = datetime.datetime.now().isoformat()

    workflow = {
        "name": "AutoGroq Workflow",
        "description": "Workflow auto-generated by AutoGroq.",
        "sender": {
            "type": "userproxy",
            "config": {
                "name": "userproxy",
                "llm_config": False,
                "human_input_mode": "NEVER",
                "max_consecutive_auto_reply": 5,

```

```

"system_message": "You are a helpful assistant.",
"is_termination_msg": None,
"code_execution_config": {
"work_dir": None,
"use_docker": False
},
"default_auto_reply": "",
"description": None
},
"timestamp": current_timestamp,
"user_id": "default",
"skills": None
},
"receiver": {
"type": "groupchat",
"config": {
"name": "group_chat_manager",
"llm_config": {
"config_list": [
{
"model": "gpt-4-1106-preview"
}
],
"temperature": 0.1,
"cache_seed": 42,
"timeout": 600,
"max_tokens": None,
"extra_body": None
},
"human_input_mode": "NEVER",
"max_consecutive_auto_reply": 10,
"system_message": "Group chat manager",
"is_termination_msg": None,
"code_execution_config": None,
"default_auto_reply": "",
"description": None
},
"groupchat_config": {
"agents": [],
"admin_name": "Admin",
"messages": [],
"max_round": 10,
"speaker_selection_method": "auto",
"allow_repeat_speaker": True
},
"timestamp": current_timestamp,
"user_id": "default",
"skills": None
},
"type": "groupchat",
"user_id": "default",
"timestamp": current_timestamp,
"summary_method": "last"
}

```

```

for index, agent in enumerate(agents):
agent_name = agent["config"]["name"]
description = agent["description"]
formatted_agent_name = sanitize_text(agent_name).lower().replace(' ', '_')
sanitized_description = sanitize_text(description)
system_message = f"You are a helpful assistant that can act as {agent_name} who
{sanitized_description}."

```

```

if index == 0:
    other_agent_names = [sanitize_text(a['config']['name']).lower().replace(' ', '_') for a in agents[1:]]
    system_message += f" You are the primary coordinator who will receive suggestions or advice from all
    the other agents ({', '.join(other_agent_names)}). You must ensure that the final response integrates
    the suggestions from other agents or team members. YOUR FINAL RESPONSE MUST OFFER THE
    COMPLETE RESOLUTION TO THE USER'S REQUEST. When the user's request has been satisfied
    and all perspectives are integrated, you can respond with TERMINATE."

```

```

agent_config = {
    "type": "assistant",
    "config": {
        "name": formatted_agent_name,
        "llm_config": {
            "config_list": [
                {
                    "model": "gpt-4-1106-preview"
                }
            ],
            "temperature": 0.1,
            "cache_seed": 42,
            "timeout": 600,
            "max_tokens": None,
            "extra_body": None
        },
        "human_input_mode": "NEVER",
        "max_consecutive_auto_reply": 8,
        "system_message": system_message,
        "is_termination_msg": None,
        "code_execution_config": None,
        "default_auto_reply": "",
        "description": None
    },
    "timestamp": current_timestamp,
    "user_id": "default",
    "skills": None # Set skills to null only in the workflow JSON
}
workflow["receiver"]["groupchat_config"]["agents"].append(agent_config)

```

```

crewai_agents = []
for index, agent in enumerate(agents):
    agent_name = agent["config"]["name"]
    description = agent["description"]
    _, crewai_agent_data = create_agent_data(agent_name, description, agent.get("skills"),
    agent.get("tools"))
    crewai_agents.append(crewai_agent_data)

```

```

return workflow, crewai_agents

```

```

def handle_begin(session_state):
    user_request = session_state.user_request

```

```

    max_retries = 3
    retry_delay = 2 # in seconds

```

```

    for retry in range(max_retries):
        try:
            rephrased_text = rephrase_prompt(user_request)
            print(f"Debug: Rephrased text: {rephrased_text}")

```

```

    if rephrased_text:

```

```

session_state.rephrased_request = rephrased_text
break # Exit the loop if successful
else:
    print("Error: Failed to rephrase the user request.")
    st.warning("Failed to rephrase the user request. Please try again.")
    return # Exit the function if rephrasing fails
except Exception as e:
    print(f"Error occurred in handle_begin: {str(e)}")
    if retry < max_retries - 1:
        print(f"Retrying in {retry_delay} second(s)...")
        time.sleep(retry_delay)
    else:
        print("Max retries exceeded.")
        st.warning("An error occurred. Please try again.")
    return # Exit the function if max retries are exceeded

rephrased_text = session_state.rephrased_request

autogen_agents, crewai_agents = get_agents_from_text(rephrased_text)
print(f"Debug: AutoGen Agents: {autogen_agents}")
print(f"Debug: CrewAI Agents: {crewai_agents}")

if not autogen_agents:
    print("Error: No agents created.")
    st.warning("Failed to create agents. Please try again.")
    return

agents_data = {}
for agent in autogen_agents:
    agent_name = agent["config"]["name"]
    agents_data[agent_name] = agent

print(f"Debug: Agents data: {agents_data}")

workflow_data, _ = get_workflow_from_agents(autogen_agents)
print(f"Debug: Workflow data: {workflow_data}")
print(f"Debug: CrewAI agents: {crewai_agents}")

autogen_zip_buffer, crewai_zip_buffer = zip_files_in_memory(agents_data, workflow_data,
crewai_agents)
session_state.autogen_zip_buffer = autogen_zip_buffer
session_state.crewai_zip_buffer = crewai_zip_buffer
session_state.agents = autogen_agents

def get_agents_from_text(text):
    try:
        api_key = get_api_key()
    except KeyError:
        st.error("GROQ_API_KEY not found. Please enter your API key.")
    return [], []

url = "https://api.groq.com/openai/v1/chat/completions"
headers = {
    "Authorization": f"Bearer {api_key}",
    "Content-Type": "application/json"
}

groq_request = {
    "model": st.session_state.model,
    "temperature": 0.5,
    "max_tokens": st.session_state.max_tokens,

```



```
"top_p": 1,
"stop": "TERMINATE",
"messages": [
```

```
{
"role": "system",
"content": f"""
```

You are an expert system designed to identify and recommend the optimal team of experts required to fulfill this specific user's request: \$userRequest Your analysis should consider the complexity, domain, and specific needs of the request to assemble a multidisciplinary team of experts. Each recommended expert should come with a defined role, a brief description of their expertise, their skill set, and the tools they would utilize to achieve the user's goal. The first agent must be qualified to manage the entire project, aggregate the work done by all the other agents, and produce a robust, complete, and reliable solution. Return the results in JSON values labeled as expert_name, description, skills, and tools. Their 'expert_name' is their title, not their given name.

Skills and tools are arrays (one expert can have multiple skills and use multiple tools).

Return ONLY this JSON response, with no other narrative, commentary, synopsis, or superfluous remarks/text of any kind. Tools should be single-purpose methods, very specific and narrow in their scope, and not at all ambiguous (e.g.: 'add_numbers' would be good, but simply 'do_math' would be bad) Skills and tools should be all lower case with underscores instead of spaces, and they should be named per their functionality, e.g.: calculate_surface_area, or search_web

```
""",
},
{
"role": "user",
"content": text
}
]
}
```

```
response_data = make_api_request(url, groq_request, headers, api_key)
```

```
if response_data and "choices" in response_data and response_data["choices"]:
content_json_string = response_data["choices"][0].get("message", {}).get("content", "")
```

```
try:
```

```
content_json = json.loads(content_json_string)
```

```
autogen_agents = []
```

```
crewai_agents = []
```

```
if isinstance(content_json, list):
```

```
for agent_data in content_json:
```

```
if isinstance(agent_data, dict):
```

```
expert_name = agent_data.get("expert_name", "")
```

```
description = agent_data.get("description", "")
```

```
skills = agent_data.get("skills", [])
```

```
tools = agent_data.get("tools", [])
```

```
else:
```

```
expert_name = ""
```

```
description = ""
```

```
skills = []
```

```
tools = []
```

```
autogen_agent_data, crewai_agent_data = create_agent_data(expert_name, description, skills, tools)
```

```
autogen_agents.append(autogen_agent_data)
```

```
crewai_agents.append(crewai_agent_data)
```

```
elif isinstance(content_json, dict):
```

```
for expert_name, agent_data in content_json.items():
```

```
description = agent_data.get("description", "")
```

```
skills = agent_data.get("skills", [])
```

```
tools = agent_data.get("tools", [])
```

```
autogen_agent_data, crewai_agent_data = create_agent_data(expert_name, description, skills, tools)
```

```

autogen_agents.append(autogen_agent_data)
crewai_agents.append(crewai_agent_data)

return autogen_agents, crewai_agents
except json.JSONDecodeError as e:
    print(f"Error: Failed to parse JSON response: {e}, Response content: {content_json_string}")
else:
    if response_data is not None:
        print("Error: Unexpected response format from the API. Full response: ", response_data)
    else:
        print("Error: No response data received from API.")

return [], []

```

```

def rephrase_prompt(user_request):
    print("Executing rephrase_prompt()")
    api_key = get_api_key()
    if not api_key:
        st.error("API key not found. Please enter your API key.")
    return None

```

```

url = "https://api.groq.com/openai/v1/chat/completions"
refactoring_prompt = f"""
Refactor the following user request into an optimized prompt for an LLM,
focusing on clarity, conciseness, and effectiveness. Provide specific details
and examples where relevant. Do NOT reply with a direct response to the request;
instead, rephrase the request as a well-structured prompt, and return ONLY that rephrased
prompt.\n\nUser request: \"{user_request}\"\\n\\nrephrased:
"""

```

```

groq_request = {
    "model": st.session_state.model,
    "temperature": 0.5,
    "max_tokens": 100,
    "top_p": 1,
    "stop": "TERMINATE",
    "messages": [
        {
            "role": "user",
            "content": refactoring_prompt,
        },
    ],
}

```

```

headers = {
    "Authorization": f"Bearer {api_key}",
    "Content-Type": "application/json",
}

```

```

print(f"Request URL: {url}")
print(f"Request Headers: {headers}")
print(f"Request Payload: {json.dumps(groq_request, indent=2)}")

```

```

try:
    print("Sending request to Groq API...")
    response = requests.post(url, json=groq_request, headers=headers, timeout=10)
    print(f"Response received. Status Code: {response.status_code}")

```

```

if response.status_code == 200:
    print("Request successful. Parsing response...")

```

```

response_data = response.json()
print(f"Response Data: {json.dumps(response_data, indent=2)}")

if "choices" in response_data and len(response_data["choices"]) > 0:
    rephrased = response_data["choices"][0]["message"]["content"]
    return rephrased.strip()
else:
    print("Error: Unexpected response format. 'choices' field missing or empty.")
    return None
else:
    print(f"Request failed. Status Code: {response.status_code}")
    print(f"Response Content: {response.text}")
    return None
except requests.exceptions.RequestException as e:
    print(f"Error occurred while sending the request: {str(e)}")
    return None
except (KeyError, ValueError) as e:
    print(f"Error occurred while parsing the response: {str(e)}")
    print(f"Response Content: {response.text}")
    return None
except Exception as e:
    print(f"An unexpected error occurred: {str(e)}")
    return None

def update_discussion_and_whiteboard(expert_name, response, user_input):
    print("Updating discussion and whiteboard...")
    print(f"Expert Name: {expert_name}")
    print(f"Response: {response}")
    print(f"User Input: {user_input}")

    if user_input:
        user_input_text = f"\n\nAdditional Input:\n\n{user_input}\n\n"
        st.session_state.discussion_history += user_input_text

    response_text = f"{expert_name}:\n\n{response}\n\n===\n\n"
    st.session_state.discussion_history += response_text

    code_blocks = extract_code_from_response(response)
    st.session_state.whiteboard = code_blocks

    st.session_state.last_agent = expert_name
    st.session_state.last_comment = response_text
    print(f"Last Agent: {st.session_state.last_agent}")
    print(f"Last Comment: {st.session_state.last_comment}")

def zip_files_in_memory(agents_data, workflow_data, crewai_agents):
    # Create separate ZIP buffers for Autogen and CrewAI
    autogen_zip_buffer = io.BytesIO()
    crewai_zip_buffer = io.BytesIO()

    # Create a ZIP file in memory
    with zipfile.ZipFile(autogen_zip_buffer, 'w', zipfile.ZIP_DEFLATED) as zip_file:
        # Write agent files to the ZIP
        for agent_name, agent_data in agents_data.items():
            agent_file_name = f"{agent_name}.json"
            agent_file_data = json.dumps(agent_data, indent=2)
            zip_file.writestr(f"agents/{agent_file_name}", agent_file_data)

    # Write workflow file to the ZIP

```

```
workflow_file_name = f"{sanitize_text(workflow_data['name'])}.json"
workflow_file_data = json.dumps(workflow_data, indent=2)
zip_file.writestr(f"workflows/{workflow_file_name}", workflow_file_data)

with zipfile.ZipFile(crewai_zip_buffer, 'w', zipfile.ZIP_DEFLATED) as zip_file:
    for index, agent_data in enumerate(crewai_agents):
        agent_file_name = f"agent_{index}.json"
        agent_file_data = json.dumps(agent_data, indent=2)
        zip_file.writestr(f"agents/{agent_file_name}", agent_file_data)

# Move the ZIP file pointers to the beginning
autogen_zip_buffer.seek(0)
crewai_zip_buffer.seek(0)

return autogen_zip_buffer, crewai_zip_buffer
```