

agent_management.py

```
import base64
import os
import re
import requests
import streamlit as st

from api_utils import send_request_to_groq_api
from bs4 import BeautifulSoup
from ui_utils import get_api_key, regenerate_json_files_and_zip, update_discussion_and_whiteboard

def agent_button_callback(agent_index):
    # Callback function to handle state update and logic execution
    def callback():
        st.session_state['selected_agent_index'] = agent_index
        agent = st.session_state.agents[agent_index]

        agent_name = agent['config']['name'] if 'config' in agent and 'name' in agent['config'] else ""
        st.session_state['form_agent_name'] = agent_name
        st.session_state['form_agent_description'] = agent['description'] if 'description' in agent else ""
        # Directly call process_agent_interaction here if appropriate
        process_agent_interaction(agent_index)
        return callback

    return callback

def construct_request(agent_name, description, user_request, user_input, rephrased_request, reference_url):
    request = f"Act as the {agent_name} who {description}."
    if user_request:
        request += f" Original request was: {user_request}."
    if rephrased_request:
        request += f" You are helping a team work on satisfying {rephrased_request}."
    if user_input:
        request += f" Additional input: {user_input}."
    if reference_url and reference_url in st.session_state.reference_html:
        html_content = st.session_state.reference_html[reference_url]
        request += f" Reference URL content: {html_content}."
    if st.session_state.discussion:
        request += f" The discussion so far has been {st.session_state.discussion[-50000:]}"
    return request

def display_agents():
    if "agents" in st.session_state and st.session_state.agents:
        st.sidebar.title("Your Agents")
        st.sidebar.subheader("Click to interact")
        display_agent_buttons(st.session_state.agents)
    if st.session_state.get('show_edit'):
        edit_index = st.session_state.get('edit_agent_index')
        if edit_index is not None and 0 <= edit_index < len(st.session_state.agents):
```

```

agent = st.session_state.agents[edit_index]
display_agent_edit_form(agent, edit_index)
else:
st.sidebar.warning("Invalid agent selected for editing.")
else:
st.sidebar.warning("No agents have yet been created. Please enter a new request.")

def display_agent_buttons(agents):
for index, agent in enumerate(agents):
agent_name = agent["config"]["name"] if agent["config"].get("name") else f"Unnamed Agent {index + 1}"
col1, col2 = st.sidebar.columns([1, 4])
with col1:
gear_icon = "" # Unicode character for gear icon
if st.button(
gear_icon,
key=f"gear_{index}",
help="Edit Agent" # Add the tooltip text
):
st.session_state['edit_agent_index'] = index
st.session_state['show_edit'] = True
with col2:
if "next_agent" in st.session_state and st.session_state.next_agent == agent_name:
button_style = ""
<style>
div[data-testid="stButton"] > button[kind="secondary"] {
background-color: green !important;
color: white !important;
}
</style>
"""
st.markdown(button_style, unsafe_allow_html=True)
st.button(agent_name, key=f"agent_{index}", on_click=agent_button_callback(index))

def display_agent_edit_form(agent, edit_index):
with st.expander(f"Edit Properties of {agent['config'].get('name', '')}", expanded=True):
col1, col2 = st.columns([4, 1])
with col1:
new_name = st.text_input("Name", value=agent['config'].get('name', ''), key=f"name_{edit_index}")
with col2:
# Add an empty space to push the button to the bottom
container = st.container()
space = container.empty()

# Add the "X" button with a confirmation prompt
if container.button("X", key=f"delete_{edit_index}"):
if st.session_state.get(f"delete_confirmed_{edit_index}", False):
st.session_state.agents.pop(edit_index)
st.session_state['show_edit'] = False

```

```

st.experimental_rerun()
else:
st.session_state[f"delete_confirmed_{edit_index}"] = True
st.experimental_rerun()

# Display the confirmation prompt if the "X" button is clicked
if st.session_state.get(f"delete_confirmed_{edit_index}", False):
if container.button("Confirm Deletion", key=f"confirm_delete_{edit_index}"):
st.session_state.agents.pop(edit_index)
st.session_state['show_edit'] = False
del st.session_state[f"delete_confirmed_{edit_index}"]
st.experimental_rerun()
if container.button("Cancel", key=f"cancel_delete_{edit_index}"):
del st.session_state[f"delete_confirmed_{edit_index}"]
st.experimental_rerun()
description_value = agent.get('new_description', agent.get('description', ""))
new_description = st.text_area("Description", value=description_value, key=f"desc_{edit_index}")

col1, col2, col3 = st.columns([1, 1, 2])

with col1:
if st.button("Re-roll ", key=f"regenerate_{edit_index}"):
print(f"Regenerate button clicked for agent {edit_index}")
new_description = regenerate_agent_description(agent)
if new_description:
agent['new_description'] = new_description
print(f"Description regenerated for {agent['config']['name']}: {new_description}")
st.experimental_rerun()
else:
print(f"Failed to regenerate description for {agent['config']['name']}")

with col2:
if st.button("Save Changes", key=f"save_{edit_index}"):
agent['config']['name'] = new_name
agent['description'] = agent.get('new_description', new_description)
st.session_state['show_edit'] = False
if 'edit_agent_index' in st.session_state:
del st.session_state['edit_agent_index']
if 'new_description' in agent:
del agent['new_description']
# Update the agent data in the session state
st.session_state.agents[edit_index] = agent

# Regenerate the JSON files and zip file
regenerate_json_files_and_zip()
st.session_state['show_edit'] = False

with col3:
# Initialize the fetch_web_content property for the agent if it doesn't exist
if "fetch_web_content" not in agent:

```

```
agent["fetch_web_content"] = False
```

```
# Use the value from the agent's fetch_web_content property for the checkbox
fetch_web_content = st.checkbox(
    "Add web browsing skill to this agent",
    value=agent["fetch_web_content"],
    key=f"fetch_web_content_{edit_index}"
)
```

```
# Update the agent's fetch_web_content property based on the checkbox value
if fetch_web_content != agent["fetch_web_content"]:
    agent["fetch_web_content"] = fetch_web_content
st.session_state.agents[edit_index] = agent # Update the agent in the session state
```

```
if "generate_images" not in agent:
    agent["generate_images"] = False
```

```
# Use the value from the agent's generate_images property for the checkbox
generate_images = st.checkbox(
    "Add image generation skill to this agent",
    value=agent["generate_images"],
    key=f"generate_images_{edit_index}"
)
```

```
# Update the agent's generate_images property based on the checkbox value
if generate_images != agent["generate_images"]:
    agent["generate_images"] = generate_images
st.session_state.agents[edit_index] = agent # Update the agent in the session state
```

```
def download_agent_file(expert_name):
    # Format the expert_name
    formatted_expert_name = re.sub(r'^[a-zA-Z0-9\s]', "", expert_name) # Remove non-alphanumeric characters
    formatted_expert_name = formatted_expert_name.lower().replace(' ', '_') # Convert to lowercase and replace spaces with underscores
```

```
# Get the full path to the agent JSON file
agents_dir = os.path.abspath(os.path.join(os.path.dirname(__file__), "agents"))
json_file = os.path.join(agents_dir, f"{formatted_expert_name}.json")
```

```
# Check if the file exists
if os.path.exists(json_file):
    # Read the file content
    with open(json_file, "r") as f:
        file_content = f.read()
```

```
# Encode the file content as base64
b64_content = base64.b64encode(file_content.encode()).decode()
```

```
# Create a download link
```

```

href = f'<a href="data:application/json;base64,{b64_content}" download="{formatted_expert_name}.json">Download
{formatted_expert_name}.json</a>'
st.markdown(href, unsafe_allow_html=True)
else:
st.error(f"File not found: {json_file}")

```

```

def process_agent_interaction(agent_index):
agent_name, description = retrieve_agent_information(agent_index)
user_request = st.session_state.get('user_request', '')
user_input = st.session_state.get('user_input', '')
rephrased_request = st.session_state.get('rephrased_request', '')
reference_url = st.session_state.get('reference_url', '')
request = construct_request(agent_name, description, user_request, user_input, rephrased_request, reference_url)
response = send_request(agent_name, request)
if response:
update_discussion_and_whiteboard(agent_name, response, user_input)
st.session_state['form_agent_name'] = agent_name
st.session_state['form_agent_description'] = description
st.session_state['selected_agent_index'] = agent_index

```

```

request = f"Act as the {agent_name} who {description}."
if user_request:
request += f" Original request was: {user_request}."
if rephrased_request:
request += f" You are helping a team work on satisfying {rephrased_request}."
if user_input:
request += f" Additional input: {user_input}."
if reference_url:
try:
response = requests.get(reference_url)
response.raise_for_status()
soup = BeautifulSoup(response.text, 'html.parser')
url_content = soup.get_text()
request += f" Reference URL content: {url_content}."
except requests.exceptions.RequestException as e:
print(f"Error occurred while retrieving content from {reference_url}: {e}")
if st.session_state.discussion:
request += f" The discussion so far has been {st.session_state.discussion[-50000:]}. "

```

```

api_key = get_api_key()
if api_key is None:
st.error("API key not found. Please enter your API key.")
return

```

```

response = send_request_to_groq_api(agent_name, request, api_key)
if response:
update_discussion_and_whiteboard(agent_name, response, user_input)
# Additionally, populate the sidebar form with the agent's information
st.session_state['form_agent_name'] = agent_name

```

```
st.session_state['form_agent_description'] = description
st.session_state['selected_agent_index'] = agent_index # Keep track of the selected agent for potential
updates/deletes
```

```
def regenerate_agent_description(agent):
    agent_name = agent['config']['name']
    print(f"agent_name: {agent_name}")
    agent_description = agent['description']
    print(f"agent_description: {agent_description}")
    user_request = st.session_state.get('user_request', "")
    print(f"user_request: {user_request}")
    discussion_history = st.session_state.get('discussion_history', "")
```

```
prompt = f"""
```

You are an AI assistant helping to improve an agent's description. The agent's current details are:

Name: {agent_name}

Description: {agent_description}

The current user request is: {user_request}

The discussion history so far is: {discussion_history}

Please generate a revised description for this agent that defines it in the best manner possible to address the current user request, taking into account the discussion thus far. Return only the revised description, without any additional commentary or narrative. It is imperative that you return ONLY the text of the new description. No preamble, no narrative, no superfluous commentary whatsoever. Just the description, unlabeled, please.

```
"""
```

```
api_key = get_api_key()
if api_key is None:
    st.error("API key not found. Please enter your API key.")
return None
```

```
print(f"regenerate_agent_description called with agent_name: {agent_name}")
print(f"regenerate_agent_description called with prompt: {prompt}")
```

```
response = send_request_to_groq_api(agent_name, prompt, api_key)
if response:
    return response.strip()
else:
    return None
```

```
def retrieve_agent_information(agent_index):
    agent = st.session_state.agents[agent_index]
    agent_name = agent["config"]["name"]
    description = agent["description"]
    return agent_name, description
```

```

def send_request(agent_name, request):
    api_key = get_api_key()
    if api_key is None:
        st.error("API key not found. Please enter your API key.")
        return None
    response = send_request_to_groq_api(agent_name, request, api_key)
    return response

```

api_utils.py

```

import requests
import streamlit as st
import time

```

```

from config import RETRY_TOKEN_LIMIT

```

```

def make_api_request(url, data, headers, api_key):
    time.sleep(2) # Throttle the request to ensure at least 2 seconds between calls
    try:
        if not api_key:
            raise ValueError("GROQ_API_KEY not found. Please enter your API key.")
        headers["Authorization"] = f"Bearer {api_key}"
        response = requests.post(url, json=data, headers=headers)
        if response.status_code == 200:
            return response.json()
        elif response.status_code == 429:
            error_message = response.json().get("error", {}).get("message", "")
            st.error(f"Rate limit reached for the current model. If you click 'Re-roll' again, we'll retry with a reduced token count. Or you can try selecting a different model.")
            st.error(f"Error details: {error_message}")
            return None
        else:
            print(f"Error: API request failed with status {response.status_code}, response: {response.text}")
            return None
    except requests.RequestException as e:
        print(f"Error: Request failed {e}")
        return None

```

```

def send_request_to_groq_api(expert_name, request, api_key):
    temperature_value = st.session_state.get('temperature', 0.1)
    if api_key is None:
        if 'api_key' in st.session_state and st.session_state.api_key:
            api_key = st.session_state.api_key
        else:
            st.error("API key not found. Please enter your API key.")
            return None

```

```

url = "https://api.groq.com/openai/v1/chat/completions"
data = {
    "model": st.session_state.model,
    "temperature": temperature_value,
    "max_tokens": st.session_state.max_tokens,
    "top_p": 1,
    "stop": "TERMINATE",
    "messages": [
        {
            "role": "system",
            "content": "You are a chatbot capable of anything and everything."
        },
        {
            "role": "user",
            "content": request
        }
    ]
}
headers = {
    "Authorization": f"Bearer {api_key}",
    "Content-Type": "application/json"
}

try:
    response = make_api_request(url, data, headers, api_key)
    if response:
        if "choices" in response and len(response["choices"]) > 0:
            message_content = response["choices"][0]["message"]["content"]
            return message_content
        else:
            print("Error: Unexpected response format from the Groq API.")
            print("Response data:", response)
            return None
    except Exception as e:
        print(f"Error occurred while making the request to Groq API: {str(e)}")
        return None

def send_request_with_retry(url, data, headers, api_key):
    response = make_api_request(url, data, headers, api_key)
    if response is None:
        # Add a retry button
        if st.button("Retry with decreased token limit"):
            # Update the token limit in the request data
            data["max_tokens"] = RETRY_TOKEN_LIMIT
            # Retry the request with the decreased token limit
            print(f"Retrying the request with decreased token limit.")
            print(f"URL: {url}")
            print(f"Retry token limit: {RETRY_TOKEN_LIMIT}")
            response = make_api_request(url, data, headers, api_key)

```



```
if response is not None:
    print(f"Retry successful. Response: {response}")
else:
    print("Retry failed.")
return response
```

config.py

```
# Retry settings
MAX_RETRIES = 3
RETRY_DELAY = 2 # in seconds
RETRY_TOKEN_LIMIT = 5000
```

```
# Model configurations
MODEL_TOKEN_LIMITS = {
    'llama3-70b-8192': 8192,
    'llama3-8b-8192': 8192,
    'mixtral-8x7b-32768': 32768,
    'gemma-7b-it': 8192
}
```

file_utils.py

```
import datetime
import importlib.resources as resources
import re
import streamlit as st
```

```
def create_agent_data(agent):
    expert_name = agent['config']['name']
    description = agent['description'] # Use the updated description from the session state
    skills = agent.get("skills", [])
    tools = agent.get("tools", [])
    current_timestamp = datetime.datetime.now().isoformat()
```

```
# Format the expert_name
formatted_expert_name = sanitize_text(expert_name)
formatted_expert_name = formatted_expert_name.lower().replace(' ', '_')
```

```
# Sanitize the description
sanitized_description = sanitize_text(description)
```

```
# Sanitize the skills and tools
sanitized_skills = [sanitize_text(skill) for skill in skills]
sanitized_tools = [sanitize_text(tool) for tool in tools]
```

```
# Create the Autogen agent data
autogen_agent_data = {
    "type": "assistant",
    "config": {
        "name": formatted_expert_name,
        "llm_config": {
```

```

"config_list": [
{
"user_id": "default",
"timestamp": current_timestamp,
"model": "gpt-4",
"base_url": None,
"api_type": None,
"api_version": None,
"description": "OpenAI model configuration"
}
],
"temperature": st.session_state.get('temperature', 0.1),
"cache_seed": None,
"timeout": None,
"max_tokens": None,
"extra_body": None
},
"human_input_mode": "NEVER",
"max_consecutive_auto_reply": 8,
"system_message": f"You are a helpful assistant that can act as {expert_name} who {sanitized_description}.",
"is_termination_msg": None,
"code_execution_config": None,
"default_auto_reply": "",
"description": description
},
"timestamp": current_timestamp,
"user_id": "default",
"skills": []
}

```

```

if agent.get('fetch_web_content', False):
    fetch_web_content_data = resources.read_text('skills', 'fetch_web_content.py')
    skill_data = create_skill_data(fetch_web_content_data)
    autogen_agent_data["skills"].append(skill_data)

```

```

if agent.get('generate_images', False):
    generate_images_data = resources.read_text('skills', 'generate_images.py')
    skill_data = create_skill_data(generate_images_data)
    autogen_agent_data["skills"].append(skill_data)

```

```

# Create the CrewAI agent data
crewai_agent_data = {
"name": expert_name,
"description": description,
"skills": sanitized_skills,
"tools": sanitized_tools,
"verbose": True,
"allow_delegation": True
}

```

```
return autogen_agent_data, crewai_agent_data
```

```
def create_skill_data(python_code):
    # Extract the function name from the Python code
    function_name_match = re.search(r"def\s+(\w+)\(", python_code)
    if function_name_match:
        function_name = function_name_match.group(1)
    else:
        function_name = "unnamed_function"

    # Extract the skill description from the docstring
    docstring_match = re.search(r'"""(.*)"""', python_code, re.DOTALL)
    if docstring_match:
        skill_description = docstring_match.group(1).strip()
    else:
        skill_description = "No description available"

    # Get the current timestamp
    current_timestamp = datetime.datetime.now().isoformat()

    # Create the skill data dictionary
    skill_data = {
        "title": function_name,
        "content": python_code,
        "file_name": f"{function_name}.json",
        "description": skill_description,
        "timestamp": current_timestamp,
        "user_id": "default"
    }

    return skill_data
```

```
def create_workflow_data(workflow):
    # Sanitize the workflow name
    sanitized_workflow_name = sanitize_text(workflow["name"])
    sanitized_workflow_name = sanitized_workflow_name.lower().replace(' ', '_')

    return workflow
```

```
def sanitize_text(text):
    # Remove non-ASCII characters
    text = re.sub(r'[^\x00-\x7F]+', '', text)
    # Remove non-alphanumeric characters except for standard punctuation
    text = re.sub(r'[^\a-zA-Z0-9\.\!\?;\'\"]+','', text)
    return text
```

main.py

```

import os
import streamlit as st

from config import MODEL_TOKEN_LIMITS

from agent_management import display_agents
from ui_utils import get_api_key, display_api_key_input, display_discussion_and_whiteboard,
display_download_button, display_user_input, display_rephrased_request, display_reset_and_upload_buttons,
display_user_request_input

def main():
    # Construct the relative path to the CSS file
    css_file = "AutoGroq/style.css"

    # Check if the CSS file exists
    if os.path.exists(css_file):
        with open(css_file) as f:
            st.markdown(f'<style>{f.read()}</style>', unsafe_allow_html=True)
    else:
        st.error(f"CSS file not found: {os.path.abspath(css_file)}")

    api_key = get_api_key()
    if api_key is None:
        api_key = display_api_key_input()
    if api_key is None:
        st.warning("Please enter your GROQ_API_KEY to use the app.")
    return

col1, col2 = st.columns([1, 1]) # Adjust the column widths as needed
with col1:
    selected_model = st.selectbox(
        'Select Model',
        options=list(MODEL_TOKEN_LIMITS.keys()),
        index=0,
        key='model_selection'
    )
    st.session_state.model = selected_model
    st.session_state.max_tokens = MODEL_TOKEN_LIMITS[selected_model]

with col2:
    temperature = st.slider(
        "Set Temperature",
        min_value=0.0,
        max_value=1.0,
        value=st.session_state.get('temperature', 0.3),
        step=0.01,
        key='temperature'
    )

```

```

st.title("AutoGroq")

# Ensure default values for session state are set
if "discussion" not in st.session_state:
    st.session_state.discussion = ""
if "whiteboard" not in st.session_state:
    st.session_state.whiteboard = "" # Apply CSS classes to elements

with st.sidebar:
    st.markdown('<div class="sidebar">', unsafe_allow_html=True)
    st.markdown('</div>', unsafe_allow_html=True)

display_agents()

with st.container():
    st.markdown('<div class="main">', unsafe_allow_html=True)
    display_user_request_input()
    display_rephrased_request()
    st.markdown('<div class="discussion-whiteboard">', unsafe_allow_html=True)
    display_discussion_and_whiteboard()
    st.markdown('</div>', unsafe_allow_html=True)
    st.markdown('<div class="user-input">', unsafe_allow_html=True)
    display_user_input()
    st.markdown('</div>', unsafe_allow_html=True)
    display_reset_and_upload_buttons()
    st.markdown('</div>', unsafe_allow_html=True)

display_download_button()

if __name__ == "__main__":
    main()

```

ui_utils.py

```

import datetime
import importlib.resources as resources
import os
import streamlit as st
import time

from config import MAX_RETRIES, RETRY_DELAY
from skills.fetch_web_content import fetch_web_content

def get_api_key():
    if 'api_key' in st.session_state and st.session_state.api_key:
        api_key = st.session_state.api_key
        print(f"API Key from session state: {api_key}")
        return api_key
    elif "GROQ_API_KEY" in os.environ:
        api_key = os.environ["GROQ_API_KEY"]

```

```
print(f"API Key from environment variable: {api_key}")
return api_key
else:
return None
```

```
def display_api_key_input():
if 'api_key' not in st.session_state:
st.session_state.api_key = "
```

```
api_key = st.text_input("Enter your GROQ_API_KEY:", type="password", value=st.session_state.api_key,
key="api_key_input")
```

```
if api_key:
st.session_state.api_key = api_key
st.success("API key entered successfully.")
print(f"API Key: {api_key}")
```

```
return api_key
```

```
import io
import json
import pandas as pd
import re
import time
import zipfile
from file_utils import create_agent_data, create_skill_data, sanitize_text
```

```
import datetime
import requests
```

```
def create_zip_file(zip_buffer, file_data):
with zipfile.ZipFile(zip_buffer, 'w', zipfile.ZIP_DEFLATED) as zip_file:
for file_name, file_content in file_data.items():
zip_file.writestr(file_name, file_content)
```

```
def display_discussion_and_whiteboard():
discussion_history = get_discussion_history()
tab1, tab2, tab3 = st.tabs(["Most Recent Comment", "Whiteboard", "Discussion History"])
with tab1:
st.text_area("Most Recent Comment", value=st.session_state.get("last_comment", ""), height=400, key="discussion")
with tab2:
if "whiteboard" not in st.session_state:
st.session_state.whiteboard = ""
st.text_area("Whiteboard", value=st.session_state.whiteboard, height=400, key="whiteboard")
with tab3:
st.write(discussion_history)
```

```

def display_discussion_modal():
discussion_history = get_discussion_history()

with st.expander("Discussion History"):
st.write(discussion_history)


def display_download_button():
if "autogen_zip_buffer" in st.session_state and "crewai_zip_buffer" in st.session_state:
col1, col2 = st.columns(2)
with col1:
st.download_button(
label="Download Autogen Files",
data=st.session_state.autogen_zip_buffer,
file_name="autogen_files.zip",
mime="application/zip",
key=f"autogen_download_button_{int(time.time())}" # Generate a unique key based on timestamp
)
with col2:
st.download_button(
label="Download CrewAI Files",
data=st.session_state.crewai_zip_buffer,
file_name="crewai_files.zip",
mime="application/zip",
key=f"crewai_download_button_{int(time.time())}" # Generate a unique key based on timestamp
)
else:
st.warning("No files available for download.")


def display_user_input():
user_input = st.text_area("Additional Input:", key="user_input", height=100)
if user_input:
url_pattern = re.compile(r'http[s]?://(?:[a-zA-Z][0-9][$_@.&+][!*\(\)\,\.](?:%[0-9a-fA-F][0-9a-fA-F]))+')
url_match = url_pattern.search(user_input)
if url_match:
url = url_match.group()
if "reference_html" not in st.session_state or url not in st.session_state.reference_html:
html_content = fetch_web_content(url)
if html_content:
if "reference_html" not in st.session_state:
st.session_state.reference_html = {}
st.session_state.reference_html[url] = html_content
else:
st.warning("Failed to fetch HTML content.")
else:
st.session_state.reference_html = {}
else:
st.session_state.reference_html = {}

```

```
return user_input
```

```
def display_rephrased_request():  
    if "rephrased_request" not in st.session_state:  
        st.session_state.rephrased_request = ""  
  
    st.text_area("Re-engineered Prompt:", value=st.session_state.get('rephrased_request', ''), height=100,  
        key="rephrased_request_area")
```

```
def display_reset_and_upload_buttons():  
    col1, col2 = st.columns(2)  
    with col1:  
        if st.button("Reset", key="reset_button"):  
            # Define the keys of session state variables to clear  
            keys_to_reset = [  
                "rephrased_request", "discussion", "whiteboard", "user_request",  
                "user_input", "agents", "zip_buffer", "crewai_zip_buffer",  
                "autogen_zip_buffer", "uploaded_file_content", "discussion_history",  
                "last_comment", "user_api_key", "reference_url"  
            ]  
            # Reset each specified key  
            for key in keys_to_reset:  
                if key in st.session_state:  
                    del st.session_state[key]  
            # Additionally, explicitly reset user_input to an empty string  
            st.session_state.user_input = ""  
            st.session_state.show_begin_button = True  
            st.experimental_rerun()  
  
    with col2:  
        uploaded_file = st.file_uploader("Upload a sample .csv of your data (optional)", type="csv")  
  
        if uploaded_file is not None:  
            try:  
                # Attempt to read the uploaded file as a DataFrame  
                df = pd.read_csv(uploaded_file).head(5)  
  
                # Display the DataFrame in the app  
                st.write("Data successfully uploaded and read as DataFrame:")  
                st.dataframe(df)  
  
                # Store the DataFrame in the session state  
                st.session_state.uploaded_data = df  
            except Exception as e:  
                st.error(f"Error reading the file: {e}")
```

```
def display_user_request_input():
```



```

user_request = st.text_input("Enter your request:", key="user_request", value=st.session_state.get("user_request",
""))
if st.session_state.get("previous_user_request") != user_request:
    st.session_state.previous_user_request = user_request
if user_request:
    if not st.session_state.get('rephrased_request'):
        handle_user_request(st.session_state)
    else:
        autogen_agents, crewai_agents = get_agents_from_text(st.session_state.rephrased_request)
        print(f"Debug: AutoGen Agents: {autogen_agents}")
        print(f"Debug: CrewAI Agents: {crewai_agents}")

if not autogen_agents:
    print("Error: No agents created.")
    st.warning("Failed to create agents. Please try again.")
    return

agents_data = {}
for agent in autogen_agents:
    agent_name = agent['config']['name']
    agents_data[agent_name] = agent

print(f"Debug: Agents data: {agents_data}")

workflow_data, _ = get_workflow_from_agents(autogen_agents)
print(f"Debug: Workflow data: {workflow_data}")
print(f"Debug: CrewAI agents: {crewai_agents}")

autogen_zip_buffer, crewai_zip_buffer = zip_files_in_memory(agents_data, workflow_data, crewai_agents)
st.session_state.autogen_zip_buffer = autogen_zip_buffer
st.session_state.crewai_zip_buffer = crewai_zip_buffer
st.session_state.agents = autogen_agents

st.experimental_rerun()

def extract_code_from_response(response):
    code_pattern = r"```(?:.|\n)*```"
    code_blocks = re.findall(code_pattern, response, re.DOTALL)

    html_pattern = r"<html.*?>.*?</html>"
    html_blocks = re.findall(html_pattern, response, re.DOTALL | re.IGNORECASE)

    js_pattern = r"<script.*?>.*?</script>"
    js_blocks = re.findall(js_pattern, response, re.DOTALL | re.IGNORECASE)

    css_pattern = r"<style.*?>.*?</style>"
    css_blocks = re.findall(css_pattern, response, re.DOTALL | re.IGNORECASE)

    all_code_blocks = code_blocks + html_blocks + js_blocks + css_blocks

```

```
unique_code_blocks = list(set(all_code_blocks))
```

```
return "\n\n".join(unique_code_blocks)
```

```
def extract_json_objects(json_string):
    objects = []
    start_index = json_string.find("{")
    while start_index != -1:
        end_index = json_string.find("}", start_index)
        if end_index != -1:
            object_str = json_string[start_index:end_index+1]
            objects.append(object_str)
            start_index = json_string.find("{", end_index + 1)
        else:
            break
    return objects
```

```
def get_agents_from_text(text, max_retries=MAX_RETRIES, retry_delay=RETRY_DELAY):
    api_key = get_api_key()
    temperature_value = st.session_state.get('temperature', 0.5)
    url = "https://api.groq.com/openai/v1/chat/completions"
    headers = {
        "Authorization": f"Bearer {api_key}",
        "Content-Type": "application/json"
    }
    groq_request = {
        "model": st.session_state.model,
        "temperature": temperature_value,
        "max_tokens": st.session_state.max_tokens,
        "top_p": 1,
        "stop": "TERMINATE",
        "messages": [
            {
                "role": "system",
                "content": f"""
```

You are an expert system designed to identify and recommend the optimal team of experts required to fulfill this specific user's request: \$userRequest Your analysis shall consider the complexity, domain, and specific needs of the request to assemble a multidisciplinary team of experts. The team should be as small as possible while still providing a complete and comprehensive talent pool able to properly address the users' requests. Each recommended expert shall come with a defined role, a brief but thorough description of their expertise, their specific skills, and the specific tools they would utilize to achieve the user's goal. The first agent must be qualified to manage the entire project, aggregate the work done by all the other agents, and produce a robust, complete, and reliable solution. Return the results in JSON values labeled as expert_name, description, skills, and tools. Their 'expert_name' is their title, not their given name. Skills and tools are arrays (one expert can have multiple specific skills and use multiple specific tools). Return ONLY this JSON response, with no other narrative, commentary, synopsis,

□ □ □

```
},
{
    "role": "user",
    "content": text
}
]
}

retry_count = 0
while retry_count < max_retries:
try:
response = requests.post(url, json=groq_request, headers=headers)
if response.status_code == 200:
response_data = response.json()
if "choices" in response_data and response_data["choices"]:
content = response_data["choices"][0]["message"]["content"]
print(f"Content: {content}")
json_objects = extract_json_objects(content)
if json_objects:
autogen_agents = []
crewai_agents = []

missing_names = False
for json_str in json_objects:
try:
agent_data = json.loads(json_str)
expert_name = agent_data.get('expert_name', '')
if not expert_name:
missing_names = True
break
description = agent_data.get('description', '')
skills = agent_data.get('skills', [])
tools = agent_data.get('tools', [])

# Create the agent data using the new signature
autogen_agent_data = {
"type": "assistant",
"config": {
"name": expert_name,
"llm_config": {
"config_list": [
{
"user_id": "default",
"timestamp": datetime.datetime.now().isoformat(),
"model": "gpt-4",
```

```

"base_url": None,
"api_type": None,
"api_version": None,
"description": "OpenAI model configuration"
}
],
"temperature": st.session_state.get('temperature', 0.1),
"timeout": 600,
"cache_seed": 42
},
"human_input_mode": "NEVER",
"max_consecutive_auto_reply": 8,
"system_message": f"You are a helpful assistant that can act as {expert_name} who {description}."
},
"description": description,
"skills": [],
"tools": tools
}

```

```

crewai_agent_data = {
"name": expert_name,
"description": description,
"skills": [],
"tools": tools,
"verbose": True,
"allow_delegation": True
}

```

```

autogen_agents.append(autogen_agent_data)
crewai_agents.append(crewai_agent_data)
except json.JSONDecodeError as e:
print(f"Error parsing JSON object: {e}")
print(f"JSON string: {json_str}")

```

```

if missing_names:
print("Missing agent names. Retrying...")
retry_count += 1
time.sleep(retry_delay)
continue

```

```

print(f"AutoGen Agents: {autogen_agents}")
print(f"CrewAI Agents: {crewai_agents}")
return autogen_agents, crewai_agents
else:
print("No valid JSON objects found in the response")
return [], []
else:
print("No agents data found in response")
else:
print(f"API request failed with status code {response.status_code}: {response.text}")

```

```

except Exception as e:
    print(f"Error making API request: {e}")

    retry_count += 1
    time.sleep(retry_delay)

print(f"Maximum retries ({max_retries}) exceeded. Failed to retrieve valid agent names.")
return [], []

```

```

def get_discussion_history():
    if "discussion_history" not in st.session_state:
        st.session_state.discussion_history = ""
    return st.session_state.discussion_history

```

```

def get_workflow_from_agents(agents):
    current_timestamp = datetime.datetime.now().isoformat()
    temperature_value = st.session_state.get('temperature', 0.3)

```

```

workflow = {
    "name": "AutoGroq Workflow",
    "description": "Workflow auto-generated by AutoGroq.",
    "sender": {
        "type": "userproxy",
        "config": {
            "name": "userproxy",
            "llm_config": False,
            "human_input_mode": "NEVER",
            "max_consecutive_auto_reply": 5,
            "system_message": "You are a helpful assistant.",
            "is_termination_msg": None,
            "code_execution_config": {
                "work_dir": None,
                "use_docker": False
            },
            "default_auto_reply": "",
            "description": None
        },
        "timestamp": current_timestamp,
        "user_id": "default",
        "skills": []
    },
    "receiver": {
        "type": "groupchat",
        "config": {
            "name": "group_chat_manager",
            "llm_config": {
                "config_list": [
                    {

```

```

"user_id": "default",
"timestamp": datetime.datetime.now().isoformat(),
"model": "gpt-4",
"base_url": None,
"api_type": None,
"api_version": None,
"description": "OpenAI model configuration"
}
],
"temperature": temperature_value,
"cache_seed": 42,
"timeout": 600,
"max_tokens": None,
"extra_body": None
},
"human_input_mode": "NEVER",
"max_consecutive_auto_reply": 10,
"system_message": "Group chat manager",
"is_termination_msg": None,
"code_execution_config": None,
"default_auto_reply": "",
"description": None
},
"groupchat_config": {
"agents": [],
"admin_name": "Admin",
"messages": [],
"max_round": 10,
"speaker_selection_method": "auto",
"allow_repeat_speaker": True
},
"timestamp": current_timestamp,
"user_id": "default",
"skills": []
},
"type": "groupchat",
"user_id": "default",
"timestamp": current_timestamp,
"summary_method": "last"
}

```

```

for index, agent in enumerate(agents):
    agent_name = agent["config"]["name"]
    description = agent["description"]
    formatted_agent_name = sanitize_text(agent_name).lower().replace(' ', '_')
    sanitized_description = sanitize_text(description)

```

```

system_message = f"You are a helpful assistant that can act as {agent_name} who {sanitized_description}."
if index == 0:
    other_agent_names = [sanitize_text(a["config"]["name"]).lower().replace(' ', '_') for a in agents[1:] if a in

```

```
st.session_state.agents] # Filter out deleted agents
system_message += f" You are the primary coordinator who will receive suggestions or advice from all the other
agents ({', '.join(other_agent_names)}). You must ensure that the final response integrates the suggestions from other
agents or team members. YOUR FINAL RESPONSE MUST OFFER THE COMPLETE RESOLUTION TO THE
USER'S REQUEST. When the user's request has been satisfied and all perspectives are integrated, you can respond
with TERMINATE."
```

```
other_agent_names = [sanitize_text(a['config']['name']).lower().replace(' ', '_') for a in agents[1:]]
system_message += f" You are the primary coordinator who will receive suggestions or advice from all the other
agents ({', '.join(other_agent_names)}). You must ensure that the final response integrates the suggestions from other
agents or team members. YOUR FINAL RESPONSE MUST OFFER THE COMPLETE RESOLUTION TO THE
USER'S REQUEST. When the user's request has been satisfied and all perspectives are integrated, you can respond
with TERMINATE."
```

```
agent_config = {
    "type": "assistant",
    "config": {
        "name": formatted_agent_name,
        "llm_config": {
            "config_list": [
                {
                    "user_id": "default",
                    "timestamp": datetime.datetime.now().isoformat(),
                    "model": "gpt-4",
                    "base_url": None,
                    "api_type": None,
                    "api_version": None,
                    "description": "OpenAI model configuration"
                }
            ],
            "temperature": temperature_value,
            "cache_seed": 42,
            "timeout": 600,
            "max_tokens": None,
            "extra_body": None
        },
        "human_input_mode": "NEVER",
        "max_consecutive_auto_reply": 8,
        "system_message": system_message,
        "is_termination_msg": None,
        "code_execution_config": None,
        "default_auto_reply": "",
        "description": None
    },
    "timestamp": current_timestamp,
    "user_id": "default",
    "skills": [] # Set skills to null only in the workflow JSON
}
```

```
workflow["receiver"]["groupchat_config"]["agents"].append(agent_config)
```

```

crewai_agents = []
for agent in agents:
    if agent not in st.session_state.agents: # Check if the agent exists in st.session_state.agents
        continue # Skip the agent if it has been deleted

    _, crewai_agent_data = create_agent_data(agent)
    crewai_agents.append(crewai_agent_data)

return workflow, crewai_agents

def handle_user_request(session_state):
    user_request = session_state.user_request
    max_retries = MAX_RETRIES
    retry_delay = RETRY_DELAY

    for retry in range(max_retries):
        try:
            rephrased_text = rephrase_prompt(user_request)
            print(f"Debug: Rephrased text: {rephrased_text}")
            if rephrased_text:
                session_state.rephrased_request = rephrased_text
                break # Exit the loop if successful
            else:
                print("Error: Failed to rephrase the user request.")
                st.warning("Failed to rephrase the user request. Please try again.")
                return # Exit the function if rephrasing fails
        except Exception as e:
            print(f"Error occurred in handle_user_request: {str(e)}")
            if retry < max_retries - 1:
                print(f"Retrying in {retry_delay} second(s)...")
                time.sleep(retry_delay)
            else:
                print("Max retries exceeded.")
                st.warning("An error occurred. Please try again.")
                return # Exit the function if max retries are exceeded

    rephrased_text = session_state.rephrased_request

    autogen_agents, crewai_agents = get_agents_from_text(rephrased_text)
    print(f"Debug: AutoGen Agents: {autogen_agents}")
    print(f"Debug: CrewAI Agents: {crewai_agents}")

    if not autogen_agents:
        print("Error: No agents created.")
        st.warning("Failed to create agents. Please try again.")
        return

    # Set the agents attribute in the session state

```



```
session_state.agents = autogen_agents
```

```
workflow_data, _ = get_workflow_from_agents(autogen_agents)
print(f"Debug: Workflow data: {workflow_data}")
print(f"Debug: CrewAI agents: {crewai_agents}")
```

```
autogen_zip_buffer, crewai_zip_buffer = zip_files_in_memory(workflow_data)
session_state.autogen_zip_buffer = autogen_zip_buffer
session_state.crewai_zip_buffer = crewai_zip_buffer
```

```
def regenerate_json_files_and_zip():
    # Get the updated workflow data
    workflow_data, _ = get_workflow_from_agents(st.session_state.agents)

    # Regenerate the zip files
    autogen_zip_buffer, crewai_zip_buffer = zip_files_in_memory(workflow_data)

    # Update the zip buffers in the session state
    st.session_state.autogen_zip_buffer = autogen_zip_buffer
    st.session_state.crewai_zip_buffer = crewai_zip_buffer
```

```
def rephrase_prompt(user_request):
    temperature_value = st.session_state.get('temperature', 0.1)
    print("Executing rephrase_prompt()")
    api_key = get_api_key()
    if not api_key:
        st.error("API key not found. Please enter your API key.")
    return None
```

```
url = "https://api.groq.com/openai/v1/chat/completions"
refactoring_prompt = f"""
Refactor the following user request into an optimized prompt for an LLM,
focusing on clarity, conciseness, and effectiveness. Provide specific details
and examples where relevant. Do NOT reply with a direct response to the request;
instead, rephrase the request as a well-structured prompt, and return ONLY that rephrased
prompt. Do not preface the rephrased prompt with any other text or superfluous narrative.
Do not enclose the rephrased prompt in quotes.
\n\nUser request: \"{user_request}\" \n\nrephrased:
"""
```

```
groq_request = {
    "model": st.session_state.model,
    "temperature": temperature_value,
    "max_tokens": 100,
    "top_p": 1,
    "stop": "TERMINATE",
    "messages": [
        {
```

```

"role": "user",
"content": refactoring_prompt,
},
],
}

headers = {
"Authorization": f"Bearer {api_key}",
"Content-Type": "application/json",
}

print(f"Request URL: {url}")
print(f"Request Headers: {headers}")
print(f"Request Payload: {json.dumps(groq_request, indent=2)}")

try:
print("Sending request to Groq API...")
response = requests.post(url, json=groq_request, headers=headers, timeout=10)
print(f"Response received. Status Code: {response.status_code}")

if response.status_code == 200:
print("Request successful. Parsing response...")
response_data = response.json()
print(f"Response Data: {json.dumps(response_data, indent=2)}")

if "choices" in response_data and len(response_data["choices"]) > 0:
rephrased = response_data["choices"][0]["message"]["content"]
return rephrased.strip()
else:
print("Error: Unexpected response format. 'choices' field missing or empty.")
return None
else:
print(f"Request failed. Status Code: {response.status_code}")
print(f"Response Content: {response.text}")
return None
except requests.exceptions.RequestException as e:
print(f"Error occurred while sending the request: {str(e)}")
return None
except (KeyError, ValueError) as e:
print(f"Error occurred while parsing the response: {str(e)}")
print(f"Response Content: {response.text}")
return None
except Exception as e:
print(f"An unexpected error occurred: {str(e)}")
return None

def update_discussion_and_whiteboard(agent_name, response, user_input):
if user_input:
user_input_text = f"\n\n\n\n{user_input}\n\n"

```

```
st.session_state.discussion_history += user_input_text
response_text = f"{agent_name}:\n\n {response}\n\n====\n\n"
st.session_state.discussion_history += response_text
code_blocks = extract_code_from_response(response)
st.session_state.whiteboard = code_blocks
st.session_state.last_agent = agent_name
st.session_state.last_comment = response_text
```

```
def zip_files_in_memory(workflow_data):
    # Create separate ZIP buffers for Autogen and CrewAI
    autogen_zip_buffer = io.BytesIO()
    crewai_zip_buffer = io.BytesIO()
    autogen_file_data = {}
    for agent in st.session_state.agents:
        agent_name = agent['config']['name']
        formatted_agent_name = sanitize_text(agent_name).lower().replace(' ', '_')
        agent_file_name = f"{formatted_agent_name}.json"
        autogen_agent_data, _ = create_agent_data(agent) # Get the updated Autogen agent data
        autogen_agent_data['config']['name'] = formatted_agent_name
        agent_file_data = json.dumps(autogen_agent_data, indent=2).encode('utf-8') # Encode to bytes
        autogen_file_data[f"agents/{agent_file_name}"] = agent_file_data
        if agent.get('fetch_web_content', False):
            # add skills/fetch_web_content.py to zip file
            fetch_web_content_data = resources.read_text('skills', 'fetch_web_content.py')
            skill_data = json.dumps(create_skill_data(fetch_web_content_data), indent=2).encode('utf-8') # Encode to bytes
            autogen_file_data[f"skills/fetch_web_content.json"] = skill_data
        if agent.get('generate_images', False):
            # add skills/generate_images.py to zip file
            generate_images_data = resources.read_text('skills', 'generate_images.py')
            skill_data = json.dumps(create_skill_data(generate_images_data), indent=2).encode('utf-8') # Encode to bytes
            autogen_file_data[f"skills/generate_images.json"] = skill_data
```

```
workflow_file_name = "workflow.json"
workflow_file_data = json.dumps(workflow_data, indent=2).encode('utf-8') # Encode to bytes
autogen_file_data[workflow_file_name] = workflow_file_data
```

```
# Prepare CrewAI file data
crewai_file_data = {}
for index, agent in enumerate(st.session_state.agents):
    agent_name = agent['config']['name']
    formatted_agent_name = sanitize_text(agent_name).lower().replace(' ', '_')
    crewai_agent_data = create_agent_data(agent)[1]
    crewai_agent_data['name'] = formatted_agent_name
    agent_file_name = f"{formatted_agent_name}.json"
    agent_file_data = json.dumps(crewai_agent_data, indent=2).encode('utf-8') # Encode to bytes
    crewai_file_data[f"agents/{agent_file_name}"] = agent_file_data
```

```
# Create ZIP files
create_zip_file(autogen_zip_buffer, autogen_file_data)
```

```
create_zip_file(crewai_zip_buffer, crewai_file_data)
```

```
# Move the ZIP file pointers to the beginning
autogen_zip_buffer.seek(0)
crewai_zip_buffer.seek(0)
```

```
return autogen_zip_buffer, crewai_zip_buffer
```

fetch_web_content.py

```
from typing import Optional
import requests
import collections
collections.Callable = collections.abc.Callable
from bs4 import BeautifulSoup
```

```
def fetch_web_content(url: str) -> Optional[str]:
    """
```

Fetches the text content from a website.

Args:

url (str): The URL of the website.

Returns:

Optional[str]: The content of the website.

```
    """
```

```
    try:
```

```
        # Send a GET request to the URL
```

```
        response = requests.get(url)
```

```
        # Check for successful access to the webpage
```

```
        if response.status_code == 200:
```

```
            # Parse the HTML content of the page using BeautifulSoup
```

```
            soup = BeautifulSoup(response.text, "html.parser")
```

```
        # Extract the content of the <body> tag
```

```
        body_content = soup.body
```

```
        if body_content:
```

```
            # Return all the text in the body tag, stripping leading/trailing whitespaces
```

```
            return " ".join(body_content.get_text(strip=True).split())
```

```
        else:
```

```
            # Return None if the <body> tag is not found
```

```
            return None
```

```
        else:
```

```
            # Return None if the status code isn't 200 (success)
```

```
            return None
```

```
    except requests.RequestException:
```

```
        # Return None if any request-related exception is caught
```

```
        return None
```

generate_images.py

```

from typing import List
import uuid
import requests # to perform HTTP requests
from pathlib import Path

from openai import OpenAI

def generate_and_save_images(query: str, image_size: str = "1024x1024") -> List[str]:
    """
    Function to paint, draw or illustrate images based on the users query or request. Generates images from a given
    query using OpenAI's DALL-E model and saves them to disk. Use the code below anytime there is a request to
    create an image.

    :param query: A natural language description of the image to be generated.
    :param image_size: The size of the image to be generated. (default is "1024x1024")
    :return: A list of filenames for the saved images.
    """

    client = OpenAI() # Initialize the OpenAI client
    response = client.images.generate(model="dall-e-3", prompt=query, n=1, size=image_size) # Generate images

    # List to store the file names of saved images
    saved_files = []

    # Check if the response is successful
    if response.data:
        for image_data in response.data:
            # Generate a random UUID as the file name
            file_name = str(uuid.uuid4()) + ".png" # Assuming the image is a PNG
            file_path = Path(file_name)

            img_url = image_data.url
            img_response = requests.get(img_url)
            if img_response.status_code == 200:
                # Write the binary content to a file
                with open(file_path, "wb") as img_file:
                    img_file.write(img_response.content)
                print(f"Image saved to {file_path}")
                saved_files.append(str(file_path))
            else:
                print(f"Failed to download the image from {img_url}")
            else:
                print("No image data found in the response!")

    # Return the list of saved files
    return saved_files

# Example usage of the function:

```

```
# generate_and_save_images("A cute baby sea otter")
```