

## Table of Contents

### .devcontainer\devcontainer.json

```
{
  "name": "Python 3",
  // Or use a Dockerfile or Docker Compose file. More info: https://containers.dev/guide/dockerfile
  "image": "mcr.microsoft.com/devcontainers/python:1-3.11-bullseye",
  "customizations": {
    "codespaces": {
      "openFiles": [
        "README.md",
        "AutoGroq/main.py"
      ]
    },
    "vscode": {
      "settings": {},
      "extensions": [
        "ms-python.python",
        "ms-python.vscode-pylance"
      ]
    },
    "updateContentCommand": "[ -f packages.txt ] && sudo apt update && sudo apt upgrade -y && sudo xargs apt install -y <packages.txt; [ -f requirements.txt ] && pip3 install --user -r requirements.txt; pip3 install --user streamlit; echo '☐ Packages installed and Requirements met'",
    "postAttachCommand": {
      "server": "streamlit run AutoGroq/pages/main.py --server.enableCORS false --server.enableXsrfProtection false"
    },
    "portsAttributes": {
      "8501": {
        "label": "Application",
        "onAutoForward": "openPreview"
      }
    },
    "forwardPorts": [
      8501
    ]
  }
}
```

### AutoGroq\agent\_management.py

```
import base64
import streamlit as st
import json
import os
import re

from api_utils import send_request_to_groq_api
from file_utils import create_agent_data
from ui_utils import update_discussion_and_whiteboard

def agent_button_callback(agent_index):
    # Callback function to handle state update and logic execution
    def callback():
        st.session_state['selected_agent_index'] = agent_index
        agent = st.session_state.agents[agent_index]
```

```

agent_name = agent['config']['name'] if 'config' in agent and 'name' in agent['config'] else ""
st.session_state['form_agent_name'] = agent_name
st.session_state['form_agent_description'] = agent['description'] if 'description' in agent else ""
# Directly call process_agent_interaction here if appropriate
process_agent_interaction(agent_index)
return callback

def delete_agent(index):
    if 0 <= index < len(st.session_state.agents):
        expert_name = st.session_state.agents[index]['expert_name']
        del st.session_state.agents[index]

# Get the full path to the JSON file
agents_dir = os.path.abspath(os.path.join(os.path.dirname(__file__), "agents"))
json_file = os.path.join(agents_dir, f"{expert_name}.json")

# Delete the corresponding JSON file
if os.path.exists(json_file):
    os.remove(json_file)
    print(f"JSON file deleted: {json_file}")
else:
    print(f"JSON file not found: {json_file}")

st.experimental_rerun()

def display_agents():
    if "agents" in st.session_state and st.session_state.agents:
        st.sidebar.title("Your Agents")
        st.sidebar.subheader("click to interact")
        for index, agent in enumerate(st.session_state.agents):
            agent_name = agent["config"]["name"]
            if "next_agent" in st.session_state and st.session_state.next_agent == agent_name:
                button_style = """
<style>
div[data-testid*="stButton"] > button[kind="secondary"] {
background-color: green !important;
color: white !important;
}
</style>
"""
            st.sidebar.markdown(button_style, unsafe_allow_html=True)
            st.sidebar.button(agent_name, key=f"agent_{index}", on_click=agent_button_callback(index))
        else:
            st.sidebar.warning("AutoGroq creates your entire team of downloadable, importable Autogen and CrewAI agents from a simple task request, including an Autogen workflow file! \n\nYou can test your agents with this interface.\n\nNo agents have yet been created. Please enter a new request.\n\n Video demo: https://www.youtube.com/watch?v=Jm4UYVTwgBI&t=84s")

def download_agent_file(expert_name):
    # Format the expert_name
    formatted_expert_name = re.sub(r'^a-zA-Z0-9[s]', "", expert_name) # Remove non-alphanumeric characters
    formatted_expert_name = formatted_expert_name.lower().replace(' ', '_') # Convert to lowercase and replace spaces with underscores

# Get the full path to the agent JSON file
agents_dir = os.path.abspath(os.path.join(os.path.dirname(__file__), "agents"))
json_file = os.path.join(agents_dir, f"{formatted_expert_name}.json")

```

```

# Check if the file exists
if os.path.exists(json_file):
# Read the file content
with open(json_file, "r") as f:
file_content = f.read()

# Encode the file content as base64
b64_content = base64.b64encode(file_content.encode()).decode()

# Create a download link
href = f"<a href='data:application/json;base64,{b64_content}'"
download="{formatted_expert_name}.json">Download {formatted_expert_name}.json</a>"
st.markdown(href, unsafe_allow_html=True)
else:
st.error(f"File not found: {json_file}")

def process_agent_interaction(agent_index):
# Retrieve agent information using the provided index
agent = st.session_state.agents[agent_index]

# Preserve the original "Act as" functionality
agent_name = agent["config"]["name"]
description = agent["description"]
user_request = st.session_state.get('user_request', "")
user_input = st.session_state.get('user_input', "")
rephrased_request = st.session_state.get('rephrased_request', "")

request = f"Act as the {agent_name} who {description}."
if user_request:
request += f" Original request was: {user_request}."
if rephrased_request:
request += f" You are helping a team work on satisfying {rephrased_request}."
if user_input:
request += f" Additional input: {user_input}."
if st.session_state.discussion:
request += f" The discussion so far has been {st.session_state.discussion[-50000:]}."

response = send_request_to_groq_api(agent_name, request)
if response:
update_discussion_and_whiteboard(agent_name, response, user_input)

# Additionally, populate the sidebar form with the agent's information
st.session_state['form_agent_name'] = agent_name
st.session_state['form_agent_description'] = description
st.session_state['selected_agent_index'] = agent_index # Keep track of the selected agent for
potential updates/deletes

```

## AutoGroq\api\_utils.py

```

import datetime
import requests
import json
import streamlit as st
import re
import time

from file_utils import create_agent_data, sanitize_text
from skills.stock_info_skill import GetStockInfo

```

```

def get_next_agent(last_agent, last_comment, expert_names, enhanced_prompt):
    url = "https://j.gravelle.us/APIs/Groq/groqApiChatCoordinator.php"
    data = {
        "last_agent": last_agent,
        "last_contribution": last_comment,
        "agents": expert_names, # Pass the expert names instead of the entire agent objects
        "enhanced_prompt": enhanced_prompt
    }
    headers = {"Content-Type": "application/json"}

    print("Payload:")
    print(json.dumps(data, indent=2))

    try:
        response = requests.post(url, json=data, headers=headers)
        print(f"Debug: RESPONSE: {response.text}")
        response.raise_for_status()
        response_data = response.json()
        print(f"Debug: RESPONSE DATA: {response_data}")
        next_agent = response_data["next_agent"].strip()
        assignment = response_data["assignment"].strip()

        if next_agent not in expert_names:
            print(f"Warning: The returned next agent '{next_agent}' is not one of the provided expert names: {expert_names}")
            print("Falling back to the last agent.")
            next_agent = last_agent
            assignment = "Please continue working on the task based on the previous assignment and the enhanced prompt."

        return f"Next Suggested Agent: {next_agent}\n\nAssignment: {assignment}\n\n"
    except (requests.exceptions.RequestException, KeyError, ValueError) as e:
        print(f"Error occurred while coordinating agents:")
        print(f"Request URL: {url}")
        print(f"Request Headers: {headers}")
        print(f"Request Payload: {json.dumps(data, indent=2)}")
        print(f"Response Content: {response.text}")
        print(f"Error Details: {str(e)}")
        return "Error occurred while coordinating agents."
    except Exception as e:
        print(f"An unexpected error occurred:")
        print(f"Error Details: {str(e)}")
        return "Error occurred while coordinating agents."

def extract_tasks(comment, agents):
    url = "https://j.gravelle.us/APIs/Groq/groqApiTaskExtractor.php"
    data = {
        "comment": comment,
        "agents": agents
    }
    headers = {"Content-Type": "application/json"}
    response = requests.post(url, json=data, headers=headers)
    response.raise_for_status()
    response_data = response.json()

    return response_data

def make_api_request(url, data, headers):
    max_retries = 3
    retry_delay = 1 # in seconds

```

```

for retry in range(max_retries):
    try:
        time.sleep(1)
        response = requests.post(url, data=json.dumps(data), headers=headers)
        print(f"Debug: API request sent: {json.dumps(data)}")
        print(f"Debug: API response received: {response.text}")

    if response.status_code == 200:
        try:
            return response.json()
        except json.JSONDecodeError:
            print(f"Error: Unexpected response format: {response.text}")
            return None
        else:
            st.error(f"Error: API request failed with status code {response.status_code}. Retrying...")
            if retry < max_retries - 1:
                time.sleep(retry_delay)
                continue
            else:
                return None
    except requests.exceptions.RequestException as e:
        st.error(f"Error: {str(e)}. Retrying...")
        if retry < max_retries - 1:
            time.sleep(retry_delay)
            continue
        else:
            return None

return None

```

```

def rephrase_prompt(user_request):
    url = "https://j.gravelle.us/APIs/Groq/groqApiRephrasePrompt.php"
    data = {"user_request": user_request}
    headers = {"Content-Type": "application/json"}
    response_data = make_api_request(url, data, headers)
    if response_data:
        rephrased = response_data.get("rephrased", "")
        if rephrased:
            return rephrased
        else:
            print("Error: Empty response received from the API.")
            return None

```

```

def get_agents_from_text(text):
    url = "https://j.gravelle.us/APIs/Groq/groqApiGetAgentsFromPrompt.php"
    data = {"user_request": text}
    headers = {"Content-Type": "application/json"}
    response_data = make_api_request(url, data, headers)
    if response_data:
        autogen_agents = []
        crewai_agents = []

        if isinstance(response_data, dict):
            for expert_name, agent_data in response_data.items():
                expert_name = agent_data.get("expert_name", "")
                description = agent_data.get("description", "")
                skills = agent_data.get("skills", [])
                tools = agent_data.get("tools", [])

```

```

autogen_agent_data, crewai_agent_data = create_agent_data(expert_name, description, skills, tools)
autogen_agents.append(autogen_agent_data)
crewai_agents.append(crewai_agent_data)
elif isinstance(response_data, list):
    for agent_data in response_data:
        expert_name = agent_data.get("expert_name", "")
        description = agent_data.get("description", "")
        skills = agent_data.get("skills", [])
        tools = agent_data.get("tools", [])
        autogen_agent_data, crewai_agent_data = create_agent_data(expert_name, description, skills, tools)
        autogen_agents.append(autogen_agent_data)
        crewai_agents.append(crewai_agent_data)
    else:
        print("Error: Unexpected response format from the API.")

return autogen_agents, crewai_agents

return [], []

```

```

def get_workflow_from_agents(agents):
    current_timestamp = datetime.datetime.now().isoformat()

    workflow = {
        "name": "AutoGroq Workflow",
        "description": "Workflow auto-generated by AutoGroq.",
        "sender": {
            "type": "userproxy",
            "config": {
                "name": "userproxy",
                "llm_config": False,
                "human_input_mode": "NEVER",
                "max_consecutive_auto_reply": 5,
                "system_message": "You are a helpful assistant.",
                "is_termination_msg": None,
                "code_execution_config": {
                    "work_dir": None,
                    "use_docker": False
                },
                "default_auto_reply": "",
                "description": None
            },
            "timestamp": current_timestamp,
            "user_id": "default",
            "skills": None
        },
        "receiver": {
            "type": "groupchat",
            "config": {
                "name": "group_chat_manager",
                "llm_config": {
                    "config_list": [
                        {
                            "model": "gpt-4-1106-preview"
                        }
                    ],
                    "temperature": 0.1,
                    "cache_seed": 42,
                    "timeout": 600,
                    "max_tokens": None,
                    "extra_body": None
                }
            }
        }
    }

```

```

},
"human_input_mode": "NEVER",
"max_consecutive_auto_reply": 10,
"system_message": "Group chat manager",
"is_termination_msg": None,
"code_execution_config": None,
"default_auto_reply": "",
"description": None
},
"groupchat_config": {
"agents": [],
"admin_name": "Admin",
"messages": [],
"max_round": 10,
"speaker_selection_method": "auto",
"allow_repeat_speaker": True
},
"timestamp": current_timestamp,
"user_id": "default",
"skills": None
},
"type": "groupchat",
"user_id": "default",
"timestamp": current_timestamp,
"summary_method": "last"
}

```

```

for index, agent in enumerate(agents):
    agent_name = agent["config"]["name"]
    description = agent["description"]
    formatted_agent_name = sanitize_text(agent_name).lower().replace(' ', '_')
    sanitized_description = sanitize_text(description)
    system_message = f"You are a helpful assistant that can act as {agent_name} who {sanitized_description}."

```

```

if index == 0:
    other_agent_names = [sanitize_text(a["config"]["name"]).lower().replace(' ', '_') for a in agents[1:]]
    system_message += f" You are the primary coordinator who will receive suggestions or advice from all the other agents ({', '.join(other_agent_names)}). You must ensure that the final response integrates the suggestions from other agents or team members. YOUR FINAL RESPONSE MUST OFFER THE COMPLETE RESOLUTION TO THE USER'S REQUEST. When the user's request has been satisfied and all perspectives are integrated, you can respond with TERMINATE."

```

```

agent_config = {
    "type": "assistant",
    "config": {
        "name": formatted_agent_name,
        "llm_config": {
            "config_list": [
                {
                    "model": "gpt-4-1106-preview"
                }
            ],
            "temperature": 0.1,
            "cache_seed": 42,
            "timeout": 600,
            "max_tokens": None,
            "extra_body": None
        },
        "human_input_mode": "NEVER",
        "max_consecutive_auto_reply": 8,
        "system_message": system_message,

```

```

"is_termination_msg": None,
"code_execution_config": None,
"default_auto_reply": "",
"description": None
},
"timestamp": current_timestamp,
"user_id": "default",
"skills": None # Set skills to null only in the workflow JSON
}
workflow["receiver"]["groupchat_config"]["agents"].append(agent_config)

crewai_agents = []
for index, agent in enumerate(agents):
    agent_name = agent["config"]["name"]
    description = agent["description"]
    _, crewai_agent_data = create_agent_data(agent_name, description, agent.get("skills"),
    agent.get("tools"))
    crewai_agents.append(crewai_agent_data)

return workflow, crewai_agents

# api_utils.py
def send_request_to_groq_api(expert_name, request):
    url = "https://j.gravelle.us/APIs/Groq/groqApiStockDiscerner.php"

    # Extract the text that follows "Additional input:" from the request
    additional_input_index = request.find("Additional input:")
    if additional_input_index != -1:
        additional_input = request[additional_input_index + len("Additional input:").strip()]
    else:
        additional_input = ""

    if additional_input:
        data = {"user_request": additional_input}
        headers = {"Content-Type": "application/json"}

    try:
        response = requests.post(url, json=data, headers=headers)
        response.raise_for_status()

    try:
        response_data = response.json()
        if "summary" in response_data:
            summary = response_data["summary"].strip()
        else:
            summary = ""
        except ValueError:
            summary = response.text.strip()

    if summary.startswith("LOOKUP"):
        ticker = summary.split("LOOKUP")[1].strip()
        stock_info = GetStockInfo(ticker)
        request += f"\n\nStock info: {stock_info}"

    except requests.exceptions.RequestException as e:
        print(f"Error occurred while making the request: {e}")
    except Exception as e:
        print(f"An unexpected error occurred: {e}")

    url = "https://j.gravelle.us/APIs/Groq/groqAPI.php"
    data = {

```



```

"model": st.session_state.model,
"temperature": 0.5,
"max_tokens": st.session_state.max_tokens,
"top_p": 1,
"stop": "TERMINATE",
"messages": [
{
"role": "system",
"content": "You are a chatbot capable of anything and everything."
},
{
"role": "user",
"content": request
}
]
}
headers = {"Content-Type": "application/json"}
response_data = make_api_request(url, data, headers)
if response_data:
if "choices" in response_data and len(response_data["choices"]) > 0:
message_content = response_data["choices"][0]["message"]["content"]
return message_content
else:
print("Error: Unexpected response format from the Groq API.")
print("Response data:", response_data)
return None
return ""

```

```

def extract_code_from_response(response):
code_pattern = r"```(?:.|\n)*```"
code_blocks = re.findall(code_pattern, response, re.DOTALL)

html_pattern = r"<html.*?>.*?</html>"
html_blocks = re.findall(html_pattern, response, re.DOTALL | re.IGNORECASE)

js_pattern = r"<script.*?>.*?</script>"
js_blocks = re.findall(js_pattern, response, re.DOTALL | re.IGNORECASE)

css_pattern = r"<style.*?>.*?</style>"
css_blocks = re.findall(css_pattern, response, re.DOTALL | re.IGNORECASE)

all_code_blocks = code_blocks + html_blocks + js_blocks + css_blocks
unique_code_blocks = list(set(all_code_blocks))

return "\n\n".join(unique_code_blocks)

```

## AutoGroq\custom\_button.py

```

import streamlit as st
import streamlit.components.v1 as components

def custom_button(expert_name, index, next_agent):
button_style = """
<style>
.custom-button {
background-color: #f0f0f0;
color: black;
padding: 0.5rem 1rem;
border: none;
border-radius: 0.25rem;

```

```

cursor: pointer;
}
.custom-button.active {
background-color: green;
color: white;
}
</style>
"""

```

```

button_class = "custom-button active" if next_agent == expert_name else "custom-button"
button_html = f'<button class="{button_class}">{expert_name}</button>'

```

```

components.html(button_style + button_html, height=50)

```

```

def agent_button(expert_name, index, next_agent):
    custom_button(expert_name, index, next_agent)

```

## AutoGroq\file\_utils.py

```

# file_utils.py
import os
import json
import re

```

```

def sanitize_text(text):
    # Remove non-ASCII characters
    text = re.sub(r'^\x00-\x7F+', "", text)
    # Remove non-alphanumeric characters except for standard punctuation
    text = re.sub(r'^a-zA-Z0-9\s.,!?:;"'-]+', "", text)
    return text

```

```

def create_agent_data(expert_name, description, skills=None, tools=None):
    # Format the expert_name
    formatted_expert_name = sanitize_text(expert_name)
    formatted_expert_name = formatted_expert_name.lower().replace(' ', '_')

```

```

# Sanitize the description
sanitized_description = sanitize_text(description)

```

```

# Sanitize the skills and tools
sanitized_skills = [sanitize_text(skill) for skill in skills] if skills else []
sanitized_tools = [sanitize_text(tool) for tool in tools] if tools else []

```

```

# Create the agent data
agent_data = {
    "type": "assistant",
    "config": {
        "name": formatted_expert_name,
        "llm_config": {
            "config_list": [
                {
                    "model": "gpt-4-1106-preview"
                }
            ],
            "temperature": 0.1,
            "timeout": 600,
            "cache_seed": 42
        },
        "human_input_mode": "NEVER",

```

```

"max_consecutive_auto_reply": 8,
"system_message": f"You are a helpful assistant that can act as {expert_name} who
{sanzitized_description}."
},
"description": sanitzitized_description,
"skills": [],
"tools": sanitzitized_tools
}

```

```

crewai_agent_data = {
"name": expert_name, # Use 'name' instead of 'expert_name'
"description": description, # Use 'description' instead of 'goal'
"skills": skills, # Add 'skills' key
"tools": sanitzitized_tools,
"verbose": True,
"allow_delegation": True
}

```

```

return agent_data, crewai_agent_data

```

```

def create_workflow_data(workflow):
# Sanitize the workflow name
sanitized_workflow_name = sanitize_text(workflow["name"])
sanitized_workflow_name = sanitized_workflow_name.lower().replace(' ', '_')

return workflow

```

## AutoGroq\main.py

```

import streamlit as st
from agent_management import display_agents
from ui_utils import display_discussion_and_whiteboard, display_download_button,
display_user_input, display_rephrased_request, display_reset_button, display_user_request_input

```

```

def main():
st.markdown("""
<style>
/* General styles */
body {
font-family: Arial, sans-serif;
background-color: #f0f0f0;
}

/* Sidebar styles */
.sidebar .sidebar-content {
background-color: #ffffff !important;
padding: 20px !important;
border-radius: 5px !important;
box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1) !important;
}

.sidebar .st-emotion-cache-k7vsyb h1 {
font-size: 12px !important;
font-weight: bold !important;
color: #007bff !important;
}

.sidebar h2 {

```

```
font-size: 16px !important;
color: #666666 !important;
}
```

```
.sidebar .stButton button {
display: block !important;
width: 100% !important;
padding: 10px !important;
background-color: #007bff !important;
color: #ffffff !important;
text-align: center !important;
text-decoration: none !important;
border-radius: 5px !important;
transition: background-color 0.3s !important;
}
```

```
.sidebar .stButton button:hover {
background-color: #0056b3 !important;
}
```

```
.sidebar a {
display: block !important;
color: #007bff !important;
text-decoration: none !important;
}
```

```
.sidebar a:hover {
text-decoration: underline !important;
}
```

```
/* Main content styles */
.main .stTextInput input {
width: 100% !important;
padding: 10px !important;
border: 1px solid #cccccc !important;
border-radius: 5px !important;
}
```

```
.main .stTextArea textarea {
width: 100% !important;
padding: 10px !important;
border: 1px solid #cccccc !important;
border-radius: 5px !important;
resize: none !important;
}
```

```
.main .stButton button {
padding: 10px 20px !important;
background-color: #dc3545 !important;
color: #ffffff !important;
border: none !important;
border-radius: 5px !important;
cursor: pointer !important;
transition: background-color 0.3s !important;
}
```

```
.main .stButton button:hover {
background-color: #c82333 !important;
}
```

```
.main h1 {
font-size: 32px !important;
```

```
font-weight: bold !important;
color: #007bff !important;
}
```

```
/* Model selection styles */
.main .stSelectbox select {
width: 100% !important;
padding: 10px !important;
border: 1px solid #cccccc !important;
border-radius: 5px !important;
}
```

```
/* Error message styles */
.main .stAlert {
color: #dc3545 !important;
}
</style>
""", unsafe_allow_html=True)
```

```
model_token_limits = {
'mixtral-8x7b-32768': 32768,
'llama3-70b-8192': 8192,
'llama3-8b-8192': 8192,
'gemma-7b-it': 8192
}
```

```
col1, col2, col3 = st.columns([2, 5, 3])
with col3:
selected_model = st.selectbox(
'Select Model',
options=list(model_token_limits.keys()),
index=0,
key='model_selection'
)
st.session_state.model = selected_model
st.session_state.max_tokens = model_token_limits[selected_model]
```

```
st.title("AutoGroq")
```

```
# Ensure default values for session state are set
if "discussion" not in st.session_state:
st.session_state.discussion = ""
if "whiteboard" not in st.session_state:
st.session_state.whiteboard = "" # Apply CSS classes to elements
```

```
with st.sidebar:
st.markdown('<div class="sidebar">', unsafe_allow_html=True)
st.markdown('</div>', unsafe_allow_html=True)
```

```
display_agents()
```

```
with st.container():
st.markdown('<div class="main">', unsafe_allow_html=True)
display_user_request_input()
display_rephrased_request()
st.markdown('<div class="discussion-whiteboard">', unsafe_allow_html=True)
display_discussion_and_whiteboard()
st.markdown('</div>', unsafe_allow_html=True)
st.markdown('<div class="user-input">', unsafe_allow_html=True)
display_user_input()
st.markdown('</div>', unsafe_allow_html=True)
display_reset_button()
```

```
st.markdown('</div>', unsafe_allow_html=True)
```

```
display_download_button()
```

```
if __name__ == "__main__":  
    main()
```

## AutoGroq\ui\_utils.py

```
import io  
import json  
import os  
import streamlit as st  
import time  
import zipfile  
from api_utils import rephrase_prompt, get_agents_from_text, extract_code_from_response,  
get_workflow_from_agents  
from file_utils import create_agent_data, sanitize_text  
  
def display_discussion_and_whiteboard():  
    col1, col2 = st.columns(2)  
    with col1:  
        st.text_area("Discussion", value=st.session_state.discussion, height=400, key="discussion")  
    with col2:  
        st.text_area("Whiteboard", value=st.session_state.whiteboard, height=400, key="whiteboard")  
  
def display_user_input():  
    user_input = st.text_area("Additional Input:", key="user_input", height=100)  
    return user_input  
  
def display_rephrased_request():  
    st.text_area("Re-engineered Prompt:", value=st.session_state.get('rephrased_request', ""), height=100,  
key="rephrased_request_area")  
  
def display_download_button():  
    if "autogen_zip_buffer" in st.session_state and "crewai_zip_buffer" in st.session_state:  
        col1, col2 = st.columns(2)  
        with col1:  
            st.download_button(  
                label="Download Autogen Files",  
                data=st.session_state.autogen_zip_buffer,  
                file_name="autogen_files.zip",  
                mime="application/zip",  
                key=f"autogen_download_button_{int(time.time())}" # Generate a unique key based on timestamp  
            )  
        with col2:  
            st.download_button(  
                label="Download CrewAI Files",  
                data=st.session_state.crewai_zip_buffer,  
                file_name="crewai_files.zip",  
                mime="application/zip",  
                key=f"crewai_download_button_{int(time.time())}" # Generate a unique key based on timestamp  
            )  
        else:  
            st.warning("No files available for download.")  
  
def display_reset_button():  
    if st.button("Reset", key="reset_button"):
```

```

# Reset specific elements without clearing entire session state
for key in ["rephrased_request", "discussion", "whiteboard", "user_request", "user_input", "agents",
"zip_buffer"]:
    if key in st.session_state:
        del st.session_state[key]

st.session_state.user_request = ""

st.session_state.show_begin_button = True
st.experimental_rerun()

def display_user_request_input():
    user_request = st.text_input("Enter your request:", key="user_request")
    if user_request and user_request != st.session_state.get("previous_user_request"):
        st.session_state.previous_user_request = user_request
        handle_begin(st.session_state)
        st.experimental_rerun()

def handle_begin(session_state):
    user_request = session_state.user_request
    max_retries = 3
    retry_delay = 1 # in seconds

    for retry in range(max_retries):
        try:
            rephrased_text = rephrase_prompt(user_request)
            print(f"Debug: Rephrased text: {rephrased_text}")

            if rephrased_text:
                session_state.rephrased_request = rephrased_text
                autogen_agents, crewai_agents = get_agents_from_text(rephrased_text)
                print(f"Debug: AutoGen Agents: {autogen_agents}")
                print(f"Debug: CrewAI Agents: {crewai_agents}")

            if not autogen_agents:
                print("Error: No agents created. Retrying...")
                if retry < max_retries - 1:
                    time.sleep(retry_delay)
                    continue
                else:
                    print("Error: Failed to create agents after maximum retries.")
                    st.warning("Failed to create agents. Please try again.")
                    return

            agents_data = {}
            for agent in autogen_agents:
                agent_name = agent["config"]["name"]
                agents_data[agent_name] = agent
            print(f"Debug: Agents data: {agents_data}")

            workflow_data, _ = get_workflow_from_agents(autogen_agents)
            print(f"Debug: Workflow data: {workflow_data}")
            print(f"Debug: CrewAI agents: {crewai_agents}")

            autogen_zip_buffer, crewai_zip_buffer = zip_files_in_memory(agents_data, workflow_data,
            crewai_agents)
            session_state.autogen_zip_buffer = autogen_zip_buffer
            session_state.crewai_zip_buffer = crewai_zip_buffer

```

```

session_state.agents = autogen_agents
break # Exit the loop if successful

else:
    print("Error: Failed to rephrase the user request.")
    st.warning("Failed to rephrase the user request. Please try again.")
    return # Exit the function if rephrasing fails

except Exception as e:
    print(f"Error occurred in handle_begin: {str(e)}")
    if retry < max_retries - 1:
        print(f"Retrying in {retry_delay} second(s)...")
        time.sleep(retry_delay)
    else:
        print("Max retries exceeded.")
        st.warning("An error occurred. Please try again.")
        return # Exit the function if max retries are exceeded

def update_discussion_and_whiteboard(expert_name, response, user_input):
    print("Updating discussion and whiteboard...")
    print(f"Expert Name: {expert_name}")
    print(f"Response: {response}")
    print(f"User Input: {user_input}")

    if user_input:
        user_input_text = f"\n\nAdditional Input:\n\n{user_input}\n\n"
        st.session_state.discussion += user_input_text

    response_text = f"{response}\n\n===\n\n"
    st.session_state.discussion += response_text

    code_blocks = extract_code_from_response(response)
    st.session_state.whiteboard = code_blocks

    # Store the last agent and their comment in session variables
    st.session_state.last_agent = expert_name
    st.session_state.last_comment = response
    print(f"Last Agent: {st.session_state.last_agent}")
    print(f"Last Comment: {st.session_state.last_comment}")

def zip_files_in_memory(agents_data, workflow_data, crewai_agents):
    # Create separate ZIP buffers for Autogen and CrewAI
    autogen_zip_buffer = io.BytesIO()
    crewai_zip_buffer = io.BytesIO()

    # Create a ZIP file in memory
    with zipfile.ZipFile(autogen_zip_buffer, 'w', zipfile.ZIP_DEFLATED) as zip_file:
        # Write agent files to the ZIP
        for agent_name, agent_data in agents_data.items():
            agent_file_name = f"{agent_name}.json"
            agent_file_data = json.dumps(agent_data, indent=2)
            zip_file.writestr(f"agents/{agent_file_name}", agent_file_data)

    # Write workflow file to the ZIP
    workflow_file_name = f"{sanitize_text(workflow_data['name'])}.json"
    workflow_file_data = json.dumps(workflow_data, indent=2)
    zip_file.writestr(f"workflows/{workflow_file_name}", workflow_file_data)

```



```

with zipfile.ZipFile(crewai_zip_buffer, 'w', zipfile.ZIP_DEFLATED) as zip_file:
    for index, agent_data in enumerate(crewai_agents):
        agent_file_name = f"agent_{index}.json"
        agent_file_data = json.dumps(agent_data, indent=2)
        zip_file.writestr(f"agents/{agent_file_name}", agent_file_data)

# Move the ZIP file pointers to the beginning
autogen_zip_buffer.seek(0)
crewai_zip_buffer.seek(0)

return autogen_zip_buffer, crewai_zip_buffer

```

## Groquments\main.py

```

import os

from groq import Groq

client = Groq(
    api_key=os.environ.get("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"),
)

# Create a groqument from local PDF
groqument = client.documents.create(
    data={
        "type": "pdf",
        "content": "./FoodshowQA.pdf",
    },
)

def groqument(groqument):
    return client.documents.create(
        data=groqument,
    )

def groq_query(groq_query):
    return client.queries.create(
        query=groq_query,
    )

# Get user input as groq_query
groq_query = input("Enter your groq query: ")

chat_completion = client.chat.completions.create(
    messages=[
        {
            "role": "system",
            "content": "{groqument}",
        },
        {
            "role": "user",
            "content": "Act as an authority on all the information in {groqument} and address user's {groq_query}.",
        }
    ],
    model="mixtral-8x7b-32768",
)

```

```
print(chat_completion.choices[0].message.content)
```

## AutoGroq\skills\stock\_info\_skill.py

```
import requests
```

```
def GetStockInfo(ticker):
    url = f"https://j.gravelle.us/APIs/Stocks/tickerApi.php?q={ticker}"
    response = requests.get(url)
    if response.status_code == 200:
        data = response.json()
        if data["status"] == "OK" and data["resultsCount"] > 0:
            result = data["results"][0]
            return f"Stock info for {ticker}: \nOpen: {result['o']} \nClose: {result['c']} \nHigh: {result['h']} \nLow: {result['l']} \nVolume: {result['v']}"
        return f"No stock info found for {ticker}"
```