

## 6.1 Interpolation of Data

- Suppose we have a collection of four values that we wish to enlarge to eight




FIGURE 6.1 Replacing four points with eight.




FIGURE 6.2 Figure 6.1 slightly redrawn.

## 6.1 Interpolation of Data




FIGURE 6.3 Filled circles are the coincide points of  $x$  and  $x'$ .

Ch6-p.122

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

CENGAGE  
Learning

## 6.1 Interpolation of Data

- The  $a$  and  $b$  of the linear function can be solved by

$$\begin{cases} 1 = a + b \\ 4 = 8a + b \end{cases}$$

- Then we can obtain the linear function

$$x = \frac{3}{7}x' + \frac{4}{7} \quad \begin{aligned} x' &= \frac{1}{3}(7x - 4), \\ x &= \frac{1}{7}(3x' + 4) \end{aligned}$$

(continuous)

Ch6-p.122

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

CENGAGE  
Learning

## 6.1 Interpolation of Data

- In digital (**discrete**), none of the  $x'_i$  points coincide exactly with an original  $x_j$ , except for the first and last
- We have to estimate function values  $f(x'_i)$  based on the known values of nearby  $f(x_j)$
- Such estimation of function values based on surrounding values is called **interpolation**

Ch6-p.122-123

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

### FIGURE 6.4

- **Nearest-neighbor interpolation**




FIGURE 6.4 Nearest-neighbor interpolation.

Ch6-p.123

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.5

- Linear interpolation




FIGURE 6.5 Linear interpolation.

Ch6-p.123

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.6




FIGURE 6.6 Calculating linearly interpolated values.

Ch6-p.124

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.2 Image Interpolation

- Using the formula given by Equation 6.1

$$f(x, y') = \mu f(x, y + 1) + (1 - \mu) f(x, y)$$

$$f(x + 1, y') = \mu f(x + 1, y + 1) + (1 - \mu) f(x + 1, y)$$

$$f(x', y') = \lambda f(x + 1, y') + (1 - \lambda) f(x, y')$$

9

Ch6-p.125

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## FIGURE 6.7




FIGURE 6.7 Interpolation on an image.

10

Ch6-p.125

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.8




FIGURE 6.8 Interpolation between four image points.

11

Ch6-p.126

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.2 Image Interpolation

- Function `imresize`

`imresize(A,k,'method')`

- Where `A` is an image of any type, `k` is a scaling factor, and `'method'` is either `'nearest'` or `'bilinear'`, etc.

```
>> c=imread('cameraman.tif');
>> head=c(33:96,90:153);
>> imshow(head)
>> head4n=imresize(head,4,'nearest');imshow(head4n)
>> head4b=imresize(head,4,'bilinear');imshow(head4b)
```

12

Ch6-p.127

© 2010 Cengage Learning  
Engineering. All Rights Reserved.



## FIGURE 6.9 & 6.10



FIGURE 6.9 The head.



(a)



(b)

FIGURE 6.10 Scaling by interpolation. (a) Nearest neighbor scaling. (b) Bilinear interpolation.

13

Ch6-p.127-128

© 2010 Cengage Learning  
Engineering. All Rights Reserved.



## 6.3 General Interpolation

$$f(x') = R(-\lambda)f(x_1) + R(1-\lambda)f(x_2). \quad (\text{Equation 6.2})$$




FIGURE 6.11 Using a general interpolation function.

14

Ch6-p.129

© 2010 Cengage Learning  
Engineering. All Rights Reserved.



FIGURE 6.12

$$R_0(u) = \begin{cases} 0 & \text{if } u \leq -0.5, \\ 1 & \text{if } -0.5 < u \leq 0.5, \\ 0 & \text{if } u > 0.5, \end{cases}$$

$$R_1(u) = \begin{cases} 1 + u & \text{if } u \leq 0, \\ 1 - u & \text{if } u \geq 0. \end{cases}$$




FIGURE 6.12 Two interpolation functions.

15


Ch6-p.129

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.3 General Interpolation

- The functions  $R_0(u)$  and  $R_1(u)$  are just two members of a family of possible interpolation functions
- Another such function provides **cubic interpolation**

$$R_3(u) = \begin{cases} 1.5|u|^3 - 2.5|u|^2 + 1 & \text{if } |u| \leq 1, \\ -0.5|u|^3 + 2.5|u|^2 - 4|u| + 2 & \text{if } 1 < |u| \leq 2. \end{cases}$$

FIGURE 6.13 The cubic interpolation function  $R_3(u)$ .

16


Ch6-p.130

© 2010 Cengage Learning  
Engineering. All Rights Reserved.



FIGURE 6.14

$$f(x') = R_3(-1 - \lambda)f(x_1) + R_3(-\lambda)f(x_2) + R_3(1 - \lambda)f(x_3) + R_3(2 - \lambda)f(x_4),$$

FIGURE 6.14 Using  $R_3(u)$  for interpolation.

17

Ch6-p.131

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.15




FIGURE 6.15 How to apply bicubic interpolation.

18

Ch6-p.131

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.16

```
>> head4c=imresize(head,4,'bicubic');imshow(head4c)
```



FIGURE 6.16 Enlargement using bicubic interpolation.

19

Ch6-p.131-132

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.4 Enlargement by Spatial Filtering

- If we merely wish to enlarge an image by a power of two, there is a quick and dirty method that uses linear filtering

e.g.

```
>> m=magic(4)
```

m =

16	2	3	13
5	11	10	8
9	7	6	12
4	14	15	1

✓ zero-interleaved

$$m_2(i,j) = \begin{cases} m((i+1)/2, (j+1)/2) & \text{if } i \text{ and } j \text{ are both odd,} \\ 0 & \text{otherwise.} \end{cases}$$

20

Ch6-p.132

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## FIGURE 6.17

This can be implemented with a simple function

```
function out=zeroint(a)
%
% ZEROINT(A) produces a zero-interleaved version of the matrix A.
% For example:
%
%   a=[1 2 3;4 5 6];
%   zeroint(a)
%
%       1     0     2     0     3
%       0     0     0     0     0
%       4     0     5     0     6
%
[m,n]=size(a); a2=reshape([a;zeros(m,n)],m,2*n);
out=reshape([a2';zeros(2*n,m)],2*n,2*m)';
```

FIGURE 6.17 A simple function for implementing zero interleaving.

21

Ch6-p.133

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.4 Enlargement by Spatial Filtering

```
>> m2=zeroint(m)
```

```
m2 =
```

```

16     0     2     0     3     0    13     0
 0     0     0     0     0     0     0     0
 5     0    11     0    10     0     8     0
 0     0     0     0     0     0     0     0
 9     0     7     0     6     0    12     0
 0     0     0     0     0     0     0     0
 4     0    14     0    15     0     1     0
 0     0     0     0     0     0     0     0
```

We can now replace the zeros by applying a spatial filter to this matrix

$$\begin{bmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

nearest-neighbor

$$\frac{1}{4} \begin{bmatrix} 1 & 2 & 1 \\ 2 & 4 & 2 \\ 1 & 2 & 1 \end{bmatrix}$$

bilinear

$$\frac{1}{64} \begin{bmatrix} 1 & 4 & 6 & 4 & 1 \\ 4 & 16 & 24 & 16 & 4 \\ 6 & 24 & 36 & 24 & 6 \\ 4 & 16 & 24 & 16 & 4 \\ 1 & 4 & 6 & 4 & 1 \end{bmatrix}$$

bicubic

22

Ch6-p.133

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.4 Enlargement by Spatial Filtering

```
>> filter2([1 1 0;1 1 0;0 0 0],m2)
```

```
ans =
```

```
16 16 2 2 3 3 13 13
16 16 2 2 3 3 13 13
5 5 11 11 10 10 8 8
5 5 11 11 10 10 8 8
9 9 7 7 6 6 12 12
9 9 7 7 6 6 12 12
4 4 14 14 15 15 1 1
4 4 14 14 15 15 1 1
```

```
>> filter2([1 2 1;2 4 2;1 2 1]/4,m2)
```

```
ans =
```

```
16.0000 9.0000 2.0000 2.5000 3.0000 8.0000 13.0000 6.5000
10.5000 8.5000 6.5000 6.5000 6.5000 8.5000 10.5000 5.2500
5.0000 8.0000 11.0000 10.5000 10.0000 9.0000 8.0000 4.0000
7.0000 8.0000 9.0000 8.5000 8.0000 9.0000 10.0000 5.0000
9.0000 8.0000 7.0000 6.5000 6.0000 9.0000 12.0000 6.0000
6.5000 8.5000 10.5000 10.5000 10.5000 8.5000 6.5000 3.2500
4.0000 9.0000 14.0000 14.5000 15.0000 8.0000 1.0000 0.5000
2.0000 4.5000 7.0000 7.2500 7.5000 4.0000 0.5000 0.2500
```

23

Ch6-p.134

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## FIGURE 6.18

```
>> imshow(hz)
>> imshow(filter2([1 1 0;1 1 0;0 0 0],hz)/255)
>> imshow(filter2([1 2 1;2 4 2;1 2 1]/4,hz)/255)
>> bfilt=[1 4 6 4 1;4 16 24 16 4;6 24 36 24 6;4 16 24 16 4;1 4 6 4 1]/64;
>> imshow(filter2(bfilt,hz)/255)
```



FIGURE 6.18 Enlargement by spatial filtering.

24

Ch6-p.134-135

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.5 Scaling Smaller

- Making an image smaller is also called **image minimization**
- **Subsampling**

e.g.

```
>> t=zeros(1024,1024);
>> for i=1:1024
    for j=1:1024
        t(i,j)=(255.5)^2<(i-512).^2+(j-512).^2&((i-512)...
            ^2+(j-512).^2<(256.5)^2);
    end
end
>> t=~t;

>> tr=imresize(t,0.25);

>> trc=imresize(t,0.25,'bicubic');
```

25

Ch6-p.135

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## FIGURE 6.19



(a)



(b)

**FIGURE 6.19** Minimization. (a) Nearest-neighbor minimization. (b) Bicubic interpolation for minimization.

26

Ch6-p.136

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.6 Rotation




FIGURE 6.20 Rotating a point through angle  $\theta$ .

27

Ch6-p.136

© 2010 Cengage Learning  
Engineering. All Rights Reserved.



## FIGURE 6.21




FIGURE 6.21 Rotating a rectangle.

28

Ch6-p.138

© 2010 Cengage Learning  
Engineering. All Rights Reserved.





## 6.6 Rotation

- In Figure 6.21, the filled circles indicate the original position, and the open circles point their positions after rotation
- We must ensure that even after rotation, the points remain in that grid
- To do this we consider a rectangle that includes the rotated image, as shown in Figure 6.22

29

Ch6-p.137

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

### FIGURE 6.22




FIGURE 6.22 A rectangle surrounding a rotated image.

30

Ch6-p.138

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.23




FIGURE 6.23 The points on a grid after rotation.

31

Ch6-p.138

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## 6.6 Rotation

The gray value at  $(x'', y'')$  can be found by interpolation, using surrounding gray values. This value is then the gray value for the pixel at  $(x', y')$  in the rotated image

32

Ch6-p.137

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.24




FIGURE 6.24 Rotating a point back into the original image.

33

Ch6-p.139

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.25

```
>> cr=imrotate(c,60);
>> imshow(cr)
>> crc=imrotate(c,60,'bicubic');
>> imshow(crc)
```



(a)



(b)

FIGURE 6.25 Rotation with interpolation. (a) Nearest neighbor. (b) Bicubic interpolation.

34

Ch6-p.139

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.26



FIGURE 6.26 The Ambassadors (1533) by Hans Holbein.

35

Ch6-p.140

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

FIGURE 6.27

```
>> a=imread('AMBASSADORS.JPG');
>> a=rgb2gray(a);
```

```
>> skull=a(566:743,157:586);
```




FIGURE 6.27 The skull alone.

36

Ch6-p.141

© 2010 Cengage Learning  
Engineering. All Rights Reserved.

## FIGURE 6.28

```
>> skull2=imresize(imrotate(skull,-22,'bicubic'),[500,150],'bicubic');
```

```
>> imshow(skull2(200:350,:))
```



FIGURE 6.28 The corrected skull.