

Frequently Asked Questions on OpenWebStart

Table of Contents

General	1
What is OpenWebStart?	1
Subscription and Premium Support	1
Is there a subscription for OpenWebStart?	1
Is there a premium support for OpenWebStart?	2
What are the costs for subscription and premium support?	2
Installation	2
Do I have to install a Java on my system to run OWS?	2
Which Java versions can be used to run my JNLP applications?	2
Is there an MSI installer for OpenWebStart?	2
Debugging and Error Reporting	2
Does OWS write log files and where do I find them?	3
Functionality	3
Does OpenWebStart support Applets?	3
How can I define a server whitelist for OWS?	3

NOTE

The authors assume no responsibility or liability for any errors or omissions in the content of this documentation. The information contained in this documentation is provided on an "as is" basis with no guarantees of completeness, accuracy, usefulness, timeliness or of the results obtained from the use of this information.

<this documentation is work in progress>

General

What is OpenWebStart?

<this documentation is work in progress>

Subscription and Premium Support

Is there a subscription for OpenWebStart?

Basic subscription provided by Karakun is the cost-effective way to support OpenWebStart. With this option you may report bugs using a dedicated communication channel and your bug reports

will have a higher priority. If you wish, we will add your company logo to our sponsor list for free. Plus, you'll get a 10% discount for development of individual features.

Is there a premium support for OpenWebStart?

With premium support provided by Karakun you may report bugs or issues using the premium communication channel. Your bug reports will have the highest priority. Karakun will guarantee reaction times depending on the severity of bugs (during business hours). Plus, you'll get a 25% discount for the development of individual features. Upon your wish, your company logo will be listed as a premium sponsor on our website.

What are the costs for subscription and premium support?

Please contact openwebstart@karakun.com to figure out which support model fits your needs best.

Installation

Do I have to install a Java on my system to run OWS?

OpenWebStart comes with a JVM Manager and a bundled Java runtime. There is no need to have any JVM installed on your system.

The bundled JVM is used solely to run OWS. The JVMs managed by the JVM Manager are used to run the JNLP applications.

Which Java versions can be used to run my JNLP applications?

Your JNLP applications can be run with either Java 8 and 11. We have not run any tests with Java 12 or 13 yet but from the experience collected while adding support for Java 11 we do not expect any big obstacles.

OpenWebStart JVM Manager will download and manage JVMs as they are requested by an application. Currently, we provide Azul and Adopt JDKs on the default download server. In the future we will add more vendors.

If your preferred JVM is not provided by our default download server, you can either add locally installed JVMs or host your own download server for JVMs to run your JNLP applications.

Is there an MSI installer for OpenWebStart?

Currently, we do not provide an MSI installer. More details on the reasons can be found at <https://github.com/karakun/OpenWebStart/issues/98>.

Debugging and Error Reporting

Does OWS write log files and where do I find them?

The log files of OWS are located in a hidden directory below your user home directory:

```
<user-home>/config/icedtea-web/log
```

where **<user-home>** depends on your operating system. By default this should be

<root>\Users\<your-username>	(Windows 10)
/Users/<your-username>	(MacOS)
/home/<your-username>/	(Linux)

Note that logging has to be activated using the OWS Settings application by checking "Activate debug logging" and "Log to file" on the "Logging" tab.

Functionality

Does OpenWebStart support Applets?

Applets are not supported and there are no plans to support them in the future. We also do not consider this as a deviation from the JNLP-standard as this is an optional feature according to the JSR-56 specs.

How can I define a server whitelist for OWS?

This field is currently not editable in the UI. Edit the deployment properties file `${userHome}/config/icedtea-web/deployment.properties` file with a text editor by adding a new line:

```
deployment.security.whitelist=10.10.10.10, google.com, some.server.net
```

The different servers are listed as a comma separated string. Localhost is implicitly always in the white list. If you delete the line again then no whitelisting is applied and all servers are reachable.

Note that whitelisting only applies while downloading resources (jars and jnlps) and not while an application is running. Thus, an application can open a connection to a server which is not in the white list.

It is also possible to specify the content of the whitelist when installing OWS (unattended installation), see <https://openwebstart.com/installation/> and <https://openwebstart.com/configuration/> for further details.