
Machine Learning and Data Mining

Introduction

Prof. Alexander Ihler







Artificial Intelligence (AI)

- Building "intelligent systems"
- Lots of parts to intelligent behavior



RoboCup



Darpa GC (Stanley)






Chess (Deep Blue v. Kasparov)


Machine learning (ML)

- One (important) part of AI
- Making predictions (or decisions)
- Getting better with experience (data)
- Problems whose solutions are "hard to describe"







- Supervised learning
 - "Labeled" training data
 - Every example has a desired target value (a "best answer")
 - Reward prediction being close to target
 - Classification: a discrete-valued prediction
 - Regression: a continuous-valued prediction






- Supervised learning
- Unsupervised learning
 - No known target values
 - No targets = nothing to predict?
 - Reward "patterns" or "explaining features"
 - Often, data mining





- Supervised learning
- Unsupervised learning
- Semi-supervised learning
 - Similar to supervised
 - some data have unknown target values
- Ex: medical data
 - Lots of patient data, few known outcomes
- Ex: image tagging
 - Lots of images on Flikr, but only some of them tagged

- Supervised learning
- Unsupervised learning
- Semi-supervised learning
- Reinforcement learning
- "Indirect" feedback on quality
 - No answers, just "better" or "worse"
 - Feedback may be delayed



Logistics

- Course webpage for assignments & other info
- EEE for homework submission & return
 - Emails: will send a test email tomorrow make sure you get it
- Piazza for questions & discussions
- No required textbook
 - Recommended: Murphy, "Machine Learning...", 2012.
 - Also
 - Duda, Hart & Stork, "Pattern classification"
 - Hastie, Tibshirani & Friedman, "Elements of Statistical Learning"
- But
 - I'll try to cover everything needed in lectures and notes
 - All textbooks mainly for reference purposes

Logistics

- Grading (approximate)
 - 25% homework (~6, drop lowest)
 - 10% project (Kaggle)
 - 5% reading quizzes
 - 25% midterm, 35% final
 - Due 5pm listed day, EEE or my office
 - No late homework (solutions posted)
 - Turn in what you have

Collaboration

- Study groups, discussion, assistance encouraged
 - Whiteboards, etc.
- Do your homework yourself
 - Don't exchange solutions or HW code

Data exploration

- Machine learning is a data science
 - Look at the data; get a "feel" for what might work
- What types of data do we have?
 - Binary values? (spam; gender; ...)
 - Categories? (home state; labels; ...)
 - Integer values? (1..5 stars; age brackets; ...)
 - (nearly) real values? (pixel intensity; prices; ...)
- Are there missing data?
- "Shape" of the data? Outliers?

Matlab and alternatives

- Matlab: interpreted language for scientific computing
 - Originally designed for linear algebra (matrices, vectors)
 - Heavily adopted in research; lots of available code
 - Can be inefficient and slow

Alternatives

- Octave: free near-equivalent to Matlab
 - Often less optimized & lags Matlab features, but almost code-equivalent
- FreeMat: another free Matlab alternative
- R: Free, heavily adopted in statistics, less so in computer science
- Python: (SciPy, MatPlotLib): some adoption, esp. in comp. bio.
- C++: Fast & efficient but slow to prototype

Representing the data (Matlab)

Have m observations (data points)

$$\left\{x^{(1)}\dots,x^{(m)}\right\}$$

Each observation is a vector consisting of n features

$$x^{(j)} = [x_1^{(j)} x_2^{(j)} \dots x_n^{(j)}]$$

Often, represent this as a "data matrix"

$$\underline{X} = \begin{bmatrix} x_0^{(1)} & \dots & x_n^{(1)} \\ \vdots & \ddots & \vdots \\ x_0^{(m)} & \dots & x_n^{(m)} \end{bmatrix}$$

```
>> load('fisheriris'); % Load Fisher's "Iris" dataset
>> X = meas; % Rename measurements as "X"
>> size(X),
ans =
150 4 % 150 data points; 4 features each
```


Basic statistics

- Look at basic information about features
 - Average value? (mean, median, etc.)
 - "Spread"? (standard deviation, etc.)
 - Maximum / Minimum values?

```
>> mean(X) % compute mean of each feature
ans =
5.8433 3.0573 3.7580 1.1993
>> std(X) % compute standard deviation of each feature
ans =
0.8281 0.4359 1.7653 0.7622
>> max(X) % largest value per feature
ans =
7.9411 4.3632 6.8606 2.5236
>> min(X) % smallest value per feature
ans =
4.2985 1.9708 1.0331 0.0536
```

Histograms

- Count the data falling in each of K bins
 - "Summarize" data as a length-K vector of counts (& plot)
 - Value of K determines "summarization"; depends on # of data
 - K too big: every data point falls in its own bin; just "memorizes"
 - K too small: all data in one or two bins; oversimplifies




% Histograms in Matlab

- >> x1 = X(:,1); % Histogram for feature #1
- \Rightarrow Bins = 4:0.25:8; % Use explicit bin locations
- >> hist(x1,Bins); % Compute & plot histogram


Scatterplots

Illustrate the relationship between two features




Scatterplots

For more than two features can use a pair plot




Supervised learning and targets

- Supervised learning: predict target values
- For discrete targets, often visualize with color



How does machine learning work?


- "Meta-programming"
 - Predict apply rules to examples
 - Score get feedback on performance




Supervised learning

Notation

- Features
- Targets
- Predictions ŷ




Regression; Scatter plots




- Suggests a relationship between x and y
- Prediction: new x, what is y?

Nearest neighbor regression



• Find training datum $x^{(i)}$ closest to $x^{(new)}$ Predict $y^{(i)}$

Nearest neighbor regression




"Predictor": Given new features: Find nearest example

Return its value

- Defines a function f(x) implicitly
- "Form" is piecewise constant

Linear regression



"Predictor":


Evaluate line:

$$r = \theta_0 + \theta_1 x_1$$

return r


- Define form of function f(x) explicitly
- Find a good f(x) within that family

Measuring error



Regression vs. Classification


Regression



Features x Real-valued target y

Predict continuous function $\hat{y}(x)$

Classification




Discrete class c


(usually 0/1 or +1/-1)

Predict discrete function ŷ(x)


Classification




Classification





Measuring error




$$ERR = \frac{1}{m} \sum_{i} \left[y^{(i)} \neq \hat{y}(x^{(i)}) \right]$$











X



How Overfitting affects Prediction



Competitions

- Training data
 - Used to build your model(s)
- Validation data
 - Used to assess, select among, or combine models
 - Personal validation; leaderboard; ...
- Test data
 - Used to estimate "real world" performance

#	Δ1w	Team Name *in the money	Score ②	Entries	Last Submission U1
1	-	BrickMover ♣ *	1.21251	40	Sat, 31 Aug 2013 23:
2	new	vsu *	1.21552	13	Sat, 31 Aug 2013 20:
3	↑2	Merlion	1.22724	29	Sat, 31 Aug 2013 23:
4	↓2	Sergey	1.22856	15	Sat, 31 Aug 2013 23:
5	new	liuyongqi	1.22980	13	Sat, 31 Aug 2013 13:

Summary

- What is machine learning?
 - Types of machine learning
 - How machine learning works
- Supervised learning
 - Training data: features x, targets y
- Regression
 - (x,y) scatterplots; predictor outputs f(x)
- Classification
 - (x,x) scatterplots
 - Decision boundaries, colors & symbols
- Complexity
 - Training vs test error
 - Under- & over-fitting