



Database Visualization

John C. Hart

Department of Computer Science

University of Illinois at Urbana Champaign



Databases

- **OLAP** - OnLine Analytical Processing
- **Data Cube** – multidimensional spreadsheet (hypercube if > 3 dim.)
- **Dimension** – database key
- **Measure** – database values
- **Cell** – element of the data cube holding specific value(s) for each of the dimensions

Sales database:


<date, product, location, amount>

(8/7/15, coffee, Seattle, \$4)

(8/8/15, tea, Beijing, \$3)


(8/5/15, espresso, Rome, \$5)

...





Data Aggregation

- **Quantitative:** sum, mean, median, minimum, maximum
- **Count:** converts ordinal or nominal data into quantitative data
- **Binning:** discretizes quantitative data into ordinal or nominal data




Data Aggregation

- **Quantitative:** sum, mean, median, minimum, maximum
- **Count:** converts ordinal or nominal data into quantitative data
- **Binning:** discretizes quantitative data into ordinal or nominal data





Data Aggregation

- **Quantitative:** sum, mean, median, minimum, maximum
- **Count:** converts ordinal or nominal data into quantitative data
- **Binning:** discretizes quantitative data into ordinal or nominal data




Histogram




Data Cubes

(a) The lattice of data cubes




(b) Projecting a three dimensional data cube



OLAP ⇔ Infovis

Cube Op	Description	Infovis Op
Slicing	Reduce dimensionality by selecting a single attribute value along one of the dimensions	Filter value
Dicing	Focus on a subcube spanning a range of values across one or more dimensions of the cube	Filter range, zoom plot area
Roll-Up	Reduces dimensionality by projecting cube along one of its axes using a summary op	Aggregation
Drill Down	Increases dimensionality by expanding summaries into values, or subdivides dimensions into finer details	Zoom fields, details on demand, (disaggregation)
Pivot	Rotates cube to display a different face comparing different dimensions	Field selection



Worlds within Worlds

- Each glyph is itself a plot
- E.g. a table of tables
- Different scales for major axis and minor axis for both horizontal and vertical axes
- Can work in 3-D or even deeper nesting (worlds within worlds within worlds), but less effectively





Tableau layout of World Bank Indicator Data

Organizing Axes

Stolte et al., Polaris...,
IEEE TVCG 8(1), 2002

- **Concatenation**

- Multiple views of data
- Quarter + Product
- Quarter + Month



- **Product**

- View of data by combination
- Quarter x Product
- Quarter x Month

- **Nesting**

- Limit to combinations in database
- Quarter / Product
- Quarter / Month

Organizing Axes

Stolte et al., Polaris...,
IEEE TVCG 8(1), 2002

- **Concatenation**

- Multiple views of data
- Quarter + Product
- Quarter + Month

- **Product**

- View of data by combination
- Quarter x Product
- Quarter x Month

Q1			Q2			Q3			Q4		
Cof.	Esp.	Tea	Cof.	Esp.	Tea	Cof.	Esp.	Tea	Cof.	Esp.	Tea

Q1			Q2			Q3			Q4																										
J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S	O	N	D

- **Nesting**

- Limit to combinations in database
- Quarter / Product
- Quarter / Month

Organizing Axes

Stolte et al., Polaris...,
IEEE TVCG 8(1), 2002

- **Concatenation**

- Multiple views of data
- Quarter + Product
- Quarter + Month

- **Product**

- View of data by combination
- Quarter x Product
- Quarter x Month

- **Nesting**

- Limit to combinations in database
- Quarter / Product
- Quarter / Month

Q1			Q2			Q3		Q4		
Cof.	Esp.		Cof.	Esp.	Tea	Cof.	Tea	Cof.	Esp.	Tea

Q1			Q2			Q3		Q4			
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec