


Chapter 2:

Introduction to C++


Addison-Wesley
is an imprint of

PEARSON

Copyright © 2012 Pearson Education, Inc.



2.1



The Part of a C++ Program

The Parts of a C++ Program

```
// sample C++ program ← comment
#include <iostream> ← preprocessor directive
using namespace std; ← which namespace to use
int main() ← beginning of function named main
{ ← beginning of block for main
    cout << "Hello, there!"; ← output statement
    return 0; ← send 0 to operating system
} ← end of block for main
```


Diagram illustrating the parts of a C++ program with annotations:

- `// sample C++ program`: comment
- `#include <iostream>`: preprocessor directive
- `using namespace std;`: which namespace to use
- `int main()`: beginning of function named `main`
- `{`: beginning of block for `main`
- `cout << "Hello, there!";`: output statement
- `"Hello, there!"`: string literal
- `return 0;`: send 0 to operating system
- `}`: end of block for `main`

Special Characters

Character	Name	Meaning
//	Double slash	Beginning of a comment
#	Pound sign	Beginning of preprocessor directive
< >	Open/close brackets	Enclose filename in #include
()	Open/close parentheses	Used when naming a function
{ }	Open/close brace	Encloses a group of statements
" "	Open/close quotation marks	Encloses string of characters
;	Semicolon	End of a programming statement

2.2



The `cout` Object

The `cout` Object

- Displays output on the computer screen
- You use the stream insertion operator `<<` to send output to `cout`:

```
cout << "Programming is fun!";
```

The cout Object

- Can be used to send more than one item to cout:

```
cout << "Hello " << "there!";
```

Or:

```
cout << "Hello ";
```

```
cout << "there!";
```

The cout Object

- This produces one line of output:

```
cout << "Programming is ";  
cout << "fun!";
```


The `endl` Manipulator

- You can use the `endl` manipulator to start a new line of output. This will produce two lines of output:

```
cout << "Programming is" << endl;  
cout << "fun!";
```

The endl Manipulator

```
cout << "Programming is" << endl;  
cout << "fun!";
```



The `endl` Manipulator

- You do NOT put quotation marks around `endl`
- The last character in `endl` is a lowercase L, not the number 1.

`endl` ← This is a lowercase L

The `\n` Escape Sequence

- You can also use the `\n` escape sequence to start a new line of output. This will produce two lines of output:

```
cout << "Programming is\n";  
cout << "fun!";
```


Notice that the `\n` is **INSIDE**
the string.

The `\n` Escape Sequence

```
cout << "Programming is\n";  
cout << "fun!";
```



2.3




The `#include` Directive

The `#include` Directive

- Inserts the contents of another file into the program
- This is a preprocessor directive, not part of C++ language
- `#include` lines not seen by compiler
- Do not place a semicolon at end of `#include` line

2.4



Variables and Literals

Variables and Literals


- Variable: a storage location in memory
 - Has a name and a type of data it can hold
 - Must be defined before it can be used:

```
int item;
```

Variable Definition in Program 2-7

Program 2-7

```
1  // This program has a variable.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      int number;
8
9      number = 5;
10     cout << "The value in number is " << number << endl;
11     return 0;
12 }
```



Program Output

The value in number is 5

Literals

- Literal: a value that is written into a program's code.


`"hello, there"` (string literal)

`12` (integer literal)

Integer Literal in Program 2-9

Program 2-9

```
1  // This program has literals and a variable.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      int apples;
8
9      apples = 20;
10     cout << "Today we sold " << apples << " bushels of apples.\n";
11     return 0;
12 }
```



20 is an integer literal

Program Output


Today we sold 20 bushels of apples.

String Literals in Program 2-9

Program 2-9

```
1 // This program has literals and a variable.
2 #include <iostream>
3 using namespace std;
4
5 int main()
6 {
7     int apples;
8
9     apples = 20;
10    cout << "Today we sold " << apples << " bushels of apples.\n",
11    return 0;
12 }
```

These are string literals




Program Output

Today we sold 20 bushels of apples.

2.5

Identifiers



Identifiers

- An identifier is a programmer-defined name for some part of a program: variables, functions, etc.

C++ Key Words

You cannot use any of the C++ key words as an identifier. These words have reserved meaning.

Table 2-4 The C++ Key Words

and	continue	goto	public	try
and_eq	default	if	register	typedef
asm	delete	inline	reinterpret_cast	typeid
auto	do	int	return	typename
bitand	double	long	short	union
bitor	dynamic_cast	mutable	signed	unsigned
bool	else	namespace	sizeof	using
break	enum	new	static	virtual
case	explicit	not	static_cast	void
catch	export	not_eq	struct	volatile
char	extern	operator	switch	wchar_t
class	false	or	template	while
compl	float	or_eq	this	xor
const	for	private	throw	xor_eq
const_cast	friend	protected	true	

Variable Names

- A variable name should represent the purpose of the variable. For example:

itemsOrdered

The purpose of this variable is to hold the number of items ordered.


Identifier Rules

- The first character of an identifier must be an alphabetic character or an underscore (_),
- After the first character you may use alphabetic characters, numbers, or underscore characters.
- Upper- and lowercase characters are distinct

Valid and Invalid Identifiers

IDENTIFIER	VALID?	REASON IF INVALID
totalSales	Yes	
total_Sales	Yes	
total.Sales	No	Cannot contain .
4thQtrSales	No	Cannot begin with digit
totalSale\$	No	Cannot contain \$

2.6



Integer Data Types

Integer Data Types

- Integer variables can hold whole numbers such as 12, 7, and -99.

Table 2-6 Integer Data Types, Sizes, and Ranges

Data Type	Size	Range
short	2 bytes	-32,768 to +32,767
unsigned short	2 bytes	0 to +65,535
int	4 bytes	-2,147,483,648 to +2,147,483,647
unsigned int	4 bytes	0 to 4,294,967,295
long	4 bytes	-2,147,483,648 to +2,147,483,647
unsigned long	4 bytes	0 to 4,294,967,295

Defining Variables

- Variables of the same type can be defined
 - On separate lines:

```
int length;  
int width;  
unsigned int area;
```
 - On the same line:

```
int length, width;  
unsigned int area;
```
- Variables of different types must be in different definitions

Integer Types in Program 2-10

Program 2-10

```
1  // This program has variables of several of the integer types.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      int checking;
8      unsigned int miles;
9      long days;
10
11     checking = -20;
12     miles = 4276;
13     days = 189000;
14     cout << "We have made a long journey of " << miles;
15     cout << " miles.\n";
16     cout << "Our checking account balance is " << checking;
17     cout << "\nAbout " << days << " days ago Columbus ";
18     cout << "stood on this spot.\n";
19     return 0;
20 }
```

This program has three variables: checking, miles, and days

Integer Literals

- An integer literal is an integer value that is typed into a program's code. For example:

```
itemsOrdered = 15;
```


In this code, 15 is an integer literal.

Integer Literals in Program 2-10

Program 2-10

```
1  // This program has variables of several of the integer types.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      int checking;
8      unsigned int miles;
9      long days;
10
11     checking = -20;
12     miles = 4276;
13     days = 189000;
14     cout << "We have made a long journey of " << miles;
15     cout << " miles.\n";
16     cout << "Our checking account balance is " << checking;
17     cout << "\nAbout " << days << " days ago Columbus ";
18     cout << "stood on this spot.\n";
19     return 0;
20 }
```


Integer Literals



Integer Literals

- Integer literals are stored in memory as `ints` by default
- To store an integer constant in a long memory location, put 'L' at the end of the number: `1234L`
- Constants that begin with '0' (zero) are base 8: `075`
- Constants that begin with '0x' are base 16: `0x75A`

2.7



The `char` Data Type

The char Data Type

- Used to hold characters or very small integer values
- Usually 1 byte of memory
- Numeric value of character from the character set is stored in memory:

CODE:

```
char letter;  
letter = 'C';
```

MEMORY:

letter



67

Character Literals

- Character literals must be enclosed in single quote marks. Example:

'A'

Character Literals in Program 2-13

Program 2-13

```
1  // This program uses character literals.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      char letter;
8
9      letter = 'A';
10     cout << letter << endl;
11     letter = 'B';
12     cout << letter << endl;
13     return 0;
14 }
```

Program Output

A
B

Character Strings


- A series of characters in consecutive memory locations:

`"Hello"`

- Stored with the null terminator, `\0`, at the end:
- Comprised of the characters between the " "

H	e	l	l	o	\0
---	---	---	---	---	----

2.8



The C++ `string` Class

The C++ `string` Class

- Special data type supports working with strings
- `#include <string>`
- Can define `string` variables in programs:
`string firstName, lastName;`
- Can receive values with assignment operator:
`firstName = "George";`
`lastName = "Washington";`
- Can be displayed via `cout`
`cout << firstName << " " << lastName;`

The `string` class in Program 2-15


Program 2-15

```
1  // This program demonstrates the string class.
2  #include <iostream>
3  #include <string> // Required for the string class.
4  using namespace std;
5
6  int main()
7  {
8      string movieTitle;
9
10     movieTitle = "Wheels of Fury";
11     cout << "My favorite movie is " << movieTitle << endl;
12     return 0;
13 }
```

Program Output

My favorite movie is Wheels of Fury

2.9



Floating-Point Data Types

Floating-Point Data Types

- The floating-point data types are:
`float`
`double`
`long double`
- They can hold real numbers such as:
12.45 -3.8
- Stored in a form similar to scientific notation
- All floating-point numbers are signed

Floating-Point Data Types

Table 2-8 Floating Point Data Types on PCs

Data Type	Key Word	Description
Single precision	<code>float</code>	4 bytes. Numbers between $\pm 3.4\text{E}-38$ and $\pm 3.4\text{E}38$
Double precision	<code>double</code>	8 bytes. Numbers between $\pm 1.7\text{E}-308$ and $\pm 1.7\text{E}308$
Long double precision	<code>long double*</code>	8 bytes. Numbers between $\pm 1.7\text{E}-308$ and $\pm 1.7\text{E}308$

Floating-Point Literals

- Can be represented in
 - Fixed point (decimal) notation:
31.4159 0.0000625
 - E notation:
3.14159E1 6.25e-5
- Are `double` by default
- Can be forced to be float (`3.14159f`) or long double (`0.0000625L`)

Floating-Point Data Types in Program 2-16


Program 2-16

```
1  // This program uses floating point data types.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      float distance;
8      double mass;
9
10     distance = 1.495979E11;
11     mass = 1.989E30;
12     cout << "The Sun is " << distance << " meters away.\n";
13     cout << "The Sun\'s mass is " << mass << " kilograms.\n";
14     return 0;
15 }
```

Program Output

```
The Sun is 1.49598e+011 meters away.
The Sun's mass is 1.989e+030 kilograms.
```

2.10



The `bool` Data Type

The `bool` Data Type

- Represents values that are `true` or `false`
- `bool` variables are stored as small integers
- `false` is represented by 0, `true` by 1:

<code>bool allDone = true;</code>	<code>allDone</code>	<code>finished</code>
<code>bool finished = false;</code>	<div>1</div>	<div>0</div>

Boolean Variables in Program 2-17


Program 2-17

```
1  // This program demonstrates boolean variables.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      bool boolValue;
8
9      boolValue = true;
10     cout << boolValue << endl;
11     boolValue = false;
12     cout << boolValue << endl;
13     return 0;
14 }
```

Program Output

1
0

2.11




Determining the Size of a Data Type

Determining the Size of a Data Type

The `sizeof` operator gives the size of any data type or variable:

```
double amount;  
cout << "A double is stored in "  
      << sizeof(double) <<  
      "bytes\n";  
cout << "Variable amount is  
stored in "  
      << sizeof(amount)  
      << "bytes\n";
```

2.12



Variable Assignments and Initialization

Variable Assignments and Initialization

- An assignment statement uses the = operator to store a value in a variable.

```
item = 12;
```

- This statement assigns the value 12 to the `item` variable.

Assignment

- The variable receiving the value must appear on the left side of the = operator.
- This will NOT work:

```
// ERROR!  
12 = item;
```

Variable Initialization

- To initialize a variable means to assign it a value when it is defined:

```
int length = 12;
```

- Can initialize some or all variables:

```
int length = 12, width = 5, area;
```


Variable Initialization in Program 2-19

Program 2-19


```
1  // This program shows variable initialization.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      int month = 2, days = 28;
8
9      cout << "Month " << month << " has " << days << " days.\n";
10     return 0;
11 }
```

Program Output

Month 2 has 28 days.

2.13

Scope



Scope


- The scope of a variable: the part of the program in which the variable can be accessed
- A variable cannot be used before it is defined

Variable Out of Scope in Program 2-20

Program 2-20

```
1  // This program can't find its variable.
2  #include <iostream>
3  using namespace std;
4
5  int main()
6  {
7      cout << value; // ERROR! value not defined yet!
8
9      int value = 100;
10     return 0;
11 }
```

2.14



Arithmetic Operators

Arithmetic Operators

- Used for performing numeric calculations
- C++ has unary, binary, and ternary operators:
 - unary (1 operand) -5
 - binary (2 operands) $13 - 7$
 - ternary (3 operands) $\text{exp1} ? \text{exp2} : \text{exp3}$

Binary Arithmetic Operators

SYMBOL	OPERATION	EXAMPLE	VALUE OF ans
+	addition	<code>ans = 7 + 3;</code>	10
-	subtraction	<code>ans = 7 - 3;</code>	4
*	multiplication	<code>ans = 7 * 3;</code>	21
/	division	<code>ans = 7 / 3;</code>	2
%	modulus	<code>ans = 7 % 3;</code>	1

A Closer Look at the / Operator

- / (division) operator performs integer division if both operands are integers

```
cout << 13 / 5;    // displays 2
```

```
cout << 91 / 7;    // displays 13
```

- If either operand is floating point, the result is floating point

```
cout << 13 / 5.0;  // displays 2.6
```

```
cout << 91.0 / 7;  // displays 13.0
```


A Closer Look at the % Operator

- % (modulus) operator computes the remainder resulting from integer division

```
cout << 13 % 5;    // displays 3
```

- % requires integers for both operands

```
cout << 13 % 5.0; // error
```

Wages calculating problem

- Write a program that calculates and displays an employee's total wages for the week. The regular hours for the work week are 40, and any hours worked over 40 are considered overtime. The employee earns \$18.25 per hour for regular hours, and \$27.78 per hour for overtime hours. The employee has worked 50 hours this week.

Wages calculating problem:

Pseudo code

- *Regular wages = base pay rate × regular hours*
- *Overtime wages = overtime pay rate × overtime hours*
- *Total wages = regular wages + overtime wages*
- *Display the total wages*

Arithmetic Operators in Program 2-21

Program 2-21


```
1 // This program calculates hourly wages, including overtime.
2 #include <iostream>
3 using namespace std;
4
5 int main()
6 {
7     double regularWages,           // To hold regular wages
8           basePayRate = 18.25,     // Base pay rate
9           regularHours = 40.0,     // Hours worked less overtime
10          overtimeWages,           // To hold overtime wages
11          overtimePayRate = 27.78, // Overtime pay rate
12          overtimeHours = 10,      // Overtime hours worked
13          totalWages;              // To hold total wages
14
15     // Calculate the regular wages.
16     regularWages = basePayRate * regularHours;
17
18     // Calculate the overtime wages.
19     overtimeWages = overtimePayRate * overtimeHours;
20
21     // Calculate the total wages.
22     totalWages = regularWages + overtimeWages;
23
24     // Display the total wages.
25     cout << "Wages for this week are $" << totalWages << endl;
26     return 0;
27 }
```

Program Output

Wages for this week are \$1007.8

2.15

Comments



Comments

- Used to document parts of the program
- Intended for persons reading the source code of the program:
 - Indicate the purpose of the program
 - Describe the use of variables
 - Explain complex sections of code
- Are ignored by the compiler

Single-Line Comments

Begin with `//` through to the end of line:

```
int length = 12; // length in  
    inches
```

```
int width = 15;    // width in inches  
int area;          // calculated area
```

```
// calculate rectangle area  
area = length * width;
```

Multi-Line Comments

- Begin with `/*`, end with `*/`


- Can span multiple lines:

```
/* this is a multi-line  
   comment  
*/
```

- Can begin and end on the same line:

```
int area;    /* calculated area */
```


2.16



Named Constants

Named Constants

- Named constant (constant variable): variable whose content cannot be changed during program execution
- Used for representing constant values with descriptive names:

```
const double TAX_RATE = 0.0675;  
const int NUM_STATES = 50;
```

- Often named in uppercase letters

Named Constants in Program 2-28


Program 2-28

```
1 // This program calculates the circumference of a circle.
2 #include <iostream>
3 using namespace std;
4
5 int main()
6 {
7     // Constants
8     const double PI = 3.14159;
9     const double DIAMETER = 10.0;
10
11     // Variable to hold the circumference
12     double circumference;
13
14     // Calculate the circumference.
15     circumference = PI * DIAMETER;
16
17     // Display the circumference.
18     cout << "The circumference is: " << circumference << endl;
19     return 0;
20 }
```

Program Output

The circumference is: 31.4159

2.17



Programming Style

Programming Style

- The visual organization of the source code
- Includes the use of spaces, tabs, and blank lines
- Does not affect the syntax of the program
- Affects the readability of the source code

Program 2-25

```
1 #include <iostream>
2 using namespace std;int main(){double shares=220.0;
3 double avgPrice=14.67;cout<<"There were "<<shares
4 <<" shares sold at $"<<avgPrice<<" per share.\n";
5 return 0;}
```

Program 2-26


```
1 // This example is much more readable than Program 2-25.
2 #include <iostream>
3 using namespace std;
4
5 int main()
6 {
7     double shares = 220.0;
8     double avgPrice = 14.67;
9
10    cout << "There were " << shares << " shares sold at $";
11    cout << avgPrice << " per share.\n";
12    return 0;
13 }
```

Programming Style

Common elements to improve readability:

- Braces { } aligned vertically
- Indentation of statements within a set of braces
- Blank lines between declaration and other statements
- Long statements wrapped over multiple lines with aligned operators

2.18



Standard and Prestandard C++

Standard and Prestandard C++

Older-style C++ programs:

- Use `.h` at end of header files:
- `#include <iostream.h>`
- Use `#define` preprocessor directive instead of `const` definitions
- Do not use `using namespace` convention
- May not compile with a standard C++ compiler

#define directive in Program 2-31

Program 2-31

```
1 // This program calculates the circumference of a circle.
2 #include <iostream>
3 using namespace std;
4
5 #define PI 3.14159
6 #define DIAMETER 10.0
7
8 int main()
9 {
10     // Variable to hold the circumference
11     double circumference;
12
13     // Calculate the circumference.
14     circumference = PI * DIAMETER;
15
16     // Display the circumference.
17     cout << "The circumference is: " << circumference << endl;
18     return 0;
19 }
```

Program Output

The circumference is: 31.4159

In the spotlight: Calculating Percentages and Discounts

- Most programming languages do not use the % symbol for determining percentages
- You should convert a percentage to a floating-point number
 - 50 percent : 0.5 and 2 percent : 0.02

Example 1.

- Suppose you earn \$6,000 per month and you are allowed to contribute a portion of your gross monthly pay to a retirement plan. You want to determine the amount of your pay that will go into the plan if you contribute 5 percent, 7 percent, or 10 percent of your gross wages.

Example 2


- suppose a retail business sells an item that is regularly priced at \$59.95, and is planning to have a sale where the item's price will be reduced by 20 percent. You have been asked to write a program to calculate the sale price of the item.

Exercise of lecture 2

- 6eds
- Programming challenges:
 - 3, 4, 6, 14, 17 (p75 -77)
- Algorithm workbench
 - 25, 26
- Book Seller Software Project
 - Do the following screen project

5. Create the Reports Menu Screen.

Create a program called `reports.cpp`. It should display the following screen:



The screenshot shows a menu screen titled "Serendipity Booksellers Reports". It contains a numbered list of seven options: 1. Inventory Listing, 2. Inventory Wholesale Value, 3. Inventory Retail Value, 4. Listing by Quantity, 5. Listing by Cost, 6. Listing by Age, and 7. Return to the Main Menu. Below the list, it says "Enter Your Choice:". The entire menu is enclosed in a decorative border.

**Serendipity Booksellers
Reports**

1. Inventory Listing
2. Inventory Wholesale Value
3. Inventory Retail Value
4. Listing by Quantity
5. Listing by Cost
6. Listing by Age
7. Return to the Main Menu

Enter Your Choice: