CHAPTER 6:

Dimensionality Reduction



Why Reduce Dimensionality?

- Reduces time complexity: Less computation
- Reduces space complexity: Less parameters
- Saves the cost of observing the feature
- Simpler models are more robust on small datasets
- More interpretable; simpler explanation
- Data visualization (structure, groups, outliers, etc) if plotted in 2 or 3 dimensions

Feature Selection vs Extraction

- *Feature selection*: Choosing $k<d$ important features, ignoring the remaining $d - k$

  Subset selection algorithms

- *Feature extraction*: Project the

  original x_i , i =1,...,d dimensions to

  new $k<d$ dimensions, z_j , j =1,...,k

  Principal components analysis (PCA), linear discriminant analysis (LDA), factor analysis (FA)

Troy University Resources

Subset Selection


- There are 2^d subsets of d features
- Forward search: Add the best feature at each step
  - Set of features F initially $\emptyset$.
  - At each iteration, find the best new feature

    $j = \text{argmin}_i E (F \cup x_i)$
  - Add x_j to F if $E (F \cup x_j) < E (F)$

- Hill-climbing $O(d^2)$ algorithm
- Backward search: Start with all features and remove one at a time, if possible.
- Floating search (Add k, remove l)


Subset Selection: Example (Forward search) 1/2

Iris data: Single feature



Subset Selection: Example (Forward Search) 2/2

Iris data: Add one more feature to F4



Principal Components Analysis (PCA)

- Find a low-dimensional space such that when $\boldsymbol{x}$ is projected there, information loss is minimized.
- Note: Only looks at the input data and not the output.
- The projection of $\boldsymbol{x}$ on the direction of $\boldsymbol{w}$ is: $z = \boldsymbol{w}^T\boldsymbol{x}$
- Find $\boldsymbol{w}$ such that Var(z) is maximized

$$\begin{aligned}\text{Var}(z) &= \text{Var}(\boldsymbol{w}^T\boldsymbol{x}) = E[(\boldsymbol{w}^T\boldsymbol{x} - \boldsymbol{w}^T\boldsymbol{\mu})^2] \\ &= E[(\boldsymbol{w}^T\boldsymbol{x} - \boldsymbol{w}^T\boldsymbol{\mu})(\boldsymbol{w}^T\boldsymbol{x} - \boldsymbol{w}^T\boldsymbol{\mu})] \\ &= E[\boldsymbol{w}^T(\boldsymbol{x} - \boldsymbol{\mu})(\boldsymbol{x} - \boldsymbol{\mu})^T\boldsymbol{w}] \\ &= \boldsymbol{w}^T E[(\boldsymbol{x} - \boldsymbol{\mu})(\boldsymbol{x} - \boldsymbol{\mu})^T]\boldsymbol{w} = \boldsymbol{w}^T \sum \boldsymbol{w}\end{aligned}$$

where $\text{Var}(\boldsymbol{x}) = E[(\boldsymbol{x} - \boldsymbol{\mu})(\boldsymbol{x} - \boldsymbol{\mu})^T] = \sum$

Goal of PCA

- Each pair of new features has 0 covariance.
- The features are ordered with respect to how much of the variance of the data each feature captures.
- The first feature captures as much of the variance of the data as possible.
- Each successive feature captures as much of the remaining variance as possible, as long as it is orthogonal to the previous components

Principal Components Analysis (PCA)

- Maximize Var(z) subject to $||\boldsymbol{w}||=1$

$$\max_{\mathbf{w}_1} \mathbf{w}_1^T \Sigma \mathbf{w}_1 - \alpha\left(\mathbf{w}_1^T \mathbf{w}_1 - 1\right)$$

$\boldsymbol{\Sigma w}_1 = \alpha \boldsymbol{w}_1$ that is, $\boldsymbol{w}_1$ is an eigenvector of $\boldsymbol{\Sigma}$
Choose the one with the largest eigenvalue for Var(z) to be max

- Second principal component: Max Var(z_2), s.t., $||\boldsymbol{w}_2||=1$ and orthogonal to $\boldsymbol{w}_1$

$$\max_{\mathbf{w}_2} \mathbf{w}_2^T \Sigma \mathbf{w}_2 - \alpha\left(\mathbf{w}_2^T \mathbf{w}_2 - 1\right) - \beta\left(\mathbf{w}_2^T \mathbf{w}_1 - 0\right)$$


$\boldsymbol{\Sigma w}_2 = \alpha \boldsymbol{w}_2$ that is, $\boldsymbol{w}_2$ is another eigenvector of $\boldsymbol{\Sigma}$
and so on.

What PCA does

$$\boldsymbol{z} = \mathbf{W}^T(\boldsymbol{x} - \boldsymbol{m})$$

where the columns of **W** are the eigenvectors of **∑**, and ***m*** is sample mean

Centers the data at the origin and rotates the axes




How to choose k ?

- Proportion of Variance (PoV) explained


$$\frac{\lambda_1 + \lambda_2 + \Lambda + \lambda_k}{\lambda_1 + \lambda_2 + \Lambda + \lambda_k + \Lambda + \lambda_d}$$


  when λ_i are sorted in descending order
- Typically, stop at PoV>0.9
- Scree graph plots of PoV vs *k*, stop at "elbow"

How to choose k ?




PCA: Example (Optdigist)






PCA: Example (Optdigist)



Linear Discriminant Analysis

- Goal: Find a low-dimensional space such that when ***x*** is projected, classes are well-separated.
- Find ***w*** that maximizes (K(Number of classes) =2)



$$J(\mathbf{w}) = \frac{(m_1 - m_2)^2}{s_1^2 + s_2^2}$$

$$m_1 = \frac{\sum_t \mathbf{w}^T \mathbf{x}^t r^t}{\sum_t r^t} \qquad s_1^2 = \sum_t \left(\mathbf{w}^T \mathbf{x}^t - m_1\right)^2 r^t$$

Linear Discriminant Analysis



- Between-class scatter:

$$\begin{aligned}(m_1 - m_2)^2 &= \left(\mathbf{w}^T\mathbf{m}_1 - \mathbf{w}^T\mathbf{m}_2\right)^2 \\ &= \mathbf{w}^T\left(\mathbf{m}_1 - \mathbf{m}_2\right)\left(\mathbf{m}_1 - \mathbf{m}_2\right)^T\mathbf{w} \\ &= \mathbf{w}^T\mathbf{S}_B\mathbf{w} \text{ where } \mathbf{S}_B = \left(\mathbf{m}_1 - \mathbf{m}_2\right)\left(\mathbf{m}_1 - \mathbf{m}_2\right)^T\end{aligned}$$

- Within-class scatter:

$$\begin{aligned}s_1^2 &= \sum_t \left(\mathbf{w}^T\mathbf{x}^t - m_1\right)^2 r^t \\ &= \sum_t \mathbf{w}^T\left(\mathbf{x}^t - \mathbf{m}_1\right)\left(\mathbf{x}^t - \mathbf{m}_1\right)^T\mathbf{w}r^t = \mathbf{w}^T\mathbf{S}_1\mathbf{w} \\ \text{where } \mathbf{S}_1 &= \sum_t \left(\mathbf{x}^t - \mathbf{m}_1\right)\left(\mathbf{x}^t - \mathbf{m}_1\right)^T r^t \\ s_1^2 + s_1^2 &= \mathbf{w}^T\mathbf{S}_W\mathbf{w} \text{ where } \mathbf{S}_W = \mathbf{S}_1 + \mathbf{S}_2\end{aligned}$$

Fisher's Linear Discriminant

- Find ***w*** that max

$$J(\mathbf{w}) = \frac{\mathbf{w}^T \mathbf{S}_B \mathbf{w}}{\mathbf{w}^T \mathbf{S}_W \mathbf{w}} = \frac{\left|\mathbf{w}^T (\mathbf{m}_1 - \mathbf{m}_2)\right|^2}{\mathbf{w}^T \mathbf{S}_W \mathbf{w}}$$


- LDA soln: $\mathbf{w} = c \cdot \mathbf{S}_W^{-1} (\mathbf{m}_1 - \mathbf{m}_2)$

- Parametric soln: $\mathbf{w} = \Sigma^{-1} (\mu_1 - \mu_2)$


$$\text{when } p(\mathbf{x} | C_i) \sim \mathcal{N}(\mu_i, \Sigma)$$

Troy University Resources


LDA (vs PCA): Example



Original



PCA



LDA

LDA: Generalization to K>2 Classes

- Within-class scatter:

$$\mathbf{S}_W = \sum_{i=1}^{K} \mathbf{S}_i \qquad \mathbf{S}_i = \sum_t r_i^t \left(\mathbf{x}^t - \mathbf{m}_i\right)\left(\mathbf{x}^t - \mathbf{m}_i\right)^T$$

- Between-class scatter:

$$\mathbf{S}_B = \sum_{i=1}^{K} N_i \left(\mathbf{m}_i - \mathbf{m}\right)\left(\mathbf{m}_i - \mathbf{m}\right)^T \qquad \mathbf{m} = \frac{1}{K}\sum_{i=1}^{K} \mathbf{m}_i$$

- Find **W** that max

$$J(\mathbf{W}) = \frac{\left|\mathbf{W}^T \mathbf{S}_B \mathbf{W}\right|}{\left|\mathbf{W}^T \mathbf{S}_W \mathbf{W}\right|}$$

The largest eigenvectors of $\mathbf{S}_W^{-1}\mathbf{S}_B$
Maximum rank of K-1

Troy University Resources

LDA: Example

