

# DSxHealth application

Blai Ras & Lasha Gochiashvili



UNIVERSITAT DE  
BARCELONA

# Topic: Wearable Devices for Prevention



JMIR MHEALTH AND UHEALTH

Sathyannarayana et al

Original Paper

## Sleep Quality Prediction From Wearable Data Using Deep Learning

Aarti Sathyannarayana<sup>1</sup>, MSc; Shafiq Joty<sup>1</sup>, PhD; Luis Fernandez-Luque<sup>1</sup>, PhD; Ferda Ofli<sup>1</sup>, PhD; Jaideep Srivastava<sup>1</sup>, PhD; Ahmed Elmagarmid<sup>1</sup>, PhD; Teresa Arora<sup>2</sup>, PhD; Shahradd Taheri<sup>2</sup>, MBBS, PhD

<sup>1</sup>Qatar Computing Research Institute, Hamad Bin Khalifa University, Qatar Foundation, Doha, Qatar

<sup>2</sup>Department of Medicine, Weill Cornell Medical College in Qatar, Qatar Foundation, Doha, Qatar

### Corresponding Author:

Luis Fernandez-Luque, PhD  
Qatar Computing Research Institute  
Hamad Bin Khalifa University, Qatar Foundation  
HBKU Research Complex  
Doha, 5825  
Qatar  
Phone: 974 50173040  
Fax: 974 44540630  
Email: [lluque@qf.org.qa](mailto:lluque@qf.org.qa)

### Related Article:

This is a corrected version. See correction statement in: <http://mhealth.jmir.org/2016/4/e130/>

# Content

## Introduction

- Background of the problem
- Role of Wearables in Sleep Health and eHealth
- Objective

## Methods

- Overview
- Data Collection
- Data Processing and Representation
- Models
- Performance Evaluation

## Results

Comparison between DL and LR models  
Comparison between DL models

## Conclusions

## Discussion

Findings  
Impact in Sleep Science and in eHealth

# Importance of the **Sleep** and connection to **Physical** activity

- **Insufficient sleep can reduce** physical, emotional, and mental **well-being** and can lead to a multitude of health complications
- Physical **activity and sleep** are highly **interrelated** health behaviors.
- Our **physical activity** during the day (ie, awake time) **influences** our quality of sleep, and vice versa
- The current popularity of **wearables for tracking** physical activity and sleep, including actigraphy devices, **can foster** the development of new advanced data analytics.
- This can help to **develop new** electronic health (eHealth) **applications** and provide **more insights** into sleep science.

# Role of Wearables in Sleep Health and eHealth

- Sleep researchers in the early 1990s developed a **technique** called **actigraphy** to study sleep interactions using wearable devices.
- There are hundreds of consumer-grade **physical activity and sleep tracking devices** (e.g. Fitbit) collecting motion
- There are successful examples of the **integration of physical activity wearable data into eHealth** tailored **applications** (e.g. Smart Watch)
- Sensors **monitor** and **observe** a patient overnight and can be **used for diagnosing** different sleep disorders


# Objectives of the study

- To test the feasibility of **predicting poor or good sleep efficiency based on physical activity** data from the awake periods from a wearable device (i.e. actigraphy)

Two-fold importance of the research	
<b>First</b> , since our approach can be <b>used</b> in cases <b>where sleep sensor data is not available</b> , our models can be used in the early detection of potential low sleep efficiency.	<b>Second</b> , our study was <b>focused</b> on <b>advanced deep learning</b> methods while traditional prediction models are based on e.g. logistic regression



# Methods of the Study



# Methods of the Study

The collection of wearable data (sleep patterns & physical activities)

The dataset used contained complete actigraphy data from a subset of 92 adolescents over 1 week.

There were 322 total sleep instances:

- 102 from boys and
- 220 from girls.





# Methods of the Study

## 2

## Data processing and representation

**Figure 2.** Sleep efficiency equation as defined by sleep specialists.

$$\text{Sleep Efficiency} = \frac{\text{TotalSleepTime}}{\text{TotalMinutesinBed}}$$

- Those achieving a sleep efficiency score of  $\geq 85\%$  are thought to be **good-quality** sleepers,
- and those with a score of  $< 85\%$  are thought to have **poor-quality** sleep

**Figure 3.** The adapted wake after sleep onset calculation.

$$\text{WASO} = \sum_{\text{Sleep Onset Time}}^{\text{Sleep Awakening Time}} \begin{cases} ||\text{WakefulPeriod}||, & ||\text{WakefulPeriod}|| > 5 \\ 0, & \text{otherwise} \end{cases}$$


WASO is the sum of all moments of wakefulness lasting longer than 5 minutes

# Methods of the Study

## Data processing and representation

2

**Figure 4.** Example of sleep definitions on accelerometer data of an actigraphy device.




# Methods of the Study

3

## Data modelling

The **input** of the models is time series vectors,  $X=(x_1, \dots, x_T)$ ,



The **output** of the model was a binary classification decision between good and poor sleep quality based on sleep efficiency (%)

- **Logistic regression**, a non-deep learning model
- Multi-layer perceptron's (**MLPs**), a deep learning model
- Convolutional neural network (**CNN**), a deep learning model
- Recurrent neural networks (**RNN**), a deep learning model
- Long short-term memory (**LSTM**) RNN, a deep learning model
- Time-batched long short-term memory (**TB-LSTM**) RNN, a deep learning model

The data were split with a

- 70% training
- 15% testing
- 15% validation

# Methods of the Study

# 4

## Performance evaluation

### Accuracy

It is computed as the **proportion of correct predictions**, both positive and negative

### Precision

It is the fraction of the number of **true positive predictions** to the number of **all positive** predictions

### Specificity

It is the fraction of the number of **true negative predictions** to the actual number of **negative instances** in the dataset

### Recall or Sensitivity

It is the fraction of the number of **true positive predictions** to the actual number of **positive instances** in the dataset

### F1-Score

An **inverse** relationship between **precision and recall** (harmonic mean of precision and recall)

### Area Under the ROC Curve

It represents the probability that a classifier will rank a randomly chosen positive instance higher than a randomly chosen negative instance

# Results of the study

Model	AUC	F 1-Score
TB-LSTM	0.97	0.85
CNN	0.95	0.94
MLP	0.94	0.91
TB-LSTM	0.85	0.92
RNN	0.71	0.77
LR	0.64	9.81

# Results of the study

Model	Sensitivity	Specificity
TB-LSTM	1	0.71
LR	0.97	0.33
CNN	0.97	0.85
LTSM	0.97	0.47
RNN	0.91	0.23
MLP	0.88	0.9



# Conclusions of the study

- We can predict sleep quality using only physical activity
- Deep learning overperforms classical methods

# Discussion & Limitations

- Models can be re-used using wearable's data
- What about the age?
- Binary simplification
- Deep learning models understanding
- Data cleaning



UNIVERSITAT DE  
BARCELONA

# Data Science for Health