

# Height Maps, Noise, Erosion and Vegetation

# Overview

- Height maps
- Noise algorithms
- Erosion Algorithm
- Vegetation Modelling

# Height Map

- When we read this grey-scale image in, each pixel represents a vertex.
- We can hence use an image to store the heights (y values) for our terrain mesh.
  - For example:




Fig. 1: Example height map with height displayed as brightness.

# Heightmap




Fig. 2: Height map from Fig.1 converted into a 3D mesh.

# Tools

- Height Map continued...
  - 256 x 256 pixels
  - Grey scale:
    - Every pixel has a value from 0 to 255.
    - R,G,B components are all equal.
- Tools
  - Terragen
    - Freeware
    - Can be used to generate height maps.
    - <http://www.planetside.co.uk/>
  - Photoshop
    - We can easily create our own...

## Tools continued

- Bryce <http://www.thebest3d.com/bryce/index.html>
- Dark Tree <http://www.darksim.com/>

These tools have many procedural algorithms for generating height-maps and also have built-in height-map editors

# Heightmap Generation

- After finishing drawing the heightmap, it needs to be saved in an 8-bit RAW file.
- RAW files simply contain the bytes of the image one after another
- This makes it easy to read the image into the program
- If any software asks to save the RAW file with a header, specify no header

# Heightmap Smoothing

- One of the problems of using an 8-bit heightmap is that it means we can only represent 256 discrete height steps .
- The truncation creates a “rougher” terrain than what may have been intended
- Once we truncate , we cannot recover the original height values but we can smooth the values



# Heightmap Smoothing

- So we load the height-map into memory by reading raw bytes
- We copy the byte array into float array so that we have a floating-point precision
- Then we apply a filter to the floating-point heightmap
- This helps to smooth the heightmap out

$i-1,j-1$	$i-1,j$	$i-1,j+1$
$i,j-1$	$i,j$	$i,j+1$
$i+1,j-1$	$i+1,j$	$i+1,j+1$

# Noise

# Noise

- In the everyday world, noise is a naturally occurring nuisance that is generally covered up as much as possible
- However, in the field of Computer Science, especially 3D modelling, noise has become increasingly useful
- Irregular bumps and nicks make 3D models look much more realistic, but are difficult and time consuming to make by hand
- Noise algorithms create pseudo-random textures quickly with little or no interaction required from the user.

# Use of Noise in Games

- In games, noise algorithms are used to generate landscapes
- Generation of these landscapes often doesn't stop with noise, often erosion, vegetation, and water models are applied to increase realism

# Types of Noise Algorithms

- Mid-point displacement
- Diamond-square
- Value noise
- Perlin noise
- Simplex noise
- Cell/Whorley noise
- Voronoi noise
- Alligator noise
- Space -convolution noise

## Basic noise algorithms

- Mid-point displacement
- Diamond Square noise
- Perlin noise

## Mid-point displacement algorithm

- The Mid Point Displacement, aka the Plasma Algorithm, is a subdivision algorithm
- The terrain is built iteratively, in each iteration the level of detail increases
- This algorithm was conceived to generate square terrains with dimensions  $(2^n + 1) \times (2^{n+1})$  where  $n$  stands for the number of iterations

# In 1 Dimension

Start with a single horizontal line segment.

Repeat for a sufficiently large number of times

{

Repeat over each line segment in the scene

{

Find the midpoint of the line segment.

Displace the midpoint in Y by a random amount.

Reduce the range for random numbers.

}

}



# In 1 Dimension




Fig 2 First Iteration




Fig 3 Second Iteration




Fig 4 Third Iteration



Fig 5 Final Iteration

# Diamond -square algorithm

- This is midpoint-displacement method in 2-dimension
- Assign a height value to each corner of the rectangle
- Divide the rectangle into 4 sub rectangles, and let their height values be the mean values of the corners of the parent rectangle.
- When computing the middle height, one should add a small error that depends on the size of the rectangle (the standard is to let the error be proportional to the size of the rectangle and some constant).
- The constant controls the "roughness" of the fractal
- A bigger constant results in more valleys and mountains.
- Iterate and subdivide each rectangle into smaller ones.









Fig 6 Diamond square algorithm

# Diamond-square



# Perlin Noise



# Perlin Noise

- Perlin Noise is an extremely powerful algorithm that is used often in procedural content generation
- The man who created it, Ken Perlin, won an academy award for the original implementation
- In game development, Perlin Noise can be used for any sort of wave-like, undulating material or texture.
- For example, it could be used for procedural terrain, fire effects, water, and clouds

## Process

- Generate Noise
  - For each point in width and height of texture
  - Generate random number
  - Smoothen the value
  - Interpolate
- Apply perlin noise algorithm per point.
- Get a gray scale value per point similar to height map.

# Perlin Noise

- Noise Function
  - A noise function is essentially a seeded number generator
- Smooth Noise

```
function SmoothNoise_2D(x, y)
```

```
    corners = ( Noise(x-1, y-1)+Noise(x+1, y-1)+Noise(x-1, y+1)+Noise(x+1, y+1) ) / 16
```

```
    sides   = ( Noise(x-1, y) +Noise(x+1, y) +Noise(x, y-1) +Noise(x, y+1) ) / 8
```

```
    center  = Noise(x, y) / 4
```

```
    return corners + sides + center
```

```
end function
```

# Perlin Noise

- Interpolation - Can be linear, cubic, cosine




Fig 7 Random numbers plotted




Fig 8 Interpolation



# Perlin Noise

- function Linear\_Interpolate(a, b, x)  
return  $a*(1-x) + b*x$   
end of function
- function Cosine\_Interpolate(a, b, x)  
 $ft = x * 3.1415927; f = (1 - \cos(ft)) * .5$   
return  $a*(1-f) + b*f$   
end of function
- function Cubic\_Interpolate(v0, v1, v2, v3,x)  
 $P = (v3 - v2) - (v0 - v1)$   
 $Q = (v0 - v1) - P$   
 $R = v2 - v0$   
 $S = v1$   
return  $Px^3 + Qx^2 + Rx + S$   
end of function


# Terminologies

- **Amplitude**

The maximum extent of a vibration or oscillation, measured from the position of equilibrium.

- **Frequency**

The distance between successive crests of a wave, esp. points in a sound wave or electromagnetic wave



# Terminologies

- Persistence
  - frequency =  $2^i$
  - amplitude = persistence<sup>i</sup>
- $i$  is the  $i^{\text{th}}$  noise function being added for each octave
- $i$  might range from 0 to 8



- Octaves

Each successive noise function you add is known as an octave


## Total Noise Per Point

```
int octaves = 8;  
float zoom = 20.0f;  
float persistance = 0.5f;  
float total = 0.0f;  
  
for (int i = 0; i < octaves - 1; i++) {  
  
    float frequency = pow(2, i)/zoom;  
    float amplitude = pow(persistance, i);  
  
    total = total + noise(x * frequency, y * frequency) * amplitude;  
}
```


# Perlin Noise




# Persistence



Octave 8




Octave 4




Octave 2

# Applications


- Color Gradient



*Grayscale gradient*



*Gradient with discrete colours*



*Fire gradient*

# Applications


- Texture Blending



*Image 1*



*Image 2*



*Perlin noise*







*Blend using noise*





# Applications

- Realtime Transition




*Real time transitions using Perlin noise*



*Blend textures*

# 3D Perlin Noise



# Erosion Algorithms

- Noise alone can create interesting landscapes, but erosion can help add an extra layer of realism.
  - Thermal Erosion
  - Hydraulic Erosion
  - Inverse Thermal Erosion

# Thermal Erosion

- Thermal erosion models gravity eroding cliffs that are too steep
- If the angle is too sharp, soil will fall to a lower area.
- Thermal erosion is fairly simple to model
- First, define the difference  $T$ , which is the maximum difference allowed before gravity takes over

# Thermal Erosion Algorithm


- For all pixel
- Get the difference in height between this pixel and the neighbouring pixel
- If the difference is greater than  $T$ , remove some amount of soil from the taller pixel and deposit it into the lower pixel.
- The speed of this algorithm can be improved further by changing the neighbourhood type.
- The three standard type are the
  - Moore neighbourhood,
  - the Von Neumann neighbourhood,
  - and the rotated Von Neumann neighbourhood

# Neighbourhood Types


- In cellular automata, the Moore neighbourhood comprises the eight cells surrounding a central cell on a two-dimensional square lattice
- In cellular automata, the von Neumann neighbourhood comprises the four cells orthogonally surrounding a central cell on a two-dimensional square lattice.
- While the Moore neighborhood provides the best results, it is also the slowest. The rotated Von Neumann neighborhood gives good results while increasing speed.

# Von-Neumann Neighbourhood Type


**Moore**



**Von Neumann**



**Rotated Von Neumann**



## Hydraulic Erosion


- Hydraulic Erosion models rainwater picking up soil, washing down into basins, then evaporating and depositing soil.
- Hydraulic erosion provides good quality results, but is very slow.
- It may use up to 3 times the memory of Thermal Erosion.




## Inverse Thermal Erosion

- For gaming, plateaus and cliffs are much more desirable than rolling hills.
- Thermal Erosion destroys cliffs and rarely creates plateaus.
- By flipping the erosion condition the opposite effect can be created.


# Hydraulic erosion




# Hydraulic erosion



# Hydraulic erosion



# Hydraulic erosion



# Vegetation Modelling

- While noise and erosion may create realistic features, without color the terrain is completely alien to the eye.
  - Simple Colour Mapping
    - Portions of height to colors or gradients of colors
  - Terrain Mandated
    - Waterflow is defined by terrain height.
    - Vegetation takes slope and height into account
  - Dynamic Modelling
    - Dynamic systems such as rainfall and water-flow could control where vegetation grows

# References

- <https://www.clicktorelease.com/blog/vertex-displacement-noise-3d-webgl-glsl-three-js/>
- <http://libnoise.sourceforge.net/tutorials/tutorial4.html>
- <http://flafla2.github.io/2014/08/09/perlinnoise.html>
- <http://devmag.org.za/2009/04/25/perlin-noise/>
- <http://paulboxley.com/blog/2011/03/terrain-generation-mark-one>
- <http://web.mit.edu/cesium/Public/terrain.pdf>
- <http://old.cescg.org/CESCG-2011/papers/TUBudapest-Jako-Balazs.pdf>
- [http://micsymposium.org/mics\\_2011\\_proceedings/mics2011\\_submission\\_30.pdf](http://micsymposium.org/mics_2011_proceedings/mics2011_submission_30.pdf)
- [https://www.reddit.com/r/gamedev/comments/1rl0vs/realtime\\_hydraulic\\_erosion\\_simulation\\_on\\_gpu/?st=j6bestag&sh=d83b301c](https://www.reddit.com/r/gamedev/comments/1rl0vs/realtime_hydraulic_erosion_simulation_on_gpu/?st=j6bestag&sh=d83b301c)