

PDBP

Program Description Based Programming
Scala eXchange

Luc Duponcheel

August 2, 2018



Intro



Intro

- this talk is about



Intro

- this talk is about
 - a *Dotty library* PDBP



Intro

- this talk is about
 - a **Dotty library** **PDBP**
 - inspired by the *function-level programming language* **FP**



John Backus




John Backus



- ACM Turing Award Winner 1977



John Backus



- ACM Turing Award Winner 1977
- *Can programming be liberated from the Von Neumann style?*



What is this?



What is this?



- A *pipe*?



What is this?



- A *pipe*?
- A *painting describing* a pipe?



What is this?



- A *pipe*?
- A *painting describing* a pipe?
- A *slide describing* a painting describing a pipe?



What is this?



- A *pipe*?
- A *painting describing* a pipe?
- A *slide describing* a painting describing a pipe?
- ...



Ceci n'est pas une pipe



Ceci n'est pas une pipe



- It is a *painting* by René Magritte *describing* a pipe



This is not a program

```
val xxxxxxxxx: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        xxxxxxxxx  
    } 'in' {  
      multiply  
    }  
  }  
}
```



This is not a program

```
val xxxxxxxxx: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        xxxxxxxxx  
    } 'in' {  
      multiply  
    }  
  }  
}
```

- It is *code describing* a program



factorial description

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }
```



factorial description

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }
```

- `factorial` *uses* capabilities *declared* in
type class `trait Program[>-->[- _, + _]]`



factorial meanings

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }
```



factorial meanings

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }
```

- different implicit object's *define* capabilities of type class trait Program[>-->[- _, + _]]



program

val program: $Z \multimap Y$



mainProgram

```
val program: Unit >--> Unit
```



Composition

```
val 'z>-->y': Z >--> Y
```

```
val 'y>-->x': Y >--> X
```

```
val 'z>-->x': Z >--> X = 'z>-->y >--> 'y>-->x'
```



program

| ----- ----- | -----
| | Z >--> Y | >--> | Y >--> X | | => | Z >--> X |
| ----- ----- | -----



mainProgram

```
val producer: Unit >--> Z
val program: Z >--> Y
val consumer: Y >--> Unit

val mainProgram: Unit >--> Unit =
  producer >--> program >--> consumer
```



mainProgram

```
-----  
| Unit >--> Unit |  
-----  
| Unit >--> Z >--> Y >--> Unit |  
-----  
                                     v  
                                     |  
-----<????>----- => | Unit >--> Unit |  
|  
v  
-----  
| Unit >--> Z >--> Y >--> Unit |  
-----  
| Unit >--> Unit |  
-----
```



FP versus PDBP



FP versus PDBP

- FP and PDBP promote *pointfree functional programming*



FP versus PDBP

- FP and PDBP promote *pointfree functional programming*
- FP is a *language*
PDBP is a *library*



FP versus PDBP

- FP and PDBP promote *pointfree functional programming*
- FP is a *language*
PDBP is a *library*
 - FP *semantics* is *fixed*
PDBP *semantics* is *not fixed*



FP versus PDBP

- FP and PDBP promote *pointfree functional programming*
- FP is a *language*
PDBP is a *library*
 - FP *semantics* is *fixed*
PDBP *semantics* is *not fixed*
 - FP *capabilities* are *fixed*
PDBP *capabilities* are *not fixed*



FP versus PDBP

- FP and PDBP promote *pointfree functional programming*
- FP is a *language*
PDBP is a *library*
 - FP *semantics* is *fixed*
PDBP *semantics* is *not fixed*
 - FP *capabilities* are *fixed*
PDBP *capabilities* are *not fixed*
 - FP *effects* are *impure*
PDBP *effects* are *pure*



Semantics

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }  
}
```



Semantics

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }  
}
```

- *production*



Semantics

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }  
}
```

- *production*
 - *recursion* using *stack*



Semantics

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }  
}
```

- *production*
 - *recursion* using *stack*
 - *recursion* using *heap*



Semantics

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }  
}
```

- *production*
 - *recursion* using *stack*
 - *recursion* using *heap*
- *test*



Semantics

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }  
}
```

- *production*
 - *recursion* using *stack*
 - *recursion* using *heap*
- *test*
 - ...



Capabilities



Capabilities

- *manipulating state*



Capabilities

- *manipulating state*
- *handling failure*



Capabilities

- *manipulating state*
- *handling failure*
- *handling latency*



Capabilities

- *manipulating state*
- *handling failure*
- *handling latency*
- *handling control*



Capabilities

- *manipulating state*
- *handling failure*
- *handling latency*
- *handling control*
- ...



Effects



Effects

- *reading*



Effects

- *reading*
- *writing*



Foundations



Foundations

- `trait Program[>-->[- _, + _]]` corresponds to *arrows*



Foundations

- `trait Program[>-->[- _, + _]]` corresponds to *arrows*
- `trait Computation[C[+ _]]` corresponds to *monads*



Monads versus arrows



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming
 - `val 'z=>x' = 'z=>y' andThen 'y=>x'`



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming
 - `val 'z=>x' = 'z=>y' andThen 'y=>x'`
 - `val 'z>-->x' = 'z>-->y' >--> 'y>-->z'`



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming
 - `val 'z=>x' = 'z=>y' andThen 'y=>x'`
 - `val 'z>-->x' = 'z>-->y' >--> 'y>-->z'`
- *monads* (`trait Computation[C[+ _]]`)
generalize *expressions*



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming
 - `val 'z=>x' = 'z=>y' andThen 'y=>x'`
 - `val 'z>-->x' = 'z>-->y' >--> 'y>-->z'`
- *monads* (`trait Computation[C[+ _]]`)
generalize *expressions*
 - *binding* based, *pointful* functional programming



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming
 - `val 'z=>x' = 'z=>y' andThen 'y=>x'`
 - `val 'z>-->x' = 'z>-->y' >--> 'y>-->z'`
- *monads* (`trait Computation[C[+ _]]`)
generalize *expressions*
 - *binding* based, *pointful* functional programming
 - `{ val z = ez ; { val y = ey ; ex(z, y) } }`



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming
 - `val 'z=>x' = 'z=>y' andThen 'y=>x'`
 - `val 'z>-->x' = 'z>-->y' >--> 'y>-->z'`
- *monads* (`trait Computation[C[+ _]]`)
generalize *expressions*
 - *binding* based, *pointful* functional programming
 - `{ val z = ez ; { val y = ey ; ex(z, y) } }`
 - `mz bind { z => my bind { y => mx(z, y) } }`



Monads versus arrows

- *arrows* (`trait Program[>-->[- _, + _]]`)
generalize *functions*
 - *composition* based, *pointfree* functional programming
 - `val 'z=>x' = 'z=>y' andThen 'y=>x'`
 - `val 'z>-->x' = 'z>-->y' >--> 'y>-->z'`
- *monads* (`trait Computation[C[+ _]]`)
generalize *expressions*
 - *binding* based, *pointful* functional programming
 - `{ val z = ez ; { val y = ey ; ex(z, y) } }`
 - `mz bind { z => my bind { y => mx(z, y) } }`
 - `mz bind { z => my bind { y => result(ex(z, y)) } }`



Monads versus arrows



Monads versus arrows

- *monads* can also be programmed *pointfree* (*kleisli arrows*)



Monads versus arrows

- *monads* can also be programmed *pointfree* (*kleisli arrows*)
- *arrows* can also be programmed *pointful* (*arrow calculus*)



Power of expressions



Power of expressions

- *monads* are more *concrete* (less *abstract*) than *arrows*



Power of expressions

- *monads* are more *concrete* (less *abstract*) than *arrows*
 - *monads* allow more *specification liberty*



Power of expressions

- *monads* are more *concrete* (less *abstract*) than *arrows*
 - *monads* allow more *specification liberty*
 - *monads* impose more *implementation constraints*



Power of expressions

- *monads* are more *concrete* (less *abstract*) than *arrows*
 - *monads* allow more *specification liberty*
 - *monads* impose more *implementation constraints*
- *Constraints Liberate, Liberties Constrain*



Elegance of use



Elegance of use

- *pointfree* programming is sometimes considered to be more *abstruse* than *pointful* programming



Elegance of use

- *pointfree* programming is sometimes considered to be more *abstruse* than *pointful* programming
- *Dotty* comes to the rescue



Elegance of use

- *pointfree* programming is sometimes considered to be more *abstruse* than *pointful* programming
- Dotty comes to the rescue
 - Dotty is a Scalable language



Elegance of use

- *pointfree* programming is sometimes considered to be more *abstruse* than *pointful* programming
- Dotty comes to the rescue
 - Dotty is a Scalable language
 - Dotty *library based* language extensions are *type safe*



Elegance of use

- *pointfree* programming is sometimes considered to be more *abstruse* than *pointful* programming
- Dotty comes to the rescue
 - Dotty is a Scalable language
 - Dotty *library based* language extensions are *type safe*
- PDBP comes with a *program description DSL*



Program description DSL

```
val factorial: BigInt >--> BigInt =  
  'if'(isZero) {  
    one  
  } 'else' {  
    'let' {  
      subtractOne >-->  
        factorial  
    } 'in' {  
      multiply  
    }  
  }
```



PDBP's choice



PDBP's choice

- the PDBP library goes for



PDBP's choice

- the PDBP library goes for
 - `private[pdbp]` *pointful monad API*
provides *power of expression* for *library* developers



PDBP's choice

- the PDBP library goes for
 - `private[pdbp]` *pointful monad API*
provides *power of expression* for *library* developers
 - `public` *pointfree arrow API*
provides *elegance of use* for *application* developers



PDBP's choice

- the PDBP library goes for
 - `private[pdbp]` *pointful monad API*
provides *power of expression* for *library* developers
 - `public` *pointfree arrow API*
provides *elegance of use* for *application* developers
- the PDBP can live with



PDBP's choice

- the PDBP library goes for
 - `private[pdbp]` *pointful monad API*
provides *power of expression* for *library* developers
 - `public` *pointfree arrow API*
provides *elegance of use* for *application* developers
- the PDBP can live with
 - corresponding implementation constraints



PDBP

[illegible]

PDBP library design decisions (cfr. Haskell)



PDBP library design decisions (cfr. Haskell)

- *description* separated from *meaning*



PDBP library design decisions (cfr. Haskell)

- *description* separated from *meaning*
- *description*



PDBP library design decisions (cfr. Haskell)

- *description* separated from *meaning*
- *description*
 - *trait*'s (*type classes*) *declare* capabilities



PDBP library design decisions (cfr. Haskell)

- *description* separated from *meaning*
- *description*
 - *trait*'s (*type classes*) *declare* capabilities
- *language level* meaning



PDBP library design decisions (cfr. Haskell)

- *description* separated from *meaning*
- *description*
 - *trait*'s (*type classes*) *declare* capabilities
- *language level* meaning
 - *implicit object*'s (*extend trait*'s) *define* capabilities



PDBP library design decisions (cfr. Haskell)

- *description* separated from *meaning*
- *description*
 - *trait*'s (*type classes*) *declare* capabilities
- *language level* meaning
 - *implicit object*'s (*extend trait*'s) *define* capabilities
- *library level* meaning



PDBP library design decisions (cfr. Haskell)

- *description* separated from *meaning*
- *description*
 - *trait*'s (*type classes*) *declare* capabilities
- *language level* meaning
 - *implicit object*'s (*extend trait*'s) *define* capabilities
- *library level* meaning
 - *natural transformations*



PDBP library design decisions (cfr. Haskell)



PDBP library design decisions (cfr. Haskell)

- *dependency injection* by `implicit import`



PDBP library design decisions (cfr. Haskell)

- *dependency injection* by `implicit import`
- *definitions* in `class`'es that *implicitly* depend on `trait`'s (*type classes*) use capabilities *declared* in those `trait`'s



PDBP library design decisions (cfr. Haskell)

- *dependency injection* by `implicit import`
- *definitions* in `class`'es that *implicitly* depend on `trait`'s (*type classes*) use capabilities *declared* in those `trait`'s
- `object`'s that *extend* those `class`'es `import implicit` `object`'s that *extend* those `trait`'s



Program (cfr. *arrow*)

```
trait Program[>-->[- _, + _]]
```



Computation (cfr. *monad*)

```
trait Computation[C[+ _]]
```



Liskov Substitution Principle



Liskov Substitution Principle

- *impose less*



Liskov Substitution Principle

- *impose less*
- *provide more*



Internet Robustness Principle



Internet Robustness Principle

- *be liberal in what you receive*



Internet Robustness Principle

- *be liberal in what you receive*
- *be generous in what you send*



PDBP library details



Program

```
trait Program[>-->[- _, + _]]  
  extends Function[>-->]  
  with Composition[>-->]  
  with Construction[>-->]  
  with Condition[>-->]  
  
  with Aggregation[>-->]
```



Function



Function

- `val 'z>-->y' = function('z=>y')`



Function

- `val 'z>-->y' = function('z=>y')`
- pure functions are *atomic programs*



Function

- `val 'z-->y' = function('z=>y')`
- pure functions are *atomic programs*
 - up to you to define granularity



Composition



Composition

- $\text{val } 'z>-->x' = 'z>-->y' >--> 'y>-->x'$



Construction



Construction

- `val 'z>-->y&& x' = 'z>-->y' & 'z>-->x'`



Construction

- `val 'z>-->y&&x' = 'z>-->y' & 'z>-->x'`
- `val 'z&&y>-->x&&w' = 'z>-->x' && 'y>-->w'`



Construction

- `val 'z>-->y&&x' = 'z>-->y' & 'z>-->x'`
- `val 'z&&y>-->x&&w' = 'z>-->x' && 'y>-->w'`
- `val 'z>-->x' =
 'let' 'z>-->y' 'in' 'z&&y>-->x'`



Condition



Condition

- `val 'y||x>-->z' = 'y>-->z' | 'x>-->z'`



Condition

- $\text{val } 'y|x \multimap z' = 'y \multimap z' \mid 'x \multimap z'$
- $\text{val } 'x|w \multimap z||y' = 'x \multimap z' \mid\mid 'w \multimap y'$



Condition

- `val 'y||x>-->z' = 'y>-->z' | 'x>-->z'`
- `val 'x||w>-->z||y' = 'x>-->z' || 'w>-->y'`
- `val 'y>-->z' =
 'if'('y>-->b') 'y>-t->z' 'else' 'y>-f->z'`



Computation

```
private[pdbp] trait Computation[C[+ _]]  
  extends Resulting[C]  
  with Binding[C]  
  with Program[[-Z, +Y] => Z => C[Y]]  
  
  with Lifting[C]  
  
  with Sequencing[C]
```



Resulting

```
val cz = result(z)
```



Binding



Binding

- `val cy = cz bind { z => 'z=>cy'(y) }`



Binding

- `val cy = cz bind { z => 'z=>cy'(y) }`
- `val cy = cz bind { z => result('z=>y'(y)) }`



Kleisli



Kleisli

- `type Kleisli[C[+ _]] = [-Z, + Y] => Z => C[Y]`



Kleisli

- `type Kleisli[C[+ _]] = [-Z, + Y] => Z => C[Y]`
- ```
private[pdbp] trait Computation[C[+ _]]
 extends Resulting[C]
 with Binding[C]
 with Program[Kleisli[C]]

 // ...
```



# HelperFunctions

```
val isZeroFunction: BigInt => Boolean =
{ i =>
 i == 0
}
def oneFunction[Z]: Z => BigInt =
{ z =>
 1
}
val subtractOneFunction: BigInt => BigInt =
{ i =>
 i - 1
}
val multiplyFunction: (BigInt && BigInt) => BigInt =
{ (i, j) =>
 i * j
}
```





# HelperPrograms

```
val isZeroHelper: BigInt >--> Boolean =
 function(isZeroFunction)
```

```
val subtractOneHelper: BigInt >--> BigInt =
 function(subtractOneFunction)
```

```
val multiplyHelper: (BigInt && BigInt) >--> BigInt =
 function(multiplyFunction)
```

```
def oneHelper[Z]: Z >--> BigInt =
 function(oneFunction)
```



# AtomicPrograms

```
val isZero: BigInt >--> Boolean =
 isZeroHelper
```

```
val subtractOne: BigInt >--> BigInt =
 subtractOneHelper
```

```
val multiply: (BigInt && BigInt) >--> BigInt =
 multiplyHelper
```

```
def one[Z]: Z >--> BigInt =
 oneHelper
```



# factorial

```
val factorial: BigInt >--> BigInt =
 'if'(isZero) {
 one
 } 'else' {
 'let' {
 subtractOne >-->
 factorial
 } 'in' {
 multiply
 }
 }
}
```



# factorialMain

```
val factorialMain: Unit >--> Unit =
 producer >-->
 factorial >-->
 consumer
```



## activeTypes

```
object activeTypes {
 type Active[+Z] = Z
 type '=>A' = Kleisli[Active]
}
```



# activeProgram

```
implicit object activeProgram
 extends Computation[Active]
 with Program['=>A'] {

 override private[pdbp] def result[Z]: Z => Active[Z] =
 'z=>az'

 override private[pdbp] def bind[Z, Y](
 az: Active[Z],
 'z=>ay': => (Z => Active[Y])): Active[Y] =
 'z=>ay'(az)

}
```



## activeMeaningOfActive

```
implicit object activeMeaningOfActive
 extends MeaningOfActive[Active]()
 with ComputationMeaning[Active, Active]()
 with ProgramMeaning['=>A', '=>A']()
```



# FactorialMain

```
import ... activeMeaningOfActive
import activeMeaningOfActive.meaning

import ... mainFactorial
import mainFactorial.factorialMain

object FactorialMain {

 def main(args: Array[String]): Unit = {

 meaning(factorialMain)()

 }
}
```





# Problems and Solutions



## Problems and Solutions

- Problem: obvious **factorial** meaning  
implementing  $\rightarrow\rightarrow$  as ' $\Rightarrow A$ ' *is not stack safe*



## Problems and Solutions

- Problem: obvious **factorial** meaning  
implementing  $\rightarrow$  as ' $\Rightarrow A$ ' *is not stack safe*
  - Solution: **FreeTransformation** and  
**FreeTransformedMeaning**



## Problems and Solutions

- Problem: obvious **factorial** meaning implementing  $\rightarrow$  as ' $\Rightarrow A$ ' *is not stack safe*
  - Solution: **FreeTransformation** and **FreeTransformedMeaning**
- Problem: obvious **producer** and **consumer** *execute effects*



## Problems and Solutions

- Problem: obvious **factorial** meaning implementing  $\>-->$  as ' $\Rightarrow A$ ' *is not stack safe*
  - Solution: **FreeTransformation** and **FreeTransformedMeaning**
- Problem: obvious **producer** and **consumer** *execute effects*
  - Solution: **Reading** resp. **Writing** extensions of **Program** with members **read** resp. **write** that *describe effects*



## NaturalBinaryTypeConstructorTransformation

```
trait '-B->'['>-F->'[- _, + _], '>-T->'[- _, + _]] {
 def apply[Z, Y]: Z '>-F->' Y => Z '>-T->' Y
}
```



## NaturalUnaryTypeConstructorTransformation

```
private[pdbp] trait '-U->'[F[+ _], T[+ _]]
 extends '-B->'[Kleisli[F], Kleisli[T]] {

 private[pdbp] def apply[Z](fz: F[Z]): T[Z]

 // ...
}

}
```



# ComputationTransformation

```
private[pdbp] trait ComputationTransformation[
 FC[+ _]: Computation, T[+ _]] {

 private[pdbp] val transform: FC '-U->' T

}
```





# ProgramMeaning

```
trait ProgramMeaning[
 '>-FP->'[- _, + _]: Program, '>-T->'[- _, + _]] {

 private[pdbp] lazy val binaryTransformation:
 '>-FP->' '-B->' '>-T->'

 lazy val meaning: '>-FP->' '-B->' '>-T->' =
 binaryTransformation

}
```



# ComputationMeaning

```
private[pdbp] trait ComputationMeaning[
 FC[+ _]: Computation, T[+ _]]
 extends ProgramMeaning[Kleisli[FC], Kleisli[T]] {

 private[pdbp] val unaryTransformation: FC '-U->' T

 // ...

}
```



# FreeTransformed

```
sealed trait Free[C[+ _], +Z]

final case class Transform[C[+ _], +Z]
 (cz: C[Z]) extends Free[C, Z]
final case class Result[C[+ _], +Z]
 (z: Z) extends Free[C, Z]
final case class Bind[C[+ _], -Z, ZZ <: Z, +Y]
 (fczz: Free[C, ZZ], 'z=>fcy': Z => Free[C, Y])
 extends Free[C, Y]

type FreeTransformed[C[+ _]] = [+Z] => Free[C, Z]
```



# FreeTransformation

```
private[pdbp]
trait FreeTransformation[C[+ _]: Computation]
 extends Computation[FreeTransformed[C]]
 with Program[Kleisli[FreeTransformed[C]]]
 with Transformation[C, FreeTransformed[C]] {

 // unfold
 // transform => Transform
 // result => Result
 // bind => Bind

}
```



## activeFreeTypes

```
object activeFreeTypes {
 type ActiveFree = FreeTransformed[Active]
 type '=>AF' = Kleisli[ActiveFree]
}
```



## activeFreeProgram

```
import ... activeProgram

implicit object activeFreeProgram
 extends Computation[ActiveFree]
 with Program['=>AF']
 with FreeTransformation[Active]()
 with ComputationTransformation[Active, ActiveFree]()
```



## FreeTransformedMeaning

```
private[pdbp] trait FreeTransformedMeaning[
 FC[+ _]: Computation, T[+ _]](
 implicit toBeTransformedMeaning: ComputationMeaning[FC, T])
 extends ComputationMeaning[FreeTransformed[FC], T] {

 // tailrecFold
 // Transform(fcz) => fcz
 // Result(z) => result(z)
 // Bind(Result(y), y2ftfcz) => tailrecFold(y2ftfcz(y))
 // Bind(Bind(fcx, x2ftfcy), y2ftfcz) =>
 // tailrecFold(Bind(fcx, Bind(x2ftfcy, y2ftfcz)))

}
```



## activeMeaningOfActiveFree

```
import ... activeMeaningOfActive

implicit object activeMeaningOfActiveFree
 extends FreeTransformedMeaning[Active, Active]()
 with ComputationMeaning[ActiveFree, Active]()
 with ProgramMeaning['=>AF', '=>A']()
```





# FactorialMain

```
import ... activeMeaningOfActiveFree
import activeMeaningOfActiveFree.meaning

import ... mainFactorial
import mainFactorial.factorialMain

object FactorialMain {

 def main(args: Array[String]): Unit = {

 meaning(factorialMain)()

 }
}
```



# Reading

```
trait Reading[R, >-->[- _, + _]] {

 private[pdbp] def 'u>-->r': Unit >--> R

}
```



# Reading

```
trait Reading[R, >-->[- _, + _]] {
 this: Function[>-->] & Composition[>-->] =>

 private[pdbp] def 'u>-->r': Unit >--> R =
 'z>-->r'[Unit]

 private[pdbp] def 'z>-->r'[Z]: Z >--> R =
 compose('z>-->u', 'u>-->r')

}
```



# Reading

```
trait Reading[R, >-->[- _, + _]] {
 this: Function[>-->] & Composition[>-->] =>

 private[pdbp] def 'u>-->r': Unit >--> R =
 'z>-->r'[Unit]

 private[pdbp] def 'z>-->r'[Z]: Z >--> R =
 compose('z>-->u', 'u>-->r')

 def read[Z]: Z >--> R = 'z>-->r'

}
```



## ReadingTransformed

```
type 'I=>'[-X, +Y] = implicit X => Y
```

```
type ReadingTransformed[R, C[+ _]] = [+Z] => R 'I=>' C[Z]
```



# ReadingTransformation

```
private[pdbp] trait ReadingTransformation[
 R, FC[+ _]: Computation]
 extends ComputationTransformation[
 FC, ReadingTransformed[R, FC]]
 with Computation[ReadingTransformed[R, FC]]
 with Program[Kleisli[ReadingTransformed[R, FC]]]
 with Reading[R, Kleisli[ReadingTransformed[R, FC]]] {

 // ...

}
```



# factorialMain

```
val factorialMain: Unit >--> Unit =
 read >-->
 factorial >-->
 consumer
```



## activeReadingTypes

```
object activeReadingTypes {
 type ActiveReading[R] = ReadingTransformed[R, Active]
 type '=>AR'[R] = Kleisli[ActiveReading[R]]
}
```





## activeIntReadingProgram

```
import ... activeProgram

implicit object activeIntReadingProgram
 extends ActiveReadingProgram[BigInt]()
 with Computation[ActiveReading[BigInt]]()
 with Program['=>AR'[BigInt]]()
 with Reading[BigInt, '=>AR'[BigInt]]()
 with ReadingTransformation[BigInt, Active]()
 with ComputationTransformation[Active, ActiveReading[BigInt]]()
```



## activeIntReadingProgram

```
import ... activeIntReadingProgram

implicit object activeIntReadingMeaningOfActiveIntReading
 extends ReadingTransformedMeaning[BigInt, Active, Active]()
 with ComputationMeaning[ActiveReading[BigInt], ActiveReading[BigInt]]()
 with ProgramMeaning['=>AR'[BigInt], '=>AR'[BigInt]]()
```



# FactorialMain

```
import ... activeIntReadingMeaningOfActiveIntReading
import activeIntReadingMeaningOfActiveIntReading.meaning

import ... mainFactorialOfIntRead
import mainFactorialOfIntRead.factorialMain

object FactorialOfIntReadMain {

 import ... readIntFromConsoleEffect

 def main(args: Array[String]): Unit = {

 meaning(factorialMain)()

 }
}
```



## factorialMultipliedByIntRead

```
val factorialMultipliedByIntRead: BigInt >--> BigInt =
 (factorial & read) >--> multiply
```



# Writing

```
trait Writing[W: Writable, >-->[- _, + _]] {

 private[pdbp] val 'w>-->u': W >--> Unit

 // ...
}
```



## Writing

```
trait Writing[W: Writable, >-->[- _, + _]] {
 this: Function[>-->] & Composition[>-->] =>

 private[pdbp] val 'w>-->u': W >--> Unit
 = write(identity)

 def write[Z]: (Z => W) 'I=>' Z >--> Unit =
 compose(function(implicitly), 'w>-->u')

 // ...

}
```



## Writing

```
def writeUsing[Z, Y, X](
 'z&&y=>x': ((Z && Y) => X)):
 (Z >--> Y) => ((X => W) 'I=>' Z >--> Y) = { 'z>-->y' =>
 val 'z&&y>-->x' = function('z&&y=>x')
 val 'z>-->(x&&y)' =
 'let' {
 'z>-->y'
 } 'in' {
 'let' {
 'z&&y>-->x'
 } 'in' {
 'z&&y&&x>-->(x&&y)'
 }
 }
 }
 compose(compose('z>-->(x&&y)', left(write)),
 'u&&y>-->y')
```



# Writable

```
private[pdbp] trait Writable[W]
 extends Startable[W]
 with Appendable[W]
```





# Startable

```
private[pdbp] trait Startable[W] {
 private[pdbp] val start: W
}
```



# Appendable

```
private[pdbp] trait Appendable[W] {
 private[pdbp] val append: W && W => W
}
```



# WritingTransformed

```
type WritingTransformed[W, FC[+ _]] = [+Z] => FC[W && Z]
```



## WritingTransformation

```
private[pdbp] trait WritingTransformation[
 W: Writable, FC[+ _]: Computation]
 extends ComputationTransformation[
 FC, WritingTransformed[W, FC]]
 with Computation[WritingTransformed[W, FC]]
 with Program[Kleisli[WritingTransformed[W, FC]]]
 with Writing[W, Kleisli[WritingTransformed[W, FC]]] {

 // ...

}
```



# ToConsole

```
case class ToConsole(effect: Effect)
```

```
type Effect = Unit => Unit
```



# ToConsole

```
implicit object toConsoleWritable extends Writable[ToConsole] {

 override private[pdbp] val start: ToConsole =
 ToConsole { _ =>
 ()
 }

 override private[pdbp] val append:
 ToConsole && ToConsole => ToConsole = {
 (tc1, tc2) =>
 ToConsole { _ =>
 { tc1.effect(()); tc2.effect(()) }
 }
 }

}
```



## infoUtils

```
def infoFunction[Z, Y](string: String): Z && Y => String = {
 case (z, y) =>
 s"INFO -- $currentCalendarInMilliseconds -- $string($z) => $y"
}

def info[
 W: Writable, Z, Y,
 >-->[- _, + _]: [>-->[- _, + _]] => Writing[W, >-->]]
 (string: String):
 (Z >--> Y) => ((String => W) 'I=>' Z >--> Y) = {
 val implicitWriting = implicitly[Writing[W, >-->]]
 implicitWriting.writeUsing(infoFunction(string))
 }
}
```



## WritingAtomicPrograms

```
val isZero: (String => W) 'I=>' BigInt >--> Boolean =
 info("isZero") { isZeroHelper }
```

```
val subtractOne: (String => W) 'I=>' BigInt >--> BigInt =
 info("subtractOne") { subtractOneHelper }
```

```
val multiply: (String => W) 'I=>' (BigInt && BigInt) >--> BigInt =
 info("multiply") { multiplyHelper }
```

```
def one[Z]: (String => W) 'I=>' Z >--> BigInt =
 info("one") { oneHelper }
```





# WritingFactorial

```
val factorial: (String => W) 'I=>' BigInt >--> BigInt =
 info("factorial") {
 'if'(isZero) {
 one
 } 'else' {
 'let' {
 subtractOne >-->
 factorial
 } 'in' {
 multiply
 }
 }
 }
```



## factorialMain

```
val factorialMain:
 (String => ToConsole) 'I=>'
 ((BigInt => ToConsole) 'I=>' Unit >--> Unit) =
 read >-->
 factorial >-->
 write
```



## activeWritingToConsoleProgram

```
import ... toConsoleWritable
import ... activeProgram

implicit object activeWritingToConsoleProgram
 extends ActiveWritingProgram[ToConsole]()
 with ComputationTransformation[Active, ActiveWriting[ToConsole]]()
 with WritingTransformation[ToConsole, Active]()
 with Writing[ToConsole, '=>AW'[ToConsole]]()
 // ...
```



## activeIntReadingWithWritingToConsoleProgram

```
import ... toConsoleWritable
import ... activeWritingToConsoleProgram

implicit object activeIntReadingWithWritingToConsoleProgram
 extends ActiveReadingWithWritingProgram[BigInt, ToConsole]()
 with Computation[ActiveReadingWithWriting[BigInt, ToConsole]]()
 with Program['=>ARW'[BigInt, ToConsole]]()
 with Reading[BigInt, '=>ARW'[BigInt, ToConsole]]()
 with Writing[ToConsole, '=>ARW'[BigInt, ToConsole]]()
 // ...
```



## activeIntReadingWithWritingToConsoleProgram

```
// ...
with ReadingWithWritingTransformation[BigInt,
 ToConsole,
 ActiveWriting[ToConsole]]()
with ReadingTransformation[BigInt, ActiveWriting[ToConsole]]()
with ComputationTransformation[
 ActiveWriting[ToConsole],
 ActiveReadingWithWriting[BigInt, ToConsole]]()
```



# FactorialOfIntRead WritingToConsoleWrittenToConsoleMain

```
import ... activeIntReadingMeaningOfActiveIntReadingWithWritingToConsole
import activeIntReadingMeaningOfActiveIntReadingWithWritingToConsole.me

import ... mainFactorialOfIntReadWritingToConsoleWrittenToConsole
import mainFactorialOfIntReadWritingToConsoleWrittenToConsole.factorial

object FactorialOfIntReadWritingToConsoleWrittenToConsoleMain {

 import ... readIntFromConsoleEffect
 import ... writeFactorialOfIntReadFromConsoleToConsoleEffect
 import ... writeToConsoleEffect

 def main(args: Array[String]): Unit = {

 meaning(factorialMain)()
 }
}
```



## running

please type an integer to read

2

```
INFO -- 2018-08-01 18:00:42.639 -- isZero(2) => false
INFO -- 2018-08-01 18:00:42.645 -- subtractOne(2) => 1
INFO -- 2018-08-01 18:00:42.646 -- isZero(1) => false
INFO -- 2018-08-01 18:00:42.647 -- subtractOne(1) => 0
INFO -- 2018-08-01 18:00:42.647 -- isZero(0) => true
INFO -- 2018-08-01 18:00:42.648 -- one(0) => 1
INFO -- 2018-08-01 18:00:42.648 -- factorial(0) => 1
INFO -- 2018-08-01 18:00:42.649 -- multiply((1,1)) => 1
INFO -- 2018-08-01 18:00:42.649 -- factorial(1) => 1
INFO -- 2018-08-01 18:00:42.650 -- multiply((2,1)) => 2
INFO -- 2018-08-01 18:00:42.650 -- factorial(2) => 2
the factorial value of the integer read is
```

2

