



LED



DESIGNED
TESTED
MANUFACTURED

GENERAL INFORMATION

The Aureled Vista has been developed with healthcare environments in mind. The Aureled Vista is available with a range of different imagery designed to promote a relaxing and reassuring environment for patients. Using creative lighting solutions creates a non-institutional feel that puts patients at ease and makes it more likely that they relax and focus on healing.

The Aureled Vista can be a focal and discussion point for young children undergoing medical examinations. By giving patients something to concentrate on they are less likely to become agitated.

Designed and constructed with a shallow 45mm profile the Aureled will slide into confined spaces. Coupled with a detachable gearbox incorporating a plug-and-play connector this luminaire is the perfect solution for locations where there are multiple services installed inside the ceiling space.

Once installed, the gearbox can be detached from the luminaire housing as required whether for upgrading to dimming or maintenance.

Download the brochure [here](#).
Antimicrobial powder coating as standard.

CODE	DESCRIPTION	LENGTH:	WIDTH:	DEPTH:	REMOTE GEAR:
EL-AUR-____-C1-____	LED C1	600	600	56	40
EL-AUR-____-C2-____	LED C2	600	1200	56	40
EL-AUR-____-C3-____	LED C3	600	1800	56	40
EL-AUR-____-C4-____	LED C4	1200	1200	56	40
EL-AUR-____-C6-____	LED C6	1200	1800	56	40
EL-AUR-____-C9-____	LED C9	1800	1800	56	40

CONTROL OPTIONS

The below controls options are standard options available for this product. Further customisation may be possible via customisation.

Please speak to your customer service representative for more details.

VARIATION	SUFFIX
Standard	-000
DALI	-200
Maintained emergency	-800
DALI monitored emergency	-801
Organic Response (SN3)	-970

OPTIONS:

DSI Dimming
DALI Dimming
Emergency
Restraint kit available

N.B. The Aureled and Aureled Vista can be customised for MRI applications. Please contact your Eagle Lighting representative for further information.

KEY FAMILY DETAILS

CCT:
4000K
CRI:
90+
R9:
70+

TECHNICAL INFORMATION

AVAILABLE NOMINAL DIMENSIONS (MM):

600x600; 600x1200; 600x1800; 1200x1200; 1200x1800; 1800x1800

DEPTH FOR ALL VERSIONS:

56mm (remote gear 40mm)

AVAILABLE CONFIGURATIONS

C1	C2	C3	C4	C6	C9		

ACCESSORIES

DESCRIPTION	CODE
Restraint Kit - 4 x gripple, 2 x 2m wire	EL-ACC-210-000

Product Advisement Statement

- All photometric (including flicker metrics), spectrometric, electrical, and thermal data have a tolerance of ±5%.
- The value indicated by the UGR icon refers to the lowest UGR value achievable by at least one standard variant of a given product family. It may not necessarily apply to all standard variants.
- The Unified Glare Rating (UGR) is a function of the entire design space, including but not limited to the optical properties of the ceiling and walls, as well as the properties and spacing of all other luminaires in the calculation space. It is not an intrinsic property of a light fitting and should not be quoted as such.
- All UGR values stated by Eagle Lighting are calculated in compliance with AS/NZS 1680.1-2006 (aligned with CIE 117-1995) and are achievable with standard room sizes and luminaire spacing based on the specific luminaire model.
- The following design parameters apply unless otherwise specified:
 - Light Loss Factor (LLF): 0.80 (Nominal)
 - Room Reflectance Values (Ceiling/Walls/Floor): 0.70/0.50/0.20
 - Ceiling Height: 2.7m
 - Horizontal Illuminance (Eh) calculated at 0.72m above finished floor level (AFL)
- Non-standard (custom) products may have UGR values higher than those of standard models, depending on the nature of the customization. Please consult your sales representative for details.
- UGR values obtained under conditions or parameters other than those specified above may differ from the stated values.
- All product heights are shown excluding the driver unless otherwise specified.
- For questions about our products or assistance with ordering accessories (where applicable), please contact your customer service representative.

