


Capri 110

Normally Stocked

Capri 110 Suspended Narrow Beam 4000K Ra80 with IP65 Upgrade

CAPRI.1101.4080.2.IP65



Optical

Optical Description	Precision designed spun aluminium reflector. Prismatic refractor for reduced glare.	Output (lm)	9830
Efficacy	91	Downward Output	9830lm
Upward Output	0lm	UWLR	0lm
Light Distribution Up %	0	Light Distribution Down %	100
CCT	4000K	CRI	Ra80
L70	>55,000hr	L80	>55,000hr
L90	48,100hr	TM-21 @ 50,000hr	0.894
Beam Spread	92 × 94	Horizontal Beam Angle	90.0
Vertical Beam Angle	95.0	IES Classification	Type VS
BUG Rating	N.A. - No Uplight	Max Intensity	4310.0
Luminous Length (X)	550	Luminous Width (Y)	550
Luminous Height (Z)	60mm		

Physical

Finish Colour	Black	Finish Type	Die cast aluminium housing in matte powdercoat finish
Housing Material	Die-cast aluminium LED module housing with highly-efficient heat sink, finished in black powdercoat. Spun aluminium reflector.	Optic Material	Precision designed spun aluminium reflector. Prismatic refractor with IP65 upgrade.
Luminaire Weight (Net)	6.6kg	Mounting Type	Suspended
Dimensions	580mm x 340mm	IP Rating	IP52

Electrical

Watts	108	Electrical Class	Class I
Driver Description	Integral 1-10V Dimmable Driver	Driver Control	1-10V Dimmable
Driver Forward Current Rating	2600	Driver Mounting	Integral
Driver IP Rating	67	Number of Drivers	1

Certifications

Warranty

5 Years