


COMO S White Reflector Wide Beam 350mA Casambi 4000K Ra90 White Trim
COMS.0000WB.0350CS.4090A.1



Optical

Optical Description	White Reflector	Output (lm)	1440
Efficacy	108	Downward Output	1440
Upward Output	0	UWLR	0
Light Distribution Up %	0	Light Distribution Down %	100
CCT	4000K	CRI	Ra90
Beam Spread	Wide Beam	Horizontal Beam Angle	85.0
Vertical Beam Angle	85.0	MacAdam Step	3
IES Classification	Type V	Max Intensity	825.0
Luminous Length (X)	90mm	Luminous Width (Y)	90mm
Luminous Height (Z)	0mm		

Physical

Finish Colour	White trim	Housing Material	Luminaire body, trim, and fastening retaining clips in die-cast enamelled aluminium
Optic Material	Die-cast aluminium	Mounting Type	Recessed
Cut Out Size	Ø98mm	Dimensions	Ø110mm x 75mm
IP Rating	IP65		

Electrical

Watts	13	Rated Voltage	220-240VAC
Electrical Class	Class II	Driver Control	Casambi
Driver Forward Current Rating	350	Driver Mounting	Remote

Certifications

Ceiling Covering Rating	CA-90	Warranty	5 Years
-------------------------	-------	----------	---------