

Circadia (white optical chambers)



EL-CIR-1100-244

CIRCADIA WHITE OPTICS Recessed/T-bar Single Luminaire Bottom Access Direct
2850lm 20.1W LED Wide beam 4000K Ra90+ 240V White reflector DALI Class I
Std AUS flex & plug 2.0m & 2 core dimming flex 2.0m L:1194mm W:293mm
H:60mm IP40 White .



TECHNICAL OVERVIEW

FINISH

White

L = LENGTH [mm]

1194

W = WIDTH/DIAMETER [mm]

293

H = HEIGHT [mm]

60

CL = RECESSING LENGTH [mm]

-



CW = RECESSING

WIDTH/DIAMETER [mm]

-

WEIGHT [KG]

6.8



NORMALISED POLAR CURVE

PHOTOMETRIC VALUES

CONTROL TYPE

DALI

CEILING TYPE/MOUNTING

Recessed/T-bar

WATTAGE [W]

20.1

CLO ENABLED

Yes

FINAL WATTAGE CLO [W]

24

SYSTEM LUMENS [lm]

2850

LUMINAIRE LUMENS [lm]

2166

EFFICACY [lm/W]

108

LIGHTING TYPE

Direct

TARGET SPACING [m]

2.4 x 2.4

TARGET H ILLUMINANCE [LUX]

330

LPD [W/m²]

3.48

NPD [W/SQM/100LUX]

1.04

BEAMWIDTH (FWHM)

-

OPTICS TYPE

White reflector

UGR

-

COLOUR QUALITY

CCT [K]
4000K
CCT1 [K]
4000K
CCT2 [K]
-
OTHER LIGHT COLOUR
-
CRI
Ra90+
COI COMPLIANCE
Compliant
CLA 2.0
-
M-DER
-

LIFETIME AND MISCELLANEOUS PARAMETERS

LM80 TEST DURATION [HRS]
12000
L90B50 LIFETIME [HRS]
66000
TM21 L70 REPORTED LIFETIME [HRS]
>72000

ACCESSORIES

DESCRIPTION	CODE
Restraint Kit - 4 x gripple, 2 x 2m wire	EL-ACC-210-000
Surface mount kit** to suit 600x300	EL-ACC-896-000
Surface mount kit** to suit 1200x300	EL-ACC-897-000
Surface mount kit** to suit 1500x300	EL-ACC-898-000
Plaster recess kit 600x300	EL-ACC-850-000
Plaster recess kit 1200x300	EL-ACC-852-000
Plaster recess kit 1500x300	EL-ACC-853-000

[**]: Surface mounting kits are 'standard white'. Other finish options available via customisation

Product Advisement Statement

- All photometric (including flicker metrics), spectrometric, electrical, and thermal data have a tolerance of ±5%.
- The value indicated by the UGR icon refers to the lowest UGR value achievable by at least one standard variant of a given product family. It may not necessarily apply to all standard variants.
- The Unified Glare Rating (UGR) is a function of the entire design space, including but not limited to the optical properties of the ceiling and walls, as well as the properties and spacing of all other luminaires in the calculation space. It is not an intrinsic property of a light fitting and should not be quoted as such.
- All UGR values stated by Eagle Lighting are calculated in compliance with AS/NZS 1680.1-2006 (aligned with CIE 117-1995) and are achievable with standard room sizes and luminaire spacing based on the specific luminaire model.
- The following design parameters apply unless otherwise specified:
 - Light Loss Factor (LLF): 0.80 (Nominal)
 - Room Reflectance Values (Ceiling/Walls/Floor): 0.70/0.50/0.20
 - Ceiling Height: 2.7m
 - Horizontal Illuminance (Eh) calculated at 0.72m above finished floor level (AFFL)
- Non-standard (custom) products may have UGR values higher than those of standard models, depending on the nature of the customization. Please consult your sales representative for details.
- UGR values obtained under conditions or parameters other than those specified above may differ from the stated values.
- All product heights are shown excluding the driver unless otherwise specified.
- For questions about our products or assistance with ordering accessories

R9
56
MELANOPIC RATIO
0.72
CIRCADIAN STIMULUS CS [%]
12
CIRCADIAN LIGHT [LUX]
86
TM-30 RF
89
TM-30 RG
96
M-EDI
-

L100B50 LIFETIME (CLO) [HRS]
72000
TM21 L90 REPORTED LIFETIME [HRS]
52000
SDCM INITIAL
3

(where applicable), please contact your customer service representative.

